



RF Exposure Evaluation

TR-902 Series

Wireless Network Adapter

Tranzeo Wireless Technologies Inc.

Date: January 12, 2007

Report No.:120107.1

Labs: 19473 Fraser Way, Pitt Meadows, BC, Canada V3Y 2V4

A handwritten signature in black ink, appearing to read 'Cam Finnigan'.

Cam Finnigan
EMC Engineer

A handwritten signature in black ink, appearing to read 'Sam Zahed'.

Sam Zahed
EMC Coordinator

RF Exposure Evaluation

FCC 1.1310 states the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Section 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Section 2.1093 of this chapter. Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation".

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

EUT Operating Condition

The maximum antenna gain is 11 dBi at 900 MHz.

RF exposure evaluation distance calculation

EUT with 11 dBi antenna

Freq (MHz)	Output Power to Antenna (dBm)	Antenna Gain (dBi)	r (cm)
908	25.3	11	23.7
910	24.94	11	23.0
913	24.4	11	21.3
915	24.84	11	22.4
920	24.8	11	22.2
923	25.21	11	23.2

As shown above, the minimum distance where the MPE limit is reached is 21.3 cm for the EUT.