

Tranzeo EMC Labs Inc.
19473 Fraser Way
Pitt Meadows, B.C.
V3Y 2V4

TR-CPE-90
2.4 GHz Wireless Network Adapter
EMC Test Report

16 May 2006



Bruce Balston, EMC Lab Manager



Andrew Marles, Technical Writer

MFE Evaluation

FCC 1.1310 states the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter. Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, ``Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation."

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100,000 | -- | -- | 1 | 30 |

9.1 Transmission Formula

Transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$ Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW.

G = gain of antenna in the direction of interest relative to an isotropic radiator.

R = the distance between the observation point and the center of the radiator in cm.

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna we can calculate the distance r where the MPE limit is reached.

9.2 EUT Operating Condition

The maximum antenna gain is 17 dBi for the TR-CPE90 as stated by the manufacturer.

9.3 RF exposure evaluation distance calculation

TR-CPE90

| Chan | Freq (MHz) | Output Power to Antenna (dBm) | Output Power to Antenna (mW) | Antenna Gain (dBi) | r (cm) |
|------|------------|-------------------------------|------------------------------|--------------------|--------|
| 1 | 2412 | 20.66 | 117 | 17 | 23 |
| 6 | 2437 | 20.07 | 102 | 17 | 21 |
| 11 | 2462 | 20.00 | 100 | 17 | 20 |

As shown above, the minimum distance where the MPE limit is reached for the TR-CPE-90 product family.