

FCC REPORT

Applicant: AZUMI S.A
Address of Applicant: AvenidaAquilino de la Guardia con Calle 47, PH Ocean Plaza,
Piso 16 of. 16-01, Marbella, Ciudad de Panamá City, Rep.
Panamá

Equipment Under Test (EUT)

Product Name: Mobile phone

Model No.: AC24 Lite

Trade mark: Azumi

FCC ID: QRP-AZUMIAC24LITE

Applicablestandards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 23 May., 2016

Date of Test: 23 May., to 15 Jun., 2016

Date of report issued: 15 Jun., 2016

Test Result: Pass*

*In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of theCCISproduct certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	15 Jun., 2016	Original

Tested by:

Steven Liu

Date:

15 Jun., 2016

Test Engineer

Reviewed by:

M. Liang

Date:

15 Jun., 2016

Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS	6
5.6 LABORATORY FACILITY	6
5.7 LABORATORY LOCATION	6
5.8 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION	11
7 TEST SETUP PHOTO	17
8 EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	AZUMI S.A
Address of Applicant:	AvenidaAquilino de la Guardia con Calle 47, PH Ocean Plaza, Piso 16 of. 16-01, Marbella, Ciudad de Panamá City, Rep. Panamá
Manufacturer	AZUMI HK LTD
Address of Manufacturer:	FLAT/RM 18 BLK 1 14/F GOLDEN INDUSTRIAL BUILDING 16-26 KWAI TAK STREET KWAI CHUNG, HK
Factory:	Longconn Electronics(Shenzhen) Co., Ltd.
Address of Factory:	(Xinchuangji Industrial park) NO.42, Xingye 1 Road, Phoenix 1st Industrial Zone, Fuyong Town, Baoan District, Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	Mobile phone
Model No.:	AC24 Lite
Power supply:	Rechargeable Li-ion Battery DC3.7V-600mAh
AC adapter :	Input: AC100-240V 50/60Hz 0.1A Output: DC 5.0V, 0.5A

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
<p>The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

5.4 Measurement Uncertainty

Items	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID
NAKAMICHI	Bluetooth earphone	T8	N/A	FCC ID

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**
 Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.
- **IC - Registration No.: 10106A-1**
 The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.
- **CNAS - Registration No.: CNAS L6048**
 Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Tel: +86-755-23118282
 Fax: +86-755-23116366

5.8 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	03-25-2016	03-25-2017
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	03-25-2016	03-25-2017
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2016	03-31-2017
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	04-01-2016	03-31-2017
6	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	03-28-2016	03-28-2017
7	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	03-28-2016	03-28-2017

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	03-24-2016	03-24-2017
3	LISN	CHASE	MN2050D	CCIS0074	03-26-2016	03-26-2017
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2016	03-31-2017


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.107														
Test Method:	ANSI C63.4:2014														
Test Frequency Range:	150kHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9kHz, VBW=30kHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
	Frequency range (MHz)		Limit (dB μ V)												
		Quasi-peak	Average												
	0.15-0.5	66 to 56*	56 to 46*												
	0.5-5	56	46												
0.5-30	60	50													
* Decreases with the logarithm of the frequency.															
Test setup:	<p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014on conducted measurement. 														
Test environment:	Temp.: 23°C Humid.: 56% Press.: 101kPa														
Test Instruments:	Refer to section 5.7 for details														
Test mode:	Refer to section 5.3 for details														
Test results:	Pass														

Measurement data:

Line:



Trace: 21


Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : Mobile Phone
 Model : AC24 Lite
 Test Mode : PC mode
 Power Rating : AC120/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: steven
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	49.40	0.14	10.78	60.32	65.56	-5.24	QP
2	0.158	34.09	0.14	10.78	45.01	55.56	-10.55	Average
3	0.190	30.41	0.15	10.76	41.32	54.02	-12.70	Average
4	0.214	45.66	0.15	10.76	56.57	63.05	-6.48	QP
5	0.222	28.21	0.15	10.75	39.11	52.74	-13.63	Average
6	0.253	26.74	0.16	10.75	37.65	51.64	-13.99	Average
7	0.270	39.76	0.16	10.75	50.67	61.12	-10.45	QP
8	0.377	22.28	0.22	10.72	33.22	48.34	-15.12	Average
9	0.426	38.07	0.24	10.73	49.04	57.33	-8.29	QP
10	0.431	25.29	0.24	10.73	36.26	47.24	-10.98	Average
11	0.479	32.13	0.24	10.75	43.12	56.36	-13.24	QP
12	0.759	30.01	0.31	10.80	41.12	56.00	-14.88	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Neutral:



Trace: 23

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : Mobile Phone
 Model : AC24 Lite
 Test Mode : PC mode
 Power Rating : AC120/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: steven
 Remark :

	Read	LISN	Cable	Limit	Over	
Freq	Level	Factor	Loss	Line	Limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	49.74	0.13	10.77	60.64	65.34	-4.70 QP
2	31.32	0.13	10.77	42.22	55.34	-13.12 Average
3	29.43	0.14	10.77	40.34	54.59	-14.25 Average
4	46.52	0.14	10.76	57.42	64.20	-6.78 QP
5	27.52	0.15	10.76	38.43	53.36	-14.93 Average
6	44.50	0.16	10.76	55.42	63.18	-7.76 QP
7	24.89	0.17	10.75	35.81	52.17	-16.36 Average
8	40.89	0.17	10.75	51.81	62.04	-10.23 QP
9	21.80	0.20	10.74	32.74	49.75	-17.01 Average
10	36.43	0.23	10.73	47.39	57.42	-10.03 QP
11	21.34	0.23	10.73	32.30	47.42	-15.12 Average
12	30.56	0.24	10.75	41.55	56.36	-14.81 QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2014				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency	Limit (dBuV/m @3m)			Remark
	30MHz-88MHz	40.0			Quasi-peak Value
	88MHz-216MHz	43.5			Quasi-peak Value
	216MHz-960MHz	46.0			Quasi-peak Value
	960MHz-1GHz	54.0			Quasi-peak Value
	Above 1GHz	54.0			Average Value
		74.0			Peak Value
Test setup:	Below 1GHz				
	Above 1GHz				

<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
<p>Test environment:</p>	<p>Temp.: 25°C Humid.: 55% Press.: 101kPa</p>
<p>Test Instruments:</p>	<p>Refer to section 5.7 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Passed</p>

Measurement Data:

Below 1GHz

Horizontal:




```

Site       : 3m chamber
Condition  : FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL
EUT       : Mobile phone
Model     : AC24 Lite
Test mode  : PC mode
Power Rating : AC120V/60Hz
Environment : Temp:25.5°C Humi:55% 101KPa
Test Engineer: steven
REMARK    :
    
```

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	143.830	56.99	11.34	2.44	29.25	41.52	43.50	-1.98	QP
2	162.041	58.41	9.88	2.60	29.12	41.77	43.50	-1.73	QP
3	216.024	55.97	11.18	2.85	28.73	41.27	46.00	-4.73	QP
4	252.063	57.55	11.86	2.82	28.54	43.69	46.00	-2.31	QP
5	324.456	55.43	13.42	3.02	28.51	43.36	46.00	-2.64	QP
6	348.027	55.91	14.06	3.09	28.56	44.50	46.00	-1.50	QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) VERTICAL
 EUT : Mobile phone
 Model : AC24 Lite
 Test mode : PC mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: steven
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	132.221	56.84	12.16	2.32	29.32	42.00	43.50 -1.50 QP
2	143.830	57.24	11.34	2.44	29.25	41.77	43.50 -1.73 QP
3	155.910	58.74	10.19	2.56	29.17	42.32	43.50 -1.18 QP
4	216.024	56.19	11.18	2.85	28.73	41.49	46.00 -4.51 QP
5	252.063	56.38	11.86	2.82	28.54	42.52	46.00 -3.48 QP
6	348.027	51.13	14.06	3.09	28.56	39.72	46.00 -6.28 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Mobile phone
 Model : AC24 Lite
 Test mode : PC mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: steven
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3296.439	48.58	26.97	8.41	39.78	44.18	74.00	-29.82	Peak
2	3296.439	40.32	26.97	8.41	39.78	35.92	54.00	-18.08	Average
3	4091.203	47.63	32.68	9.73	41.05	48.99	74.00	-25.01	Peak
4	4091.203	40.02	32.68	9.73	41.05	41.38	54.00	-12.62	Average
5	5028.418	45.52	36.77	10.82	40.00	53.11	74.00	-20.89	Peak
6	5028.418	37.24	36.77	10.82	40.00	44.83	54.00	-9.17	Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Mobile phone
 Model : AC24 Lite
 Test mode : PC mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: steven
 REMARK :

	ReadAntenna	Cable	Preamp	Limit	Over				
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	3277.252	46.22	26.89	8.38	39.93	41.56	74.00	-32.44 Peak	
2	3277.252	37.57	26.89	8.38	39.93	32.91	54.00	-21.09 Average	
3	4091.203	43.34	32.68	9.73	41.05	44.70	74.00	-29.30 Peak	
4	4091.203	35.24	32.68	9.73	41.05	36.60	54.00	-17.40 Average	
5	5028.418	45.03	36.77	10.82	40.00	52.62	74.00	-21.38 Peak	
6	5028.418	37.88	36.77	10.82	40.00	45.47	54.00	-8.53 Average	