Key Terminal AS x70 KT

The Handheld KeyTerminal is a battery operated small reader to be operated single-handed for keymotion[™] technology. Its key functions are authorisation verification and value debiting.



Features

- Data carrier compatible with all SKIDATA[™] Systems with keymotion[™] technology
- Single hand operation
- Rigid design; applicable for outdoor uses
- Large display for simple user guidance
- Powerful microprocessor for application programs

Versions, Accessories

937340000	. ASx70KT KeyTerminal
937340010	. ASx70KT/DH (with backlit
	display)
937340030	. ASx70KT/C KeyTerminal

SKIDATA AG • Untersbergstraße 40 • A-5083 Gartenau

[t] +43 (0) 62 46/8 88-0 • [f] +43 (0) 62 46/8 88-7 • [e] info@skidata.com • [w] www.skidata.com

Version 1.0 • 17.06.2003 • Copyright © 2003 by SKIDATA AG

This documentation may contain representations of registered product or service trademarks owned by SKIDATAAG or third parties, as well as references to proprietary know-how protected by copyright laws or other legal provisions.

In any case the intellectual property rights remain exclusively with their respective owners. This document is subject to change without notice. It cannot form part of a binding contract.



Key Terminal AS x70 KT

Technical Characteristics

Data Carriers	. keycard, Swatch Access, KeyBand, KeyRing, GORE-TEX® Glove, GemFree, ISO 15693
Measures	. 175 x 92 x 37 mm (l x w x h)
Weight	. 0.3 kg
Input Voltage	. 9V DC
Power consumption	. 5 W typ.
Interface	. RS 232
Temperature Range	. Operation: -10°C to +40°C; when charging: +5°C to +40°C
Colour	. Blue RELIUS E-14-45, Orange (PANTONE 151 C)
Radio Frequency	. 125 KHz / 13 MHz
Display	. 4 rows at 20 characters each, non-backlit (graphical resolution 120 x 32 pixels, backlighting optional)
Keypad	. 16 keys, silicon rubber
Rechargeable battery cell	. Li-Ion 3.7 V / 200 mAh
Standards	. EN 300330-2, EN 301489-3, Pacemaker Safety VDE 0848- 3-1
Safety Class	. IP 31

Please note the instructions for battery recharging!



