

The CO x70i TX is a fast and compact universal ticket printer and coder. Coding units read, print and code ISO-format tickets. The CO x70i TX applies supplementary visual imprints to colored, preprinted blank tickets, e.g. authorizations or a bar code or personalizing. A built-in bar-code reader module (optional) can be employed for checking freshly printed bar codes. In addition to these features, the CO x70i TX can process ThermoReWrite KeyCards. These tickets can be reused a number of times, as they are equipped with a thermo sensitive coating for receiving visual imprints which can be erased at any time.



Picture may vary from actual product

Features

- Compatible with the data carriers used in all SkiData systems
- Flexibility by way of economical, speedy printing of uniform blank cards
- Direct thermoprinting
- Standard parallel interface (IEEE 1284)
- Safe from manipulation because tickets are printed and coded in a single step
- Contactless data carriers such as Swatch Access can be coded via the integrated groove antenna
- Simple handling due to the omission of colour ribbons and ink cartridges
- Electronic coding for 122.88 KHz and 13.56 MHz
- ISO 15693-compatible
- For erasing and printing ThermoReWrite KeyCards
- Top printing quality by using a 300 dpi thermal head
- Extremely high output speed

Versions, Accessories

937100020	CO x70i TX. For coding contactless data carriers, 122.88 kHz and 13.56-MHz KeyCards and Swatch Access on built-in antenna, erase function for ThermoReWrite KeyCards, manual insertion into front
937100025	CO x70i TX/BC. For coding contactless data carriers, 122.88 kHz and 13.56-MHz KeyCards and Swatch Access on built-in antenna, erase function for ThermoReWrite KeyCards, can be used to issue barcode tickets, manual insertion into front
937100810	COx70TX/1S: Single Tray. Ticket hopper for 150 to 450 tickets, for attachment to the rear of CO x70 TX
937100820	COx70TX/3S: Multiple Tray. Multiple-tray (three) ticket hopper for 150 to 450 tickets, for attachment to rear of CO x70i TX
CPZUBEHÖR4113	Cleaning set for KeyPrinter

Technical Characteristics

Data Carriers	Barcode card (optional), KeyCard, Swatch Access, KeyBand, GORE-TEX® Glove
Tickets	84 x 54 mm, thickness: 0.3 - 1.2 mm
Input voltage	85 - 132 V or 170 - 265 V, 47 - 63 Hz
Power consumption	200 W max.
Standards	CE symbol, FTV 525, ETS 300 330, ISO 9001
Ambient conditions	+10° - +35°C, 25% - 85% humidity
Dimensions [in mm]	Printer Multiple Tray: 365 x 250 x 330 (w x h x d); Single Tray: 210 x 250 x 330 (w x h x d); Power supply: 120 x 70 x 240 (w x h x d)
Weight	Printer: 8.2 kg; power supply: 1.7 kg
Printing area	81.5 x 48 mm, edge: 2 mm (l) or 2.5 mm (w)
Resolution	300 dpi
Chassis base colors	Gray RAL 6009, Blue RELIUS E-14-45, Orange (PANTONE 151 C)

