

TEST REPORT

Report No.: BCTC2112205315E

Applicant: ZAGG Inc.

Product Name: HALO Wireless Charging Dock Power Bank
10K/mophie powerstation wireless dock


Model/Type
reference: HWCDPB-10K/MPWDPB-10K

Tested Date: 2021-12-06 to 2021-12-14

Issued Date: 2021-12-14




Shenzhen BCTC Testing Co., Ltd.



FCC ID: QTG-HWCDPB10K

Product Name: HALO Wireless Charging Dock Power Bank 10K/mophie powerstation wireless dock
Trademark: HALO/mophie
Model/Type reference: HWCDPB-10K/MPWDPB-10K
Prepared For: ZAGG Inc.
Address: 910 West Legacy Center Way, Midvale Utah 84047, United States
Manufacturer: ZAGG Inc.
Address: 910 West Legacy Center Way, Midvale Utah 84047, United States
Prepared By: Shenzhen BCTC Testing Co., Ltd.
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: 2021-12-06
Sample tested Date: 2021-12-06 to 2021-12-14
Issue Date: 2021-12-14
Report No.: BCTC2112205315E
Test Standards: FCC Part15.209
ANSI C63.10-2013
Test Results: PASS

Tested by:



Willem Wang/Project Handler

Approved by:




Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content


	Page
Test Report Declaration	
1. Version	4
2. Test Summary	5
3. Measurement Uncertainty	6
4. Product Information And Test Setup	7
4.1 Product Information.....	7
4.2 Test Setup Configuration	7
4.3 Support Equipment	8
4.4 Test Mode	8
4.5 Copy of marking plate	9
5. Test Facility And Test Instrument Used.....	10
5.1 Test Facility.....	10
5.2 Test Instrument Used.....	10
6. Conducted Emissions.....	12
6.1 Block Diagram Of Test Setup.....	12
6.2 Limit	12
6.3 Test procedure.....	12
6.4 EUT operating Conditions	12
6.5 Test Result.....	13
7. Radiated Emissions.....	15
7.1 Block Diagram Of Test Setup.....	15
7.2 Limit	16
7.3 Test procedure.....	16
7.4 Test Result.....	17
8. EUT Photographs.....	20
9. EUT Test Setup Photographs.....	21

(Note: N/A means not applicable)



1. Version

Report No.	Issue Date	Description	Approved
BCTC2112205315E	2021-12-14	Original	Valid



2. Test Summary


The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No	Results
1	Conducted Emission	15.207	PASS
2	Radiated Emission	15.209	PASS


Remark: Based on the following changes in the product, the RF chip remains unchanged. So the report is only updated Conducted emissions and Radiated Emissions for the original report (BCTC2011000939-1E) .

Changes : 1. The new product charging IC adds diode.

Original:



new



3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	Conducted Emission (150kHz-30MHz)	U=3.2dB
3	humidity uncertainty	U=5.3%
4	Temperature uncertainty	U=0.59°C

4. Product Information And Test Setup


4.1 Product Information

Model/Type Ref.:	HWCDPB-10K/MPWDPB-10K
Model differences:	N/A
Product Description:	HALO Wireless Charging Dock Power Bank 10K/mophie powerstation wireless dock
Operation Frequency:	115kHz-205kHz
Antenna installation:	Inductive loop coil antenna
Ratings:	Battery: DC 3.7V 10000mAh 37Wh Pogo Pin Input: DC 9V 2A Type-C PD Input: DC 5V 3A, DC 9V 2A, DC 12V 1.5A Wireless Output: 5W, 7.5W, 10W(Max) USB-A Output: DC 5V 3A, DC 9V 2A, DC 12V 1.5A Type-C Output: DC 5V 3A, DC 9V 2A, DC 12V 1.5A
Hardware Version:	S04
Software Version:	V1.4


4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Conducted Emission:



Radiated Spurious Emission:



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Data Cable	Remark
E-1	HALO Wireless Charging Dock Power Bank 10K/mophie powerstation wireless dock	HALO/ mophie	HWCDPB-10K /MPWDPB-10 K	N/A	N/A	EUT
E-2	Adapter	N/A	BCTC-001	N/A	Auxiliary	-
E-3	Dummy load	N/A	DL01	N/A	Auxiliary	-

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Modes1	Charging mode*
Test Modes2	Wireless output(5W)
Test Modes3	Wireless output(7.5W)
Test Modes4	Wireless output(10W)

Note:

All test mode were tested and passed, only Conducted Emissions, Radiated Emissions shows is the worst case mode which were recorded in this report.

4.5 Copy of marking plate



HALO Wireless Charging Dock Power Bank 10K

M/N: HWCDPB-10K

Battery: 3.7V 10000mAh 37Wh

USB-C Input: 5V \equiv 3A, 9V \equiv 2A, 12V \equiv 1.5APogo pin Input: 9V \equiv 2AUSB-C Output: 5V \equiv 3A, 9V \equiv 2A, 12V \equiv 1.5AUSB-A Output: 5V \equiv 3A, 9V \equiv 2A, 12V \equiv 1.5A

Wireless Output: 10W max

Multi Output: 5V \equiv 3A max FCC ID: QTG-HWCDPB10KFollow Manufacturer's Instructions.
Made In China. 2021QU 110-07848-A

mophie powerstation wireless dock

M/N: MPWDPB-10K

Battery: 3.7V 10000mAh 37Wh

USB-C Input: 5V \equiv 3A, 9V \equiv 2A, 12V \equiv 1.5APogo pin Input: 9V \equiv 2AUSB-C Output: 5V \equiv 3A, 9V \equiv 2A, 12V \equiv 1.5AUSB-A Output: 5V \equiv 3A, 9V \equiv 2A, 12V \equiv 1.5A

Wireless Output: 10W max

Multi Output: 5V \equiv 3A max

FCC ID: QTG-HWCDPB10K

© 2021 mophie inc. MADE IN CHINA 110-08678-A

ZAGG Inc | 910 Legacy Center Way, Ste. 500, Midvale, Utah 84047

ZAGG International | 103 Shannon Industrial Estate, Shannon Co. Clare,
V14 PH21, Ireland

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

IC Registered No.: 23583


5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 28, 2021	May 27, 2022
LISN	R&S	ENV216	101375	May 28, 2021	May 27, 2022
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Attenuator	\	10dB DC-6GHz	1650	May 28, 2021	May 27, 2022

Radiated Emissions Test (966 Chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	Jun. 06. 2020	Jun. 05, 2023
Receiver	R&S	ESR3	102075	May 28, 2021	May 27, 2022
Receiver	R&S	ESRP	101154	May 28, 2021	May 27, 2022
Amplifier	SKET	LAPA_01G18 G-45dB	\	May 28, 2021	May 27, 2022
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 28, 2021	May 27, 2022
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	Jun. 01, 2021	May 31, 2022
Horn Antenna	Schwarzbeck	BBHA9120D	1541	Jun. 02, 2021	Jun. 01, 2022
Horn Antenn(18GH z-40GHz)	Schwarzbeck	BBHA9170	00822	Jun. 15, 2021	Jun. 14, 2022
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 28, 2021	May 27, 2022
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	Jun. 02, 2021	Jun. 01, 2022
RF cables1(9kHz- 30MHz)	Huber+Suhnar	9kHz-30MHz	B1702988-000 8	May 28, 2021	May 27, 2022
RF cables2(30MH z-1GHz)	Huber+Suhnar	30MHz-1GHz	1486150	May 28, 2021	May 27, 2022
RF cables3(1GHz -40GHz)	Huber+Suhnar	1GHz-40GHz	1607106	May 28, 2021	May 27, 2022
Power Metter	Keysight	E4419	\	May 28, 2021	May 27, 2022
Power Sensor (AV)	Keysight	E9300A	\	May 28, 2021	May 27, 2022
Signal Analyzer20kH z-26.5GHz	Keysight	N9020A	MY49100060	May 28, 2021	May 27, 2022
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	\	May 28, 2021	May 27, 2022
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:
 1. *Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.

6.3 Test procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 1	Test Voltage:	AC 120V/60Hz




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1500	35.52	19.61	55.13	66.00	-10.87	QP
2		0.1500	19.78	19.61	39.39	56.00	-16.61	AVG
3		0.2971	27.17	19.61	46.78	60.32	-13.54	QP
4		0.2971	11.24	19.61	30.85	50.32	-19.47	AVG
5		0.6338	25.24	19.62	44.86	56.00	-11.14	QP
6		0.6338	10.49	19.62	30.11	46.00	-15.89	AVG
7	*	1.0541	27.63	19.63	47.26	56.00	-8.74	QP
8		1.0541	12.47	19.63	32.10	46.00	-13.90	AVG
9		6.3186	17.46	19.73	37.19	60.00	-22.81	QP
10		6.3186	8.27	19.73	28.00	50.00	-22.00	AVG
11		10.3972	20.04	19.80	39.84	60.00	-20.16	QP
12		10.3972	10.02	19.80	29.82	50.00	-20.18	AVG

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 1	Test Voltage:	AC 120V/60Hz


Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1500	29.50	19.61	49.11	66.00	-16.89	QP
2		0.1500	14.13	19.61	33.74	56.00	-22.26	AVG
3		0.2940	23.27	19.61	42.88	60.41	-17.53	QP
4		0.2940	7.47	19.61	27.08	50.41	-23.33	AVG
5	*	1.1940	27.72	19.63	47.35	56.00	-8.65	QP
6		1.1940	10.10	19.63	29.73	46.00	-16.27	AVG
7		3.9885	17.82	19.68	37.50	56.00	-18.50	QP
8		3.9885	4.41	19.68	24.09	46.00	-21.91	AVG
9		8.5515	20.51	19.77	40.28	60.00	-19.72	QP
10		8.5515	7.31	19.77	27.08	50.00	-22.92	AVG
11		12.8310	17.34	19.79	37.13	60.00	-22.87	QP
12		12.8310	6.44	19.79	26.23	50.00	-23.77	AVG


7. Radiated Emissions

7.1 Block Diagram Of Test Setup

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



7.2 Limit

FCC §15.209; §15.205.

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		74.0	Peak	3	

7.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).

h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis.

The worst case emissions were reported.

7.4 Test Result

9kHz-30MHz

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	DC 3.7V
Test Mode:	Mode 4(the worst data)	Polarization :	---

Frequency (kHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
21.03	42.53	20.15	62.68	141.15	-78.47	PK
21.03	45.85	20.15	66.00	121.15	-55.15	AV
60.13	51.36	20.33	71.69	132.02	-60.33	PK
60.13	45.85	20.33	66.18	112.02	-45.84	AV
150.84	63.62	20.55	84.17	124.03	-39.86	PK
150.84	61.43	20.55	81.98	104.03	-22.05	AV
519.03	37.15	20.64	57.79	73.30	-15.51	QP
751.66	36.72	21.26	57.98	70.51	-12.53	QP
1210.22	31.55	22.32	53.87	65.95	-12.08	QP

Note:


Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.

Margin = Emission Level- Limit.

Between 30MHz – 1GHz


Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 4(the worst data)	Test Voltage:	DC 3.7V



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		113.7143	42.80	-17.16	25.64	43.50	-17.86	QP
2		164.3301	41.29	-18.58	22.71	43.50	-20.79	QP
3		263.8190	47.30	-14.72	32.58	46.00	-13.42	QP
4		312.1794	51.97	-13.27	38.70	46.00	-7.30	QP
5	*	360.4476	50.71	-11.99	38.72	46.00	-7.28	QP
6		455.9058	42.71	-9.85	32.86	46.00	-13.14	QP

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 4(the worst data)	Test Voltage:	DC 3.7V



Remark:
 Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		112.5244	33.33	-17.09	16.24	43.50	-27.26	QP
2		159.7844	34.82	-18.87	15.95	43.50	-27.55	QP
3		252.0627	36.03	-15.09	20.94	46.00	-25.06	QP
4		312.1794	39.07	-13.27	25.80	46.00	-20.20	QP
5	*	360.4476	41.86	-11.99	29.87	46.00	-16.13	QP
6		434.0651	36.68	-10.33	26.35	46.00	-19.65	QP

8. EUT Photographs

EUT Photo 1




EUT Photo 2





9. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos



STATEMENT

- 1.The equipment lists are traceable to the national reference standards.
- 2.The test report can not be partially copied unless prior written approval is issued from our lab.
- 3.The test report is invalid without stamp of laboratory.
- 4.The test report is invalid without signature of person(s) testing and authorizing.
- 5.The test process and test result is only related to the Unit Under Test.
- 6.The quality system of our laboratory is in accordance with ISO/IEC17025.
- 7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL : 400-788-9558

P.C.: 518103

FAX : 0755-33229357

Website : <http://www.chnbctc.com>

E-Mail : bctc@bctc-lab.com.cn

***** END *****