



Shenzhen Centre Quality Accreditation Technology Co., Ltd.

Address:1 F., Block B of Complex Building, Baisha Logistics Park, No.3011
Shahe West Road, Nanshan District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report No.: CQASZ161201363E
Report Version: V01

MEASUREMENT REPORT

Test Report

Applicant: ZAGG Inc.

Address of Applicant: 910 West Legacy Center Way Midvale, Utah, United States, 84047

Manufacturer: ZAGG Inc.

Address of Manufacturer: 910 West Legacy Center Way Midvale, Utah, United States, 84047

Equipment Under Test (EUT):

Product: Coda Wireless Speaker

Model No.: IFOPBS-BK0, IFOPBS-BL0, IFOPBS-RD0, IFOPBS-RG0

Test Model No.: IFOPBS-BK0

Brand Name: IFROGZ


FCC ID: QTG-IFOPBS

Standards: 47 CFR Part 15, Subpart C


Date of Test: 2016-12-30 to 2017-01-13

Date of Issue: 2017-02-10


Test Result : **PASS***

Reviewed By: 

(Aaron Ma)

Approved By: 

(Owen Zhou)



* In the configuration tested, the EUT complied with the standards specified above.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ161201363E	Rev.01	Initial report	2017-02-10

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

3 Contents

	Page
COVER PAGE	1
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 TEST ENVIRONMENT	7
4.4 DESCRIPTION OF SUPPORT UNITS	7
4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	8
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
4.8 EQUIPMENT LIST	9
5 TEST RESULTS AND MEASUREMENT DATA	10
5.1 ANTENNA REQUIREMENT	10
5.2 CONDUCTED EMISSIONS	11
5.3 CONDUCTED PEAK OUTPUT POWER	14
5.4 20dB OCCUPY BANDWIDTH	21
5.5 CARRIER FREQUENCIES SEPARATION	27
5.6 HOPPING CHANNEL NUMBER	34
5.7 DWELL TIME	37
5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	43
5.9 SPURIOUS RF CONDUCTED EMISSIONS	50
5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	69
5.11 RADIATED SPURIOUS EMISSION	71
5.11.1 <i>Radiated Emission below 1GHz</i>	74
5.11.2 <i>Transmitter Emission above 1GHz</i>	76
5.12 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	78
6 PHOTOGRAPHS - EUT TEST SETUP	81
6.1 CONDUCTED EMISSION	81
6.2 RADIATED EMISSION	81
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	83

4 General Information

4.1 Client Information

Applicant:	ZAGG Inc.
Address of Applicant:	910 West Legacy Center Way Midvale, Utah, United States, 84047
Manufacturer:	ZAGG Inc.
Address of Manufacturer:	910 West Legacy Center Way Midvale, Utah, United States, 84047

4.2 General Description of EUT

Product Name:	Coda Wireless Speaker
Model No.:	IFOPBS-BK0, IFOPBS-BL0, IFOPBS-RD0, IFOPBS-RG0
Test Model No.:	IFOPBS-BK0
Trade Mark:	IFROGZ
Hardware Version:	JY-BK-LSB32 V2.0
Software Version:	BK3254_28P_JY_(IFROG CODE SP)_YGO_MFB_MIC_V2.5
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.1
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	portable production
Test Software of EUT:	RF Test (manufacturer declare)
Antenna Type:	Integral antenna
Antenna Gain:	1.0dBi
Power Supply:	Lithium ion batteries: DC3.7V Charging by USB: DC5V

Note: The new battery is used for testing.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

4.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	995mbar
Test Mode:	Use test software (RF Test) to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
PC	Lenovo	Lenovo ideapad 100-14IBY	Provide by lab	DOC
Mouse	Lenovo	KM040	Provide by lab	DOC
AC/DC Adapter	Lenovo	PA-1450-55LN	Provide by lab	DOC
Adapter	HCSD	HCSD-288D50100	Provide by lab	DOC

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Tongce Testing Lab** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for **TCT** laboratory is reported:

Test	Range	Uncertainty	Notes
Radiated Emission	Below 1GHz	±3.92dB	(1)
Radiated Emission	Above 1GHz	±4.28dB	(1)
Conducted Disturbance	0.15~30MHz	±2.56dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.6 Test Location

Shenzhen Tongce Testing Lab,

1F, Leinu Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 572331

Shenzhen Tongce Testing Lab has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 572331

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Equipment List


Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
1	ESPI Test Receiver	R&S	ESVD	100008	2017/08/11
2	Spectrum Analyzer	R&S	FSEM	848597/001	2017/08/11
3	Spectrum Analyzer	Agilent	N9020A	MY49100060	2017/08/12
4	Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	2017/08/11
5	Pre-amplifier	HP	8447D	2727A05017	2017/08/11
6	Loop antenna	ZHINAN	ZN30900A	12024	2017/08/13
7	Broadband Antenna	R&S	VULB9163	340	2017/08/13
8	Horn Antenna	R&S	BBHA 9120D	631	2017/08/13
9	Horn Antenna	R&S	BBHA 9170	373	2017/08/13
10	Antenna Mast	CCS	CC-A-4M	N/A	N/A
11	Coax cable (9KHz~40GHz)	TCT	RE-low-01	N/A	2017/08/11
12	Coax cable (9KHz~40GHz)	TCT	RE-high-02	N/A	2017/08/11
13	Coax cable (9KHz~40GHz)	TCT	RE-low-02	N/A	2017/08/11
14	Coax cable (9KHz~40GHz)	TCT	RE-high-04	N/A	2017/08/11
15	Spectrum Analyzer	R&S	FSU	200054	2017/08/11
16	Antenna Connector	TCT	RFC-01	N/A	2017/08/12
17	RF cable(9KHz~40GHz)	TCT	RE-06	N/A	2017/08/12
18	LISN	R&S	NSLK 8126	8126453	2017/08/16

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
EUT Antenna:	
<p>The antenna is Integral antenna and no consideration of replacement. The best case gain of the antenna is 1.0dBi.</p>	

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207														
Test Method:	ANSI C63.10: 2013														
Test Frequency Range:	150kHz to 30MHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Setup:															


Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.


Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



	Read Freq	Level	LISII Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.17	32.34	9.73	42.07	65.08	-23.01	Peak
2	0.19	30.64	9.74	40.38	63.98	-23.60	Peak
3	0.23	29.15	9.74	38.89	62.39	-23.50	Peak
4	0.32	27.16	9.74	36.90	59.80	-22.90	Peak
5	0.37	25.83	9.74	35.57	58.56	-22.99	Peak
6 pp	0.55	30.34	9.74	40.08	56.00	-15.92	Peak

Neutral line:




	Read Freq	Level	LISN Factor	Limit Level	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1 pk	0.49	30.73	9.80	40.53	56.14	-15.61 Peak
2 pp	0.55	29.60	9.80	39.40	46.00	-6.60 Average
3 qp	0.55	34.60	9.80	44.40	56.00	-11.60 QP
4	0.80	26.32	9.80	36.12	56.00	-19.88 Peak
5	1.09	26.08	9.82	35.90	56.00	-20.10 Peak
6	1.39	24.80	9.84	34.64	56.00	-21.36 Peak
7	1.67	24.69	9.86	34.55	56.00	-21.45 Peak

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer</p> <p style="text-align: center;">E.U.T</p> <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p> <p><i>Remark:</i> Factor: the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Limit:	30dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-0.44	21.00	Pass
Middle	2.69	21.00	Pass
Highest	2.98	21.00	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-2.58	21.00	Pass
Middle	0.41	21.00	Pass
Highest	0.64	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-2.15	21.00	Pass
Middle	1.16	21.00	Pass
Highest	1.41	21.00	Pass

Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




*RBW 3 MHz Marker 1 [T1]
 *VBW 3 MHz 2.98 dBm
 Ref 21.5 dBm *Att 30 dB SWT 2.5 ms 2.479879808 GHz




Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------




*RBW 3 MHz Marker 1 [T1]
 *VBW 3 MHz -2.58 dBm
 Ref 21.5 dBm *Att 30 dB SWT 2.5 ms 2.401959936 GHz




Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------



Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------



Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------




Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------



* RBW 3 MHz Marker 1 [T1]
 * VBW 3 MHz 1.41 dBm
 SWT 2.5 ms 2.479959936 GHz


Ref 21.5 dBm * Att 30 dB

1 PK
MAXH



Center 2.48 GHz 2.5 MHz/

5.4 20dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data


Test channel	20dB Occupy Bandwidth (kHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	894.23	1216.35	1216.35
Middle	899.04	1216.35	1216.35
Highest	894.23	1216.35	1216.35

Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



*RBW 30 kHz Marker 1 [T1]
 *VBW 100 kHz 0.87 dBm
 Ref 21.5 dBm *Att 30 dB SWT 15 ms 2.480000000 GHz

1 PK
MAXH




Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------



*RBW 30 kHz Marker 1 [T1]
 *VBW 100 kHz -5.30 dBm
 Ref 21.5 dBm *Att 30 dB SWT 15 ms 2.402000000 GHz

1 PK
MAXH




Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------



*RBW 30 kHz Marker 1 [T1] -2.18 dBm
 *VBW 100 kHz
 Ref 21.5 dBm *Att 30 dB SWT 15 ms 2.441000000 GHz

1 PK
MAXH




Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------



*RBW 30 kHz Marker 1 [T1] -1.90 dBm
 *VBW 100 kHz
 Ref 21.5 dBm *Att 30 dB SWT 15 ms 2.480000000 GHz

1 PK
MAXH




Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------



*RBW 30 kHz Marker 1 [T1]
 *VBW 100 kHz -5.31 dBm
 Ref 21.5 dBm *Att 30 dB SWT 15 ms 2.402000000 GHz

1 PR
MAXH




Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------



*RBW 30 kHz Marker 1 [T1]
 *VBW 100 kHz -2.17 dBm
 Ref 21.5 dBm *Att 30 dB SWT 15 ms 2.441000000 GHz


1 PR
MAXH




Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------



1 PK
MAXH



5.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Limit:	2/3 of the 20dB bandwidth Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

GFSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1001.6	≥599.36	Pass
Middle	1001.6	≥599.36	Pass
Highest	1001.6	≥599.36	Pass
π/4DQPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1001.6	≥810.90	Pass
Middle	1001.6	≥810.90	Pass
Highest	1001.6	≥810.90	Pass
8DPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1001.6	≥810.90	Pass
Middle	1001.6	≥810.90	Pass
Highest	1001.6	≥810.90	Pass

Note: According to section 6.4,


Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	899.04	599.36
π/4DQPSK	1216.35	810.90
8DPSK	1216.35	810.90

Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




*RBW 100 kHz Delta 2 [T1] -1.69 dB
 *VBW 300 kHz
 Ref 21.5 dBm *Att 30 dB SWT 2.5 ms -1.001602564 MHz




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------




*RBW 100 kHz Delta 2 [T1] -0.05 dB
 *VBW 300 kHz
 Ref 21.5 dBm *Att 30 dB SWT 2.5 ms -1.001602564 MHz




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------



Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------



Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------




Ref 21.5 dBm * Att 30 dB * RBW 100 kHz Delta 2 [T1] -1.65 dB
 * VBW 300 kHz -1.001602564 MHz
 SWT 2.5 ms



Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------




Ref 21.5 dBm * Att 30 dB * RBW 100 kHz Delta 2 [T1] -0.04 dB
 * VBW 300 kHz -1.001602564 MHz
 SWT 2.5 ms




Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------



* RBW 100 kHz Delta 2 [T1]
 * VBW 300 kHz -0.06 dB
 * Att 30 dB SWT 2.5 ms -1.001602564 MHz
 Ref 21.5 dBm Offset 1.1 dB



5.6 Hopping Channel Number


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Limit:	At least 15 channels
Test Mode:	Hopping transmitting with all kind of modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data


Mode	Hopping channel numbers	Limit
GFSK	79	≥15
$\pi/4$ DQPSK	79	≥15
8DPSK	79	≥15

Test plot as follows:

Test mode:	GFSK
------------	------




Test mode:	$\pi/4$ DQPSK
------------	---------------




Test mode: 8DPSK



* RBW 100 kHz Delta 2 [T1]
 * VBW 300 kHz 3.06 dB
 SWT 10 ms 78.013621795 MHz



5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	
Instruments Used:	Refer to section 5.10 for details
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.124	≤0.4
	DH3	0.262	≤0.4
	DH5	0.309	≤0.4
π/4DQPSK	2-DH1	0.130	≤0.4
	2-DH3	0.266	≤0.4
	2-DH5	0.309	≤0.4
8DPSK	3-DH1	0.128	≤0.4
	3-DH3	0.265	≤0.4
	3-DH5	0.310	≤0.4

Test Result:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

The lowest channel (2402MHz), middle channel (2441MHz), highest channel (2480MHz) as below

$$\text{DH1 time slot} = 0.389(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 124\text{ms}$$

$$\text{DH3 time slot} = 1.639(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 262\text{ms}$$


$$\text{DH5 time slot} = 2.901(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 309\text{ms}$$

Test plot as follows:

Test Packet:	DH1
--------------	-----




1 PK
VIEW



Test Packet:	DH3
--------------	-----




1 PK
VIEW



Test Packet:	DH5
--------------	-----




Ref 21.5 dBm * Att 30 dB
 RBW 1 MHz Delta 3 [T1] -50.55 dB
 * VBW 1 MHz SWT 7.5 ms 3.729968 ms



Test Packet:	2-DH1
--------------	-------




Ref 21.5 dBm * Att 30 dB
 RBW 1 MHz Delta 3 [T1] -51.87 dB
 * VBW 1 MHz SWT 2.5 ms 1.229968 ms



Test Packet:	2-DH3
--------------	-------




Ref 21.5 dBm *Att 30 dB RBW 1 MHz Delta 3 [T1]
 *VBW 1 MHz -49.61 dB
 SWT 5 ms 2.487981 ms



Test Packet:	2-DH5
--------------	-------




Ref 21.5 dBm *Att 30 dB RBW 1 MHz Delta 3 [T1]
 *VBW 1 MHz -53.25 dB
 SWT 7.5 ms 3.713942 ms



Test Packet:	3-DH1
--------------	-------




Ref 21.5 dBm * Att 30 dB RBW 1 MHz Delta 3 [T1] -52.22 dB
 * VBW 1 MHz SWT 2.5 ms 1.229968 ms



Test Packet:	3-DH3
--------------	-------




Ref 21.5 dBm * Att 30 dB RBW 1 MHz Delta 3 [T1] -52.52 dB
 * VBW 1 MHz SWT 5 ms 2.479968 ms




Test Packet:	3-DH5
--------------	-------



RBW 1 MHz Delta 3 [T1] -50.50 dB
 * VBW 1 MHz -50.50 dB
 Ref 21.5 dBm * Att 30 dB SWT 7.5 ms 3.717949 ms





5.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>Remark: Factor: the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------





*RBW 100 kHz Marker 1 [T1] 2.45 dBm
 *VBW 300 kHz
 Ref 21.5 dBm *Att 30 dB SWT 10 ms 2.479807692 GHz



*RBW 100 kHz Marker 1 [T1] 2.45 dBm
 *VBW 300 kHz
 Ref 21.5 dBm *Att 30 dB SWT 10 ms 2.479807692 GHz



Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -0.99 dBm
 *Att 30 dB 2.480008013 GHz
 SWT 10 ms

Ref 21.5 dBm Offset 1.5 dB


1 PK
VIEW





*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -0.99 dBm
 *Att 30 dB 2.480008013 GHz
 SWT 10 ms

Ref 21.5 dBm Offset 1.5 dB

1 PK
VIEW




Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------




Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------




*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -0.98 dBm
 Ref 21.5 dBm *Att 30 dB SWT 10 ms 2.479847756 GHz





*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -0.97 dBm
 Ref 21.5 dBm *Att 30 dB SWT 10 ms 2.480008013 GHz



5.9 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>Remark: Factor: the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------








*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -52.96 dBm
 SWT 125 ms 4.482566667 GHz



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -0.90 dBm
 SWT 2.5 s 2.401317667 GHz




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------








*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -53.45 dBm
 SWT 125 ms 4.310133333 GHz



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 0.94 dBm
 SWT 2.5 s 2.440437333 GHz




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------








*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -52.78 dBm
 SWT 125 ms 4.379533333 GHz





*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 1.61 dBm
 SWT 2.5 s 2.479557000 GHz







Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------





Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------






Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------



* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -52.77 dBm
 SWT 125 ms 1.636833333 GHz

Ref 21.5 dBm * Att 30 dB

1 PK
MAXH




Start 1 GHz 100 MHz/ Stop 2 GHz





* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -1.22 dBm
 SWT 125 ms 2.479966667 GHz

Ref 21.5 dBm * Att 30 dB



1 PK
VIEW



Start 2 GHz 100 MHz/ Stop 3 GHz




Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------








*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz -53.74 dBm
SWT 125 ms 4.674166667 GHz



*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz -5.07 dBm
SWT 2.5 s 2.402150000 GHz




Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------








*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -53.09 dBm
 SWT 125 ms 4.519500000 GHz





*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -1.97 dBm
 SWT 2.5 s 2.440437333 GHz



Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------







Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
<p>The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p> <p>Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.</p> <p>The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.</p>	
<p>Compliance for section 15.247(a)(1)</p>	
<p>According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</p> <ul style="list-style-type: none"> • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <div data-bbox="300 1375 1355 1527" data-label="Diagram">  </div> <p style="text-align: center;"><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> <p>An example of Pseudorandom Frequency Hopping Sequence as follow:</p> <div data-bbox="274 1624 1262 1771" data-label="Diagram">  </div> <p>Each frequency used equally on the average by each transmitter.</p> <p>According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.</p>	
<p>Compliance for section 15.247(g)</p>	
<p>According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.</p>	

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

5.11 Radiated Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a.
 - 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	<p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
<p>Exploratory Test Mode:</p>	<p>Non-hopping transmitting mode with all kind of modulation and all kind of data type</p>
<p>Final Test Mode:</p>	<p>Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode, For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.</p>
<p>Instruments Used:</p>	<p>Refer to section 5.10 for details</p>
<p>Test Results:</p>	<p>Pass</p>


5.11.1 Radiated Emission below 1GHz

30MHz~1GHz (PEAK)		
Test mode:	Transmitting	Vertical



	Ant Freq	Cable Factor	Cable Loss	Read Level	Limit Level	Over Limit	Remark	Pol/Phase
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	33.92	21.24	0.31	10.10	31.65	40.00	-8.35	Peak
2	143.83	9.10	0.56	12.75	22.41	43.50	-21.09	Peak
3	207.12	9.66	0.70	12.38	22.74	43.50	-20.76	Peak
4	437.12	15.74	1.05	11.47	28.26	46.00	-17.74	Peak
5	568.61	17.50	1.27	11.24	30.01	46.00	-15.99	Peak
6	932.27	22.16	1.67	10.96	34.79	46.00	-11.21	Peak

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Ant Freq	Factor	Cable Loss	Read Level	Level	Limit Line	Over Limit	Remark	Pol/Phase	
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB			
1	pp	30.11	21.13	0.31	10.46	31.90	40.00	-8.10	Peak	HORIZONTAL
2		33.68	21.06	0.31	10.43	31.80	40.00	-8.20	Peak	HORIZONTAL
3		115.73	10.41	0.49	10.54	21.44	43.50	-22.06	Peak	HORIZONTAL
4		208.58	9.73	0.70	12.29	22.72	43.50	-20.78	Peak	HORIZONTAL
5		313.28	12.90	0.85	11.13	24.88	46.00	-21.12	Peak	HORIZONTAL
6		487.32	16.50	1.15	11.49	29.14	46.00	-16.86	Peak	HORIZONTAL

5.11.2 Transmitter Emission above 1GHz

Worse case mode:	GFSK(DH1)	Test channel:	Lowest
------------------	-----------	---------------	--------

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4804	49.36	-5.18	44.18	74	-29.82	peak	H
4804	36.85	-5.18	31.67	54	-22.33	AVG	H
7206	49.80	-6.45	43.35	74	-30.65	peak	H
7206	35.17	-6.45	28.72	54	-25.28	AVG	H
4804	49.18	-5.18	44.00	74	-30.00	peak	V
4804	36.32	-5.18	31.14	54	-22.86	AVG	V
7206	49.86	-6.45	43.41	74	-30.59	peak	V
7206	36.71	-6.45	30.26	54	-23.74	AVG	V

Worse case mode:	GFSK(DH1)	Test channel:	Middle
------------------	-----------	---------------	--------

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4882	49.83	-5.19	44.64	74	-29.36	peak	H
4882	37.58	-5.19	32.39	54	-21.61	AVG	H
7323	48.45	-6.47	41.98	74	-32.02	peak	H
7323	35.95	-6.47	29.48	54	-24.52	AVG	H
4882	49.25	-5.19	44.06	74	-29.94	peak	V
4882	37.37	-5.19	32.18	54	-21.82	AVG	V
7323	50.04	-6.47	43.57	74	-30.43	peak	V
7323	35.85	-6.47	29.38	54	-24.62	AVG	V

Worse case mode:	GFSK(DH1)	Test channel:	Highest
------------------	-----------	---------------	---------

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4960	49.76	-5.2	44.56	74	-29.44	peak	H
4960	37.34	-5.2	32.14	54	-21.86	AVG	H
7440	49.30	-6.47	42.83	74	-31.17	peak	H
7440	37.78	-6.47	31.31	54	-22.69	AVG	H
4960	50.12	-5.2	44.92	74	-29.08	peak	V
4960	37.89	-5.2	32.69	54	-21.31	AVG	V
7440	50.52	-6.47	44.05	74	-29.95	peak	V
7440	37.78	-6.47	31.31	54	-22.69	AVG	V

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

<p>Test Procedure:</p>	<p>a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</p> <p>g. Test the EUT in the lowest channel , the Highest channel</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
<p>Exploratory Test Mode:</p>	<p>Non-hopping transmitting mode with all kind of modulation and all kind of data type</p>
<p>Final Test Mode:</p>	<p>Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case Only the worst case is recorded in the report.</p>
<p>Instruments Used:</p>	<p>Refer to section 5.10 for details</p>
<p>Test Results:</p>	<p>Pass</p>

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Vertical
------------------	------------	---------------	--------	---------	----------

Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2390	48.53	-4.36	44.17	74	-29.83	peak
2390	35.58	-4.36	31.22	54	-22.78	AVG
2400	53.43	-4.36	49.07	74	-24.93	peak
2400	40.37	-4.36	36.01	54	-17.99	AVG

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Horizontal
------------------	------------	---------------	--------	---------	------------

Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2390	46.46	-4.36	42.10	74	-31.90	peak
2390	35.29	-4.36	30.93	54	-23.07	AVG
2400	53.90	-4.36	49.54	74	-24.46	peak
2400	40.60	-4.36	36.24	54	-17.76	AVG

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Vertical
------------------	------------	---------------	---------	---------	----------

Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2483.5	59.53	-4.22	55.31	74	-18.69	peak
2483.5	47.21	-4.22	42.99	54	-11.01	AVG

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Horizontal
------------------	------------	---------------	---------	---------	------------

Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
2483.5	59.81	-4.22	55.59	74	-18.41	peak
2483.5	45.86	-4.22	41.64	54	-12.36	AVG

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor


6 Photographs - EUT Test Setup

6.1 Conducted Emission



6.2 Radiated Emission

Below 1GHz:




Above 1GHz:





7 Photographs - EUT Constructional Details







Test Model No.: IFOPBS-BK0



















END OF THE REPORT