

Report No.: SZEM151000664802

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 95

FCC REPORT

Application No: SZEM1510006648CR

Applicant: ZAGG Inc Manufacturer: ZAGG Inc

Factory: Shenzhen Aoni Electronic Industry Co., Ltd

Product Name: ZAGG Now Cam

Model No.(EUT): ZGACTC-GY0

Add Model No.: ZGACTC-WH0

Trade Mark: ZAGG

FCC ID: QTG-ZCAM

Standards: 47 CFR Part 15, Subpart C (2014)

Date of Receipt: 2015-11-12

Date of Test: 2015-11-17 to 2015-12-03

Date of Issue: 2015-12-04

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM151000664802

Page: 2 of 95

2 Version

Revision Record					
Version Chapter Date Modifier Remark					
00		2015-12-04		Original	

Authorized for issue by:		
Tested By	Gebin Sun	2015-12-03
	(Gebin Sun) /Project Engineer	Date
Prepared By	Venus Wu	2015-12-04
	(Venus Wu) /Clerk	Date
Checked By	Eric Fu	2015-12-04
	(Eric Fu) /Reviewer	Date



Report No.: SZEM151000664802

Page: 3 of 95

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2009)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS

Remark:

Model No.: ZGACTC-GY0, ZGACTC-WH0

Only the Model ZGACTC-GY0 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models. Only different on model No. and color.



Report No.: SZEM151000664802

Page: 4 of 95

4 Contents

		Page
1	COVER PAGE	1
2	2 VERSION	2
3		_
4	CONTENTS	4
5	GENERAL INFORMATION	5
	5.1 CLIENT INFORMATION	5
	5.2 GENERAL DESCRIPTION OF EUT	
	5.3 TEST ENVIRONMENT	
	5.4 DESCRIPTION OF SUPPORT UNITS	7
	5.5 TEST LOCATION	7
	5.6 Test Facility	
	5.7 DEVIATION FROM STANDARDS	
	5.8 ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10 EQUIPMENT LIST	
6	TEST RESULTS AND MEASUREMENT DATA	11
	6.1 Antenna Requirement	11
	6.2 CONDUCTED PEAK OUTPUT POWER	12
	6.3 20DB OCCUPY BANDWIDTH	
	6.4 CARRIER FREQUENCIES SEPARATION	
	6.5 HOPPING CHANNEL NUMBER	
	6.6 DWELL TIME	
	6.7 BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.8 SPURIOUS RF CONDUCTED EMISSIONS	
	6.9 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	
	6.10.1 Radiated Emission below 1GHz	
	6.10.2 Transmitter Emission above 1GHz	
	6.11 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7		
•		
	7.1 RADIATED SPURIOUS EMISSION	94
Ω	R PHOTOGRAPHS - FUT CONSTRUCTIONAL DETAILS	05



Report No.: SZEM151000664802

Page: 5 of 95

5 General Information

5.1 Client Information

Applicant:	ZAGG Inc	
Address of Applicant:	3855 South 500 West, Suite Q Salt Lake City, Utah, 84115	
Manufacturer:	ZAGG Inc	
Address of Manufacturer:	3855 South 500 West, Suite Q Salt Lake City, Utah, 84115	
Factory:	Shenzhen Aoni Electronic Industry Co., Ltd	
Address of Factory:	No.5,Bldg.,Honghui Industrial Park, 2nd Liuxian, Xin'an, Bao'an District, SZ, China	

5.2 General Description of EUT

Product Name:	ZAGG Now Cam		
Model No.:	ZGACTC-GY0		
Trade Mark:	ZAGG		
Carrier Frequency:	BT 2402-2480MHz		
Bluetooth Version:	BT4.1		
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)		
Modulation Type:	GFSK, π/4DQPSK, 8DPSK		
Number of Channel:	79		
Hopping Channel Type:	Adaptive Frequency Hopping syste	ems	
Sample Type:	Portable production		
Antenna Type:	Integral		
Antenna Gain:	0.5dBi		
Battery Lithium-ion battery:3.7V 300mAh(charge by USB)		charge by USB)	



Report No.: SZEM151000664802

Page: 6 of 95

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency		
The Lowest channel	2402MHz		
The Middle channel	2441MHz		
The Highest channel	2480MHz		



Report No.: SZEM151000664802

Page: 7 of 95

5.3 Test Environment

Operating Environment:				
Temperature:	25.0 °C			
Humidity:	53 % RH			
Atmospheric Pressure:	1015mbar			

5.4 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Test Board	Supplied by client	V1.2	N/A

Remark: The test board is only use to configure the engineering mode and it has not been used during the test.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM151000664802

Page: 8 of 95

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM151000664802

Page: 9 of 95

5.10 Equipment List

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEL0198	2016-03-01
2	EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEL0175	2016-05-13
3	EMI Test software	AUDIX	E3	SEL0201	N/A
4	Coaxial cable	SGS	N/A	SEL0202	2016-03-01
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2017-11-15
6	Amplifier (0.1-1300MHz)	HP	8447D	SEL0153	2016-10-09

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2016-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2016-10-09
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	Coaxial cable	SGS	N/A	SEL0028	2016-05-13
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	2017-11-01
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2016-05-13
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0005	2018-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2016-10-17
9	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2017-11-24
10	Band filter	Amindeon	Asi 3314	SEL0094	2016-05-13
11	Loop Antenna	ETS-LINDGREN	6502	SEL0802	2016-08-14



Report No.: SZEM151000664802

Page: 10 of 95

RF connected test						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24	2016-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-17	2016-10-17
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25
8	POWER METER	R&S	NRVS	SEL0144	2015-10-09	2016-10-09
9	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-04-25	2016-04-25



Report No.: SZEM151000664802

Page: 11 of 95

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.



Report No.: SZEM151000664802

Page: 12 of 95

6.2 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)		
Test Method:	ANSI C63.10:2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Limit:	30dBm		
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.		
Instruments Used:	Refer to section 5.10 for details		
Test Results:	Pass		





Report No.: SZEM151000664802

Page: 13 of 95

Measurement Data

measurement Data					
GFSK mode					
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result		
Lowest	-0.17	30.00	Pass		
Middle	-2.20	30.00	Pass		
Highest	-5.66	30.00	Pass		
	π/4DQPSK m	node			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result		
Lowest	0.22	30.00	Pass		
Middle	-1.62	30.00	Pass		
Highest	-5.20	30.00	Pass		
	8DPSK mode				
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result		
Lowest	0.33	30.00	Pass		
Middle	-1.40	30.00	Pass		
Highest	-5.29	30.00	Pass		




Report No.: SZEM151000664802


Page: 14 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM151000664802

Page: 15 of 95

Test mode: GFSK Test channel: Highest











Report No.: SZEM151000664802

Page: 16 of 95

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM151000664802

Page: 17 of 95

Test mode: 8DPSK Test channel: Lowest











Report No.: SZEM151000664802

Page: 18 of 95








Report No.: SZEM151000664802

Page: 19 of 95

6.3 20dB Occupy Bandwidth



Measurement Data

Toot shannal	20dB Occupy Bandwidth (kHz)		
Test channel	GFSK	π/4DQPSK	8DPSK
Lowest	843.000	1248.000	1218.000
Middle	849.000	1245.000	1224.000
Highest	915.000	1248.000	1227.000




Report No.: SZEM151000664802


Page: 20 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM151000664802

Page: 21 of 95

Test mode: GFSK Test channel: Highest











Report No.: SZEM151000664802

Page: 22 of 95

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM151000664802

Page: 23 of 95

Test mode: 8DPSK Test channel: Lowest











Report No.: SZEM151000664802

Page: 24 of 95








Report No.: SZEM151000664802

Page: 25 of 95

6.4 Carrier Frequencies Separation





Report No.: SZEM151000664802

Page: 26 of 95

Measurement Data

Wicasarcinicit Bata					
GFSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Middle	1011.000	≥610.000	Pass		
	π/4DQPSK mode				
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Middle	1011.000	≥832.000	Pass		
8DPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Middle	996.000	≥818.000	Pass		

Note: According to section 6.4,

Mode	20dB bandwidth (kHz)	Limit (kHz)	
	(worse case)	(Carrier Frequencies Separation)	
GFSK	915.000	610.000	
π/4DQPSK	1248.000	832.000	
8DPSK	1227.000	818.000	




Report No.: SZEM151000664802


Page: 27 of 95

Test plot as follows:

Test mode:	GFSK	Test channel:	Middle
1 CSt IIIOGC.	Gran	i Cot Chariner.	I WIIGGIC











Report No.: SZEM151000664802

Page: 28 of 95








Report No.: SZEM151000664802

Page: 29 of 95

6.5 Hopping Channel Number



Measurement Data

Mode	Hopping channel numbers	Limit	
GFSK	79	≥15	
π/4DQPSK	79	≥15	
8DPSK	79	≥15	





Report No.: SZEM151000664802


Page: 30 of 95

Test plot as follows:

Test mode: GFSK











Report No.: SZEM151000664802

Page: 31 of 95








Report No.: SZEM151000664802

Page: 32 of 95

6.6 Dwell Time



Measurement Data

weasurement bata				
Mode	Packet	Dwell time (second)	Limit (second)	
	DH1	0.119	0.4	
GFSK	DH3	0.296	0.4	
	DH5	0.214	0.4	
	2-DH1	0.129	0.4	
π/4DQPSK	2-DH3	0.279	0.4	
	2-DH5	0.203	0.4	
	3-DH1	0.105	0.4	
8DPSK	3-DH3	0.279	0.4	
	3-DH5	0.377	0.4	





Report No.: SZEM151000664802

Page: 33 of 95

Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

On (ms)*total number=dwell time (ms)

The middle channel (2402MHz), as below:

DH1 time slot= 0.383(ms)*total number= 118.730 (ms)

DH3 time slot= 1.644 (ms)* total number = 295.92 (ms)

DH5 time slot= 1.648 (ms)* total number = 214.240 (ms)

2-DH1 time slot= 0.390 (ms)*total number= 128.700 (ms)

2-DH3 time slot= 1.641 (ms)* total number = 278.970 (ms)

2-DH5 time slot= 2.900 (ms)* total number = 203.000 (ms)

3-DH1 time slot= 0.390 (ms)*total number= 105.300(ms)

3-DH3 time slot= 1.641 (ms)* total number = 278.970 (ms)

3-DH5 time slot= 2.900 (ms)* total number = 377.000(ms)





Report No.: SZEM151000664802

Page: 34 of 95

Test plot as follows:











Report No.: SZEM151000664802

Page: 35 of 95











Report No.: SZEM151000664802

Page: 36 of 95











Report No.: SZEM151000664802

Page: 37 of 95











Report No.: SZEM151000664802

Page: 38 of 95












Report No.: SZEM151000664802

Page: 39 of 95











Report No.: SZEM151000664802

Page: 40 of 95












Report No.: SZEM151000664802

Page: 41 of 95











Report No.: SZEM151000664802

Page: 42 of 95











Report No.: SZEM151000664802

Page: 43 of 95

6.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2009
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass





Report No.: SZEM151000664802

Page: 44 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM151000664802

Page: 45 of 95











Report No.: SZEM151000664802

Page: 46 of 95












Report No.: SZEM151000664802

Page: 47 of 95












Report No.: SZEM151000664802

Page: 48 of 95












Report No.: SZEM151000664802

Page: 49 of 95









Report No.: SZEM151000664802

Page: 50 of 95


6.8 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2009
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Report No.: SZEM151000664802

Page: 51 of 95











Report No.: SZEM151000664802

Page: 52 of 95











Report No.: SZEM151000664802

Page: 53 of 95









Report No.: SZEM151000664802

Page: 54 of 95











Report No.: SZEM151000664802

Page: 55 of 95









Report No.: SZEM151000664802

Page: 56 of 95









Report No.: SZEM151000664802

Page: 57 of 95











Report No.: SZEM151000664802

Page: 58 of 95









Report No.: SZEM151000664802

Page: 59 of 95









Report No.: SZEM151000664802

Page: 60 of 95











Report No.: SZEM151000664802

Page: 61 of 95









Report No.: SZEM151000664802

Page: 62 of 95









Report No.: SZEM151000664802

Page: 63 of 95











Report No.: SZEM151000664802

Page: 64 of 95









Report No.: SZEM151000664802

Page: 65 of 95










Report No.: SZEM151000664802

Page: 66 of 95











Report No.: SZEM151000664802

Page: 67 of 95









Report No.: SZEM151000664802

Page: 68 of 95









Report No.: SZEM151000664802

Page: 69 of 95











Report No.: SZEM151000664802

Page: 70 of 95









Report No.: SZEM151000664802

Page: 71 of 95









Report No.: SZEM151000664802

Page: 72 of 95













Report No.: SZEM151000664802

Page: 73 of 95









Report No.: SZEM151000664802

Page: 74 of 95










Report No.: SZEM151000664802

Page: 75 of 95











Report No.: SZEM151000664802

Page: 76 of 95









Report No.: SZEM151000664802

Page: 77 of 95





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM151000664802

Page: 78 of 95

6.9 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage


outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- · Number of shift register stages: 9
- Length of pseudo-random sequence: 29 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift



Report No.: SZEM151000664802

Page: 79 of 95

frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: SZEM151000664802

Page: 80 of 95

6.10 Radiated Spurious Emission


Test Requirement:	47 CFR Part 15C Section	on 1	5.209 and 15.	205				
Test Method:	ANSI C63.10: 2009							
Test Site:	Measurement Distance	Measurement Distance: 3m (Semi-Anechoic Chamber)						
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark		
	0.009MHz-0.090MH	Z	Peak	10kHz	z 30kHz	Peak		
	0.009MHz-0.090MH	Z	Average	10kHz	z 30kHz	Average		
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	z 30kHz	Quasi-peak		
	0.110MHz-0.490MH	z	Peak	10kHz	z 30kHz	Peak		
	0.110MHz-0.490MH	Z	Average	10kHz	z 30kHz	Average		
	0.490MHz -30MHz		Quasi-peak	10kHz	30kHz	Quasi-peak		
	30MHz-1GHz		Quasi-peak	100 kH	lz 300kHz	Quasi-peak		
	Above 1GHz		Peak	1MHz	3MHz	Peak		
	Above 1GHz		Peak	1MHz	10Hz	Average		
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m	11	
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300		
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30		
	1.705MHz-30MHz		30	-	-	30		
	30MHz-88MHz		100	40.0	Quasi-peak	3		
	88MHz-216MHz		150	43.5	Quasi-peak	3		
	216MHz-960MHz		200	46.0	Quasi-peak	3		
	960MHz-1GHz		500	54.0	Quasi-peak	3		
	Above 1GHz	500	54.0	Average	3			
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.							



Report No.: SZEM151000664802

Page: 81 of 95

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB



Report No.: SZEM151000664802

Page: 82 of 95

	margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.			
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode.			
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.			
Instruments Used:	Refer to section 5.10 for details			
Test Results:	Pass			






Report No.: SZEM151000664802

Page: 83 of 95

6.10.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting	Vertical



Condition: 47 CFR PART 15.209 3m 3142C 2015 VERTICAL


Job No. : 6648CR Mode : TX


> Ant Preamp Limit Over Read Freq Loss Factor Factor Limit Level Level Line MHz dBuV dBuV/m dBuV/m dB dB/m dB dB 1 32.86 0.60 17.50 26.00 26.22 18.32 40.00 -21.68 166.07 28.13 13.54 43.50 -29.96 2 1.35 9.87 25.81 3 312.18 11.66 25.69 31.67 19.58 46.00 -26.42 1.94 2.65 4 545.18 14.95 25.61 26.44 18.43 46.00 -27.57 5 897.00 3.59 21.47 25.08 30.78 30.76 46.00 -15.24 945.44 22.13 24.75 29.38 30.41 46.00 -15.59 3.65



Report No.: SZEM151000664802

Page: 84 of 95





Condition: 47 CFR PART 15.209 3m 3142C 2015 Horizontal

Job No. : 6648CR Mode : TX

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	31.95	0.60	17.50	26.00	25.03	17.13	40.00	-22.87
2	166.65	1.35	9.83	25.81	25.56	10.93	43.50	-32.57
3	444.85	2.39	13.39	25.64	25.09	15.23	46.00	-30.77
4	543.27	2.65	14.97	25.61	25.69	17.70	46.00	-28.30
5	709.18	2.93	17.88	25.72	25.24	20.33	46.00	-25.67
6	945.44	3.65	22.13	24.75	24.36	25.39	46.00	-20.61



Report No.: SZEM151000664802

Page: 85 of 95

6.10.2 Transmitter Emission above 1GHz

Worse case i	mode:	GFSK(DH1)	Test	channel:	Lowest	Rema	ırk:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3765.000	-31.10	32.90	0.00	43.50	45.30	74	-28.70	Vertical
4800.000	-30.40	34.30	0.00	47.00	50.90	74	-23.10	Vertical
6000.000	-28.80	34.90	0.00	40.30	46.40	74	-27.60	Vertical
7200.000	-27.90	35.80	0.00	40.30	48.20	74	-25.80	Vertical
9660.000	-25.00	37.20	0.00	32.60	44.80	74	-29.20	Vertical
12630.000	-23.00	38.10	0.00	34.60	49.70	74	-24.30	Vertical
3765.000	-31.10	32.90	0.00	40.80	42.60	74	-31.40	Horizontal
4804.000	-30.40	34.30	0.00	52.40	56.30	74	-17.70	Horizontal
5895.000	-29.20	34.60	0.00	39.20	44.60	74	-29.40	Horizontal
7206.000	-27.90	35.80	0.00	47.20	55.10	74	-18.90	Horizontal
9608.000	-25.10	37.20	0.00	35.40	47.50	74	-26.50	Horizontal
12645.000	-23.10	38.10	0.00	34.70	49.70	74	-24.30	Horizontal

Worse case	mode:	GFSK(DH1)) Tes	t channel:	Lowest	Rem	nark:	Average
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.000	-30.40	34.30	0.00	34.40	38.30	54	-15.70	Horizontal
7206.000	-27.90	35.80	0.00	28.80	36.70	54	-17.30	Horizontal



Report No.: SZEM151000664802

Page: 86 of 95

Worse case	mode:	GFSK(DH1)	Tes	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3765.000	-31.10	32.90	0.00	44.30	46.10	74	-27.90	Vertical
4882.000	-30.40	34.60	0.00	51.70	55.90	74	-18.10	Vertical
5865.000	-29.40	34.50	0.00	39.70	44.80	74	-29.20	Vertical
7323.000	-27.90	35.70	0.00	42.40	50.20	74	-23.80	Vertical
9764.000	-24.90	37.30	0.00	34.60	47.00	74	-27.00	Vertical
12630.000	-23.00	38.10	0.00	34.80	49.90	74	-24.10	Vertical
3841.547	-31.20	33.30	0.00	39.90	42.00	74	-32.00	Horizontal
4882.000	-30.40	34.60	0.00	50.20	54.40	74	-19.60	Horizontal
6000.000	-28.80	34.90	0.00	40.20	46.30	74	-27.70	Horizontal
7323.000	-27.90	35.70	0.00	46.00	53.80	74	-20.20	Horizontal
9764.000	-24.90	37.30	0.00	35.90	48.30	74	-25.70	Horizontal
12630.000	-23.00	38.10	0.00	34.60	49.70	74	-24.30	Horizontal

Worse case	mode:	GFSK(DH1)) Tes	st channel:	Middle	Rem	ark:	Average
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.000	-30.40	34.60	0.00	33.60	37.80	54	-16.20	Vertical
4882.000	-30.40	34.60	0.00	34.10	38.30	54	-15.70	Horizontal
7323.000	-27.90	35.70	0.00	28.20	36.00	54	-18.00	Horizontal



Report No.: SZEM151000664802

Page: 87 of 95

Worse case	mode:	GFSK(DH1)	Tes	t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3750.000	-31.10	32.90	0.00	46.80	48.60	74	-25.40	Vertical
4960.000	-30.30	34.60	0.00	51.70	56.00	74	-18.00	Vertical
6000.000	-28.80	34.90	0.00	39.70	45.80	74	-28.20	Vertical
7440.000	-27.90	35.80	0.00	41.70	49.60	74	-24.40	Vertical
9920.000	-23.90	37.30	0.00	34.80	48.20	74	-25.80	Vertical
12660.000	-23.20	38.10	0.00	34.40	49.30	74	-24.70	Vertical
3750.000	-31.10	32.90	0.00	41.20	43.00	74	-31.00	Horizontal
4960.000	-30.30	34.60	0.00	50.60	54.90	74	-19.10	Horizontal
6060.000	-29.00	35.00	0.00	39.60	45.60	74	-28.40	Horizontal
7440.000	-27.90	35.80	0.00	41.90	49.80	74	-24.20	Horizontal
9920.000	-23.90	37.30	0.00	35.10	48.50	74	-25.50	Horizontal
12645.000	-23.10	38.10	0.00	34.50	49.50	74	-24.50	Horizontal

Worse case	mode:	GFSK(DH1) Te	st channel:	Highest	Ren	nark:	Average
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.000	-30.30	34.60	0.00	33.40	37.70	54	-16.30	Vertical
4960.000	-30.30	34.60	0.00	34.50	38.80	54	-15.20	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the above measurement data were shown in the report.




Report No.: SZEM151000664802

Page: 88 of 95

6.11 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205							
Test Method:	ANSI C63.10: 2009							
Test Site:	Measurement Distance: 3m	(Semi-Anechoic Chambe	r)					
Limit:	Frequency	Limit (dBuV/m @3m)	Remark					
	30MHz-88MHz	40.0	Quasi-peak Value					
	88MHz-216MHz	43.5	Quasi-peak Value					
	216MHz-960MHz	46.0	Quasi-peak Value					
	960MHz-1GHz	54.0	Quasi-peak Value					
	Above 1GHz	54.0	Average Value					
	Above IGHZ	74.0	Peak Value					
Test Setup:								






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: SZEM151000664802

Page: 89 of 95


a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Protest the EUT at Transmitting mode with all kind of modulation and all kind of data type Transmitting mode. Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode. found the Transmitting mode which it is worse case Only the worst case is recorded in the report.		
Exploratory Test Mode: Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode. Final Test Mode: Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode. found the Transmitting mode which it is worse case Only the worst case is recorded in the report. Instruments Used: Refer to section 5.10 for details	Test Procedure:	the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel, the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was
data type Transmitting mode. Final Test Mode: Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode. found the Transmitting mode which it is worse case Only the worst case is recorded in the report. Instruments Used: Refer to section 5.10 for details		•
the worst case. Pretest the EUT at Transmitting mode. found the Transmitting mode which it is worse case Only the worst case is recorded in the report. Instruments Used: Refer to section 5.10 for details	Exploratory Test Mode:	data type
which it is worse case Only the worst case is recorded in the report. Instruments Used: Refer to section 5.10 for details	Final Test Mode:	
Instruments Used: Refer to section 5.10 for details		which it is worse case
		Refer to section 5.10 for details
Test Results: Pass	Test Results:	Pass



Report No.: SZEM151000664802

Page: 90 of 95

Test plot as follows:




Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2390	46.2	74.0	27.8	32.5	0.0	-19.3	V
2 F	2401.865	87.9	74.0	-13.9	32.6	0.0	-19.3	V
Avg								
1	2390	32.5	54.0	21.5	32.5	0.0	-19.3	V
2	2401.865	49.9	54.0	4.1	32.6	0.0	-19.3	V



Report No.: SZEM151000664802

Page: 91 of 95




Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2390	46.3	74.0	27.7	32.5	0.0	-19.3	Н
2 F	2402.055	88.5	74.0	-14.5	32.6	0.0	-19.3	Н
Avg								
1	2390	32.5	54.0	21.5	32.5	0.0	-19.3	Н
2	2402.055	49.9	54.0	4.1	32.6	0.0	-19.3	Н



Report No.: SZEM151000664802

Page: 92 of 95




Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1 F	2479.800	83.9	74.0	-9.9	32.5	0.0	-19.1	V
2	2483.5	45.9	74.0	28.1	32.5	0.0	-19.1	V
Avg								
1	2479.800	48.5	54.0	5.5	32.5	0.0	-19.1	V
2	2483.5	32.8	54.0	21.2	32.5	0.0	-19.1	V





Report No.: SZEM151000664802

Page: 93 of 95



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1 F	2479.725	83.6	74.0	-9.6	32.5	0.0	-19.1	Н
2	2483.5	46.0	74.0	28.0	32.5	0.0	-19.1	Н
Avg								
1	2479.725	48.1	54.0	5.9	32.5	0.0	-19.1	Н
2	2483.5	32.5	54.0	21.5	32.5	0.0	-19.1	Н

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor



Report No.: SZEM151000664802

Page: 94 of 95

7 Photographs - EUT Test Setup

Test model No.: ZGACTC-GY0

7.1 Radiated Spurious Emission








Report No.: SZEM151000664802

Page: 95 of 95





8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1510006648CR.