

<b>Applicant:</b>	<b>ZAGG Inc.</b>		
<b>FCC ID:</b>	<b>QTG-ZKIS</b>		
<b>Section 15.212 Modular Transmitters</b>			
<b>Request for Limited Modular Approval</b>			
	<b>Requirements</b>	<b>EUT Conditions</b>	<b>Comply (Y/N)</b>
1	The radio elements of the modular transmitter must have their own shielding.	No, this RF Module does not have its own RF shielding and therefore does not comply to this requirement. The RF Module is subject to controlled integration and the integrator is advised on how to ensure compliance of the final end-product into which this RF Module is integrated to the FCC regulations.	N
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided)	Yes, The modular transmitter (U2) has buffered modulation/data inputs.	Y
3	The modular transmitter must have its own power supply regulation.	Yes, this RF module has own power supply regulation (U1 and U3).	Y
4	The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler (at all connections between the module and the antenna, including the cable).	Yes, the antenna is permanently attached because it is a PCB trace antenna.	Y
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with Part 15 requirements.	No, due to the fact that this RF module is not equipped with its own RF shielding, the radiated measurements are performed with the RF Module installed in a dedicated host.	N
6	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. (A) If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	Yes, the RF module is labeled with its own FCC ID. The outside of device in to which the module is installed will also be labeled with the FCCID.	Y

7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	Yes, this RF module will be exclusively integrated into battery powered host devices.	Y
8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Yes, this RF Module meets the FCC SAR Exemption, so it does comply with any applicable RF exposure requirements in its final configuration.	Y
<p>A limited modular approval may be granted for single or split modular transmitters that do not comply with all of the above requirements, e.g., shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.</p>			