

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15C_RM-632_08.doc	Date of Report:	22-Apr-2010
Number of pages:	13	Customer's Contact person:	Shao Xu
Testing laboratory:	TCC Nokia Beijing Laboratory Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550	Customer:	Nokia Corporation Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934
FCC listing no.:	975940		
IC recognition no.:	661AH-1		
Tested devices/ accessories:	Phone RM-632 / Battery BL-4D / AC-charger AC-8E / Headset WH-102		
FCC ID:	QTKRM-632	IC:	661AD-RM632
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards, RSS-210 (Issue 7, June 2007). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Jia Dongsheng, System Manager

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	01-Apr-2010
Testing completed	22-Apr-2010
The customer's contact person	Shao Xu
Test Plan referred to	T:\Projects\Projects\RM-632\TestPlan\RS_testplan_RM-632.xls
Notes	-
Document name	FCC15C_RM-632_08.doc

1.1. EUT and Accessory Information

The EUT is a 7-band (GSM850/900/1800/1900) and WCDMA Band (I/II(1900)/VIII) mobile phone with GPRS, EGPRS, HSDPA, HSUPA and WLAN and Bluetooth. Bluetooth and WLAN are tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-632	004401109337705	0200B	-	041.007 RD	51629
Battery	BL-4D	4181579161001101133;0670603	-	-	-	51399
AC-charger	AC-8E	4868679464320602195;0675387	-	-	-	51633
Headset	WH-102	0694323923554107290	-	-	-	51587

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8(0.4(2))	Conducted peak output power	NP
15.247(d)	A8(0.5)	Band edge compliance of RF emissions	NP
15.247(d)	A8(0.5)	Spurious RF conducted emissions	NP
15.247(d), 15.209	A8(0.5)	Spurious radiated emissions	NP
15.207	7.2.2	AC powerline conducted emissions	NP
15.247(a)(1)	A8(0.1(1))	20dB(bandwidth)	NP
15.247(a)(1)	A8(0.1(2))	Carrier frequency separation	NP
15.247(a)(1)(iii)	A8(0.1(4))	Number of hopping frequencies	NP
15.247(a)(1)(iii)	A8(0.1(4))	Time of occupancy	NP

WLAN:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8(0.4(4))	Conducted peak output power	NP
15.247(d)	A8(0.5)	Band edge compliance of RF emissions	PASSED
15.247(d)	A8(0.5)	Spurious RF conducted emissions	NP
15.247(d), 15.209	A8(0.5)	Spurious radiated emissions	PASSED
15.207	7.2.2	AC powerline conducted emissions	NP
15.247(a)(2)	A8(0.1(1))	6dB(bandwidth)	NP
15.247(a)(1)(iii)	A8(0.1(4))	Power spectral density	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Laboratory.


CONTENTS

1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Band edge compliance of RF emissions (FCC §15.247(d), RSS-210 A8.5)	5
2.1. Test Setup.....	5
2.2. Test method and limit.....	5
2.3. WLAN Test results	6
3. Spurious radiated emissions (FCC §22.917(a), §24.238(a), §2.1053, RSS-132 4.5, RSS-133 6.5).....	8
3.1. Test Setup.....	8
3.2. Test method and limit.....	8
3.3. WLAN Test results	10
4. Test Equipment.....	13
4.1. Conducted measurements	13
4.2. Radiated measurements	13

2. Band edge compliance of RF emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-632, DUT 51629
Accessories with DUT numbers	BL-4D, DUT 51399 ; AC-8E, DUT 51633 ; WH-102, DUT 51587
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 34 / 101.7
Date of measurements	22-Apr-2010
Measured by	Jia Dongsheng

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).


Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit Average [dBμV/m]	Limit Peak [dBμV/m]
Below 2390 and above 2483.5	≤54	≤74

2.3. WLAN Test results


2.3.1 DSSS mode, QPSK modulation, 11 Mbps data rate

Channel 1 / 2412 MHz



Detector (RBW: 1 MHz, VBW: 1 MHz)	E [dB μ V/m]	Result
Peak	58.70	PASSED
Average	45.40	PASSED


Channel 11 / 2462 MHz



Detector (RBW: 1 MHz, VBW: 1 MHz)	E [dB μ V/m]	Result
Peak	59.00	PASSED
Average	44.80	PASSED


2.3.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel 1 / 2412 MHz



Detector (RBW: 1 MHz, VBW: 1 MHz)	E [dB μ V/m]	Result
Peak	73.00	PASSED
Average	52.80	PASSED

Channel 11 / 2462 MHz




Detector (RBW: 1 MHz, VBW: 1 MHz)	E [dB μ V/m]	Result
Peak	73.80	PASSED
Average	51.30	PASSED

3. Spurious radiated emissions (FCC §22.917(a), §24.238(a), §2.1053, RSS-132 4.5, RSS-133 6.5)

EUT with DUT number	RM-632, DUT 51629
Accessories with DUT numbers	BL-4D, DUT 51399 ; AC-8E, DUT 51633 ; WH-102, DUT 51587
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 34 / 101.6
Date of measurements	14-Apr-2010
Measured by	Yin Hongpeng

3.1. Test Setup



3.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
30 - 88	100	40	Quasi peak
88 - 216	150	43.5	Quasi peak
216 - 960	200	46	Quasi peak
960 - 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

3.3. WLAN Test results

3.3.1 DSSS mode, QPSK modulation, 11 Mbps data rate

Channel 1 / 2412 MHz

Average(RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4824	33.68	48.311	33.96	-0.28	HORIZONTAL	PASSED
7236.8	32.46	41.976	28.09	4.37	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4824	47.52	237.766	47.8	-0.28	HORIZONTAL	PASSED
7236.8	45.4	186.273	41.03	4.37	VERTICAL	PASSED

Channel 7 / 2442 MHz

Average(RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
2800.301	39.95	99.437	29.99	9.96	HORIZONTAL	PASSED
2884.269	39.48	94.156	29.19	10.29	HORIZONTAL	PASSED
3900	28.93	27.954	29.5	-0.57	HORIZONTAL	PASSED
3910.32	28.65	27.071	29.37	-0.72	VERTICAL	PASSED
17929.86	46.38	208.401	27.06	19.32	VERTICAL	PASSED

Quasi peak (RBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
77.617	31.28	36.656	51.89	-20.61	VERTICAL	PASSED
77.637	31.56	37.827	52.17	-20.61	VERTICAL	PASSED
77.645	31.2	36.32	51.81	-20.61	VERTICAL	PASSED
77.906	31.7	38.446	52.3	-20.6	VERTICAL	PASSED
903.165	22.32	13.068	27.16	-4.84	HORIZONTAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
2800.301	52.46	419.759	42.5	9.96	HORIZONTAL	PASSED
2884.269	52.79	435.763	42.5	10.29	HORIZONTAL	PASSED
3900	42.06	126.707	42.63	-0.57	HORIZONTAL	PASSED
3910.32	41.52	119.11	42.24	-0.72	VERTICAL	PASSED
17929.86	58.54	845.182	39.22	19.32	VERTICAL	PASSED

Channel 11 / 2462 MHz

Average(RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4924.1	33.05	44.921	32.48	0.57	VERTICAL	PASSED
7387.7	32.97	44.514	28.53	4.44	HORIZONTAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4924.1	46.66	215.229	46.09	0.57	VERTICAL	PASSED
7387.7	46.55	212.447	42.11	4.44	HORIZONTAL	PASSED

3.3.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel 1 / 2412 MHz

Average(RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4824.4	30.65	34.084	30.94	-0.29	HORIZONTAL	PASSED
7235.5	32.48	42.063	28.1	4.38	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4824.4	43.6	151.339	43.89	-0.29	HORIZONTAL	PASSED
7235.5	45.41	186.445	41.03	4.38	VERTICAL	PASSED

Channel 7 / 2442 MHz

Average(RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
2496.834	39.02	89.31	32.04	6.98	VERTICAL	PASSED
2814.43	40.16	101.906	29.57	10.59	VERTICAL	PASSED
3902.807	28.83	27.65	29.44	-0.61	VERTICAL	PASSED
3927.256	28.29	25.972	29.23	-0.94	VERTICAL	PASSED
17998.098	46.31	206.705	26.62	19.69	HORIZONTAL	PASSED

Quasi peak (RBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
37.094	29.55	30.037	38.08	-8.53	VERTICAL	PASSED
75.05	28.48	26.549	49.19	-20.71	VERTICAL	PASSED
835.033	21.07	11.31	26.98	-5.91	VERTICAL	PASSED
899.822	22.29	13.012	27.11	-4.82	VERTICAL	PASSED
906.712	22.31	13.045	27.11	-4.8	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
2496.834	56.18	644.466	49.2	6.98	VERTICAL	PASSED
2814.43	53.09	451.284	42.5	10.59	VERTICAL	PASSED
3902.807	41.62	120.559	42.23	-0.61	VERTICAL	PASSED
3927.256	41.3	116.091	42.24	-0.94	VERTICAL	PASSED
17998.098	59.68	963.274	39.99	19.69	HORIZONTAL	PASSED

Channel 11 / 2462 MHz

Average(RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4925.2	30.65	34.076	30.11	0.54	HORIZONTAL	PASSED
7386.1	32.73	43.301	28.29	4.44	HORIZONTAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4925.2	43.3	146.134	42.76	0.54	HORIZONTAL	PASSED
7386.1	45.74	193.664	41.3	4.44	HORIZONTAL	PASSED

4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCHW0020	DC Power supply	HP6632B	HP	22/24/27, 15C
BJPCPT0040	Receiver	ESCS30	R&S	15C, 15B
BJPCPT0069	LISN 50 μ H	ESH3-Z5	R&S	15C, 15B
BJPCPT0073	Signal Generator	SMR 20	R&S	22/24/27, 15C, 15B
BJPCPT0079	LISN 50 μ H	ESH3-Z5	R&S	15C, 15B
BJPCPT0131	Communication Tester	CMU200	R&S	15C, 15B
BJPCPT0191	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
BJPCTC0017	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0067	Bluetooth Tester	CBT	R&S	22/24/27, 15C
BJPCTC0089	Temperature Test chamber	VT4002	Votsch	22/24/27, 15C
BJPCTC0090	FSP spectrum analyzer	FSP30	R&S	22/24/27, 15C
BJPCTC0094	GPIO-RS232 convertor	GPIO-RS232	NI	22/24/27, 15C

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B
BJPCPT0072	Receiver	ESI B26	R&S	22/24/27, 15C, 15B
BJPCPT0130	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
BJPCPT0150	High Pass Filter	WHKS1200-10SS	Wainwright	22/24/27, 15C, 15B
BJPCPT0151	Band Reject Filter	WRCD1880/2000-	Wainwright	24, 15B
BJPCPT0154	Band Reject Filter	WRCT2402/2480-	Wainwright	15C, 15B
BJPCPT0162	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0007	Antenna	HL562	R&S	22/24/27, 15C, 15B
BJPCTC0029	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0034	Band Reject Filter	WRCT 800/880-0.2/40-	Wainwright	22, 15B
BJPCTC0049	Preamplifier	Blma 0118-1A-Bt	Bonn	22/24/27, 15C, 15B
BJPCTC0055	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0058	Bluetooth Tester	CBT	R&S	15C, 15B
BJPCTC0064	Band Reject Filter	WRCG1877/1883-	Wainwright	24, 15B
BJPCTC0065	Band Reject Filter	WRCG832/838-	Wainwright	27, 15B
BJPCTC0071	Multi-Device Controller	2090	EMCO	22/24/27, 15C, 15B
BJPCTC0072	Anechoic Chamber	3 m Semi / Full	ETS	22/24/27, 15C, 15B
BJPCTC0073	MAST	Model-TR/POL	ETS	22/24/27, 15C, 15B
BJPCTC0074	MAST	Model 2070-2	ETS	22/24/27, 15C, 15B
BJPCTC0075	Turntable	Model 2188	ETS-EMCO	22/24/27, 15C, 15B
BJPCTC0096	Preamplifier	AFS4-00100300-20-	Miteq	22/24/27, 15C, 15B