

RF EXPOSURE REPORT

REPORT NO.: SA980505A01C

MODEL NO.: BH-105

VERSION: HW: 0.41, SW: 1.01, MV: 0.4, Proto: B4.11

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT : Nokia(China) Investment Co., LTD.

ADDRESS : B2, Nokia China Campus.Beijing Economic and Tech
Development Area, No.5. Donghuan Zhonglu.P.O. Box
100176, Beijing, China

ISSUED BY : Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS : No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien, 244 Taiwan

Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	5.21	3.319
EIRP Power	8.03	6.353

***Note:** The antenna is IFA antenna with 2.82dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 6.353mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---