

RF EXPOSURE REPORT

REPORT NO.: SA980505A01J

MODEL NO.: BH-106

FCC ID: QTLBH-106

VERSION: Build: BR.1, HW: vR.1, SW: vR.1, MV: vR.1

RECEIVED: Dec. 15, 2011

TESTED: Dec. 15, 2011 ~ Jan. 17, 2012

ISSUED: Feb. 3, 2012

APPLICANT: Nokia(China) Investment Co., LTD.

ADDRESS: B2, Nokia China Campus.Beijing Economic and
Tech Development Area, No.5. Donghuan
Zhonglu.P.O. Box 100176, Beijing, China

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City 244, Taiwan (R.O.C.)

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. CONCLUSION	5



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA980505A01J	Original release	Feb. 3, 2012

1. CERTIFICATION

PRODUCT: Bluetooth Headset
BRAND NAME: NOKIA
MODEL NO.: BH-106
APPLICANT: Nokia(China) Investment Co., LTD.
TESTED: Dec. 15, 2011 ~ Jan. 17, 2012
TEST ITEM: ENGINEERING SAMPLE
STANDARDS: FCC Part 2 (Section 2.1091)
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Annie Chang , **DATE:** Feb 3, 2012
(Annie Chang / Senior Specialist)

APPROVED BY : Ken Liu , **DATE:** Feb. 3, 2012
(Ken Liu / Manager)

2. CONCLUSION

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	5.8	3.8
EIRP Power	8.6	7.2

***Note:** The antenna is IFA antenna with 2.82dBi gain

Threshold for no SAR evaluation is 24.58mW
Transmitter power is 7.2mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---