

# RF EXPOSURE REPORT

**REPORT NO.:** SA990810D06

**MODEL NO.:** BH-218

**FCC ID:** QTLBH-218

**VERSION:** Proto: B4.2/ B4.3, HW: 0.33/ 0.34, MV: 0.32,  
SW: 0.3C/ 0.3E

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT :** Nokia(China) Investment Co., LTD.

**ADDRESS :** B2, Nokia China Campus.Beijing Economic and Tech  
Development Area, No.5. Donghuan Zhonglu.P.O. Box  
100176, Beijing, China

**ISSUED BY :** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS :** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien, 244 Taiwan

## Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	-1.4	0.7
EIRP Power	2.6	1.8

**\*Note:** The antenna is PIFA antenna with 4dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 1.8mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---