

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15CBT_RM-768_05.docx	Date of Report:	28-Mar-2012
Number of pages:	40	Customer's Contact person:	Hu Helen
Testing laboratory:	TCC Nokia Beijing Laboratory Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550	Customer:	Nokia Corporation Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550
FCC listing no.:	975940		
IC recognition no.:	661AH-1		
Tested devices/ accessories:	Phone RM-768 / Battery BL-4U / AC Charger AC-11E / Headset WH-102		
FCC ID:	QTLRM-768	IC:	661AB-RM768
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards, RSS-210 (Issue 8, December 2010). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Gao Sherina, Engineer, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	14-Mar-2012
Testing completed	19-Mar-2012
The customer's contact person	Hu Helen
Test Plan referred to	T:\Projects\RM-768\TestPlan\RS_testplan_RM-768.xls
Notes	-
Document name	FCC15CBT_RM-768_05.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WLAN/Bluetooth

The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-768	004402137405282	0302	-	ga12w09.2	52691
Battery	BL-4U	4955401232021186771;0670560	-	-	-	52685
AC Charger	AC-11E	4090491397970509487;0675479	-	-	-	52682
Headset	WH-102	0694323152311D23429	-	-	-	52689
Phone	RM-768	004402137405332	0302	-	ga12w09.2	52692
Battery	BL-4U	4955401232021186770;0670560	-	-	-	52686
AC Charger	AC-11E	4090491397970509534;0675479	-	-	-	52683
Headset	WH-102	0694323152311D23677	-	-	-	52688
Phone	RM-768	004402137405365	0302	-	ga12w09.2	52694
Battery	BL-4U	4955401232021114643;0670560	-	-	-	52687
AC Charger	AC-11E	4090491397970509515;0675479	-	-	-	52684
Headset	WH-102	0694323152311D23534	-	-	-	52690

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8(0.4(2))	Conducted peak output power	PASSED
15.247(d), 15.205(b)	A8(0.5)	Band edge compliance of RF emissions	PASSED
15.247(d)	A8(0.5)	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8(0.5)	Spurious radiated emissions	PASSED
15.207	7.2.2	AC powerline conducted emissions	PASSED
15.247(a)(1)	A8(0.1(1))	20dB(bandwidth)	PASSED
15.247(a)(1)	A8(0.1(2))	Carrier frequency separation	PASSED
15.247(a)(1)(iii)	A8(0.1(4))	Number of hopping frequencies	PASSED
15.247(a)(1)(iii)	A8(0.1(4))	Time of occupancy	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Laboratory.

CONTENTS


1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information.....	2
1.2. Summary of Test Results.....	2
2. Conducted peak output power (15.247(b)(1), RSS-210 A8.4 (2))	5
2.1. Test Setup.....	5
2.2. Test method and limit.....	5
2.3. Bluetooth Test results	6
3. Band edge compliance of RF emissions (FCC §15.247(d), 15.205(b), RSS-210 A8.5).....	9
3.1. Test Setup.....	9
3.2. Test method and limit.....	9
3.3. Bluetooth Test results	10
4. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5).....	16
4.1. Test Setup.....	16
4.2. Test method and limit.....	16
4.3. Bluetooth Test results	17
5. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)	20
5.1. Test Setup.....	20
5.2. Test method and limit.....	20
5.3. Bluetooth Test results	22
6. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)	25
6.1. Test Setup.....	25
6.2. Test method and limit.....	25
6.3. Bluetooth Test results	26
7. 20 dB bandwidth 15.247(a)(1), A8.1 (a).....	27
7.1. Test Setup.....	27
7.2. Test method and limit.....	27
7.3. Bluetooth Test results	28
8. Carrier frequency separation 15.247(a)(1), A8.1 (b)	31
8.1. Test Setup.....	31

8.2.	Test method and limit.....	31
8.3.	Bluetooth Test results	32
9.	Number of hopping frequencies	
15.247(a)(1)(iii), A8.1 (d)		34
9.1.	Test Setup.....	34
9.2.	Test method and limit.....	34
9.3.	Bluetooth Test results	35
10.	Time of occupancy	
15.247(a)(1)(iii), A8.1 (d)		37
10.1.	Test Setup.....	37
10.2.	Test method and limit.....	37
10.3.	Bluetooth Test results	38
11.	Test Equipment	40
11.1.	Conducted measurements	40
11.2.	Radiated measurements	40

2. Conducted peak output power (15.247(b)(1), RSS-210 A8.4 (2))

EUT with DUT number	RM-768, DUT 52694
Accessories with DUT numbers	BL-4U, DUT 52687 ; AC-11E, DUT 52684 ; WH-102, DUT 52690
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19/54/102
Date of measurements	19-Mar-2012
Measured by	Zou Ming

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for conducted peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5	≤ 1	≤ 30

2.3. Bluetooth Test results


2.3.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	5.57	3.606	PASSED
40 / 2442	8.21	6.622	PASSED
78 / 2480	5.85	3.846	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)




Channel 78 / 2480 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)




2.3.2 8DPSK modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	3.05	2.018	PASSED
40 / 2442	6.97	4.977	PASSED
78 / 2480	3.28	2.128	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)




Channel 78 / 2480 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



3. Band edge compliance of RF emissions (FCC §15.247(d), 15.205(b), RSS-210 A8.5)

EUT with DUT number	RM-768, DUT 52691
Accessories with DUT numbers	BL-4U, DUT 52685 ; AC-11E, DUT 52682 ; WH-102, DUT 52689
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/55/102.4
Date of measurements	15-Mar-2012
Measured by	Gao Sherina

3.1. Test Setup



3.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).

Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit Average [dBμV/m]	Limit Peak [dBμV/m]
Below 2390 and above 2483.5	<=54	<=74

3.3. Bluetooth Test results

3.3.1 GFSK modulation, PRBS packet type


Average (RBW: 1 MHz, VBW: 10 Hz)

Channel / f_c [MHz]	E [dB μ V/m]	E [μ V/m]	U_{RX} [dB μ V]	A_{TOT} [dB]	Result
0 / 2402	46.15	202.904	43.62	2.53	PASSED
Hopping on, low end	46.15	202.904	43.62	2.53	PASSED
78 / 2480	50.05	318.033	47.05	3	PASSED
Hopping on, high end	47.05	225.129	44.05	3	PASSED


Peak (RBW: 1 MHz, VBW: 1 MHz)

Channel / f_c [MHz]	E [dB μ V/m]	E [μ V/m]	U_{RX} [dB μ V]	A_{TOT} [dB]	Result
0 / 2402	60.91	1109.994	58.38	2.53	PASSED
Hopping on, low end	62.77	1375.937	60.24	2.53	PASSED
78 / 2480	68.66	2709.379	65.66	3	PASSED
Hopping on, high end	68.04	2523.452	65.04	3	PASSED


GFSK mode. Channel 0 / 2402 MHz




GFSK mode. Hopping on, low end



GFSK mode. Channel 78 / 2480 MHz



GFSK mode. Hopping on, high end



3.3.2 8DPSK modulation, PRBS packet type


Average (RBW: 1 MHz, VBW: 10 Hz)

Channel / f_c [MHz]	E [dB μ V/m]	E [μ V/m]	U_{RX} [dB μ V]	A_{TOT} [dB]	Result
0 / 2402	46.15	202.904	43.62	2.53	PASSED
Hopping on, low end	46.15	202.904	43.62	2.53	PASSED
78 / 2480	50.69	342.497	47.69	3	PASSED
Hopping on, high end	47.05	225.129	44.05	3	PASSED


Peak (RBW: 1 MHz, VBW: 1 MHz)

Channel / f_c [MHz]	E [dB μ V/m]	E [μ V/m]	U_{RX} [dB μ V]	A_{TOT} [dB]	Result
0 / 2402	60.3	1034.693	57.77	2.53	PASSED
Hopping on, low end	59.95	994.366	57.42	2.53	PASSED
78 / 2480	63.22	1449.415	60.22	3	PASSED
Hopping on, high end	65.04	1786.616	62.04	3	PASSED


8DPSK mode. Channel 0 / 2402 MHz




8DPSK mode. Hopping on, low end



8DPSK mode. Channel 78 / 2480 MHz




8DPSK mode. Hopping on, high end



4. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-768, DUT 52694
Accessories with DUT numbers	BL-4U, DUT 52687 ; AC-11E, DUT 52684 ; WH-102, DUT 52690
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19/54/102
Date of measurements	19-Mar-2012
Measured by	Zou Ming

4.1. Test Setup



4.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

4.3. Bluetooth Test results

4.3.1 GFSK modulation, PRBS packet type


Channel 0 / 2402 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4837.6	-35.33	PASSED
7228.2	-34.44	PASSED


Channel 40 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4926.8	-38.7	PASSED
7333.8	-38.24	PASSED

Channel 78 / 2480 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4981.2	-35.77	PASSED
7422.6	-35.26	PASSED

4.3.2 8DPSK modulation, PRBS packet type


Channel 0 / 2402 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4839.6	-31.09	PASSED
7220.4	-30.7	PASSED


Channel 40 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4863.6	-35.74	PASSED
7312.2	-34.96	PASSED

Channel 78 / 2480 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4943.2	-30.86	PASSED
7407	-30.14	PASSED

5. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)

EUT with DUT number	RM-768, DUT 52691
Accessories with DUT numbers	BL-4U, DUT 52685 ; AC-11E, DUT 52682 ; WH-102, DUT 52689
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/55/102.4
Date of measurements	15-Mar-2012
Measured by	Gao Sherina

5.1. Test Setup



5.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu V/m$]	Limit [$dB\mu V/m$]	Detector
30 - 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

5.3. Bluetooth Test results

5.3.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4805.4	41.47	118.44	42.11	-0.64	HORIZONTAL	PASSED
7204.1	45.25	183.042	40.63	4.62	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4805.4	28.27	25.903	28.91	-0.64	HORIZONTAL	PASSED
7204.1	32.56	42.438	27.94	4.62	VERTICAL	PASSED

Channel 40 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
33.026	21.01	11.233	24.69	-3.68	VERTICAL	PASSED
33.027	24.33	16.468	28.01	-3.68	VERTICAL	PASSED
44.469	24	15.843	35.8	-11.8	VERTICAL	PASSED
47.665	27.66	24.149	41.34	-13.68	VERTICAL	PASSED
47.715	27.87	24.757	41.58	-13.71	VERTICAL	PASSED
47.916	27.71	24.288	41.53	-13.82	VERTICAL	PASSED
47.936	27.77	24.46	41.61	-13.84	VERTICAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3912.627	39.78	97.533	41.86	-2.08	HORIZONTAL	PASSED
3941.379	40.77	109.32	42.86	-2.09	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3912.627	27.25	23.028	29.33	-2.08	HORIZONTAL	PASSED
3941.379	27.13	22.72	29.22	-2.09	VERTICAL	PASSED

Channel 78 / 2480 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4959.6	47.18	228.586	47.32	-0.14	HORIZONTAL	PASSED
7438.3	46.32	206.943	41.49	4.83	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4959.6	29.55	30.037	29.69	-0.14	HORIZONTAL	PASSED
7438.3	32.94	44.376	28.11	4.83	VERTICAL	PASSED

5.3.2 8DPSK modulation, PRBS packet type

Channel 0 / 2402 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.7	40.84	110.179	41.49	-0.65	HORIZONTAL	PASSED
7205.1	45.6	190.436	41	4.6	HORIZONTAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.7	28.22	25.751	28.87	-0.65	HORIZONTAL	PASSED
7205.1	32.46	41.995	27.86	4.6	HORIZONTAL	PASSED

Channel 40 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
44.509	25.54	18.917	37.37	-11.83	VERTICAL	PASSED
44.709	26.33	20.716	38.28	-11.95	VERTICAL	PASSED
47.705	23.46	14.899	37.16	-13.7	VERTICAL	PASSED
47.835	25.22	18.247	39	-13.78	VERTICAL	PASSED
47.967	25.29	18.393	39.14	-13.85	VERTICAL	PASSED
48.016	28.04	25.241	41.92	-13.88	VERTICAL	PASSED
904.366	24.25	16.308	26.09	-1.84	HORIZONTAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3922.843	41.35	116.856	43.48	-2.13	VERTICAL	PASSED
3935.372	40	100.012	42.11	-2.11	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
3922.843	27.33	23.259	29.46	-2.13	VERTICAL	PASSED
3935.372	27.36	23.321	29.47	-2.11	VERTICAL	PASSED

Channel 78 / 2480 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4959.4	42.6	134.881	42.74	-0.14	HORIZONTAL	PASSED
7438.2	45.7	192.775	40.87	4.83	HORIZONTAL	PASSED


Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4959.4	29.56	30.061	29.7	-0.14	HORIZONTAL	PASSED
7438.2	32.94	44.351	28.11	4.83	HORIZONTAL	PASSED

6. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-768, DUT 52692
Accessories with DUT numbers	BL-4U, DUT 52686 ; AC-11E, DUT 52683 ; WH-102, DUT 52688
Operation Voltage [V] / [Hz]	115/60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/48/102.4
Date of measurements	15-Mar-2012
Measured by	Zou Ming

6.1. Test Setup



6.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

6.3. Bluetooth Test results

6.3.1 GFSK modulation, PRBS packet type

Channel 40 / 2442 MHz



QuasiPeak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
1.115	39.88	L1	PASSED
1.3	40.05	L1	PASSED
1.485	39.89	L1	PASSED
1.67	39.35	L1	PASSED
1.92	38.81	L1	PASSED


Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.5	31.51	L1	PASSED
0.685	29.08	L1	PASSED
0.755	30.9	L1	PASSED
1.2	29.17	L1	PASSED
1.395	27.89	L1	PASSED

7. 20 dB bandwidth 15.247(a)(1), A8.1 (a)

EUT with DUT number	RM-768, DUT 52694
Accessories with DUT numbers	BL-4U, DUT 52687 ; AC-11E, DUT 52684 ; WH-102, DUT 52690
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19/54/102
Date of measurements	19-Mar-2012
Measured by	Zou Ming

7.1. Test Setup



7.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for 20 dB bandwidth measurements


Limit [MHz]
N/A

7.3. Bluetooth Test results


7.3.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	20 dB bandwidth [kHz]
0 / 2402	848
40 / 2442	796
78 / 2480	844


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz




Channel 78 / 2480 MHz




7.3.2 8DPSK modulation, PRBS packet type

Channel / f _c [MHz]	20 dB bandwidth [kHz]
0 / 2402	1268
40 / 2442	1264
78 / 2480	1264


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz



Channel 78 / 2480 MHz




8. Carrier frequency separation

15.247(a)(1), A8.1 (b)

EUT with DUT number	RM-768, DUT 52694
Accessories with DUT numbers	BL-4U, DUT 52687 ; AC-11E, DUT 52684 ; WH-102, DUT 52690
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19/54/102
Date of measurements	19-Mar-2012
Measured by	Zou Ming

8.1. Test Setup



8.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for carrier frequency separation measurements


Limit [MHz]
≥ 0.025 or $2/3$ of the 20 dB bandwidth

8.3. Bluetooth Test results

8.3.1 GFSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1000	PASSED


Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



8.3.2 8DPSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1000	PASSED

Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz




9. Number of hopping frequencies

15.247(a)(1)(iii), A8.1 (d)

EUT with DUT number	RM-768, DUT 52694
Accessories with DUT numbers	BL-4U, DUT 52687 ; AC-11E, DUT 52684 ; WH-102, DUT 52690
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19/54/102
Date of measurements	19-Mar-2012
Measured by	Zou Ming

9.1. Test Setup



9.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for number of hopping frequencies measurements


Limit [number]
≥ 15

9.3. Bluetooth Test results

9.3.1 GFSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
78	PASSED


Hopping on, number of hopping frequencies



9.3.2 8DPSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
73	PASSED


Hopping on, number of hopping frequencies



10. Time of occupancy 15.247(a)(1)(iii), A8.1 (d)

EUT with DUT number	RM-768, DUT 52694
Accessories with DUT numbers	BL-4U, DUT 52687 ; AC-11E, DUT 52684 ; WH-102, DUT 52690
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19/54/102
Date of measurements	19-Mar-2012
Measured by	Zou Ming

10.1. Test Setup



10.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

The total time of occupancy is get by multiplying the measured number of transmissions occurred during 31.6 second period with the duration of one transmission.

Limits for time of occupancy measurements


Limit [s]
<= 0.4

10.3. Bluetooth Test results


10.3.1 GFSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [ms]	Time of occupancy [s]	Result
81	2.944	0.238	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz




Hopping on, duration of one transmission, channel 40 / 2442 MHz




10.3.2 8DPSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [ms]	Time of occupancy [s]	Result
84	2.944	0.247	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz



Hopping on, duration of one transmission, channel 40 / 2442 MHz



11. Test Equipment

11.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCWH0020	DC Power supply	HP6632B	HP	22/24/27, 15C
BJPCPT0040	Receiver	ESCS30	R&S	15C, 15B
BJPCPT0073	Signal Generator	SMR 20	R&S	22/24/27, 15C, 15B
BJPCPT0079	LISN 50 μ H	ESH3-Z5	R&S	15C, 15B
BJPCPT0131	Communication Tester	CMU200	R&S	15C, 15B
BJPCPT0191	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
BJPCTC0017	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0067	Bluetooth Tester	CBT	R&S	22/24/27, 15C
BJPCTC0089	Temperature Test chamber	VT4002	Votsch industrietechnik	22/24/27, 15C
BJPCTC0090	FSP spectrum analyzer	FSP30	R&S	22/24/27, 15C
BJPCTC0094	GPIO-RS232 convertor	GPIO-RS232	NI	22/24/27, 15C
BJPCTC0112	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0114	Signal Generator	E8357C	Agilent	22/24/27, 15C
BJPCTC0115	Communication Tester	CMU200	R&S	22/24/27, 15B, 15C

11.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCPT0072	Receiver	ESI B26	R&S	22/24/27, 15C, 15B
BJPCPT0130	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
BJPCPT0150	High Pass Filter	WHKS1200-10SS	Wainwright	22/24/27, 15C, 15B
BJPCPT0151	Band Reject Filter	WRCD1880/2000-0.2/40-5SSK	Wainwright	24, 15B
BJPCPT0154	Band Reject Filter	WRCT2402/2480-2400/2483.5-30-20SS	Wainwright	15C, 15B
BJPCPT0162	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0007	Antenna	HL562	R&S	22/24/27, 15C, 15B
BJPCTC0029	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0034	Band Reject Filter	WRCT 800/880-0.2/40-5SSK	Wainwright	22, 15B
BJPCTC0049	Preamplifier	Blma 0118-1A-Bt	Bonn	22/24/27, 15C, 15B
BJPCTC0055	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0058	Bluetooth Tester	CBT	R&S	15C, 15B
BJPCTC0064	Band Reject Filter	WRCG1877/1883-1870/1890-40/6SS	Wainwright	24, 15B
BJPCTC0065	Band Reject Filter	WRCG832/838-825/845-40/5SS	Wainwright	27, 15B
BJPCTC0071	Multi-Device Controller	2090	EMCO	22/24/27, 15C, 15B
BJPCTC0072	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	ETS	22/24/27, 15C, 15B
BJPCTC0073	MAST	Model-TR/POL	ETS	22/24/27, 15C, 15B
BJPCTC0074	MAST	Model 2070-2	ETS	22/24/27, 15C, 15B
BJPCTC0075	Turntable	Model 2188	ETS-EMCO	22/24/27, 15C, 15B
BJPCTC0096	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
BJPCTC0113	Receiver	ESI B26	R&S	22/24/27, 15B, 15C
BJPCTC0115	Communication Tester	CMU200	R&S	22/24/27, 15B, 15C
BJPCTC0124	Attenuator	SA18N200W-40	Fairview Microwave	-