

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15CWLAN_RM-941_10.docx	Date of Report:	09-Jun-2013
Number of pages:	47	Customer's Contact person:	Wang Jinling (jinliwan)
Testing laboratory:	TCC Nokia Beijing Laboratory Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550	Customer:	Nokia Corporation Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550
FCC listing no.:	975940		
IC recognition no.:	661AH-1		
Tested devices/ accessories:	Phone RM-941 / Battery BP-4GWA / AC-Charger AC-20U / Headset WH-108		
FCC ID:	QTLRM-941	IC:	
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), DTS procedures KDB 558074, IC standards. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Gao Sherina, Engineer, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	21-May-2013
Testing completed	27-Jun-2013
The customer's contact person	Wang Jinling (jinliwan)
Test Plan referred to	T:\Projects\RM-941\TestPlan\RS_TestPlan_RM-941.xlsm
Notes	-
Document name	FCC15CWLAN_RM-941_10.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WCDMA/WLAN/Bluetooth

The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-941	004402472993447	2000	-	3037.0000.1318.0000	53347
Battery	BP-4GWA	-	-	-	-	53353
AC-Charger	AC-20U	4868673112350508822;0675629	-	-	-	53339
Headset	WH-108	1046	0.1	0.3	-	53341
Phone	RM-941	004402472996440	2001	-	3037.0000.1318.0000	53377
Dummy battery	-	-	-	-	-	53378
Headset	WH-108	122	0.1	0.3	-	53379
Phone	RM-941	004402472993215	2000	-	3037.0000.1318.0000	53350
Battery	BP-4GWA	-	-	-	-	53351
AC-Charger	AC-20U	4868673112340509970;0675629	-	-	-	53340
Headset	WH-108	1253	0.1	0.3	-	53343

1.2. Summary of Test Results

WLAN:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8(0.4(4))	Conducted peak output power	PASSED
15.247(d), 15.205(b)	A8(0.5)	Band edge compliance of RF emissions	PASSED
15.247(d)	A8(0.5)	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8(0.5)	Spurious radiated emissions	PASSED
15.207	7.2.2	AC powerline conducted emissions	NP
15.247(a)(2)	A8(0.1(1))	6dB(bandwidth)	PASSED
15.247(e)	A8(0.1(2))	Power spectral density	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Laboratory.

CONTENTS


1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information.....	2
1.2. Summary of Test Results.....	2
2. Conducted peak output power (15.247(b)(1), RSS-210 A8.4 (4))	5
2.1. Test Setup.....	5
2.2. Test method and limit.....	5
2.3. Power results summary.....	6
2.4. WLAN Test results	6
2.5. WLAN Test results	7
3. Band edge compliance of RF emissions (FCC §15.247(d), 15.205(b), RSS-210 A8.5).....	12
3.2. Test method and limit.....	12
3.3. WLAN test results	13
4. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)	19
4.1. Test Setup.....	19
4.2. Test method and limit.....	19
4.3. WLAN Test results	20
5. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5).....	23
5.1. Test Setup.....	23
5.2. Test method and limit.....	23
5.3. WLAN Test results	24
6. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)	29
6.2. Test method and limit.....	29
6.3. WLAN test results	31
7. 6 dB bandwidth (FCC §15.247(a)(2), RSS-210 A8.2 (1)).....	35
7.1. Test Setup.....	35
7.2. Test method and limit.....	35
7.3. WLAN Test results	36
8. Power spectral density (FCC §15.247(e), RSS-210 A8.2 (2))	41
8.1. Test Setup.....	41

8.2.	Test method and limit.....	41
8.3.	WLAN Test results	42
9.	Test Equipment.....	46
9.1.	Conducted measurements	46
9.2.	Radiated measurements	46

2. Conducted peak output power (15.247(b)(1), RSS-210 A8.4 (4))

EUT with DUT number	RM-941, DUT 53377
Accessories with DUT numbers	Dummy battery, DUT 53378; WH-108, DUT 53379
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24/55/100.6
Date of measurements	27-May-2013
Measured by	Gao Sherina

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for conducted peak output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5 5725 - 5850	<= 1	<= 30

2.3. Power results summary

Channel / f _c [MHz]	Mode	Modulation	Data rate	Level [dBm]
1 / 2412	802.11b	QPSK	11 Mbps	15.36
6 / 2437	802.11b	QPSK	11 Mbps	14.92
11 / 2462	802.11b	QPSK	11 Mbps	16.65
1 / 2412	802.11g	64QAM	48 Mbps	13.87
6 / 2437	802.11g	64QAM	48 Mbps	13.39
11 / 2462	802.11g	64QAM	48 Mbps	14.85
1 / 2412	802.11n	BPSK	6.5 / 7.25 Mbps	13.86
6 / 2437	802.11n	BPSK	6.5 / 7.25 Mbps	13.55
11 / 2462	802.11n	BPSK	6.5 / 7.25 Mbps	14.8

2.4. WLAN Test results


WLAN 2.4 GHz, peak output power [dBm]	
Mode & data speed	Ch 6
b-mode WLAN DSSS 1 Mbps	13.55
b-mode WLAN DSSS 2 Mbps	13.48
b-mode WLAN DSSS 5.5 Mbps	14.67
b-mode WLAN DSSS 11 Mbps	15.19
g-mode WLAN OFDM 6 Mbps	14.05
g-mode WLAN OFDM 9 Mbps	14.1
g-mode WLAN OFDM 12 Mbps	13.76
g-mode WLAN OFDM 18 Mbps	13.77
g-mode WLAN OFDM 24 Mbps	14.08
g-mode WLAN OFDM 36 Mbps	14.18
g-mode WLAN OFDM 48 Mbps	14.24
g-mode WLAN OFDM 54 Mbps	14.16

2.5. WLAN Test results


2.5.1 802.11b mode, QPSK modulation, 11 Mbps data rate

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	15.36	34.356	PASSED
6 / 2437	14.92	31.046	PASSED
11 / 2462	16.65	46.238	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz




2.5.2 802.11g mode, 64QAM modulation, 48 Mbps data rate

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	13.87	24.378	PASSED
6 / 2437	13.39	21.827	PASSED
11 / 2462	14.85	30.549	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz




2.5.3 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	13.86	24.322	PASSED
6 / 2437	13.55	22.646	PASSED
11 / 2462	14.8	30.2	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz



3. Band edge compliance of RF emissions (FCC §15.247(d), 15.205(b), RSS-210 A8.5)

EUT with DUT number	RM-941, DUT 53350
Accessories with DUT numbers	BP-4GWA, DUT 53351 ; AC-20U, DUT 53340 ; WH-108, DUT 53343
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24/45/100.7
Date of measurements	22-May-2013
Measured by	Zou Ming

3.1.1 Test setup



3.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).


Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit
Below 2390 and above 2483.5	54 dBuV/m (avg) and 74 dBuV/m (pk)

3.3. WLAN test results

3.3.1 802.11b, QPSK modulation, 11 Mbps data rate.

Channel 1 / 2412 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2388	47.84	246.519	48.28	-0.44	-0.441	PASSED

Average (RBW: 1 MHz, VBW: 10 Hz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2388	35.39	58.83	35.83	-0.44	-0.441	PASSED

Channel 11 / 2462 MHz



Peak (RBW: 1 MHz, VBW: 1 MHz)


Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2484	49.09	284.61	49.12	-0.03	-0.026	PASSED

Average (RBW: 1 MHz, VBW: 10 Hz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2484	37.24	72.744	37.27	-0.03	-0.026	PASSED

3.3.2 802.11g, 64QAM modulation, 48 Mbps data rate.

Channel 1 / 2412 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2390	50.3	327.19	50.74	-0.44	-0.441	PASSED

Average (RBW: 1 MHz, VBW: 10 Hz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2390	34.64	53.97	35.08	-0.44	-0.441	PASSED

Channel 11 / 2462 MHz



Peak (RBW: 1 MHz, VBW: 1 MHz)


Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2484	57.44	744.818	57.47	-0.03	-0.026	PASSED

Average (RBW: 1 MHz, VBW: 10 Hz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2484	38.47	83.888	38.5	-0.03	-0.026	PASSED

3.3.3 802.11n, BPSK modulation, 6.5 / 7.25 Mbps data rate.

Channel 1 / 2412 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2390	55.64	605.48	56.08	-0.44	-0.441	PASSED

Average (RBW: 1 MHz, VBW: 10 Hz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2390	37.34	73.595	37.78	-0.44	-0.441	PASSED

Channel 11 / 2462 MHz



Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2484	57.14	719.532	57.17	-0.03	-0.026	PASSED


Average (RBW: 1 MHz, VBW: 10 Hz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Correction [dB]	Results
2484	40.97	111.789	41	-0.03	-0.026	PASSED

4. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-941, DUT 53347
Accessories with DUT numbers	BP-4GWA, DUT 53353 ; AC-20U, DUT 53339 ; WH-108, DUT 53341
Operation Voltage [V] / [Hz]	115 / 60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24/38/99.6
Date of measurements	20-May-2013
Measured by	Gao Sherina

4.1. Test Setup



4.2. Test method and limit

The measurement is made according to procedure KDB 558074 D01 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

4.3. WLAN Test results

4.3.1 802.11b mode, QPSK modulation, 11 Mbps data rate

Channel 6 / 2437 MHz



QuasiPeak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
4.11	39.29	N	PASSED
4.28	40.46	N	PASSED
4.295	40.16	L1	PASSED
4.345	40.39	N	PASSED
4.495	39.25	L1	PASSED
4.51	39.55	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
1.725	28.95	L1	PASSED
3.56	30.21	N	PASSED
3.96	30.03	L1	PASSED
4.035	30.27	N	PASSED
4.41	30.38	L1	PASSED
4.415	30.38	L1	PASSED

4.3.2 802.11g mode, 64QAM modulation, 48 Mbps data rate

Channel 6 / 2437 MHz



QuasiPeak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
1.715	39.89	N	PASSED
3.88	40.13	N	PASSED
4.275	40.62	N	PASSED
4.59	39.45	N	PASSED
4.9	39.31	N	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
3.805	30.43	L1	PASSED
4.29	30.44	L1	PASSED
4.34	30.41	L1	PASSED
4.64	30.19	N	PASSED
4.75	30.22	N	PASSED
4.865	30.37	L1	PASSED

4.3.3 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate

Channel 6 / 2437 MHz



QuasiPeak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
1.73	40.19	N	PASSED
4.335	39.62	N	PASSED
4.345	39.88	N	PASSED
4.46	39.2	N	PASSED
4.725	39.69	L1	PASSED
4.795	39.16	N	PASSED


Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
3.95	30.19	N	PASSED
4.225	30.02	L1	PASSED
4.415	30.16	L1	PASSED
4.425	30.22	N	PASSED
4.47	30.02	L1	PASSED
4.72	30.1	L1	PASSED

5. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-941, DUT 53377
Accessories with DUT numbers	Dummy battery, DUT 53378; WH-108, DUT 53379
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24/55/100.6
Date of measurements	27-May-2013
Measured by	Gao Sherina

5.1. Test Setup



5.2. Test method and limit

The measurement is made according to Public notice KDB 558 074 and IC standard RSS-210.

The reference level for the -20 dBc measurement was obtained as instructed in section 5.4.1.1 of the KDB 558074, using 5-30 % wider span than the EBW.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

5.3. WLAN Test results

5.3.1 802.11b mode, QPSK modulation, 11 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBm]	Result
4844.000	-30.70	PASSED
7258.800	-31.39	PASSED


Channel 6 / 2437 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBm]	Result
4858.000	-31.25	PASSED
7269.000	-30.04	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
4951.600	-33.35	PASSED
7429.200	-32.91	PASSED

5.3.2 802.11g mode, 64QAM modulation, 48 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
4785.720	-27.52	PASSED
7279.200	-26.62	PASSED


Channel 6 / 2437 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
4831.600	-26.16	PASSED
7301.400	-26.05	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
4972.000	-28.15	PASSED
7421.400	-28.11	PASSED

5.3.3 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
4817.200	-26.07	PASSED
7254.000	-26.35	PASSED


Channel 6 / 2437 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
4853.200	-27.00	PASSED
7353.000	-25.44	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
4950.800	-28.49	PASSED
7410.600	-27.31	PASSED

6. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)

EUT with DUT number	RM-941, DUT 53350
Accessories with DUT numbers	BP-4GWA, DUT 53351 ; AC-20U, DUT 53340 ; WH-108, DUT 53343
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24/45/100.7
Date of measurements	22-May-2013
Measured by	Zou Ming

6.1.1 Test setup



6.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
30 - 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

6.3. WLAN test results

6.3.1 802.11b, QPSK modulation, 11 Mbps data rate.

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4824	45.74	193.575	44.27	1.47	28.2	74	PASSED
7236.4	48.68	271.644	38.48	10.2	76.6	125	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4824	31.93	39.496	30.46	1.47	22	54	PASSED
7236.4	36.11	63.87	25.91	10.2	---	---	PASSED

Channel 6 / 2437 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4878.2	42.43	132.343	40.81	1.62	31.5	74	PASSED
7318.4	49.15	286.649	39.1	10.05	24.8	74	PASSED

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
31.32	23.27	14.565	31.37	-8.1	16.7	40	PASSED
31.71	33.48	47.228	41.83	-8.35	6.5	40	PASSED
837.743	22.2	12.887	27.23	-5.03	23.8	46	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4878.2	29.69	30.5	28.07	1.62	24.3	54	PASSED
7318.4	36.01	63.139	25.96	10.05	18	54	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4924	47.91	248.485	46.05	1.86	26.1	74	PASSED
7385	49.08	284.577	38.72	10.36	24.9	74	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4924	34.37	52.276	32.51	1.86	19.6	54	PASSED
7385	36.29	65.268	25.93	10.36	17.7	54	PASSED

6.3.2 802.11g, 64QAM modulation, 48 Mbps data rate.

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4822.9	42.27	129.852	40.81	1.46	31.7	74	PASSED
7237.5	48.67	271.206	38.48	10.19	76.6	125	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4822.9	28.9	27.864	27.44	1.46	25.1	54	PASSED
7237.5	36.07	63.57	25.88	10.19	---	---	PASSED

Channel 6 / 2437 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4879.6	42.91	139.782	41.3	1.61	31.1	74	PASSED
7321.2	48.92	279.222	38.85	10.07	25.1	74	PASSED

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
31.83	34.5	53.064	42.92	-8.42	5.5	40	PASSED
31.918	32.87	43.995	41.35	-8.48	7.1	40	PASSED
31.92	25.41	18.636	33.89	-8.48	14.6	40	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4879.6	29.22	28.913	27.61	1.61	24.8	54	PASSED
7321.2	35.99	63.023	25.92	10.07	18	54	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4923	42.9	139.701	41.05	1.85	31.1	74	PASSED
7387.8	49.71	305.774	39.35	10.36	24.3	74	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4923	29.98	31.546	28.13	1.85	24	54	PASSED
7387.8	36.18	64.38	25.82	10.36	17.8	54	PASSED

6.3.3 802.11n, BPSK modulation, 6.5 / 7.25 Mbps data rate.

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4824.6	42.16	128.233	40.69	1.47	31.8	74	PASSED
7236.5	49.18	287.64	38.98	10.2	76.1	125	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4824.6	28.83	27.631	27.36	1.47	25.2	54	PASSED
7236.5	36.03	63.336	25.83	10.2	---	---	PASSED

Channel 6 / 2437 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4880.2	42.05	126.561	40.45	1.6	31.9	74	PASSED
7321.7	48.55	267.455	38.48	10.07	25.4	74	PASSED

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
31.77	26.68	21.575	35.07	-8.39	13.3	40	PASSED
31.8	26.51	21.147	34.92	-8.41	13.5	40	PASSED
906.667	23.41	14.806	27.3	-3.89	22.6	46	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4880.2	29.29	29.127	27.69	1.6	24.7	54	PASSED
7321.7	35.9	62.381	25.83	10.07	18.1	54	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4922.3	42.53	133.814	40.69	1.84	31.4	74	PASSED
7387.6	49.21	288.802	38.85	10.36	24.8	74	PASSED


Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Margin	Limit [dBμV/m]	Results
4922.3	29.82	30.978	27.98	1.84	24.2	54	PASSED
7387.6	36.15	64.202	25.79	10.36	17.8	54	PASSED

7. 6 dB bandwidth (FCC §15.247(a)(2), RSS-210 A8.2 (1))

EUT with DUT number	RM-941, DUT 53377
Accessories with DUT numbers	Dummy battery, DUT 53378; WH-108, DUT 53379
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24/55/100.6
Date of measurements	27-May-2013
Measured by	Gao Sherina

7.1. Test Setup



7.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for 6 dB bandwidth measurements


Limit [kHz]
>= 500

7.3. WLAN Test results


7.3.1 802.11b mode, XXX modulation, 11 Mbps data rate

Channel / f _c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	8802	PASSED
6 / 2437	8802	PASSED
11 / 2462	8766	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz




7.3.2 802.11g mode, 64QAM modulation, 48 Mbps data rate

Channel / f _c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	16454	PASSED
6 / 2437	16480	PASSED
11 / 2462	16378	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz




7.3.3 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate

Channel / f_c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	17724	PASSED
6 / 2437	17724	PASSED
11 / 2462	17640	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz



8. Power spectral density (FCC §15.247(e), RSS-210 A8.2 (2))

EUT with DUT number	RM-941, DUT 53377
Accessories with DUT numbers	Dummy battery, DUT 53378; WH-108, DUT 53379
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	24/55/100.6
Date of measurements	27-May-2013
Measured by	Gao Sherina

8.1. Test Setup



8.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Result is corrected by bandwidth correction factor -15.2dB (BWCF = $10\log(3\text{ kHz}/100\text{ kHz}) = -15.2\text{ dB}$).

Limits for power spectral density measurements

Limit [dBm] @ 3 kHz
≤ 8


8.3. WLAN Test results

8.3.1 802.11b mode, QPSK modulation, 11 Mbps data rate


Peak (RBW: 100 kHz, VBW: 300 kHz, Max hold)

Channel / f _c [MHz]	P [dBm]	Result
1 / 2412	-14.72	PASSED
6 / 2437	-14.94	PASSED
11 / 2462	-12.19	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz




8.3.2 802.11g mode, 64QAM modulation, 48 Mbps data rate


Peak (RBW: 100 kHz, VBW: 300 kHz, Max hold)

Channel / f _c [MHz]	P [dBm]	Result
1 / 2412	-19.01	PASSED
6 / 2437	-19.31	PASSED
11 / 2462	-17.24	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz




8.3.3 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate


Peak (RBW: 100 kHz, VBW: 300 kHz, Max hold)

Channel / f_c [MHz]	P [dBm]	Result
1 / 2412	-20.37	PASSED
6 / 2437	-21.47	PASSED
11 / 2462	-17.84	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz



9. Test Equipment

9.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCHW0020	DC Power supply	HP6632B	HP	22/24/27, 15C
BJPCPT0040	Receiver	ESCS30	R&S	15C,15B
BJPCPT0069	LISN 50 µH	ESH3-Z5	R&S	15C,15B
BJPCPT0073	Signal Generator	SMR 20	R&S	22/24/27, 15C, 15B
BJPCPT0191	Pulse Limiter	ESH3-Z2	R&S	15C,15B
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C,15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C,15R
BJPCTC0017	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0062	AC Power source	6812B	Hp	15C,15B
BJPCTC0067	Bluetooth Tester	CBT	R&S	22/24/27, 15C
BJPCTC0082	Humidity and Temperature Sensor	175-H2	Testo	15B,15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B,15C
BJPCTC0089	Tempreature Test chamber	VT4002	Votsch industrietechnik	22/24/27, 15C
BJPCTC0090	FSP spectrum analyzer	FSP30	R&S	22/24/27, 15C
BJPCTC0094	GPB-RS232 convertor	GPB-RS232	NI	22/24/27, 15C
BJPCTC0112	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0114	Signal Generator	E8257C	Agilent	22/24/27, 15C
BJPCTC0115	Communication Tester	CMU200	R&S	22/24/27, 15B, 15C
BJPCTC0127	AC Power source	SOYI-500VA	SOYI	15B 15C
BJPCTC0128	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0129	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27 15B 15C
BJPCTC0136	Communication antenna	JXTXLB-880-NF	A-INFOMW	15B 15C
BJPCTC0306	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0305	GPB converter	GPB-RS232	NI	22/24/27, 15C
BJPCTC0304	Spectrum Analyser	FSV30	R&S	22/24/27, 15C

9.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCPT0072	Receiver	ESI B26	R&S	22/24/27, 15C, 15B
BJPCPT0130	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
BJPCPT0150	High Pass Filter	WHKS1200-10SS	Wainwright	22/24/27, 15C, 15B
BJPCPT0151	Band Reject Filter	WRCD1880/2000-0.2/40-5SSK	Wainwright	24, 15B
BJPCPT0154	Band Reject Filter	WRCT2402/2480-2400/2483.5-30-20SS	Wainwright	15C, 15B
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C,15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C,15R
BJPCTC0007	Antenna	HL562	R&S	22/24/27, 15C, 15B
BJPCTC0029	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0034	Band Reject Filter	WRCT 800/880-0.2/40-5SSK	Wainwright	22, 15B
BJPCTC0049	Preamplifier	Blma 0118-1A-Bt	Bonn	22/24/27, 15C, 15B
BJPCTC0055	Communication Tester	CMU200	R&S	22/24/27,15C,15B
BJPCTC0058	Bluetooth Tester	CBT	R&S	15C, 15B
BJPCTC0062	AC Power source	6812B	Hp	15C,15B
BJPCTC0064	Band Reject Filter	WRCG1877/1883-1870/1890-40/6SS	Wainwright	24, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCTC0065	Band Reject Filter	WRCG832/838-825/845-40/5SS	Wainwright	27, 15B
BJPCTC0071	Multi-Device Controller	2090	EMCO	22/24/27, 15C, 15B
BJPCTC0072	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	ETS	22/24/27, 15C, 15B
BJPCTC0073	MAST	Model-TR/POL	ETS	22/24/27, 15C, 15B
BJPCTC0074	MAST	Model 2070-2	ETS	22/24/27, 15C, 15B
BJPCTC0075	Turntable	Model 2188	ETS-EMCO	22/24/27, 15C, 15B
BJPCTC0081	Humidity and Temperature Sensor	175-H2	Testo	15B, 15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B,15C
BJPCTC0096	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
BJPCTC0113	Receiver	ESI B26	R&S	22/24/27, 15B, 15C
BJPCTC0115	Communication Tester	CMU200	R&S	22/24/27, 15B, 15C
BJPCTC0124	Attenuator	SA18N200W-40	Fairview Microwave	-
BJPCTC0125	Loop Antenna	HFH2-Z2	R&S	15C
BJPCTC0126	Tripod	FHU-Z	R&S	15C
BJPCTC0128	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0129	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27 15B 15C
BJPCTC0133	Open Swith and contril unit	OSP 150	R&S	15B,15C
BJPCTC0134	Open Swith and contril unit	OSP 150	R&S	15B,15C
BJPCTC0135	Open Swith and contril unit	OSP 130	R&S	15B,15C
BJPCTC0136	Communication antenna	JXTXLB-880-NF	A-INFOMW	15B 15C