



NVLAP LAB CODE 200707-0



FCC PART 95

EMI MEASUREMENT AND TEST REPORT

For

China and Hong Kong Telecom Engineering Co Ltd

Unit 608, 6/F, New Tech Plaza, 34 Tai Yau Street, San Po Kong , Kowloon, Hong Kong.

FCC ID: QTWG066

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: FRS/GMRS
Test Engineer: William Chan	<i>William - Chan</i>
Report No.: RSZ07030101	
Test Date: 2007-03-09 to 2007-03-14	
Report Date: 2007-03-16	
Reviewed By: EMC Manager: Boni Baniquid	<i>Boni</i>
Prepared By: Bay Area Compliance Laboratory Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratory Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
DESCRIPTION OF TEST CONFIGURATION	4
EQUIPMENT MODIFICATIONS	4
CONFIGURATION OF TEST SETUP	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
§1.1310 and §2.1093 – RF EXPOSURE.....	7
STANDARD APPLICABLE	7
MEASUREMENT RESULT:	7
§2.1046, §95.135 and §95.639(d) - RF OUTPUT POWER.....	8
APPLICABLE STANDARD	8
TEST EQUIPMENT LIST AND DETAILS.....	8
TEST PROCEDURE	8
TEST DATA	9
§2.1047 and §95.637(a) - MODULATION CHARACTERISTIC	10
APPLICABLE STANDARD	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST PROCEDURE	10
TEST DATA	10
§2.1049 and § 95.633(a) (c) – OCCUPIED BANDWIDTH	14
APPLICABLE STANDARD	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST PROCEDURE	14
TEST DATA	14
§2.1053 and §95.635(b) (7) - UNWANTED RADIATION EMISSIONS	18
APPLICABLE STANDARD	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST PROCEDURE	18
TEST RESULTS SUMMARY.....	18
TEST DATA	19
§2.1055 (d), §95.627(b) and §95.621- FREQUENCY STABILITY	21
APPLICABLE STANDARD	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST PROCEDURE	21
TEST DATA	21

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *China and Hong Kong Telecom Engineering Co Ltd*'s product, model number: G-066 or the "EUT" as referred to in this report is a FRS/GMRS. The EUT is measured approximately 22.5 cm L x 4.5 cmW x 2.5 cmH rated input voltage: DC 3.7 V Battery, with permanent Antenna.

** The test data gathered are from production sample, serial number: 0702022 provided by the manufacturer, we received the EUT on 2007-03-01.*

Objective

This Type approval report is prepared on behalf of *China and Hong Kong Telecom Engineering Co Ltd* in accordance with Part 2, Subpart J, and Part 95 of the Federal Communication Commissions rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with TIA/EIA 603-C and Part 95 Subpart B and Subpart E of the Federal Communication Commissions rules.

All emissions measurement was performed and Bay Area Compliance Laboratory Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratory Corp. (Shenzhen) to collect radiated and conducted emission measurement data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratory Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179 and Industrial Canada registration test site No.: 5500A. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0). The current scope of accreditations can be found at

<http://ts.nist.gov/ts/htdocs/210/214/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Equipment Modifications

Bay Area Compliance Laboratory Corp. (Shenzhen) has not done any modification on the EUT.

Configuration of Test Setup



Lying View




Side View



Standing View

Note: We tested Lying orientation, Side orientation and standing orientation, the Standing orientation is the worst mode, so we select the Standing orientation to test.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§1.1310, §2.1093	RF Radiation Exposure	Compliant
§2.1046, §95.135 and §95.639(d)	RF Output Power	Compliant
§2.1047, and §95.637(a)	Modulation Characteristic	Compliant
§2.1049, and §95.633(a)(c)	Occupied Bandwidth	Compliant
§2.1053 §95.635(b) (7)	Spurious Radiated Emissions	Compliant
§2.1055 (d), §95.627(b) and §95.621	Frequency stability	Compliant

§1.1310 and §2.1093 – RF EXPOSURE

Standard Applicable

According to §1.1310, §2.1093, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to FCC Exclusion list, In the following table, f_{GHz} is mid-band frequency in GHz, and d is the distance to a person's body, excluding hands, wrists, feet, and ankles.

Exposure category	<u>low threshold</u>	<u>high threshold</u>
general population	$(60/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(120/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(900/f_{\text{GHz}})$ mW, $d < 20$ cm
occupational	$(375/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(900/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(2250/f_{\text{GHz}})$ mW, $d < 20$ cm

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Measurement Result:

This is a portable device and the Max peak output power is 79 mW < 128 mW $= (60/0.467\text{GHz})$ mW, SAR measurement is not required.

§2.1046, §95.135 and §95.639(d) - RF OUTPUT POWER

Applicable Standard

Per FCC §2.1046, and §95.639(d), No FRS Unit, under any condition of modulation, shall exceed a 0.500 w effective radiated power (ERP).

Per §95.135, A small base station must transmit with no more than 5 watts effective radiated power (ERP).

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Signal Generator	HP8657A	2849U00982	2006-09-29	2007-09-29
Agilent	Spectrum Analyzer	8564E	3943A01781	2006-11-22	2007-11-22
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2006-08-14	2007-08-14
COM POWER	Dipole Antenna	AD-100	041000	2006-09-25	2007-09-25

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the emissions were measured by the substitution.

Test Data**Environmental Conditions**

Temperature:	25 ° C
Relative Humidity:	50%
ATM Pressure:	1005mbar

The testing was performed by William Chan on 2007-03-09.

Test Mode: Transmitting

Indicated		Table	Test Antenna		Substituted			Antenna Gain Correction	Cable Loss (dB)	FCC Part 95			
Frequency (MHz)	Reading (dBuV)		Angle Degree	Height (m)	Polar H/V	Frequency (MHz)	Level (dBm)			Absolute Level (dBm)	Absolute Level (W)	Limit (W)	Comments
462.6375	85.46	0	1.50	V	462.6375	21.02	V	0	3.86	17.16	0.051	0.5	FRS Channel 4
467.6375	87.01	0	1.50	V	467.6375	22.85	V	0	3.87	18.98	0.079	0.5	FRS Channel 11
462.6250	85.82	0	1.50	V	462.6250	21.25	V	0	3.86	17.39	0.054	5	GMRS Channel 18

Test Result: Pass

§2.1047 and §95.637(a) - MODULATION CHARACTERISTIC

Applicable Standard

§2.1047 & §95.637:

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.
- (c) A FRS Unit that transmits emission type F3E must not exceed peak frequency deviation of plus or minus 2.5 kHz.
- (d) A GMRS transmitter that transmits emission type F3E must not exceed a peak frequency deviation of plus or minus 5 kHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Modulation Analyzer	8901B	3438A05208	2007-03-01	2008-03-01
NANYAN	Audio Generator	NY2201	019829	2006-12-23	2007-12-23

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

Test Method: TIA/EIA-603-C

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50%
ATM Pressure:	1005mbar

The testing was performed by William Chan on 2007-03-09.


Test Result: Pass

Test Mode: Transmitting

For 12.5 kHz Channel Bandwidth (FRS -Channel 4) :


Audio Input (mV)	300 Hz Deviation (kHz)	1kHz Deviation (kHz)	3 kHz Deviation (kHz)
0.0	0.431	0.435	0.442
4.0	0.435	0.701	0.572
8.0	0.478	1.031	0.796
12.0	0.530	1.368	0.953
16.0	0.576	1.726	1.128
20.0	0.615	2.010	1.268
24.0	0.659	2.047	1.271
28.0	0.737	2.117	1.279
32.0	0.796	2.130	1.285
36.0	0.824	2.150	1.297

Modulation Limit




For 20 kHz Channel Bandwidth (GMRS – Channel 18):


Audio Input (mV)	300 Hz Deviation (kHz)	1kHz Deviation (kHz)	3 kHz Deviation (kHz)
0. 0	0. 443	0. 440	0. 437
4. 0	0. 456	0. 702	0. 577
8. 0	0. 512	1. 312	0. 786
12. 0	0. 567	1. 680	0. 905
16. 0	0. 659	1. 923	1. 119
20. 0	0. 671	2. 062	1. 286
24. 0	0. 911	2. 117	1. 302
28. 0	0. 934	2. 129	1. 428
32. 0	1. 090	2. 207	1. 525
36. 0	1. 154	2. 106	1. 587



Audio frequency response:



Audio Low Pass Filter:



§2.1049 and § 95.633(a) (c) – OCCUPIED BANDWIDTH

Applicable Standard

Per FCC §2.1049 and FCC §95.633(a) (c), the authorized bandwidth for emission type F3E or F2D transmitted by an FRS Unit is 12.5 kHz. and The authorized bandwidth for emission type F1D, G1D, F3E or G3E transmitted by an GMRS Unit is 20 kHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
NANYAN	Audio Generator	NY2201	019829	2006-12-23	2007-12-23
Rohde&Schwarz	EMI Test Receiver	ESCI	100035	2006-08-17	2007-08-17

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

The antenna was disconnected from the transmitter and the short cable was connected to the transmitter RF output.

The RF output was connected to the input of the spectrum analyzer through sufficient attenuation.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50%
ATM Pressure:	1005mbar


The testing was performed by William Chan on 2007-03-14.

Test Result: Pass.

Test Mode: Transmitting


Please refer to the hereinafter plots.

Emission mask




Emission Mask (FRS -- Channel 4)

Date: 14.MAR.2007 23:27:28



Emission Mask (FRS -- Channel 11)

Date: 14.MAR.2007 23:21:02



Emission Mask (GMRS -- Channel 18)

Date: 14.MAR.2007 23:51:33

§2.1053 and §95.635(b) (7) - UNWANTED RADIATION EMISSIONS

Applicable Standard

§2.1053 and §95.635

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Signal Generator	HP8657A	2849U00982	2006-09-29	2007-09-29
Agilent	Spectrum Analyzer	8564E	3943A01781	2006-11-22	2007-11-22
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2006-08-14	2007-08-14
COM POWER	Dipole Antenna	AD-100	041000	2006-09-25	2007-09-25
SUNOL SCIENCES	Horn Antenna	DRH-118	A052604	2006-09-25	2007-09-25

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 log₁₀ (TXpwr in Watts/0.001) - the absolute level

Spurious attenuation limit in dB = 43 + 10 log₁₀ (power out in Watts)

Test Results Summary

For channel 4: 23.79 dB at 2775.825 MHz. (FRS)

For channel 11: 22.19 dB at 2805.825 MHz. (FRS)

For channel 18: 22.38 dB at 2775.75 MHz. (GMRS)

Test Data**Environmental Conditions**

Temperature:	25 ° C
Relative Humidity:	50%
ATM Pressure:	1005mbar

The testing was performed by William Chan on 2007-03-12.

Test Mode: Transmitting (Channel 4, 462.6375MHz)

FRS

Frequency (MHz)	ERP (dBm)	Polar H/V	Transmission power (dBm)	Attenuation (dBc)	Spurious Attenuation Limit (dB)	Margin (dB)
2775.825	-36.71	V	17.16	53.87	30.08	23.79
1850.55	-37.13	V	17.16	54.29	30.08	24.21
2775.825	--37.91	H	17.16	55.07	30.08	24.99
1387.9125	-38.53	H	17.16	55.69	30.08	25.61
1850.55	-39.03	H	17.16	56.19	30.08	26.11
925.2750	-39.12	V	17.16	56.28	30.08	26.20
925.2750	-39.72	H	17.16	56.88	30.08	26.80
1387.9125	-40.63	V	17.16	57.79	30.08	27.71
2313.1875	-42.28	H	17.16	59.44	30.08	29.36
3238.4625	-43.47	H	17.16	60.63	30.08	30.55
2313.1875	-43.82	V	17.16	60.98	30.08	30.90
3238.4625	-45.67	V	17.16	62.83	30.08	32.75

NOTE:

Transmission Power = 0.051w =17.16 dBm

Spurious Attenuation Limit = $43 + \log (0.051) = 30.08$ dB

Test Mode: Transmitting (Channel 11, 467.6375MHz)

FRS

Frequency (MHz)	ERP (dBm)	Polar H/V	Transmission power (dBm)	Attenuation (dBc)	Spurious Attenuation Limit (dB)	Margin (dB)
2805.825	-35.21	V	18.98	54.19	32.0	22.19
1870.550	-36.53	V	18.98	55.51	32.0	23.51
2805.825	--38.41	H	18.98	57.39	32.0	25.39
1402.9125	-38.63	V	18.98	57.61	32.0	25.61
935.275	-38.92	V	18.98	57.90	32.0	25.90
1870.550	-38.93	H	18.98	57.91	32.0	25.91
935.275	-40.22	H	18.98	59.20	32.0	27.20
1402.9125	-40.93	H	18.98	59.91	32.0	27.91
2338.1875	-41.82	V	18.98	60.80	32.0	28.80
3273.4625	-43.57	V	18.98	62.55	32.0	30.55
2338.1875	-44.52	H	18.98	63.50	32.0	31.50
3273.4625	-45.07	H	18.98	64.05	32.0	32.05

NOTE:

Transmission Power = $0.079w = 18.98 \text{ dBm}$

Spurious Attenuation Limit = $43 + \log (0.079) = 32.0 \text{ dB}$

Test Mode: Transmitting (Channel 18, 462.625MHz)

GMRS

Frequency (MHz)	ERP (dBm)	Polar H/V	Transmission power (dBm)	Attenuation (dBc)	Spurious Attenuation Limit (dB)	Margin (dB)
2775.75	-35.31	V	17.39	52.70	30.32	22.38
1850.50	-37.13	V	17.39	54.52	30.32	24.20
925.25	-37.82	V	17.39	55.21	30.32	24.89
1387.875	-38.03	V	17.39	55.42	30.32	25.1
925.25	-39.02	H	17.39	56.41	30.32	26.09
1387.875	-39.53	H	17.39	56.92	30.32	26.6
1850.50	-39.83	H	17.39	57.22	30.32	26.90
2313.325	-40.12	V	17.39	57.51	30.32	27.19
3238.375	-41.37	V	17.39	58.76	30.32	28.44
2313.325	-41.42	H	17.39	58.81	30.32	28.49
2775.75	-41.61	H	17.39	59.00	30.32	28.68
3238.375	-44.37	H	17.39	61.76	30.32	31.44

NOTE:

Transmission Power = $0.054w = 17.39 \text{ dBm}$

Spurious Attenuation Limit = $43 + \log (0.054) = 30.32 \text{ dB}$

§2.1055 (d), §95.627(b) and §95.621- FREQUENCY STABILITY

Applicable Standard

According to FCC §2.1055(a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$, and according to FCC 2.1055(d)(2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.627(b), Each FRS Unit must be maintained within a frequency tolerance of 0.00025%.

According to FCC §95.621, Each GMRS transmitter for mobile station, small base station and control station operation must be maintained within a frequency tolerance of 0.0005%.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde&Schwarz	EMI Test Receiver	ESCI	100035	2006-09-29	2007-09-29

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Spectrum Analyzer via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable DC power supply Source. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50%
ATM Pressure:	1005mbar

The testing was performed by William Chan on 2007-03-14.

Test Result: Pass

Test Mode: Transmitting

FRS Channel 4:

Reference Frequency: 462.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Measured Frequency (MHz)	Frequency Error (ppm)
50	3.7	462.63795	+ 0.97
40	3.7	462.63782	+ 0.69
30	3.7	462.63776	+ 0.56
20	3.7	462.63765	+ 0.32
10	3.7	462.63768	+ 0.38
0	3.7	462.63741	- 0.19
-10	3.7	462.63724	- 0.56
-20	3.7	462.63709	- 0.88
-30	3.7	462.63692	- 1.25

Reference Frequency: 462.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Measured Frequency (MHz)	Frequency Error (ppm)
20	3.2	462.63762	+0.25

FRS Channel 11:

Reference Frequency: 462.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Measured Frequency (MHz)	Frequency Error (ppm)
50	3.7	467.63798	+ 1.03
40	3.7	467.63784	+ 0.73
30	3.7	467.63771	+ 0.45
20	3.7	467.63758	+ 0.33
10	3.7	467.63767	+ 0.36
0	3.7	467.63732	- 0.37
-10	3.7	467.63716	- 0.72
-20	3.7	467.63704	- 0.98
-30	3.7	467.63695	- 1.21

Reference Frequency: 462.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Measured Frequency (MHz)	Frequency Error (ppm)
20	3.2	467.63768	+ 0.38

GMRS Channel 18:

Reference Frequency: 462.62500 MHz, Limit: ± 5 ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Measured Frequency (MHz)	Frequency Error (ppm)
50	3.7	462.62544	+ 0.95
40	3.7	462.62531	+ 0.67
30	3.7	462.62519	+ 0.41
20	3.7	462.62506	+ 0.12
10	3.7	462.62485	- 0.32
0	3.7	462.62481	- 0.41
-10	3.7	462.62476	- 0.51
-20	3.7	462.62472	- 0.60
-30	3.7	462.62465	- 0.75

Reference Frequency: 462.62500 MHz, Limit: ± 5 ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Measured Frequency (MHz)	Frequency Error (ppm)
20	3.2	462.62472	+ 0.63