

# MPE Calculation

FCC ID: QV3DMS12100A

RF function or Mode	Frequency range (MHz)	Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm <sup>2</sup> )	Requirement (mW/cm <sup>2</sup> )
Bluetooth(1Mbps)	2402.00 ~ 2480.00	2.00	0.50	2.50	1.779	0.00036	1.000
Bluetooth(2,3Mbps)	2402.00 ~ 2480.00	1.50	0.50	2.00	1.585	0.00032	1.000
	~						
	~						
	~						
	~						
	~						
	~						

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 1.779 / (4 \times 20^2 \times \pi) \\
 &= 0.00036 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm<sup>2</sup>)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna

## ▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averageing time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

**Conclusion : The exposure condition of this device is compliant with FCC**