



REGULATORY COMPLIANCE REPORT

FCC CFR 47 Part 1.1310

Report No.: BLYK08-U5 Rev A (FCC MPE)

Company: Novanta Corporation

Model Name: M7E-TERA

REGULATORY COMPLIANCE REPORT

Company Name: Novanta Corporation

Model Name: M7E-TERA

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: BLYK08-U5 Rev A (FCC MPE)

This report supersedes: NONE

Applicant: Novanta Corporation
125 Middlesex Turnpike,
Bedford Massachusetts 01730
USA

Issue Date: 16th December 2023

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSIBLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = $EIRP / (4 * \pi * d^2)$

$EIRP = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

Because the EUT belongs to the General Population/Uncontrolled Exposure group, the limit of power density for devices operating below 1500 MHz equals $f/1500$ mW/cm², where f = frequency in MHz.

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
902.75 – 927.25	6.0	3.98	30.0	1000.0	0.80	0.60	23.0

From the above calculation the minimum safe distance between users and the EUT to meet the FCC §1.1310 requirements is 23.0 cm

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310 for General Population/Uncontrolled Exposure.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com