

White Vinyl 3 mils
Background color: grayscale 30%
Laminated adhesive 3M #300SLE
Material must be rated for outdoor use (sunlight, water
and marine exposure)
Unique serial numbers, starting at 95000 in 16 pt Times
New Roman Bold Black

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LOAD SYSTEMS INTERNATIONAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF LOAD SYSTEMS INTERNATIONAL IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED DIMENSION ARE IN INCHES **TOLERANCE ARE:** DECIMALS **FRACTIONS** ± 0.1 ± 1/32 X.X ± 0.05 > 1/2 X.XX ± 0.01 >=1/2 ± 1/16 ANGLE ± 0.5° X.XXX± 0.002 X.XXXX ± 0.0005 ROUGHTNESS 125 🗸

APPROVALS DATE

DRAWN M. Cloutier 2009-05-08

CHECKED

MAT. WEIGHT

L

Treatment:

Load Systems International

www.load-systems.com

Α

REV.

DESCRIPTION DATE

UB305 Label

REVISIONS

Ajout boite "Model No"

A GS22X-XX DWG. NO. UB305_rev20090520 A

CALE: 1:1 RELEASE DATE: SHEET 1 OF 1

2009/05/20

APPROVED



GS22X label location

