



Report No.: RZA1104-0662MPE

# MPE REPORT

Product Name	Full Size EVDO PCle Data Card
Model	MV84PG
FCC ID	QVZ-MV84PG
Client	CHENG UEI PRECISION IND. CO., LTD
Test date	2011-05-12

## Test By

**Company:** TA Technology (Shanghai) Co., Ltd.  
**Address:** No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China  
**Contact:** Yang Weizhong  
**Telephone:** +86-021-50791141/2/3  
**Fax:** +86-021-50791141/2/3-8000  
**Website:** <http://www.ta-shanghai.com>  
**E-mail:** [yangweizhong@ta-shanghai.com](mailto:yangweizhong@ta-shanghai.com)

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.RZA2010-1422-FCC

Page 2 of 5

### Maximum Permissible Exposure

Type of EUT: Full Size EVDO PCIe Data Card

Model: MV84PG

Client: CHENG UEI PRECISION IND. CO., LTD

Manufacturer: CHENG UEI PRECISION IND. CO., LTD

Maximum conducted output power (measured) and antenna Gain:

Band	Maximum conducted output power(dBm)	Antenna Gain(dBi)
CDMA Cellular	23.91	1.26
CDMA PCS	23.56	1.56

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.RZA2010-1422-FCC

Page 3 of 5

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TABLE 1 – LIMITS FOR MAXIMUN PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0 .....	614	1.63	*(100)	6
3-30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300 .....	61.4	0.163	1.0	6
300-1500 .....	.....	.....	f/300	6
1500-100,000 .....	.....	.....	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34 .....	614	1.63	*(100)	30
1.34-30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300 .....	27.5	0.073	0.2	30
300-1500 .....	.....	.....	f/1500	30
1500-100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.RZA2010-1422-FCC

Page 4 of 5

The maximum permissible exposure for 300~1500MHz is  $f/1500$ , 1500~100,000MHz is 1.0. So

Band	The maximum permissible exposure
<b>CDMA Cellular</b>	<b>0.56 mW/cm<sup>2</sup></b>
<b>CDMA PCS</b>	<b>1 mW/cm<sup>2</sup></b>

**IMPORTANT NOTE:** To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.RZA2010-1422-FCC

Page 5 of 5

### RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided.

This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in OET Bulletin 65 is used in the calculation.

Equation from OET Bulletin 65, Edition 97-01 is:

$$S = PG / 4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**CDMA Cellular:** PG = 23.91dBm+ (1.26dBi) =25.17dBm=0.329W

**CDMA PCS:** PG = 23.56dBm+ (1.56dBi) =25.12dBm=0.325W

R =20 cm

$\pi$  = 3.1416

Solving for S, the power density at 20 cm is

Band	Result (mW/cm <sup>2</sup> )	Limit Value (mW/cm <sup>2</sup> )
CDMA Cellular	0.065	0.56
CDMA PCS	0.065	1.0

Note: For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of 47 CFR Part 15.247 (b) (5)