



TEST REPORT

Product Name : 802.11g / b WLAN Cardbus Adapter

Model Number : MWL-31G1

Applicant : Microlink Communications Inc.

Address : 6F, No. 30, Raykuang Rd., Neihu, Taipei, Taiwan.

Received Date : Jun. 30, 2003

Tested Date : Aug. 22, 2003

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to testing, and be invalid as separately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the data issued.





Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000

Report No. : ER03-07-084FRF

Page 2 of 59

Test Report Certification

Product Name : 802.11g / b WLAN Cardbus Adapter
Model Number : MWL-31G1
Applicant : Microlink Communications Inc.

Measurement Standard :

47 CFR Part 15, Subpart B and Subpart C (Section 15.247),
ANSI C63.4-2001

Tested By : K. P. Pang, **Date** : (Sept. 08, 2003)
(K. P. Pang)

Reviewed By : Roger Sheng, **Date** : (Sept. 08, 2003)
(Roger Sheng)

Approved By : Chieh-De Tsai, **Date** : (Sept. 08, 2003)
(Chieh-De Tsai, Manager)



WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



TABLE OF CONTENTS

TITLE	PAGE NO.
1. GENERAL INFORMATION	5
1.1 General Statement.....	5
1.2 General Description of EUT & Power.....	5
1.3 Description of Peripherals.....	6
1.4 EUT & Peripherals Setup Diagram.....	7
1.5 EUT Operating Condition.....	7
1.6 Description of Test Site	8
1.7 Summary of Test Results	8
2. CONDUCTED POWERLINE TEST	9
2.1 Test Equipments	9
2.2 Test Setup	9
2.3 Conducted Power Line Emission Limit.....	10
2.4 Test Procedure	10
2.5 Uncertainty of Conducted Emission	10
2.6 Conducted RF Voltage Measurement.....	11-12
2.7 Photos of Conduction Test.....	13
3. RADIATED EMISSION TEST	14
3.1 Test Equipments	14
3.2 Test Setup	14
3.3 Radiation Limit.....	15
3.4 Test Procedures.....	16
3.5 Uncertainty of Radiated Emission	16
3.6 Radiated RF Noise Measurement	17-41
3.7 Photos of Open Site	42-43
4. 6dB BANDWIDTH MEASUREMENT	42
4.1 Test Equipments	44
4.2 Test Setup	44
4.3 Limits of 6dB Bandwidth Measurement.....	44
4.4 Test Procedure	44
4.5 Uncertainty of Conducted Emission	44
4.6 Test Results.....	45
4.7 Photo of 6db Bandwidth Measurement.....	46-47
5. MAXIMUM PEAK OUTPUT POWER	48
5.1 Test Equipments	48
5.2 Test Setup	48
5.3 Limits of Maximum Peak Output Power.....	48
5.4 Test Procedure	49
5.5 Uncertainty of Conducted Emission	49
5.6 Test Results.....	49
6. POWER SPECTRAL DENSITY MEASUREMENT	50
6.1 Test Equipments	50
6.2 Test Setup	50
6.3 Limits of Power Spectral Density Measurement	50
6.4 Test Procedure	51
6.5 Uncertainty of Conducted Emission	51
6.6 Test Results.....	51
6.7 Photo of Power Spectral Density Measurement	52-53



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 4 of 59

TABLE OF CONTENTS

<u>TITLE</u>	<u>PAGE NO.</u>
7. OUT OF BAND MEASUREMENT	54
7.1 Test Equipments	54
7.2 Test Setup	54
7.3 Limits of Out of Band Emissions Measurement	54
7.4 Test Procedure	55
7.5 Uncertainty of Conducted Emission	55
7.6 Test Results	55-56
7.7 Photo of Out of Band Measurement	57-58
8. ANTENNA REQUIREMENT	59
8.1 Standard Applicable	59
8.2 Antenna Connected Construction	59



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000

Report No. : ER03-07-084FRF

Page 5 of 59

1. GENERAL INFORMATION

1.1 General Statement

MEASUREMENT DEVIATION : Comply with standard in full

TRACEABILITY : This test result is traceable to national or international std.

1.2 General Description of EUT & Power

MANUFACTURER : Microlink Communications Inc.
SAMPLE NAME : 802.11g / b WLAN Cardbus Adapter
MODEL NAME : MWL-31G1
FREQUENCY RANGE : 2412 MHz TO 2462MHz
CHANNEL NUMBER : 1~11CH
CHANNEL SEPARATION : 5MHz
AIR DATA RATE : 54Mbps (802.11g Mode), 11Mbps(802.11b Mode)
TYPE OF MODULATION : Orthogonal Frequency Division Multiplex or Direct Sequence Spread Spectrum
FREQUENCY SELECTION : BY SOFTWARE
EUT Description : 2.4GHz (Orthogonal Frequency Division Multiplex or Direct Sequence Spread Spectrum) Data Transceiver for 802.11g / b WLAN Cardbus Adapter
ANTENNA TYPE : Printed Antenna, Gain = 1 dBi
POWER SOURCE : 5V/3.3VDC(From Notebook PC)

Data applied to :

1. Company name : Amigo Technology Co., Ltd.
Sample name : 802.11g / b WLAN Cardbus Adapter
Model name : AWP-631IL
Address : 1F, No. 285, Sec. 2, Ti-Ding Blvd. Neihu. Taipei, Taiwan, R.O.C.
2. Company name : Paradigm Technology Inc.
Sample name : 802.11g / b WLAN Cardbus Adapter
Model name : PWB-311
Address : 3F, No. 285, Sec. 2, Ti-Ding Blvd, Naihu, Taipei, Taiwan, R.O.C.
3. Company name : Xinetron Co., LTD.
Sample name : 802.11g / b WLAN Cardbus Adapter
Model name : GWP22G
Address : 4F, No. 171, Sec. 2, Tatung Road. Hsinchih, Taipei Hsien, Taiwan.
4. Company name : InterEpoch Technology, Inc.
Sample name : 802.11g / b WLAN Cardbus Adapter
Model name : IWE180-X
Address : 6F, No. 1, Alley 1, Lane 235, Pao-Chiao Rd., Hsin-Tiencity, Taipei Hsin, Taiwan, R.O.C.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd.,ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 6 of 59

5. Company name : Zonet Technology, Inc.
Sample name : 802.11g / b WLAN Cardbus Adapter r
Model name : ZEW1500
Address : 5F, No. 789, Boai St., Jubei City, Hsin-Chu, Taiwan, 30241 R.O.C.

Note : The RF-Chip combined with 802.11b&g mode. It will auto-detect the situation then switch the mode. The 802.11g mode is the worse case than the 802.11b mode . So it is only listed the 802.11b mode in some test result.

1.3 Description of Peripherals

(1) Notebook PC

MANUFACTURER : DELL CORP.
MODEL NUMBER : PP01L
SERIAL NUMBER : CN-09C748-48155-1AP-6081
FCC : DOC
POWER CORD : Unshielded, Detachable, 1.8m

(2) Printer

MANUFACTURER : Hp Corp.
MODEL NUMBER : C6431D
SERIAL NUMBER : CN19T6S011
FCC ID : DOC
POWER SOURCE : 100-240VAC,50/60Hz,0.7A
SIGNAL CABLE : Shielded , Undetachable , 1.8m


(3) Modem

MANUFACTURER : ZYXEL communication Corp.
MODEL NUMBER : Omni 56K
SERIAL NUMBER : S1Z4107729
FCC ID : 1880MN156K
POWER SOURCE : 9VAC(From Power Adapter)
SIGNAL CABLE : Shielded , Undetachable , 1.8m

(4) Notebook PC

MANUFACTURER : DELL CORP.
MODEL NUMBER : PP01L
SERIAL NUMBER : CN-09C748-48155-1AP-6630
FCC : DOC
POWER CORD : Unshielded, Detachable, 1.8m

1.4 EUT & Peripherals Setup Diagram



1.5 EUT Operating Condition

1. Set up all computers like the setup diagram.
2. NB (1) ping 192.168.1.90 -t -l 5000 to NB(4)
3. NB (4) ping 192.168.1.80 -t -l 5000 to NB(1)
4. All of the function are under run.
5. Start test.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 8 of 59

1.6 Description of Test Site

SITE DESCRIPTION : FCC Certificate NO. : 90585
BSMI Certificate NO. : SL2-IN-E-0002
NVLAP Lab code : 200118-0
CNLA Certificate NO. : CNLA-ZL97018
VCCI Certificate NO. : R-1229, C-1250

NAME OF SITE : Ecom Sertech Corp. Hsinchu
(Spin-off from ITRI / ERSO on Apr. 01, 2003)

SITE LOCATION : Rm.258, Bldg.17, NO.195 , Sec. 4, Chung Hsing Rd.,
Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

1.7 Summary of Test Results

The EUT has been tested according to the following specifications :

APPLIED STANDARD : 47 CFR Part 15, Subpart B and Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.107 15.207	AC Power Conducted Emission Limit : 15.107	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Orthogonal Frequency Division Multiplex System Limit : 6dB bandwidth > 500KHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit : max. 30dBm	PASS	Meet the requirement of limit
15.109 15.205 15.209	Transmitter Radiated Emissions Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(d)	Power Spectral Density Limit : max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Out of Band Emission and Restricted Band Radiation Limit:20dB less than peak value of fundamental frequency Restricted band Limit:Table 15.209	PASS	Meet the requirement of limit




2. CONDUCTED POWERLINE TEST

2.1 Test Equipments

The following test equipments are used during the conducted powerline tests :

Manufacturer or Type	Model No	Serial No.	Date of Calibration	Calibration Period	Remark
SPECTRUM ANALYZER & DISPLAY	HP 8568A	2235A02320	APR. 01, 2003	1 Year	PRETEST
QUASI-PEAK ADAPTER	HP 85650 A	2341A00672	APR. 01, 2003	1 Year	PRETEST
ISOLATION TRANSFORMER	SOLAR 7032-1	N/A	N/A	N/A	FINAL
L.I.S.N.	EMCO 3850/2	9311-1025 9401-1028	JAN. 08, 2003 For Characteristic impedance MAY 18, 2003 For Insertion loss	1 Year	FINAL
TEST RECEIVER	R/S ESHS30	838550/003	JUN. 07, 2003	1 Year	FINAL
SHIELDED ROOM	KEENE 5983	NO.1	N/A	N/A	FINAL
PULSE LIMIT	R/S EHS3Z2	357.8810.52	JUL. 10, 2003	1 Year	FINAL
N TYPE COAXIAL CABLE	-----	-----	JUL. 10, 2003	1 Year	FINAL
50Ω TERMINATOR	-----	-----	JUL. 10, 2003	1 Year	FINAL

2.2 Test Setup





2.3 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Frequency (MHz)	Maximum RF Line Voltage (Db μ v)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56	56-46
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

For intentional device, according to § 15.207(a) Line Conducted Emission Limit is same as above table.

2.4 Test Procedure

The test procedure is performed in a 12ft×12ft×8ft(L×W×H) shielded room. the EUT along with its peripherals were placed on a 1.0m(W)× 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chasis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chasis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

2.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.36 dB.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 11 of 59

2.6 Conducted RF Voltage Measurement

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 26 °C

Humidity : 65 % RH

Frequency (MHz)	Loss(dB)		Measurement				L1 Emission (dBμV)		L2 Emission (dBμV)		Limits (dBμV)	
			L1(dBμV)		L2(dBμV)		Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.
	L1	L2	Q.P.	A.V.	Q.P.	A.V.						
0.150	0.1	0.2	*	*	*	*	*	*	*	*	66.00	56.00
0.177	0.1	0.2	45.20	*	48.20	*	45.30	*	48.40	*	64.63	54.63
0.297	0.1	0.2	34.60	*	*	*	34.70	*	*	*	60.33	50.33
0.348	0.1	0.2	*	*	37.10	*	*	*	37.30	*	59.01	49.01
0.660	0.1	0.2	28.70	*	*	*	28.80	*	*	*	56.00	46.00
1.047	0.1	0.2	*	*	40.60	*	*	*	40.80	*	56.00	46.00
1.944	0.1	0.2	*	*	34.20	*	*	*	34.40	*	56.00	46.00
2.082	0.1	0.2	29.60	*	*	*	29.70	*	*	*	56.00	46.00
3.627	0.2	0.2	39.20	*	*	*	39.40	*	*	*	56.00	46.00
3.738	0.2	0.2	*	*	34.20	*	*	*	34.40	*	56.00	46.00
4.740	0.2	0.2	*	*	32.60	*	*	*	32.80	*	56.00	46.00
4.818	0.2	0.2	38.70	*	*	*	38.90	*	*	*	56.00	46.00
8.925	0.4	0.4	39.30	*	*	*	39.70	*	*	*	60.00	50.00
12.453	0.5	0.5	*	*	38.40	*	*	*	38.90	*	60.00	50.00
28.092	1.4	1.4	41.60	*	*	*	43.00	*	*	*	60.00	50.00
28.617	1.4	1.6	*	*	38.90	*	*	*	40.50	*	60.00	50.00
30.000	1.4	1.8	*	*	*	*	*	*	*	*	60.00	50.00

REMARKS : 1. * Undetectable or the Q.P. value is lower than the limits of Ave.

2. Mode : wireless 802.11b.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 12 of 59

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.


Temperature : 26 °C

Humidity : 65 % RH

Frequency (MHz)	Loss(dB)		Measurement				L1 Emission (dBμV)		L2 Emission (dBμV)		Limits (dBμV)	
			L1(dBμV)		L2(dBμV)		Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.
	L1	L2	Q.P.	A.V.	Q.P.	A.V.						
0.150	0.1	0.2	*	*	*	*	*	*	*	66.00	56.00	
0.177	0.1	0.2	50.30	*	51.90	*	50.40	*	52.10	64.63	54.63	
0.294	0.1	0.2	37.50	*	39.30	*	37.60	*	39.50	60.41	50.41	
0.648	0.1	0.2	*	*	29.60	*	*	*	29.80	56.00	46.00	
1.047	0.1	0.2	35.10	*	*	*	35.20	*	*	56.00	46.00	
1.944	0.1	0.2	28.60	*	28.70	*	28.70	*	28.90	56.00	46.00	
3.708	0.2	0.2	36.70	*	*	*	36.90	*	*	56.00	46.00	
3.723	0.2	0.2	*	*	33.60	*	*	*	33.80	56.00	46.00	
4.728	0.2	0.2	*	*	32.70	*	*	*	32.90	56.00	46.00	
4.947	0.2	0.2	33.90	*	*	*	34.10	*	*	56.00	46.00	
13.011	0.5	0.5	37.10	*	*	*	37.60	*	*	60.00	50.00	
14.595	0.6	0.6	*	*	38.40	*	*	*	39.00	60.00	50.00	
28.617	1.4	1.6	*	*	38.60	*	*	*	40.20	60.00	50.00	
28.974	1.4	1.7	38.90	*	*	*	39.30	*	*	60.00	50.00	
30.000	1.4	1.8	*	*	*	*	*	*	*	60.00	50.00	

REMARKS : 1. * Undetectable or the Q.P. value is lower than the limits of Ave.
 2. Mode : wireless 802.11g.

2.7 Photos of Conduction Test



3. RADIATED EMISSION TEST


3.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.


Manufacturer or Type	Model No	Serial No	Date of Calibration	Calibration Period	Remark
CHASE BI-LOG ANTENNA	CBL6112B	2421	MAY 07, 2003	1 Year	FINAL
SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003	1 Year	FINAL
OPEN SITE	-----	No.2	JAN. 10, 2003	1 Year	FINAL
N TYPE COAXIAL CABLE	CHA9525	4	JUL. 13, 2003	1 Year	FINAL
Horn Antenna	AH-118	10089	FEB. 25, 2003	1 Year	FINAL
HP Pre-amplifier	8449B	3008A01471	OCT. 11, 2002	1 Year	FINAL
HP High pass filter	84300/80038	011	cal. on use	1 Year	FINAL
Horn Antenna	AH-840	03077	FEB. 25, 2003	1 Year	FINAL

3.2 Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 to 1GHz.



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



Antenna Elevation Variable

3.3 Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/M)	Radiated (μ V/M)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.



3.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

3.5 Uncertainty of Radiated Emission

The uncertainty of radiated emission is ± 2.72 dB.



3.6 Radiated RF Noise Measurement

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 25 °C

Humidity : 65 % RH

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Meter Reading at 3m(dBμV/M)		Limits at 3m (dBμV/M)	Emission Level at 3m(dBμV/M)	
			Horizontal	Vertical		Horizontal	Vertical
30.00	17.98	0.90	*	*	40.00	*	*
319.99	14.25	3.72	17.90	11.50	46.00	35.87	29.47
359.99	15.74	3.96	11.20	11.00	46.00	30.90	30.70
399.99	17.24	4.20	10.40	11.30	46.00	31.84	32.74
439.99	17.67	4.48	9.60	10.40	46.00	31.75	32.55
479.98	18.10	4.76	8.30	10.20	46.00	31.16	33.06
519.98	18.56	5.00	8.30	9.20	46.00	31.86	32.76
559.98	19.05	5.20	7.60	9.70	46.00	31.85	33.95
600.26	19.54	5.40	8.80	10.70	46.00	33.74	35.64
701.99	19.45	5.91	9.10	10.40	46.00	34.46	35.76
1000.00	21.30	7.00	*	*	54.00	*	*

REMARKS : 1. *Undetectable

2. Emission level (dB μ V/M) =Antenna Factor (dB/m) + Cable loss (dB)
+ Meter Reading (dB μ V).

3. According to technical experiences, all spurious emission at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representation for the test.

4.The 802.11g is worse case than 802.11b. It is only listed Data for 802.11g mode as a representation.

5. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 18 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.94	48.13	34.44	2.77	35.38	9.5	0	40.46	74	-33.54	P	1.0
4823.94	42.70	34.44	2.77	35.38	9.5	0	35.03	54	-18.97	A	1.0
7236.35	42.23	39.81	3.94	35.56	9.5	0	40.92	74	-33.08	P	1.0
7236.35	32.82	39.81	3.94	35.56	9.5	0	31.51	54	-22.49	A	1.0
9647.92	51.24	38.54	4.10	35.67	9.5	0	48.70	74	-25.30	P	1.0
9647.92	47.64	38.54	4.10	35.67	9.5	0	45.10	54	-8.90	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 19 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 RX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.96	51.79	34.44	2.77	35.38	9.5	0	44.12	74	-29.88	P	1.0
4823.96	49.28	34.44	2.77	35.38	9.5	0	41.61	54	-12.39	A	1.0
7236.63	42.51	39.81	3.94	35.56	9.5	0	41.20	74	-32.80	P	1.0
7236.63	32.74	39.81	3.94	35.56	9.5	0	31.43	54	-22.57	A	1.0
9647.97	54.12	38.54	4.10	35.67	9.5	0	51.58	74	-22.42	P	1.0
9647.97	51.53	38.54	4.10	35.67	9.5	0	48.99	54	-5.01	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd.,ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 20 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.98	47.06	34.77	2.80	35.40	9.5	0	39.73	74	-34.27	P	1.0
4873.98	41.45	34.77	2.80	35.40	9.5	0	34.12	54	-19.88	A	1.0
7311.44	43.60	39.78	4.00	35.57	9.5	0	42.31	74	-31.69	P	1.0
7311.44	33.94	39.78	4.00	35.57	9.5	0	32.65	54	-21.35	A	1.0
9747.92	53.25	38.53	4.02	35.72	9.5	0	50.57	74	-23.43	P	1.0
9747.92	50.36	38.53	4.02	35.72	9.5	0	47.68	54	-6.32	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 21 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 RX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.96	51.47	34.77	2.80	35.40	9.5	0	44.14	74	-29.86	P	1.0
4873.96	48.11	34.77	2.80	35.40	9.5	0	40.78	54	-13.22	A	1.0
7311.59	41.92	39.78	4.00	35.57	9.5	0	40.63	74	-33.37	P	1.0
7311.59	32.61	39.78	4.00	35.57	9.5	0	31.32	54	-22.68	A	1.0
9747.91	55.32	38.53	4.02	35.72	9.5	0	52.64	74	-21.36	P	1.0
9747.91	53.22	38.53	4.02	35.72	9.5	0	50.54	54	-3.46	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 22 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4923.96	47.12	35.10	2.83	35.41	9.5	0	40.14	74	-33.86	P	1.0
4923.96	41.37	35.10	2.83	35.41	9.5	0	34.39	54	-19.61	A	1.0
7386.35	41.86	39.75	4.06	35.57	9.5	0	40.59	74	-33.41	P	1.0
7386.35	32.75	39.75	4.06	35.57	9.5	0	31.48	54	-22.52	A	1.0
9847.83	54.23	38.52	3.93	35.77	9.5	0	51.41	74	-22.59	P	1.0
9847.83	51.92	38.52	3.93	35.77	9.5	0	49.10	54	-4.90	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 23 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4923.39	51.02	35.09	2.83	35.41	9.5	0	44.03	74	-29.97	P	1.0
4923.39	48.21	35.09	2.83	35.41	9.5	0	41.22	54	-12.78	A	1.0
7386.59	43.03	39.75	4.06	35.57	9.5	0	41.76	74	-32.24	P	1.0
7386.59	33.87	39.75	4.06	35.57	9.5	0	32.60	54	-21.40	A	1.0
9847.86	56.95	38.52	3.93	35.77	9.5	0	54.13	74	-19.87	P	1.0
9847.86	54.36	38.52	3.93	35.77	9.5	0	51.54	54	-2.46	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 24 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.96	47.02	34.44	2.77	35.38	9.5	0	39.35	74	-34.65	P	1.0
4823.96	41.62	34.44	2.77	35.38	9.5	0	33.95	54	-20.05	A	1.0
7236.75	43.05	39.81	3.94	35.56	9.5	0	41.74	74	-32.26	P	1.0
7236.75	33.52	39.81	3.94	35.56	9.5	0	32.21	54	-21.79	A	1.0
9647.88	50.34	38.54	4.10	35.67	9.5	0	47.80	74	-26.20	P	1.0
9647.88	47.67	38.54	4.10	35.67	9.5	0	45.13	54	-8.87	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 25 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.95	51.72	34.44	2.77	35.38	9.5	0	44.05	74	-29.95	P	1.0
4823.95	48.94	34.44	2.77	35.38	9.5	0	41.27	54	-12.73	A	1.0
7236.84	41.52	39.81	3.94	35.56	9.5	0	40.21	74	-33.79	P	1.0
7236.84	32.73	39.81	3.94	35.56	9.5	0	31.42	54	-22.58	A	1.0
9647.88	53.21	38.54	4.10	35.67	9.5	0	50.67	74	-23.33	P	1.0
9647.88	50.61	38.54	4.10	35.67	9.5	0	48.07	54	-5.93	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 26 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.93	46.12	34.77	2.80	35.40	9.5	0	38.79	74	-35.21	P	1.0
4873.93	39.94	34.77	2.80	35.40	9.5	0	32.61	54	-21.39	A	1.0
7311.63	41.75	39.78	4.00	35.57	9.5	0	40.46	74	-33.54	P	1.0
7311.63	32.39	39.78	4.00	35.57	9.5	0	31.10	54	-22.90	A	1.0
9747.94	52.75	38.53	4.02	35.72	9.5	0	50.07	74	-23.93	P	1.0
9747.94	49.72	38.53	4.02	35.72	9.5	0	47.04	54	-6.96	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 27 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.99	50.97	34.77	2.80	35.40	9.5	0	43.64	74	-30.36	P	1.0
4873.99	47.50	34.77	2.80	35.40	9.5	0	40.17	54	-13.83	A	1.0
7311.61	43.12	39.78	4.00	35.57	9.5	0	41.83	74	-32.17	P	1.0
7311.61	33.48	39.78	4.00	35.57	9.5	0	32.19	54	-21.81	A	1.0
9747.94	54.31	38.53	4.02	35.72	9.5	0	51.63	74	-22.37	P	1.0
9747.94	52.28	38.53	4.02	35.72	9.5	0	49.60	54	-4.40	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 28 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4923.94	46.70	35.10	2.83	35.41	9.5	0	39.72	74	-34.28	P	1.0
4923.94	41.04	35.10	2.83	35.41	9.5	0	34.06	54	-19.94	A	1.0
7386.72	44.03	39.75	4.06	35.57	9.5	0	42.76	74	-31.24	P	1.0
7386.72	33.10	39.75	4.06	35.57	9.5	0	31.83	54	-22.17	A	1.0
9847.86	53.72	38.52	3.93	35.77	9.5	0	50.90	74	-23.10	P	1.0
9847.86	51.07	38.52	3.93	35.77	9.5	0	48.25	54	-5.75	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd.,ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 29 of 59

Test Requirement: 15.109 ,15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/17
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4923.99	50.13	35.10	2.83	35.41	9.5	0	43.15	74	-30.85	P	1.0
4923.99	47.02	35.10	2.83	35.41	9.5	0	40.04	54	-13.96	A	1.0
7386.19	41.32	39.75	4.06	35.57	9.5	0	40.05	74	-33.95	P	1.0
7386.19	31.73	39.75	4.06	35.57	9.5	0	30.46	54	-23.54	A	1.0
9847.85	55.74	38.52	3.93	35.77	9.5	0	52.92	74	-21.08	P	1.0
9847.85	53.75	38.52	3.93	35.77	9.5	0	50.93	54	-3.07	A	1.0

1. Measurement was up to 18GHz harmonic,“---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The test limit is 3M limit.
7. The other emission levels were very low against the limit.
8. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 30 of 59

Test Requirement: 15.205
 The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2413.25	78.37	31.79	2.36	0.00	9.50	0.00	103.02	Fundamental Frequency		P	1.00
2413.25	71.41	31.79	2.36	0.00	9.50	0.00	96.06			A	1.00
*4824.04	46.12	34.44	2.77	35.38	9.50	1.00	39.45	74	-34.55	P	1.00
*4824.04	38.02	34.44	2.77	35.38	9.50	1.00	31.35	54	-22.65	A	1.00
7236.61	42.32	39.81	3.94	35.56	9.50	1.00	42.01	74	-31.99	P	1.00
7236.61	34.32	39.81	3.94	35.56	9.50	1.00	34.01	54	-19.99	A	1.00
9647.89	49.03	38.54	4.10	35.67	9.50	1.00	47.49	74	-26.51	P	1.03
9647.89	44.42	38.54	4.10	35.67	9.50	1.00	42.88	54	-11.12	A	1.03
*12062.80	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14475.36	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16887.92	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19300.48	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21713.04	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24125.60	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 31 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2413.20	74.31	31.79	2.36	0.00	9.50	0.00	98.96	Fundamental Frequency		P	1.00
2413.20	67.46	31.79	2.36	0.00	9.50	0.00	92.11			A	1.00
*4824.03	48.03	34.44	2.77	35.38	9.50	1.00	41.36	74	-32.64	P	1.00
*4824.03	42.72	34.44	2.77	35.38	9.50	1.00	36.05	54	-17.95	A	1.00
7236.14	42.05	39.81	3.94	35.56	9.50	1.00	41.74	74	-32.26	P	1.00
7236.14	33.07	39.81	3.94	35.56	9.50	1.00	32.76	54	-21.24	A	1.00
9647.92	51.52	38.54	4.10	35.67	9.50	1.00	49.98	74	-24.02	P	1.00
9647.92	48.45	38.54	4.10	35.67	9.50	1.00	46.91	54	-7.09	A	1.00
*12059.15	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14470.98	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16882.81	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19294.64	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21706.47	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24118.30	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 32 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2438.30	78.26	31.76	2.43	0.00	9.50	0.00	102.95	Fundamental Frequency		P	1.00
2438.30	71.16	31.76	2.43	0.00	9.50	95.85	A			1.00	
*4874.04	45.72	34.77	2.80	35.40	9.50	1.00	39.39	74	-34.61	P	1.00
*4874.04	38.25	34.77	2.80	35.40	9.50	1.00	31.92	54	-22.08	A	1.00
*7311.33	41.97	39.78	4.00	35.57	9.50	1.00	41.68	74	-32.32	P	1.00
*7311.33	33.05	39.78	4.00	35.57	9.50	1.00	32.76	54	-21.24	A	1.00
9747.91	50.67	38.53	4.02	35.72	9.50	1.00	48.99	74	-25.01	P	1.00
9747.91	46.13	38.53	4.02	35.72	9.50	1.00	44.45	54	-9.55	A	1.00
*12191.85	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14630.22	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17068.59	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19506.96	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21945.33	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24383.70	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 33 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2438.35	75.26	31.76	2.43	0.00	9.50	0.00	99.95	Fundamental Frequency		P	1.00
2438.35	38.37	31.76	2.43	0.00	9.50	0.00	63.06			A	1.00
*4873.98	49.77	34.77	2.80	35.40	9.50	1.00	43.44	74	-30.56	P	1.00
*4873.98	44.06	34.77	2.80	35.40	9.50	1.00	37.73	54	-16.27	A	1.00
*7311.16	42.14	39.78	4.00	35.57	9.50	1.00	41.85	74	-32.15	P	1.00
*7311.16	33.14	39.78	4.00	35.57	9.50	1.00	32.85	54	-21.15	A	1.00
9747.92	52.82	38.53	4.02	35.72	9.50	1.00	51.14	74	-22.86	P	1.00
9747.92	49.81	38.53	4.02	35.72	9.50	1.00	48.13	54	-5.87	A	1.00
*12186.35	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14623.62	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17060.89	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19498.16	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21935.43	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24372.70	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 34 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2463.40	80.03	31.74	2.49	0.00	9.50	0.00	104.76	Fundamental Frequency		P	1.00
2463.40	73.12	31.74	2.49	0.00	9.50	0.00	97.85			A	1.00
*4923.99	45.03	35.10	2.83	35.41	9.50	1.00	39.05	74	-34.95	P	1.03
*4923.99	36.94	35.10	2.83	35.41	9.50	1.00	30.96	54	-23.04	A	1.03
*7386.26	43.12	39.75	4.06	35.57	9.50	1.00	42.85	74	-31.15	P	1.00
*7386.26	33.03	39.75	4.06	35.57	9.50	1.00	32.76	54	-21.24	A	1.00
9847.90	55.42	38.52	3.93	35.77	9.50	1.00	53.60	74	-20.40	P	1.13
9847.90	53.31	38.52	3.93	35.77	9.50	1.00	51.49	54	-2.51	A	1.13
*12312.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14775.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17237.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19700.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22162.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24625.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11b transmitting (11Mbps).
- The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 35 of 59

Test Requirement: 15.205
 The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2463.35	75.25	31.74	2.49	0.00	9.50	0.00	99.98	Fundamental Frequency		P	1.00
2463.35	68.08	31.74	2.49	0.00	9.50	0.00	92.81			A	1.00
*4923.98	48.42	35.10	2.83	35.41	9.50	1.00	42.44	74	-31.56	P	1.03
*4923.98	42.41	35.10	2.83	35.41	9.50	1.00	36.43	54	-17.57	A	1.03
*7386.43	41.06	39.75	4.06	35.57	9.50	1.00	40.79	74	-33.21	P	1.00
*7386.43	32.93	39.75	4.06	35.57	9.50	1.00	32.66	54	-21.34	A	1.00
9847.88	55.32	38.52	3.93	35.77	9.50	1.00	53.50	74	-20.50	P	1.00
9847.88	52.68	38.52	3.93	35.77	9.50	1.00	50.86	54	-3.14	A	1.00
*12316.60	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14779.92	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17243.24	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19706.56	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22169.88	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24633.20	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11b transmitting (11Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 36 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2414.35	76.49	31.79	2.36	0.00	9.50	0.00	101.14	Fundamental Frequency		P	1.00
2414.35	68.36	31.79	2.36	0.00	9.50	93.01	A			1.00	
*4823.93	45.07	34.44	2.77	35.38	9.50	1.00	38.40	74	-35.60	P	1.00
*4823.93	36.91	34.44	2.77	35.38	9.50	1.00	30.24	54	-23.76	A	1.00
7236.08	41.66	39.81	3.94	35.56	9.50	1.00	41.35	74	-32.65	P	1.00
7236.08	33.16	39.81	3.94	35.56	9.50	1.00	32.85	54	-21.15	A	1.00
9647.94	49.44	38.54	4.10	35.67	9.50	1.00	47.90	74	-26.10	P	1.03
9647.94	43.98	38.54	4.10	35.67	9.50	1.00	42.44	54	-11.56	A	1.03
*12062.80	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14475.36	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16887.92	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19300.48	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21713.04	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24125.60	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 37 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH1 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2413.77	73.24	31.79	2.36	0.00	9.50	0.00	97.89	Fundamental Frequency		P	1.00
2413.77	63.89	31.79	2.36	0.00	9.50	0.00	88.54			A	1.00
*4823.97	43.12	34.44	2.77	35.38	9.50	1.00	36.45	74	-37.55	P	1.00
*4823.97	32.89	34.44	2.77	35.38	9.50	1.00	26.22	54	-27.78	A	1.00
7236.94	41.69	39.81	3.94	35.56	9.50	1.00	41.38	74	-32.62	P	1.00
7236.94	31.27	39.81	3.94	35.56	9.50	1.00	30.96	54	-23.04	A	1.00
9647.91	42.68	38.54	4.10	35.67	9.50	1.00	41.14	74	-32.86	P	1.00
9647.91	31.10	38.54	4.10	35.67	9.50	1.00	29.56	54	-24.44	A	1.00
*12059.15	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14470.98	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16882.81	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19294.64	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21706.47	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24118.30	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 38 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2435.44	76.92	31.76	2.42	0.00	9.50	0.00	101.60	Fundamental Frequency		P	1.00
2435.44	68.81	31.76	2.42	0.00	9.50	93.49	A			1.00	
*4873.99	46.12	34.77	2.80	35.40	9.50	1.00	39.79	74	-34.21	P	1.00
*4873.99	37.63	34.77	2.80	35.40	9.50	1.00	31.30	54	-22.70	A	1.00
*7311.04	42.69	39.78	4.00	35.57	9.50	1.00	42.40	74	-31.60	P	1.00
*7311.04	33.67	39.78	4.00	35.57	9.50	1.00	33.38	54	-20.62	A	1.00
9748.25	52.08	38.53	4.02	35.72	9.50	1.00	50.40	74	-23.60	P	1.00
9748.25	45.76	38.53	4.02	35.72	9.50	1.00	44.08	54	-9.92	A	1.00
*12191.85	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14630.22	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17068.59	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19506.96	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21945.33	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24383.70	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd.,ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 39 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH6 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2435.39	72.91	31.76	2.42	0.00	9.50	0.00	97.59	Fundamental Frequency		P	1.00
2435.39	64.97	31.76	2.42	0.00	9.50	0.00	89.65			A	1.00
*4873.74	41.62	34.77	2.80	35.40	9.50	1.00	35.29	74	-38.71	P	1.00
*4873.74	30.17	34.77	2.80	35.40	9.50	1.00	23.84	54	-30.16	A	1.00
*7310.97	40.46	39.78	4.00	35.57	9.50	1.00	40.17	74	-33.83	P	1.00
*7310.97	29.57	39.78	4.00	35.57	9.50	1.00	29.28	54	-24.72	A	1.00
9747.94	52.07	38.53	4.02	35.72	9.50	1.00	50.39	74	-23.61	P	1.00
9747.94	49.22	38.53	4.02	35.72	9.50	1.00	47.54	54	-6.46	A	1.00
*12186.35	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14623.62	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17060.89	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19498.16	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21935.43	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24372.70	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
7. The other emission levels were very low against the limit
8. The test limit is 3M limit.
9. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 40 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2464.30	78.72	31.74	2.50	0.00	9.50	0.00	103.45	Fundamental Frequency		P	1.00
2464.30	70.53	31.74	2.50	0.00	9.50	0.00	95.26			A	1.00
*4923.93	44.61	35.10	2.83	35.41	9.50	1.00	38.63	74	-35.37	P	1.03
*4923.93	35.87	35.10	2.83	35.41	9.50	1.00	29.89	54	-24.11	A	1.03
*7391.91	44.23	39.74	4.07	35.57	9.50	1.00	43.97	74	-30.03	P	1.00
*7391.91	34.50	39.74	4.07	35.57	9.50	1.00	34.24	54	-19.76	A	1.00
9848.05	57.62	38.52	3.93	35.77	9.50	1.00	55.80	74	-18.20	P	1.13
9848.05	49.70	38.52	3.93	35.77	9.50	1.00	47.88	54	-6.12	A	1.13
*12312.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14775.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17237.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19700.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22162.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24625.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
7. The other emission levels were very low against the limit
8. The test limit is 3M limit.
9. Mode : wireless 802.11g transmitting (6Mbps).



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
 Report No. : ER03-07-084FRF
 Page 41 of 59

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Microlink	Test Date :	2003/8/7
Product Name	802.11g / b WLAN Cardbus Adapter	Test By:	K. P. Pang
Model Name	MWL-31G1	TEMP&Humidity :	34.5°C , 43%

CH11 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2464.25	73.63	31.74	2.50	0.00	9.50	0.00	98.36	Fundamental Frequency		P	1.00
2464.25	65.49	31.74	2.50	0.00	9.50	0.00	90.22			A	1.00
*4923.92	47.23	35.10	2.83	35.41	9.50	1.00	41.25	74	-32.75	P	1.03
*4923.92	42.57	35.10	2.83	35.41	9.50	1.00	36.59	54	-17.41	A	1.03
*7386.29	42.05	39.75	4.06	35.57	9.50	1.00	41.78	74	-32.22	P	1.00
*7386.29	32.32	39.75	4.06	35.57	9.50	1.00	32.05	54	-21.95	A	1.00
9847.88	54.74	38.52	3.93	35.77	9.50	1.00	52.92	74	-21.08	P	1.00
9847.88	52.14	38.52	3.93	35.77	9.50	1.00	50.32	54	-3.68	A	1.00
*12316.60	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14779.92	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17243.24	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19706.56	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22169.88	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24633.20	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$, $Margin = Level - Limit$
- The other emission levels were very low against the limit
- The test limit is 3M limit.
- Mode : wireless 802.11g transmitting (6Mbps).

3.7 Photos of Open Site





Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 43 of 59



4. 6dB BANDWIDTH MEASUREMENT


4.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2 Test Setup



4.3 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500KHz

4.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 200KHz.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 45 of 59

4.6 Test Results

Input Power (System)	5V/3.3VDC (From Notebook PC)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	12.70	0.5	PASS
6	2437	12.70	0.5	PASS
11	2462	12.62	0.5	PASS


NOTE: FOR 802.11b

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.55	0.5	PASS
6	2437	16.55	0.5	PASS
11	2462	16.55	0.5	PASS


NOTE: FOR 802.11g




4.7 Photo of 6db Bandwidth Measurement



Channel 1



Channel 6



Channel 11


NOTE: FOR 802.11b




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720


FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 47 of 59



Channel 1



Channel 6



Channel 11

NOTE: FOR 802.11g

5. MAXIMUM PEAK OUTPUT POWER


5.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A
GIGA-TRONICS POWER METER	8542	1828329	SEP. 21, 2002

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.2 Test Setup



5.3 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.



5.4 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

5.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.82 dB.

5.6 Test Results

Input Power (System)	5V/3.3VDC (From Notebook PC)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	17.85	30	PASS
6	2437	17.70	30	PASS
11	2462	18.43	30	PASS

NOTE: FOR 802.11b (11Mbps)

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	17.53	30	PASS
6	2437	17.43	30	PASS
11	2462	17.17	30	PASS

NOTE: FOR 802.11g (6 Mbps)



6. POWER SPECTRAL DENSITY MEASUREMENT


6.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

6.2 Test Setup



6.3 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.



6.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 30KHz VBW, set sweep time=span / 3KHz.

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

6.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.82 dB.

6.6 Test Results

Input Power (System)	5V/3.3VDC (From Notebook PC)	Environmental Conditions	27°C , 70%RH,
Tested By	K. P. Pang		

Cable loss = 1dB

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
1	2412	-9.62	8	PASS
6	2437	-7.92	8	PASS
11	2462	-7.94	8	PASS

NOTE: 1. FOR 802.11b (11Mbps)

2. Power Spectral Density = power spectral density reading + cable loss

Cable loss = 1dB


Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
1	2412	-11.05	8	PASS
6	2437	-11.34	8	PASS
11	2462	-11.33	8	PASS

NOTE: 1. FOR 802.11g (6 Mbps)


2. Power Spectral Density = power spectral density reading + cable loss




6.7 Photo of Power Spectral Density Measurement



Channel 1



Channel 6



Channel 11


NOTE: 802.11b (11 Mbps)




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720


FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 53 of 59



Channel 1



Channel 6



Channel 11

NOTE: 802.11g (6 Mbps)



7. OUT OF BAND MEASUREMENT


7.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

7.2 Test Setup



7.3 Limits of Out of Band Emissions Measurement

1. Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.



7.4 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100KHz with suitable frequency span including 100KHz bandwidth from band edge. The band edges was measured and recorded.

7.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.82 dB.

7.6 Test Results

A. Conducted

Refer to 7.7 photo of out band Emission measurement

B. Radiated

For 802.11b Mode

NOTE1: The band edge emission plot on the following first figure shows 47.10dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.3897GHz). The emission of carrier strength list in the test result of channel 1 at the item 3.6 is 96.06 dBuV/m(AV), so the maximum field strength in restrict band is 96.06-47.10=48.96 dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second figure shows 45.65 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.4844GHz). The emission of carrier strength list in the test result of channel 11 at the item 3.6 is 97.85 dBuV/m(AV), so the maximum field strength in restrict band is 97.85-45.65=52.20 dBuV/m which is under 54 dBuV/m limit.

Input Power (System)	5V/3.3VDC (From Notebook PC)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel Frequency (MHz)	Required Limit (dBc)	Pass / Fail
<2400	>20	PASS
>2483.5	>20	PASS



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 56 of 59

For 802.11g Mode

NOTE1: The band edge emission plot on the following first figure shows 43.71dB delta between carrier maximum power and local maximum emission in restrict band (2.3895GHz). The emission of carrier strength list in the test result of channel 1 at the item 3.6 is 93.01dBuV/m(AV), so the maximum field strength in restrict band is $93.01 - 43.71 = 49.30$ dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second figure shows 41.43dB delta between carrier maximum power and local maximum emission in restrict band (2.4844GHz). The emission of carrier strength list in the test result of channel 11 at the item 3.6 is 95.26dBuV/m(AV), so the maximum field strength in restrict band is $95.26 - 41.43 = 53.83$ dBuV/m which is under 54 dBuV/m limit.

Input Power (System)	5V/3.3VDC (From Notebook PC)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel Frequency (MHz)	Required Limit (dBc)	Pass / Fail
<2400	>20	PASS
>2483.5	>20	PASS




Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 57 of 59

7.7 Photo of Out of Band Measurement



FRONT



BACK


NOTE: FOR 802.11b (11 Mbps)




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : QVZ20090000
Report No. : ER03-07-084FRF
Page 58 of 59



FRONT



BACK

NOTE: FOR 802.11g (6 Mbps)



8. ANTENNA REQUIREMENT

8.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.2 Antenna Connected Construction

The antenna used in this product is Printed antenna. The maximum gain of these antennas are only 1 dBi.