

10.4 Radiated Emission Data

a) Channel 0

Operation Mode : Receiving /Transmitting

Fundamental Frequency : 2402 MHz

Test Date : May 23, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB) (H/V Max)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave (H/V Max.)	Peak	Ave.			
2390.000	50.3	---	50.8	---	-2.1	48.7	---	74.0	54.0	-5.3	180	1.0
2483.500	59.0	---	56.0	49.3	-1.7	57.3	47.6	74.0	54.0	-6.4	0	1.0

b) Channel 39

Operation Mode : Receiving / Transmitting

Fundamental Frequency : 2441MHz

Test Date : May 23, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB) (H/V Max)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave (H/V Max.)	Peak	Ave.			
2383.000	50.2	---	50.3	---	-2.1	48.2	---	74.0	54.0	-5.8	180	1.0
2483.500	58.7	---	56.2	48.8	-1.7	56.0	47.1	74.0	54.0	-6.9	360	1.0

c) Channel 78

Operation Mode : Receiving / Transmitting

Fundamental Frequency : 2480 MHz

Test Date : May 23, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB) (H/V Max)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave (H/V Max.)	Peak	Ave.			
2390.000	50.4	---	51.0	---	-2.1	48.9	---	74.0	54.0	-5.1	180	1.0
2483.500	58.7	---	56.0	49.1	-1.7	57.0	47.4	74.0	54.0	-6.6	0	1.0