

Analysis Report

The Equipment Under Test (EUT) is a portable 2.4GHz Transceiver (Controller) operating at the frequency range of 2439-2480MHz with 1 MHz channel spacing.

The EUT is powered by 6*1.5V AA battery. And it is able to control the drone after being turned on.

Antenna Type: Internal integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 95.8dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 98.8dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS \cdot D)^2 \cdot 1000 / 30] = 2.276\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain
So;

Conducted Power = 2.276mW.

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 \cdot 5 / \text{sqrt}(2.402)$ mW

= 9.68 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.