

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Drone Thunderbolt Jet X2 operating at 2.4G Band.
The EUT can be powered by DC 3.7V (1 x 3.7V rechargeable battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: -10.0 dBm (± 3 dB)

The nominal radiated output power (e.i.r.p) specified: -10.0 dBm (± 3 dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 86.4 dB μ V/m at 3m in the frequency 2440MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -8.83dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 83.3 dB μ V/m at 3m in the frequency 2468MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -11.93dBm

which is within the production variation.

The maximum conducted output power specified is -7.0dBm= 0.200mW

The source- based time-averaging conducted output power
=0.200* Duty cycle mW <0.200 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$\begin{aligned} P_{th}(\text{mW}) &= ERP_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left(\frac{60}{ERP_{20\text{cm}} \sqrt{f}} \right)) \\ &= 3060 * (0.5/20)^{1.9} \text{ mW} \\ &= 2.72 \text{ mW} \end{aligned}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 7.6522ms

Effective period of the cycle = 58.0 μ s x1 +275.4 μ s x1 = 0.3334ms

DC =0.3334ms / 7.6522ms =0.0436 or 4.36%