

# FCC Radio Test Report

## FCC ID: QWHIP300

This report concerns (check one): Original Grant Class I Change Class II Change

**Project No.** : 1705C233  
**Equipment** : Loudspeaker System  
**Model Name** : iP300  
**Applicant** : MUSIC Group Manufacturing PH Ltd.  
**Address** : 17A Brunswick Street Hamilton HM 10 Bermuda

**Date of Receipt** : May 25, 2017  
**Date of Test** : May 25, 2017 ~ Jul. 10, 2017  
**Issued Date** : Jul. 11, 2017  
**Tested by** : BTL Inc.

**Testing Engineer** : Shawn Xiao  
(Shawn Xiao)

**Technical Manager** : David Mao  
(David Mao)

**Authorized Signatory** : Steven Lu  
(Steven Lu)

# **B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,  
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

<b>Table of Contents</b>	<b>Page</b>
<b>1 . CERTIFICATION</b>	<b>7</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>8</b>
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
<b>3 . GENERAL INFORMATION</b>	<b>10</b>
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.5 DESCRIPTION OF SUPPORT UNITS	13
<b>4 . EMC EMISSION TEST</b>	<b>14</b>
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
4.1.2 TEST PROCEDURE	14
4.1.3 DEVIATION FROM TEST STANDARD	14
4.1.4 TEST SETUP	15
4.1.5 EUT OPERATING CONDITIONS	15
4.1.6 EUT TEST CONDITIONS	15
4.1.7 TEST RESULTS	15
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 RADIATED EMISSION LIMITS	16
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 EUT TEST CONDITIONS	19
4.2.7 TEST RESULTS (9 KHZ TO 30 MHZ)	19
4.2.8 TEST RESULTS (30 MHZ TO 1000 MHZ)	19
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	19
<b>5 . NUMBER OF HOPPING CHANNEL</b>	<b>20</b>
5.1 APPLIED PROCEDURES	20
5.1.1 TEST PROCEDURE	20
5.1.2 DEVIATION FROM STANDARD	20
5.1.3 TEST SETUP	20
5.1.4 EUT OPERATION CONDITIONS	20
5.1.5 EUT TEST CONDITIONS	20
5.1.6 TEST RESULTS	20
<b>6 . AVERAGE TIME OF OCCUPANCY</b>	<b>21</b>

<b>Table of Contents</b>	<b>Page</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>	<b>21</b>
6.1.1 TEST PROCEDURE	21
6.1.2 DEVIATION FROM STANDARD	21
6.1.3 TEST SETUP	21
6.1.4 EUT OPERATION CONDITIONS	22
6.1.5 EUT TEST CONDITIONS	22
6.1.6 TEST RESULTS	22
<b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>23</b>
7.1 APPLIED PROCEDURES / LIMIT	23
7.1.1 TEST PROCEDURE	23
7.1.2 DEVIATION FROM STANDARD	23
7.1.3 TEST SETUP	23
7.1.4 EUT TEST CONDITIONS	23
7.1.5 TEST RESULTS	23
<b>8 . BANDWIDTH TEST</b>	<b>24</b>
8.1 APPLIED PROCEDURES	24
8.1.1 TEST PROCEDURE	24
8.1.2 DEVIATION FROM STANDARD	24
8.1.3 TEST SETUP	24
8.1.4 EUT OPERATION CONDITIONS	24
8.1.5 EUT TEST CONDITIONS	24
8.1.6 TEST RESULTS	24
<b>9 . PEAK OUTPUT POWER TEST</b>	<b>25</b>
9.1 APPLIED PROCEDURES / LIMIT	25
9.1.1 TEST PROCEDURE	25
9.1.2 DEVIATION FROM STANDARD	25
9.1.3 TEST SETUP	25
9.1.4 EUT OPERATION CONDITIONS	25
9.1.5 EUT TEST CONDITIONS	25
9.1.6 TEST RESULTS	25
<b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>26</b>
10.1 APPLIED PROCEDURES / LIMIT	26
10.1.1 TEST PROCEDURE	26
10.1.2 DEVIATION FROM STANDARD	26
10.1.3 TEST SETUP	26
10.1.4 EUT OPERATION CONDITIONS	26
10.1.5 EUT TEST CONDITIONS	26
10.1.6 TEST RESULTS	26
<b>11 . MEASUREMENT INSTRUMENTS LIST</b>	<b>27</b>
<b>12 . EUT TEST PHOTO</b>	<b>29</b>

**Table of Contents****Page**

<b>ATTACHMENT A - CONDUCTED EMISSION</b>	<b>33</b>
<b>ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)</b>	<b>36</b>
<b>ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>41</b>
<b>ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>48</b>
<b>ATTACHMENT E - NUMBER OF HOPPING CHANNEL</b>	<b>73</b>
<b>ATTACHMENT F - AVERAGE TIME OF OCCUPANCY</b>	<b>75</b>
<b>ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>88</b>
<b>ATTACHMENT H - BANDWIDTH</b>	<b>93</b>
<b>ATTACHMENT I - PEAK OUTPUT POWER</b>	<b>98</b>
<b>ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>103</b>

### REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1705C233	Original Issue.	Jul. 11, 2017

## 1. CERTIFICATION

Equipment : Loudspeaker System  
Brand Name : TURBOSOUND  
Model Name : iP300  
Applicant : MUSIC Group Manufacturing PH Ltd.  
Manufacturer : MUSIC Group Manufacturing PH Ltd.  
Address : 17A Brunswick Street Hamilton HM 10 Bermuda  
Factory : Zhongshan Eurotec Electronics Ltd.  
Address : Eurotec Industrial Park #1 Junjing Rd., Min Zhong Town, Zhongshan,  
Guangdong 528441 China.  
Date of Test : May 25, 2017 ~ Jul. 10, 2017  
Test Sample : Engineering Sample  
Standard(s) : FCC Part15, Subpart C (15.247)  
ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1705C233) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

**Test results included in this report is only for the Bluetooth EDR part.**

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15, Subpart C (15.247)			
Standard(s) Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	Hopping Channel Separation	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247 (b)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205	Restricted Bands	PASS	
15.203	Antenna Requirement	PASS	

Note:

(1) "N/A" denotes test is not applicable in this test report



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 319330

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150 KHz ~ 30MHz	2.32

### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	H	3.78
		200MHz ~ 1,000MHz	V	4.10
		200MHz ~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

### C. Other Measurement:

Test Item	Uncertainty
Conducted Spurious Emission	2.67dB
Hopping Channel Separation	53.46MHz
Peak Output Power	0.95dB
Number of Hopping Frequency	53.46MHz
Temperature	0.08°C
Humidity	1.5%

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Loudspeaker System	
Brand Name	TURBOSOUND	
Model Name	iP300	
Model Difference	N/A	
Output Power (Max.)	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps) $\pi$ /4-DQPSK(2Mbps)
	Bit Rate of Transmitter	8-DPSK(3Mbps)
	Output Power Max.	6.84 dBm(1Mbps) 7.46 dBm(3Mbps)
Power Source	AC Mains	
Power Rating	100-120V, 50/60Hz	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PIFA	N/A	0

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

**Note:**


- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software Version	CC256x_Bluetooth_Hardware_Evaluation_Tool_V1.0_Setup		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	14	14	14
Parameters(3Mbps)	14	14	14

**3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**



**3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.2m	AC Cable

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 -0.50	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)  
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C/RSS-247.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### 4.2.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.2.3 DEVIATION FROM TEST STANDARD


No deviation

**4.2.4 TEST SETUP**


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 4.2.7 TEST RESULTS (9 KHZ TO 30 MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.2.8 TEST RESULTS (30 MHZ TO 1000 MHZ)

Please refer to the Attachment C.

#### 4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 5.1.6 TEST RESULTS

Please refer to the Attachment E

## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS


#### 6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
- j. DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
- k. DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### **6.1.5 EUT TEST CONDITIONS**

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### **6.1.6 TEST RESULTS**

Please refer to the Attachment F

## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels
  - Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span
  - Video (or Average) Bandwidth (VBW)  $\geq$  RBW
  - Sweep = Auto
  - Detector function = Peak
  - Trace = Max Hold

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 7.1.5 TEST RESULTS

Please refer to the Attachment G

## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 8.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 8.1.6 TEST RESULTS

Please refer to the Attachment H



**9. PEAK OUTPUT POWER TEST**

**9.1 APPLIED PROCEDURES / LIMIT**

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	1 Watt or 30dBm ( hopping channel >75) 0.125Watt or 21dBm (hopping channel <75	2400-2483.5	PASS

**9.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

**9.1.2 DEVIATION FROM STANDARD**

No deviation.

**9.1.3 TEST SETUP**



**9.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

**9.1.5 EUT TEST CONDITIONS**

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz

**9.1.6 TEST RESULTS**

Please refer to the Attachment I

## 10. ANTENNA CONDUCTED SPURIOUS EMISSION

### 10.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

#### 10.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.
- Offset=antenna gain+cable loss

#### 10.1.2 DEVIATION FROM STANDARD

No deviation.

#### 10.1.3 TEST SETUP



#### 10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 10.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 10.1.6 TEST RESULTS

Please refer to the Attachment J

## 11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Mar. 26, 2018
2	LISN	EMCO	3816/2	52765	Mar. 26, 2018
3	50Ω Terminator	SHX	TF2-3G-A	8122901	Mar. 26, 2018
4	TWO-LINE V-NETWORK	R&S	ENV216	101447	Mar. 26, 2018
5	Cable	emci	RG223(9KHz-30 MHz)(5m)	N/A	Mar. 07, 2018
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 26, 2018
2	Amplifier	HP	8447D	2944A09673	Oct. 20, 2017
3	Receiver	AGILENT	N9038A	MY52130039	Sep. 04, 2017
4	Cable	emci	LMR-400(30MHz-1GHz)(8m+5m)	N/A	Jun. 26, 2018
5	Control	CT	SC100	N/A	N/A
6	Position Control	MF	MF-7802	MF780208416	N/A
7	Antenna	ETS	3115	00075789	Mar. 26, 2018
8	Amplifier	Agilent	8449B	3008A02274	Feb. 22, 2018
9	Receiver	AGILENT	N9038A	MY52130039	Sep. 04, 2017
10	Test Cable	emci	EMC104-SM-S M-10000(1GHz-26.5GHz)	C-68	Jun. 26, 2018
11	Controller	CT	SC100	N/A	N/A
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Apr. 22, 2018
13	Microwave Pre-amplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 26, 2018
14	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Sep. 06, 2017
15	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

**Number of Hopping Channel**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Sep. 04, 2017

**Average Time of Occupancy**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Sep. 04, 2017

**Hopping Channel Separation Measurement**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Sep. 04, 2017

**Bandwidth**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Sep. 04, 2017

**Peak Output Power**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Sep. 04, 2017

**Antenna Conducted Spurious Emission**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Sep. 04, 2017

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
 All calibration period of equipment list is one year.

## 12. EUT TEST PHOTO

### Conducted Measurement Photos



## Radiated Measurement Photos


9KHz to 30MHz






## Radiated Measurement Photos

30MHz to 1000MHz



**Radiated Measurement Photos**

**Above 1000MHz**






## ATTACHMENT A - CONDUCTED EMISSION

Test Mode: TX Mode


### Line



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1815	41.52	9.77	51.29	64.42	-13.13	Peak	
2	0.2310	42.05	9.76	51.81	62.41	-10.60	Peak	
3	0.2310	22.80	9.76	32.56	52.41	-19.85	AVG	
4	0.2670	44.64	9.76	54.40	61.21	-6.81	Peak	
5	0.2670	22.70	9.76	32.46	51.21	-18.75	AVG	
6	0.4470	35.57	9.80	45.37	56.93	-11.56	Peak	
7	0.4470	20.30	9.80	30.10	46.93	-16.83	AVG	
8	11.6475	38.91	10.41	49.32	60.00	-10.68	Peak	
9 *	11.6475	33.61	10.41	44.02	50.00	-5.98	AVG	
10	14.3115	36.57	10.56	47.13	60.00	-12.87	Peak	
11	14.3115	32.70	10.56	43.26	50.00	-6.74	AVG	

Test Mode: TX Mode

### Neutral




No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1770	38.92	9.68	48.60	64.63	-16.03	Peak	
2	0.2355	41.10	9.68	50.78	62.25	-11.47	Peak	
3	0.2355	23.90	9.68	33.58	52.25	-18.67	AVG	
4	0.2670	42.88	9.67	52.55	61.21	-8.66	Peak	
5	0.2670	20.00	9.67	29.67	51.21	-21.54	AVG	
6	0.4650	34.34	9.69	44.03	56.60	-12.57	Peak	
7	11.6520	38.81	10.39	49.20	60.00	-10.80	Peak	
8 *	11.6520	34.70	10.39	45.09	50.00	-4.91	AVG	
9	14.9820	37.46	10.63	48.09	60.00	-11.91	Peak	
10	14.9820	31.30	10.63	41.93	50.00	-8.07	AVG	

## ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0093	37.44	21.06	58.50	128.24	-69.74	AVG	
2	*	0.0256	32.09	19.45	51.54	119.44	-67.90	AVG	
3		0.0522	25.47	18.68	44.15	113.25	-69.10	AVG	

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.3286	26.90	16.60	43.50	97.27	-53.77	AVG	
2	*	2.2250	27.18	15.44	42.62	69.54	-26.92	QP	
3		5.1800	20.34	14.34	34.68	69.54	-34.86	QP	

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0144	20.21	20.35	40.56	124.44	-83.88	AVG	
2		0.0321	18.46	19.26	37.72	117.47	-79.75	AVG	
3	*	0.0574	15.08	18.58	33.66	112.43	-78.77	AVG	

Test Mode: TX Mode

Ant 90°




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	0.1712	20.57	16.89	37.46	102.94	-65.48	AVG	
2 *	2.2427	23.03	15.44	38.47	69.54	-31.07	QP	
3	3.5278	17.09	15.08	32.17	69.54	-37.37	QP	



# ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX 2402MHz \_CH00\_1Mbps


## Vertical



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	53.2800	41.81	-13.88	27.93	40.00	-12.07	Peak	
2 *	76.5600	45.91	-17.44	28.47	40.00	-11.53	Peak	
3	172.5900	40.89	-12.26	28.63	43.50	-14.87	Peak	
4	433.5200	29.94	-10.41	19.53	46.00	-26.47	Peak	
5	618.7900	29.81	-6.06	23.75	46.00	-22.25	Peak	
6	770.1100	30.57	-2.01	28.56	46.00	-17.44	Peak	

Test Mode: TX 2402MHz \_CH00\_1Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	76.5600	35.30	-17.44	17.86	40.00	-22.14	Peak	
2	135.7300	37.52	-14.43	23.09	43.50	-20.41	Peak	
3 *	203.6300	42.96	-13.83	29.13	43.50	-14.37	Peak	
4	270.5600	40.76	-15.78	24.98	46.00	-21.02	Peak	
5	452.9200	32.46	-9.87	22.59	46.00	-23.41	Peak	
6	741.0100	30.13	-2.71	27.42	46.00	-18.58	Peak	

Test Mode: TX 2441MHz \_CH39\_1Mbps

### Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	53.2800	41.81	-13.88	27.93	40.00	-12.07	Peak	
2 *	76.5600	45.91	-17.44	28.47	40.00	-11.53	Peak	
3	172.5900	40.89	-12.26	28.63	43.50	-14.87	Peak	
4	400.5400	30.32	-11.34	18.98	46.00	-27.02	Peak	
5	648.8600	29.55	-5.50	24.05	46.00	-21.95	Peak	
6	879.7200	29.98	0.61	30.59	46.00	-15.41	Peak	

Test Mode: TX 2441MHz \_CH39\_1Mbps

### Horizontal


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	75.5899	34.97	-17.22	17.75	40.00	-22.25	Peak	
2	194.9000	39.06	-13.29	25.77	43.50	-17.73	Peak	
3	216.2400	42.12	-13.93	28.19	46.00	-17.81	Peak	
4	452.9200	31.86	-9.87	21.99	46.00	-24.01	Peak	
5	791.4500	29.75	-1.55	28.20	46.00	-17.80	Peak	
6 *	908.8200	29.15	1.20	30.35	46.00	-15.65	Peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps

**Vertical**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	53.2800	42.79	-13.88	28.91	40.00	-11.09	Peak	
2	75.5899	45.83	-17.22	28.61	40.00	-11.39	Peak	
3	162.8900	40.89	-12.76	28.13	43.50	-15.37	Peak	
4	352.0400	29.73	-11.93	17.80	46.00	-28.20	Peak	
5	531.4900	30.27	-8.09	22.18	46.00	-23.82	Peak	
6	745.8600	30.82	-2.57	28.25	46.00	-17.75	Peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps

**Horizontal**

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	76.5600	35.48	-17.44	18.04	40.00	-21.96	Peak	
2	161.9200	38.03	-12.82	25.21	43.50	-18.29	Peak	
3 *	203.6300	43.44	-13.83	29.61	43.50	-13.89	Peak	
4	272.5000	43.54	-15.58	27.96	46.00	-18.04	Peak	
5	487.8400	29.93	-9.02	20.91	46.00	-25.09	Peak	
6	687.6599	29.73	-4.32	25.41	46.00	-20.59	Peak	

## ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)



Test Mode : TX 2402MHz \_CH00\_1Mbps

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	21.11	33.06	54.17	74.00	-19.83	Peak	
2	2390.0000	11.86	33.06	44.92	54.00	-9.08	AVG	
3	2401.8500	74.29	33.10	107.39	74.00	33.39	Peak	No Limit
4 *	2402.0000	73.34	33.10	106.44	54.00	52.44	AVG	No Limit

Test Mode : TX 2402MHz \_CH00\_1Mbps

### Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4803.8350	38.00	6.27	44.27	74.00	-29.73	Peak	
2 *	4803.9950	29.39	6.27	35.66	54.00	-18.34	AVG	

Test Mode : TX 2402MHz \_CH00\_1Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	22.82	33.06	55.88	74.00	-18.12	Peak	
2	2390.0000	13.17	33.06	46.23	54.00	-7.77	AVG	
3 *	2402.0000	70.11	33.10	103.21	54.00	49.21	AVG	No Limit
4	2402.1500	71.16	33.10	104.26	74.00	30.26	Peak	No Limit

Test Mode : TX 2402MHz \_CH00\_1Mbps

**Horizontal**


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4803.9049	26.08	6.27	32.35	54.00	-21.65	AVG	
2	4803.9550	35.71	6.27	41.98	74.00	-32.02	Peak	

Test Mode : TX 2441MHz \_CH39\_1Mbps

**Vertical**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2440.8500	73.00	33.25	106.25	74.00	32.25	Peak	No Limit
2 *	2441.0000	72.02	33.25	105.27	54.00	51.27	AVG	No Limit

Test Mode : TX 2441MHz \_CH39\_1Mbps

### Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.8600	38.42	6.46	44.88	74.00	-29.12	Peak	
2 *	4881.9100	32.12	6.46	38.58	54.00	-15.42	AVG	

Test Mode : TX 2441MHz \_CH39\_1Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0000	70.06	33.25	103.31	54.00	49.31	AVG	No Limit
2	2441.1500	71.12	33.25	104.37	74.00	30.37	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_1Mbps

**Horizontal**

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.9100	36.56	6.46	43.02	74.00	-30.98	Peak	
2 *	4881.9550	30.22	6.46	36.68	54.00	-17.32	AVG	



Test Mode : TX 2480MHz \_CH78\_1Mbps

**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2480.0000	71.34	33.39	104.73	54.00	50.73	AVG	No Limit
2	2480.1500	72.33	33.40	105.73	74.00	31.73	Peak	No Limit
3	2483.5000	24.17	33.41	57.58	74.00	-16.42	Peak	
4	2483.5000	12.22	33.41	45.63	54.00	-8.37	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps

**Vertical**


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.5400	40.78	6.66	47.44	74.00	-26.56	Peak	
2 *	4959.9500	35.79	6.66	42.45	54.00	-11.55	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2480.0000	69.88	33.39	103.27	54.00	49.27	AVG	No Limit
2	2480.1500	70.95	33.40	104.35	74.00	30.35	Peak	No Limit
3	2483.5000	23.09	33.41	56.50	74.00	-17.50	Peak	
4	2483.5000	13.67	33.41	47.08	54.00	-6.92	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps

### Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4959.9600	31.31	6.66	37.97	54.00	-16.03	AVG	
2	4960.2300	38.60	6.66	45.26	74.00	-28.74	Peak	

Test Mode : TX 2402MHz \_CH00\_3Mbps

### Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	22.45	33.06	55.51	74.00	-18.49	Peak	
2	2390.0000	12.07	33.06	45.13	54.00	-8.87	AVG	
3	2402.0000	73.72	33.10	106.82	74.00	32.82	Peak	No Limit
4 *	2402.0000	69.42	33.10	102.52	54.00	48.52	AVG	No Limit

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Vertical**


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4803.9700	31.83	6.27	38.10	54.00	-15.90	AVG	
2	4804.4300	40.12	6.27	46.39	74.00	-27.61	Peak	

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	23.27	33.06	56.33	74.00	-17.67	Peak	
2	2390.0000	13.29	33.06	46.35	54.00	-7.65	AVG	
3	2402.0000	70.48	33.10	103.58	74.00	29.58	Peak	No Limit
4 *	2402.0000	66.19	33.10	99.29	54.00	45.29	AVG	No Limit

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Horizontal**

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4803.9500	29.15	6.27	35.42	54.00	-18.58	AVG	
2	4804.1400	37.55	6.27	43.82	74.00	-30.18	Peak	



Test Mode : TX 2441MHz \_CH39\_3Mbps

**Vertical**

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2441.0000	72.67	33.25	105.92	74.00	31.92	Peak	No Limit
2 *	2441.0000	68.42	33.25	101.67	54.00	47.67	AVG	No Limit

Test Mode : TX 2441MHz \_CH39\_3Mbps

### Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.5299	39.51	6.46	45.97	74.00	-28.03	Peak	
2 *	4881.9600	30.58	6.46	37.04	54.00	-16.96	AVG	

Test Mode : TX 2441MHz \_CH39\_3Mbps

### Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2440.9000	70.51	33.25	103.76	74.00	29.76	Peak	No Limit
2 *	2441.0000	66.35	33.25	99.60	54.00	45.60	AVG	No Limit

Test Mode : TX 2441MHz \_CH39\_3Mbps

### Horizontal


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4874.8600	37.98	6.44	44.42	74.00	-29.58	Peak	
2 *	4874.9400	29.84	6.44	36.28	54.00	-17.72	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

### Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2480.0000	72.04	33.39	105.43	74.00	31.43	Peak	No Limit
2 *	2480.0000	67.95	33.39	101.34	54.00	47.34	AVG	No Limit
3	2483.5000	28.28	33.41	61.69	74.00	-12.31	Peak	
4	2483.5000	15.82	33.41	49.23	54.00	-4.77	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

### Vertical

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.0600	39.12	6.66	45.78	74.00	-28.22	Peak	
2 *	4959.9300	29.06	6.66	35.72	54.00	-18.28	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

### Horizontal

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2480.0000	70.42	33.39	103.81	74.00	29.81	Peak	No Limit
2 *	2480.0000	66.22	33.39	99.61	54.00	45.61	AVG	No Limit
3	2483.5000	27.12	33.41	60.53	74.00	-13.47	Peak	
4	2483.5000	15.97	33.41	49.38	54.00	-4.62	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

### Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.0600	36.12	6.66	42.78	74.00	-31.22	Peak	
2 *	4959.9300	27.06	6.66	33.72	54.00	-20.28	AVG	




## ATTACHMENT E - NUMBER OF HOPPING CHANNEL

**Test Mode**      **Hopping Mode\_1Mbps**  
Number of Hopping Channel      79



Date: 3.JUL.2017 14:59:44

**Test Mode**      **Hopping Mode\_3Mbps**  
Number of Hopping Channel      79




Date: 3.JUL.2017 15:14:15

## ATTACHMENT F - AVERAGE TIME OF OCCUPANCY

Test Mode :	TX Mode_1Mbps
-------------	---------------


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	2.9200	0.3115	0.4000	Pass
DH3	2402	1.6600	0.2656	0.4000	Pass
DH1	2402	0.3950	0.1264	0.4000	Pass
DH5	2441	2.8800	0.3072	0.4000	Pass
DH3	2441	1.6600	0.2656	0.4000	Pass
DH1	2441	0.3900	0.1248	0.4000	Pass
DH5	2480	2.8800	0.3072	0.4000	Pass
DH3	2480	1.6400	0.2624	0.4000	Pass
DH1	2480	0.3900	0.1248	0.4000	Pass

### CH00-DH1




Date: 3.JUL.2017 14:54:18

### CH00-DH3




Date: 3.JUL.2017 15:01:09

### CH00-DH5




Date: 3.JUL.2017 15:01:40

### CH39-DH1




Date: 3.JUL.2017 14:54:38

### CH39-DH3




Date: 3.JUL.2017 15:01:13

### CH39-DH5




Date: 3.JUL.2017 15:01:43

### CH78-DH1



Date: 3.JUL.2017 14:54:42


### CH78-DH3



Date: 3.JUL.2017 15:01:17



### CH78-DH5




Date: 3.JUL.2017 15:01:47

Test Mode :	TX Mode_3Mbps
-------------	---------------


Data Packet	Frequency	Pulse Duration(ms)	Dwell Time(s)	Limits(s)	Test Result
DH5	2402	2.8800	0.3072	0.4000	Pass
DH3	2402	1.6400	0.2624	0.4000	Pass
DH1	2402	0.3750	0.1200	0.4000	Pass
DH5	2441	2.8800	0.3072	0.4000	Pass
DH3	2441	1.6400	0.2624	0.4000	Pass
DH1	2441	0.3950	0.1264	0.4000	Pass
DH5	2480	2.9200	0.3115	0.4000	Pass
DH3	2480	1.6600	0.2656	0.4000	Pass
DH1	2480	0.3950	0.1264	0.4000	Pass

### CH00-DH1




Date: 3.JUL.2017 15:09:03

### CH00-DH3




Date: 3.JUL.2017 15:15:40

### CH00-DH5




Date: 3.JUL.2017 15:17:56

### CH39-DH1




Date: 3.JUL.2017 15:09:08

### CH39-DH3




Date: 3.JUL.2017 15:15:43

### CH39-DH5




Date: 3.JUL.2017 15:18:02

### CH78-DH1




Date: 3.JUL.2017 15:09:11

### CH78-DH3



Date: 3.JUL.2017 15:15:49

### CH78-DH5



Date: 3.JUL.2017 15:18:05

# ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT






### CH39



\*RBW 30 kHz Delta 1 [T1 ]  
\*VBW 100 kHz 1.22 dB  
SWT 5 ms 1.005000000 MHz




Date: 3.JUL.2017 14:56:55

### CH78



\*RBW 30 kHz Delta 1 [T1 ]  
\*VBW 100 kHz -0.92 dB  
SWT 5 ms 1.002000000 MHz




Date: 3.JUL.2017 14:57:58



### CH39



\*RBW 30 kHz Delta 1 [T1 ]  
\*VBW 100 kHz -0.26 dB  
SWT 5 ms 1.001000000 MHz




Date: 3.JUL.2017 15:11:26

### CH78



\*RBW 30 kHz Delta 1 [T1 ]  
\*VBW 100 kHz -0.07 dB  
SWT 5 ms 996.000000000 kHz




Date: 3.JUL.2017 15:12:29

## ATTACHMENT H - BANDWIDTH


Test Mode : TX Mode \_1Mbps

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	0.914	0.844	Pass
2441	0.974	0.872	Pass
2480	0.950	0.864	Pass




Date: 3.JUL.2017 15:21:24

### CH39



Date: 3.JUL.2017 15:23:08


### CH78



Date: 3.JUL.2017 15:23:58

Test Mode : TX Mode \_3Mbps


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.314	1.216	Pass
2441	1.316	1.212	Pass
2480	1.320	1.212	Pass



Date: 3.JUL.2017 15:03:35




**CH39**



Date: 3.JUL.2017 15:07:08

**CH78**




Date: 3.JUL.2017 15:07:56

## ATTACHMENT I - PEAK OUTPUT POWER


Test Mode : TX Mode \_1Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	6.84	0.0048	30.00	1.00	Pass
2441	6.58	0.0045	30.00	1.00	Pass
2480	6.21	0.0042	30.00	1.00	Pass




Date: 3.JUL.2017 15:21:56

### CH39



Date: 3.JUL.2017 15:23:13


### CH78



Date: 3.JUL.2017 15:24:29


Test Mode : TX Mode \_3Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	7.46	0.0056	30.00	1.00	Pass
2441	7.26	0.0053	30.00	1.00	Pass
2480	6.97	0.0050	30.00	1.00	Pass




Date: 3.JUL.2017 15:04:06

### CH39



Date: 3.JUL.2017 15:07:14


### CH78



Date: 3.JUL.2017 15:08:28


# ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION

### CH00 (Lower)\_1Mbps



Date: 3.JUL.2017 15:21:03


### CH78 (Upper)\_1Mbps



Date: 3.JUL.2017 15:23:36




### CH00 Hopping on mode (Lower)\_1Mbps




Date: 3.JUL.2017 15:00:18

### CH78 Hopping on mode (Upper)\_1Mbps




Date: 3.JUL.2017 15:00:52


### CH00 (10 Harmonic of the frequency) \_1Mbps



Date: 3.JUL.2017 15:21:37




Date: 3.JUL.2017 15:21:44




Date: 3.JUL.2017 15:21:50


### CH39 (10 Harmonic of the frequency) \_1Mbps



Date: 3.JUL.2017 15:22:33




Date: 3.JUL.2017 15:22:40




Date: 3.JUL.2017 15:22:46


### CH78 (10 Harmonic of the frequency) \_1Mbps



Date: 3.JUL.2017 15:24:11




Date: 3.JUL.2017 15:24:17




Date: 3.JUL.2017 15:24:24

### CH00 (Lower) \_3Mbps




Date: 3.JUL.2017 15:03:19

### CH78 (Upper) \_3Mbps




Date: 3.JUL.2017 15:07:41

### CH00 Hopping on mode (Lower)\_3Mbps



Date: 3.JUL.2017 15:14:49


### CH78 Hopping on mode (Upper)\_3Mbps




Date: 3.JUL.2017 15:15:23




### CH00 (10 Harmonic of the frequency) \_3Mbps



Date: 3.JUL.2017 15:03:47




Date: 3.JUL.2017 15:03:54




Date: 3.JUL.2017 15:04:01


### CH39 (10 Harmonic of the frequency) \_3Mbps



Date: 3.JUL.2017 15:06:38




Date: 3.JUL.2017 15:06:45




Date: 3.JUL.2017 15:06:51


### CH78 (10 Harmonic of the frequency) \_3Mbps



Date: 3.JUL.2017 15:08:09



Date: 3.JUL.2017 15:08:15



Date: 3.JUL.2017 15:08:22