

## RF EXPOSURE REPORT

**REPORT NO.**: SA990720E03

MODEL NO.: snom USB BT, BTD-320

FCC ID: QWOUSBBT

ACCORDING: FCC Guidelines for Human Exposure

**IEEE C95.1** 

APPLICANT: Rayson Technology Co., Ltd

ADDRESS: 1F, No.9, R&D II Road, Science-Based Industrial

Park, Hsin-Chu, Taiwan 300

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

1

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

FCC ID: QWOUSBBT

**Report No.: SA990720E03** 



## No SAR Evaluation Required if power is below the following threshold:

Tunable Range			
F(GHz) Low	F(GHz) High	Center of Tunable Band (GHz)	60/f SAR Limitation (mW)
2.402	2.480	2.441	24.58

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
5.2	3.3	-1.96	2.10

Threshold for no SAR evaluation is 24.58 mW Maximum TX Power is 3.3 mW Conducted and 2.10 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold