



**CONFORMANCE TEST REPORT  
FOR  
FCC 47 CFR, Part 15 Subpart B & C**

**Report No.: ET93S-11-101-01**

Client: Chung-Hsin Electric & Machinery Mfg. Corp.  
Product: Bluetooth Pan Access Point  
Model: BAP-100  
FCC ID: QWTBAP-100  
Manufacturer/supplier: Chung-Hsin Electric & Machinery Mfg. Corp.

Date test item received: 2004/11/11  
Date test campaign completed: 2004/12/27  
Date of issue: 2004/12/31




**The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.**

*Total number of pages of this test report: 98 pages*

*Total number of pages of photos: External photos 3 pages*

*Internal photos 3 pages*

*Setup photos 2 pages*

Test Engineer	Checked By	Approved By
 Mark	 Joe Hsieh	 Tsung-Ching Lin

ELECTRONICS TESTING CENTER, TAIWAN  
NO.8, LANE 29, WEN-MING RD.,  
LO-SHAN TSUN, KUI-SHAN HSIANG,  
TAOYUAN HSIEN 333  
TAIWAN, R.O.C.

TEL: (03) 3276170~4  
INT: +886-3-3276170~4  
FAX: (03) 3276188  
INT: +886-3-3276188



Client : Chung-Hsin Electric & Machinery Mfg. Corp.

Address : No. 25, Wen-Te Rd., Lo-Shan Village, Kwei Shan Hsiang, Taoyuan Hsien, Taiwan, R.O.C.

Manufacturer : Chung-Hsin Electric & Machinery Mfg. Corp.

Address : No. 25, Wen-Te Rd., Lo-Shan Village, Kwei Shan Hsiang, Taoyuan Hsien, Taiwan, R.O.C.

EUT : Bluetooth Pan Access Point

Trade name : Mobia

Model No. : BAP-100

Power Source : Adapter Model No.: RHH-050100-1  
Input: 100-240Vac, 50/60Hz, 0.15A  
Output: DC 5Vdc, 1A

Regulations applied : FCC 47 CFR, Part 15 Subpart B & C (2003)

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to believe the sellers from their legal and/or contractual obligations.

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9001: TÜV Product Service
- ② ISO/IEC 17025: BSMI, CNLA, DGT, NVLAP, CCIBLAC, UL, Compliance
- ③ Filing: FCC, Industry Canada, VCCI
- ④ MRA: Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through CNLA



NVLAP Lab Code 200133-0

<b>Table of Contents</b>	<b>Page</b>
<b>1 GENERAL INFORMATION .....</b>	<b>5</b>
1.1 Product Description.....	5
1.2 Characteristics of Device .....	5
1.3 Test Methodology .....	5
1.4 Modification List of EUT .....	5
1.5 Test Facility.....	5
<b>2 PROVISIONS APPLICABLE .....</b>	<b>6</b>
2.1 Definition .....	6
2.2 Requirement for Compliance .....	7
2.3 Restricted Bands of Operation .....	9
2.4 Labeling Requirement .....	9
2.5 User Information .....	10
<b>3. SYSTEM TEST CONFIGURATION .....</b>	<b>11</b>
3.1 Justification .....	11
3.2 Devices for Tested System .....	11
<b>4 RADIATED EMISSION MEASUREMENT .....</b>	<b>12</b>
4.1 Applicable Standard .....	12
4.2 Measurement Procedure .....	12
4.3 Measuring Instrument .....	14
4.4 Radiated Emission Data .....	15
4.5 Field Strength Calculation.....	52
<b>5 CONDUCTED EMISSION MEASUREMENT .....</b>	<b>53</b>
5.1 Standard Applicable .....	53
5.2 Measurement Procedure .....	53
5.3 Conducted Emission Data .....	54
5.4 Result Data Calculation.....	60
5.4 Result Data Calculation.....	61
5.5 Conducted Measurement Equipment .....	61
<b>6 ANTENNA REQUIREMENT .....</b>	<b>62</b>
6.1 Standard Applicable .....	62
6.2 Antenna Construction and Directional Gain .....	62
<b>7 20dB EMISSION BANDWIDTH MEASUREMENT .....</b>	<b>63</b>
7.1 Standard Applicable .....	63
7.2 Measurement Procedure .....	63

7.3 Measurement Equipment .....	63
7.4 Measurement Data.....	64
<b>8 OUTPUT POWER MEASUREMENT .....</b>	<b>68</b>
8.1 Standard Applicable .....	68
8.2 Measurement Procedure .....	68
8.3 Measurement Equipment .....	68
8.4 Measurement Data.....	69
<b>9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT .....</b>	<b>73</b>
9.1 Standard Applicable .....	73
9.2 Measurement Procedure .....	73
9.3 Measurement Equipment .....	73
9.4 Measurement Data.....	74
<b>10 NUMBER OF HOPPING CHANNELS .....</b>	<b>80</b>
10.1 Standard Applicable .....	80
10.2 Measurement Procedure .....	80
10.3 Measurement Equipment .....	80
10.4 Measurement Data.....	80
<b>11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED .....</b>	<b>82</b>
11.1 Standard Applicable .....	82
11.2 Measurement Procedure .....	82
11.3 Measurement Equipment .....	82
11.4 Measurement Data.....	83
<b>12 POWER SPECTRAL DENSITY.....</b>	<b>87</b>
12.1 Standard Applicable .....	87
12.2 Measurement Procedure .....	87
12.3 Measurement Equipment .....	87
12.4 Measurement Data.....	88
<b>13 DWELL TIME.....</b>	<b>92</b>
13.1 Standard Applicable .....	92
13.2 Measurement Procedure .....	92
13.3 Measurement Equipment .....	92
13.4 Measurement Data.....	92

# 1 GENERAL INFORMATION

## 1.1 Product Description

- a) Type of EUT : Bluetooth Pan Access Point
- b) Trade Name : Mobia
- c) Model No. : BAP-100
- d) Power Supply : Adapter Model No.: RHH-050/00-1  
Input: 100-240Vac, 50/60Hz, 0.15A  
Output: DC 5Vdc, 1A

## 1.2 Characteristics of Device

The EUT is a Bluetooth Pan Access Point on the Bluetooth technology. Bluetooth is a short-range radio link intended to be a cable replacement between portable or fixed electronic devices. Bluetooth operates in the unlicensed ISM Band at 2.4GHz. In this band, 79 RF channels spaced 1MHz apart are defined. The rated output power is 13.34 dBm ( 21.58 mW).

## 1.3 Test Methodology

All testing were performed according to the procedures in ANSI C63.4 and FCC CFR 47 Part 2 and Part 15.

## 1.4 Modification List of EUT

N/A

## 1.5 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

## 2 PROVISIONS APPLICABLE

### 2.1 Definition

**Unintentional radiator:**

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

**Class A Digital Device:**

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

**Class B Digital Device :**

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

**Intentional radiator:**

A device that intentionally generates and emits radio frequency energy by radiation or induction.

## 2.2 Requirement for Compliance

### (1) Conducted Emission Requirement

For unintentional device, according to §15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB $\mu$ V	Average dB $\mu$ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

\*Decreases with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

### (2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB $\mu$ V/m	Radiated $\mu$ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

### (3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

**(4) 20dB Bandwidth Requirement**

For frequency hopping systems, according to 15.247(a)(1), hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

**(5) Output Power Requirement**

For frequency hopping systems, according to 15.247(1), operating in the 2400-2483.5MHz band employing at least 75 hopping channels. The maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

**(6) 100 kHz Bandwidth of Frequency Band Edges Requirement**

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

**(7) Number of Hopping Channels**

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels.

**(8) Channel Carrier Frequencies Separation**

According to 15.247(a)(1)(iii), the frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

**(9) Dwell Time**

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

**(10) Power Spectral Density**

According to 15.247(d), for bluetooth device, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

## 2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

\*\* : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

## 2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## 2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

### 3. SYSTEM TEST CONFIGURATION

#### 3.1 Justification


For the purposes of this test report ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT during the test. Notebook PC was used to control the RF channel under the highest, middle and lowest frequency and transmit the maximum RF power. Customer would not use it. But never the less ancillary equipment can influence the test results..

#### 3.2 Devices for Tested System

Device	Manufacture	Model	Cable Description
*Bluetooth Pan Access Point	Chung-Hsin Electric & Machinery Mfg. Corp.	BAP-100	1.8m, Unshielded Line / Adapter
Portable Pen Terminal	Chung-Hsin Electric & Machinery Mfg. Corp.	PPT-120	----
Notebook PC	ASUS	L7245	3.3m, Unshielded Network Cable
Test Jig	----	----	1.8m, Unshielded Signal Line 0.5m, Unshielded Signal Line 1.8m, Unshielded Power Line / Adapter

Note:

1. Remark “\*” means equipment under test.
2. After the control is completed every time, the Notebook PC and Test Jig will move out during the test.



## 4 RADIATED EMISSION MEASUREMENT

### 4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and digitally modulated, and the out band emission shall be comply with §15.247 (c)

### 4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in continuous operating function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions and then each selected frequency is precisely measured. As the same purpose, for emission measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission measured below and above 1 GHz, set the spectrum analyzer on a 120 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



### 4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	Hewlett-Packard	8546A	09/06/2005
Horn Antenna	EMCO	3115	06/04/2005
LogBicone Antenna	Schwarzbeck	9160	10/26/2005
Horn Antenna	EMCO	3116	07/19/2005
Preamplifier	Hewlett-Packard	8449B	09/16/2005
Spectrum Analyzer	Hewlett-Packard	8564EC	09/15/2005

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
2390 & 2483.5	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

## 4.4 Radiated Emission Data

### 4.4.1 RF Portion

a) Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Dec. 27, 2004

Temperature : 23°C

Humidity : 71%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave (H/V Max.)	Peak	Ave.			
1201.000	---	---	---	---	-13.9	---	---	74.0	54.0	---	---	---
4804.000	---	---	---	---	-4.6	---	---	74.0	54.0	---	---	---
12010.000	---	---	---	---	2.9	---	---	74.0	54.0	---	---	---
16216.000	---	---	---	---	3.8	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

## b) Channel 39

Operation Mode : Transmitting

Fundamental Frequency : 2441 MHz

Test Date : Dec. 27, 2004

Temperature : 23°C

Humidity : 71%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	Ave	V Peak	Ave		Peak	Ave (H/V Max.)	Peak	Ave.			
1220.500	---	---	---	---	-13.9	---	---	74.0	54.0	---	---	---
4882.000	---	---	---	---	-4.6	---	---	74.0	54.0	---	---	---
7323.000	---	---	---	---	-1.0	---	---	74.0	54.0	---	---	---
12205.000	---	---	---	---	2.9	---	---	74.0	54.0	---	---	---
19528.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

## c) Channel 78

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Test Date : Dec. 27, 2004

Temperature : 23°C

Humidity : 71%

Frequency  (MHz)	Reading (dBuV)				Factor (dB)  Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave.			
	Peak	Ave	Peak	Ave								
1240.00	---	---	---	---	-13.9	---	---	74.0	54.0	---	---	---
4960.000	---	---	---	---	-4.6	---	---	74.0	54.0	---	---	---
7440.000	---	---	---	---	-1.0	---	---	74.0	54.0	---	---	---
12400.000	---	---	---	---	2.9	---	---	74.0	54.0	---	---	---
19840.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---
22320.000	---	---	---	---	1.3	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

**4.4.2 Other Emission**

## 4.4.2.1

Operation Mode: 2402MHz

Test Date : Dec. 27, 2004      Temperature : 23°C      Humidity : 71%

Emission Frequency ( MHz )	Meter Reading ( dBuV )		CORR'd Factor ( dB )	Results ( dBuV/m )		Limit (3m) (dBuV/m)	Margins ( dB )	Table Degree (deg)		Ant. High (m)	
	HOR.	VERT.		HOR.	VERT.			HOR.	VERT.	HOR.	VERT.
30.000	***	16.6	13.1	***	29.7	40.0	-10.3	***	312	***	1.0
58.130	***	15.2	13.2	***	28.4	40.0	-11.6	***	148	***	1.2
245.340	13.5	***	14.6	28.1	***	46.0	-17.9	32	***	1.0	***
300.630	***	13.3	16.8	***	30.1	46.0	-15.9	***	193	***	1.3
320.030	***	13.6	17.5	***	31.1	46.0	-14.9	***	243	***	1.0
363.680	12.4	***	18.8	31.2	***	46.0	-14.8	149	***	1.0	***
387.930	12.3	***	18.8	31.1	***	46.0	-14.9	313	***	1.2	***
405.390	***	10.8	19.4	***	30.2	46.0	-15.8	***	194	***	1.2
426.730	***	10.0	20.1	***	30.1	46.0	-15.9	***	131	***	1.0
604.240	14.0	***	23.8	37.8	***	46.0	-8.2	278	***	1.3	***
676.990	12.2	***	25.7	37.9	***	46.0	-8.1	254	***	1.2	***
754.590	12.1	***	27.0	39.1	***	46.0	-6.9	178	***	1.0	***

Note :

1. Place of Measurement: Measuring site of the ETC.
2. Remark “\*\*\*” means that the emissions level is too low to be measured.
3. Remark “#” means the noise was low, so record the peak value.
4. Item “Margin” referred to Q.P. limit while there is only peak result.
5. Please refer to page 20 to page 51 for chart

## 4.4.2.2

Operation Mode: Unintentional Emission

Test Date : Dec. 27, 2004      Temperature : 23°C      Humidity : 71%

Emission Frequency ( MHz )	Meter Reading ( dBuV )		CORR'd Factor ( dB )	Results ( dBuV/m )		Limit (3m) (dBuV/m)	Margins ( dB )	Table Degree (deg)		Ant. High (m)	
	HOR.	VERT.		HOR.	VERT.			HOR.	VERT.	HOR.	VERT.
284.140	15.0	***	15.7	30.7	***	46.0	-15.3	32	***	1.2	***
225.940	***	25.4	13.7	***	39.1	46.0	-6.9	***	312	***	1.0
303.540	21.8	24.3	16.8	38.6	41.1	46.0	-4.9	143	334	1.2	1.2
387.930	17.3	15.4	18.8	36.1	34.2	46.0	-9.9	212	243	1.0	1.2
484.930	13.6	12.8	21.1	34.7	33.9	46.0	-11.3	314	197	1.0	1.0
504.330	16.6	13.4	21.5	38.1	34.9	46.0	-7.9	189	168	1.0	1.0
676.990	***	10.8	25.7	***	36.5	46.0	-9.5	***	231	***	1.2
771.080	13.0	***	27.2	40.2	***	46.0	-5.8	79	***	1.0	***

Note :


1. Place of Measurement: Measuring site of the ETC.
2. Remark “\*\*\*” means that the emissions level is too low to be measured.
3. Remark “#” means the noise was low, so record the peak value.
4. Item “Margin” referred to Q.P. limit while there is only peak result.
5. Please refer to page 20 to page 51 for chart

Horizontal



ETC TEST LABORTARY

Data#: 4073 File#: C:\Program Files\E3\MARK.emi




Site : MOO SITE  
Condition : FCC PART15 B 3m HORIZONTAL  
EUT :  
MODEL : BAP-100  
memo : CHO

Vertical




ETC TEST LABORTARY

Data#: 4070 File#: C:\Program Files\E3\MARK.emi




Site : MOO SITE  
Condition : FCC PART15 B 3m VERTICAL  
EUT :  
MODEL : BAP-100  
memo : CHO


Horizontal




Vertical




Horizontal




Vertical




Horizontal




Vertical



Horizontal



Vertical




Horizontal



ETC TEST LABORTARY

Data#: 4074 File#: C:\Program Files\E3\MARK.emi




Site : MOO SITE  
Condition : FCC PART15 B 3m HORIZONTAL  
EUT :  
MODEL : BAP-100  
memo : CH39

Vertical




ETC TEST LABORTARY

Data#: 4071      File#: C:\Program Files\E3\MARK.emi




Site : MOO SITE  
Condition : FCC PART15 B 3m VERTICAL  
EUT :  
MODEL : BAP-100  
memo : CH39


Horizontal




Vertical




Horizontal




Vertical



Horizontal




Vertical




Horizontal

CH39\_K1



Vertical




## Horizontal



ETC TEST LABORTARY

Data#: 4075 File#: C:\Program Files\E3\MARK.emi




Site : MOO SITE  
Condition : FCC PART15 B 3m HORIZONTAL  
EUT :  
MODEL : BAP-100  
memo : CH78

Vertical




ETC TEST LABORTARY

Data#: 4072      File#: C:\Program Files\E3\MARK.emi




Site : MOO SITE  
Condition : FCC PART15 B 3m VERTICAL  
EUT :  
MODEL : BAP-100  
memo : CH78


Horizontal



Vertical




Horizontal




Vertical


CH78-V




Horizontal



Vertical



Horizontal



Vertical

CH98\_V1

