



Federal Communications Commission  
Authorization and Evaluation Division  
Equipment Authorization Branch  
7435 Oakland Mills Road, Columbia, MD 21046, U.S.A.

Subject: FCC Compliance Statements

Date: January 10, 2007

FCC ID: QWY-CKII-RAZR

Gentlemen:

**PEIKER acoustic** hereby confirms that the attached FCC Compliance Statements (§15.21 and §15.105 Information to the User) will be readily visible to the user, and will be placed at a prominent location in the front section of the user's manual.

Should you have any questions or comments concerning the above, please do not hesitate to contact me.

Sincerely Yours,

Wolfgang Förderer  
Department Manager  
PEIKER acoustic GmbH & Co. KG

Andreas Froidl  
Technical Project Manager

**RF Exposure statement:**

The antenna shown in this filing must not be co-located or operated in conjunction with any other antenna or transmitter.

integrators need no SAR evaluation. The max source-based time-averaged output of 0.0005 W is below the low threshold of 24mW for  $d < 1.5$  cm.

**Statement according to FCC part 15.21:**

Modifications not expressly approved by this company could void the user's authority to operate the equipment.

**Statement according to FCC part 15.105:**

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.