

CETECOM™

CETECOM ICT Services
consulting - testing - certification >>>

TEST REPORT

Test report no.: 1-0438/15-01-04-C



Deutsche
Akkreditierungsstelle
D-PL-12076-01-01

Testing laboratory

CETECOM ICT Services GmbH
Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <http://www.cetecom.com>
e-mail: ict@cetecom.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS). The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-01

Applicant

peiker acustic GmbH & Co. KG
Max-Planck Str. 28-32
61381 Friedrichsdorf / GERMANY
Phone: -/-
Fax: +49 6172-767-220
Contact: Philippe Seguret
e-mail: philippe.seguret@peiker.de
Phone: +49 6172 767- 1754

Manufacturer

peiker acustic GmbH & Co. KG
Max-Planck Str. 28-32
61381 Friedrichsdorf / GERMANY


Test standard/s

47 CFR Part 22 Title 47 of the Code of Federal Regulations; Chapter I; Part 22 - Public mobile services
RSS - 132 Issue 3 Spectrum Management and Telecommunications Radio Standards Specification - Cellular Telephone Systems Operating in the Bands 824-849 MHz and 869-894 MHz

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: NAD Module
Model name: V1140-104-1
FCC ID: QWY-V1140-104-1
Frequency: LTE Band 5 FDD 824 MHz to 849 MHz
Technology tested: LTE FDD
Antenna: External antenna
Power supply: 3.8 V DC
Temperature range: -30°C to +50°C



This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:

Andreas Luckenbill
Lab Manager
Radio Communications & EMC

Test performed:

Tobias Wittenmeier
Testing Manager
Radio Communications & EMC

1 Table of contents

1 Table of contents2

2 General information3

 2.1 Notes and disclaimer3

 2.2 Application details.....3

3 Test standard/s3

 3.1 Measurement guidance.....3

4 Test environment.....4

5 Test item4

 5.1 General description4

 5.2 Additional information4

6 Test laboratories sub-contracted4

7 Description of the test setup5

 7.1 Shielded fully anechoic chamber6

 7.2 Conducted measurements normal and extreme conditions.....7

8 Measurement uncertainty8

9 Sequence of testing9

 9.1 Sequence of testing radiated spurious 9 kHz to 30 MHz.....9

 9.2 Sequence of testing radiated spurious 30 MHz to 1 GHz.....10

 9.3 Sequence of testing radiated spurious 1 GHz to 12.75 GHz11

10 Summary of measurement results.....12

 10.1 LTE band V12

11 RF measurements.....13

 11.1 Results LTE band V13

 11.1.1 RF output power13

 11.1.2 Frequency stability20

 11.1.3 Spurious emissions radiated.....22

 11.1.4 Spurious emissions conducted27

 11.1.5 Block edge compliance48

 11.1.6 Occupied bandwidth57

12 Observations67

Annex A Document history68

Annex B Further information.....68

Annex C Accreditation Certificate69

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

The testing service provided by CETECOM ICT Services GmbH has been rendered under the current "General Terms and Conditions for CETECOM ICT Services GmbH".

CETECOM ICT Services GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM ICT Services GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM ICT Services GmbH test report include or imply any product or service warranties from CETECOM ICT Services GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM ICT Services GmbH.

All rights and remedies regarding vendor's products and services for which CETECOM ICT Services GmbH has prepared this test report shall be provided by the party offering such products or services and not by CETECOM ICT Services GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

This test report replaces the test report with the number 1-0438/15-01-04-B and dated 2016-12-05

2.2 Application details

Date of receipt of order:	2015-09-28	
Date of receipt of test item:	2015-09-28	receipt of test item for retest: 2016-02-01
Start of test:	2015-09-29	start of retests: 2016-02-02
End of test:	2015-10-27	end of retests: 2016-02-10
Person(s) present during the test:	-/-	

3 Test standard/s

Test standard	Date	Test standard description
47 CFR Part 22	-/-	Title 47 of the Code of Federal Regulations; Chapter I; Part 22 - Public mobile services
RSS - 132 Issue 3	January 2013	Spectrum Management and Telecommunications Radio Standards Specification - Cellular Telephone Systems Operating in the Bands 824-849 MHz and 869-894 MHz

3.1 Measurement guidance

Guidance	Version	Description
ANSI C63.4-2014	-/-	American national standard for methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz

7 Description of the test setup


Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
v/k!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

7.1 Shielded fully anechoic chamber



OP = AV + D - G + CA
 (OP-output power; AV-analyzer value; D-distance; G-antenna gain+amplifier gain; CA-loss signal path)


Example calculation:

OP [dBm] = -11.0 [dBm] + 47 [dB] - 8 [dB] + 5 [dB] = 33 [dBm] (2 W)

Equipment table:

No.	Lab / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A	Power Supply 0-20V	6632A	HP	2851A01814	300000924	ne	09.11.2005	
2	A	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9709-5290	300000212	k	13.08.2015	13.08.2017
3	A	EMI Test Receiver 20Hz- 26.5GHz	ESU26	R&S	100037	300003555	k	22.01.2015	22.01.2016
4	A.	Highpass Filter	WHK1.1/15G-10SS	Wainwright	37	400000148	ne		
5	A	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	300003789	ne		
6	A	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	318	300003696	k	22.04.2014	22.04.2017
7	A	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000032	300004510	ne		
8	A	Messrechner und Monitor	Intel Core i3 3220/3,3 GHz, Prozessor	Agilent Technologies	2V2403033A54 21	300004591	ne		
9	A	NEXIO EMV-Software	BAT EMC	EMCO	2V2403033A54 21	300004682	ne		
10	A	Active Loop Antenna 10 kHz to 30 MHz	6502	EMCO/2	8905-2342	300000256	k	24.06.2015	24.06.2017
11	A	Wideband Radio Communication Tester	CMW500	R&S	102375	300004187	k	28.01.2015	28.01.2017

7.2 Conducted measurements normal and extreme conditions



OP = AV + CA
 (OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

Equipment table:

No.	Lab / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A, B	Switch / Control Unit	3488A	HP	2605e08770	300001443	ne		
2	A, B	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	22.01.2015	22.01.2016
3	A, B	Power Supply 0-20V; 0-5A	6632B	HP	US37478366	400000117	vIKI!	20.01.2015	20.01.2017
4	A, B	Wideband Radio Communication Tester	CMW500	R&S	102375	300004187	vIKI!	28.01.2015	28.01.2017
5	B	Temperature Test Chamber	VT 4002	Heraeus Voetsch	521/83761	300002326	Ve	26.09.2015	26.09.2017
6	A, B	RF-Cable	ST18/SMAm/SMAm/72	Huber & Suhner	Batch no. 699714	400001184	ev		
7	A, B	DC-Blocker 0.1-40 GHz	8141A	Inmet		400001185	ev		
8	A, B	Coax Attenuator 10 dB 2W 0-40 GHz	MCL BW-K10-2W44+	Mini Circuits		400001186	ev		

8 Measurement uncertainty

Measurement uncertainty	
Test case	Uncertainty
RF output power conducted	± 1 dB
RF output power radiated	± 3 dB
Frequency stability	± 20 Hz
Spurious emissions radiated below 30 MHz	± 3 dB
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB
Spurious emissions radiated above 12.75 GHz	± 4.5 dB
Spurious emissions conducted	± 3 dB
Block edge compliance	± 3 dB
Occupied bandwidth	± RBW

9 Sequence of testing

9.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the premeasurement are maximized by the software by rotating the turntable from 0° to 360°. In case of the 2-axis positioner is used the elevation axis is also rotated from 0° to 360°.
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

9.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

9.3 Sequence of testing radiated spurious 1 GHz to 12.75 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

10 Summary of measurement results

<input checked="" type="checkbox"/>	No deviations from the technical specifications were ascertained
<input type="checkbox"/>	There were deviations from the technical specifications ascertained
<input type="checkbox"/>	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	CFR Part 22 RSS 132	See table below	2016-05-31	-/-

10.1 LTE band V

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Frequency Stability	Nominal & Extreme	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Radiated	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Spurious Emissions Conducted	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Block Edge Compliance	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
Occupied Bandwidth	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-

Note: C – Compliant; NC – Not compliant; NA = Not applicable; NP = Not performed

11 RF measurements

11.1 Results LTE band V

The EUT was set to transmit the maximum power.

11.1.1 RF output power

Description:

This paragraph contains average power, peak output power, PAPR and ERP measurements for the mobile station.

The plots in this test report represents only an example of the measurements. All plots of this chapter are available on request.

The red line in the measurements indicates the ideal Gaussian distribution for the measured amplitude range.

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

To determine the Peak-To-Average Power Ratio (PAPR) the measurement was performed with the Power Complementary Cumulative Distribution Function (CCDF).

Measurement parameters	
Detector:	Sample
AQT:	15.6 ms
Resolution bandwidth:	40 MHz
Used equipment:	see chapter 7.1 – A and chapter 7.2 – A
Measurement uncertainty:	see chapter 8

Limits:

FCC	IC
CFR Part 22.913 CFR Part 2.1046	RSS 132
Nominal Peak Output Power	
+38.45 dBm	
In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	

Results:

Output Power (conducted)								
Bandwidth (MHz)	Frequency (MHz)	Resource block allocation	Peak Output Power (dBm)	Average Output Power (dBm)	Peak to Average Ratio (dB)	Peak Output Power (dBm)	Average Output Power (dBm)	Peak to Average Ratio (dB)
			QPSK	QPSK	CCDF	16-QAM	16-QAM	CCDF
1.4	824.7	1 RB low	28.51	22.6	5.5	28.58	21.4	6.8
		1 RB high	28.69	22.7	5.5	28.71	21.6	6.5
		50% RB mid	28.66	22.6	5.5	28.72	21.6	6.5
		100% RB	28.42	21.7	5.9	28.62	20.8	7.0
	836.5	1 RB low	29.18	22.6	5.9	29.22	21.6	7.0
		1 RB high	29.07	22.6	6.0	29.37	21.7	7.1
		50% RB mid	29.35	22.7	6.0	29.39	21.7	6.8
		100% RB	28.95	21.8	6.3	28.96	20.7	7.1
	848.3	1 RB low	29.22	22.5	5.7	29.05	21.6	7.0
		1 RB high	28.72	22.3	5.9	29.01	21.3	7.2
		50% RB mid	29.01	22.5	5.8	29.22	21.5	6.9
		100% RB	28.58	21.6	6.1	28.79	20.6	7.0
3	825.5	1 RB low	28.38	22.7	5.4	28.59	21.6	6.6
		1 RB high	28.62	22.5	5.7	28.72	21.6	6.7
		50% RB mid	28.17	21.7	5.9	28.56	20.8	6.8
		100% RB	28.39	21.7	5.9	28.59	20.7	6.8
	836.5	1 RB low	29.31	22.7	6.1	29.34	21.8	7.0
		1 RB high	29.11	22.7	5.9	29.24	21.8	6.9
		50% RB mid	28.81	21.8	6.1	28.87	20.9	7.2
		100% RB	29.10	21.6	6.1	29.25	20.7	7.0
	847.5	1 RB low	29.19	22.5	5.9	29.24	21.4	7.2
		1 RB high	28.52	22.3	5.7	28.91	21.4	7.0
		50% RB mid	28.83	21.6	6.1	29.06	20.7	7.2
		100% RB	28.79	21.6	6.1	28.85	20.7	7.0
5	826.5	1 RB low	28.45	22.7	5.3	28.53	21.7	6.6
		1 RB high	28.65	22.6	5.7	28.82	21.7	6.8
		50% RB mid	28.40	21.7	5.9	28.45	20.8	6.8
		100% RB	28.48	21.7	5.9	28.63	20.9	6.7
	836.5	1 RB low	29.11	22.6	5.9	29.26	21.6	7.2
		1 RB high	29.14	22.7	5.7	29.13	21.8	6.9
		50% RB mid	29.14	21.7	6.1	29.10	20.7	7.0
		100% RB	29.13	21.8	6.1	29.04	20.8	7.0
	846.5	1 RB low	29.11	22.7	5.9	29.13	21.7	7.1
		1 RB high	28.76	22.5	5.9	28.96	21.4	6.9
		50% RB mid	28.95	21.7	6.1	29.09	20.8	7.0
		100% RB	29.02	21.9	6.1	29.08	20.9	7.0


10	829	1 RB low	28.42	22.4	5.5	28.42	21.3	6.6
		1 RB high	29.35	22.6	5.9	29.19	21.6	7.2
		50% RB mid	28.63	21.7	6.0	28.68	20.7	6.9
		100% RB	28.79	21.6	6.0	29.04	20.7	6.8
	836.5	1 RB low	29.10	22.5	5.9	29.19	21.7	6.9
		1 RB high	29.34	22.7	5.9	29.18	21.6	6.9
		50% RB mid	29.03	21.6	6.1	28.98	20.6	7.0
		100% RB	29.04	21.6	6.1	29.21	20.5	7.0
	844	1 RB low	28.91	22.4	5.9	28.95	21.5	7.1
		1 RB high	29.13	22.4	5.9	29.08	21.4	7.1
		50% RB mid	29.18	21.7	6.1	28.99	20.7	6.9
		100% RB	28.88	21.6	6.1	29.05	20.6	6.9

The radiated output power is measured in the mode with the highest conducted output power.


Output Power (radiated)			
Bandwidth (MHz)	Frequency (MHz)	Average Output Power (dBm)	
		QPSK	16-QAM
1.4	824.7	20.3	19.2
	836.5	21.9	20.9
	848.3	21.1	20.2
3	825.5	20.3	19.2
	836.5	21.9	21.0
	847.5	21.1	20.0
5	826.5	20.3	19.3
	836.5	21.9	21.0
	846.5	21.3	20.3
10	829.0	20.2	19.2
	836.5	21.9	20.9
	844.0	21.0	20.1
Measurement uncertainty		± 3.0 dB	

Plots: example 100% #RB


Plot 1: 1.4 MHz cell bandwidth, mid channel, 100% #RB, QPSK




Plot 2: 1.4 MHz cell bandwidth, mid channel, 100% #RB, 16-QAM




Plot 3: 3 MHz cell bandwidth, mid channel, 100% #RB, QPSK




Plot 4: 3 MHz cell bandwidth, mid channel, 100% #RB, 16-QAM




Plot 5: 5 MHz cell bandwidth, mid channel, 100% #RB, QPSK




Plot 6: 5 MHz cell bandwidth, mid channel, 100% #RB, 16-QAM



Plot 7: 10 MHz cell bandwidth, mid channel, 100% #RB, QPSK



Plot 8: 10 MHz cell bandwidth, mid channel, 100% #RB, 16-QAM



11.1.2 Frequency stability

Description:

In order to measure the carrier frequency under normal conditions it is necessary to make measurements with the mobile station connected to R&S CMW500 Wideband Radio Communication Tester.

1. Measure the carrier frequency at room temperature.
2. Subject the mobile station to overnight soak at -30 C.
3. With the mobile station, powered with V_{nom} , connected to the CMW500 on the centre channel with channel bandwidth of 10 MHz, measure the carrier frequency. These measurements should be made within two minutes of powering up the mobile station, to prevent significant self warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 15 minutes at each temperature, unpowered, before making measurements.
5. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Measurement:

Measurement parameters	
Detector:	Measured with CMW500
Sweep time:	
Video bandwidth:	
Resolution bandwidth:	
Span:	
Trace-Mode:	
Test setup:	see chapter chapter 7.2 – B
Measurement uncertainty:	see chapter 8

Limits:

FCC	IC
CFR Part 22.355 CFR Part 2.1055	RSS 132
Frequency Stability	
± 2.5 ppm	

Results:**AFC FREQ ERROR versus VOLTAGE**

Voltage (V)	Frequency Error (Hz)	Frequency Error (%)	Frequency Error (ppm)
3.8	+5	0.0000006	0.006

* The module requires an external stabilized power supply.

AFC FREQ ERROR versus TEMPERATURE

Temperature (°C)	Frequency Error (Hz)	Frequency Error (%)	Frequency Error (ppm)
-30	+4	0.0000005	0.005
-20	+4	0.0000005	0.005
-10	+2	0.0000002	0.002
± 0	+5	0.0000006	0.006
10	+5	0.0000006	0.006
20	+4	0.0000005	0.005
30	+4	0.0000005	0.005
40	+4	0.0000005	0.005
50	+4	0.0000005	0.005

11.1.3 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 9 kHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 848.3 MHz. Measurement made up to 12.75 GHz. The resolution bandwidth is set as outlined in Part 22.917. The spectrum was scanned with the mobile station transmitting at the middle carrier frequency of the LTE band V.

Measurement:

Measurement parameters	
Detector:	Peak / RMS
Sweep time:	5 ms/MHz
Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Span:	different steps
Trace-Mode:	Max Hold
Used equipment:	see chapter 7.1 - A
Measurement uncertainty:	see chapter 8

Limits:

FCC	IC
CFR Part 22.917 CFR Part 2.1053	RSS 132
Spurious Emissions Radiated	
Attenuation $\geq 43 + 10\log(P)$ (P, Power in Watts)	
-13 dBm	

Results:

Radiated emissions measurements were made only at the center carrier frequency of the LTE band V (836.5 MHz). It was decided that measurements at this carrier frequency would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

The final open field radiated levels are presented on the next pages. All measurements were done in horizontal and vertical polarization; the plots show the worst case. The plots show only the middle channel. If spurious were detected, the lowest and highest channel were checked too. The found values are stated in the table below.

As can be seen from this data, the emissions from the test item were within the specification limit.

QPSK:


Spurious Emission Level (dBm)		
Harmonic	Middle channel Freq. (MHz)	Level [dBm]
2	1673.0	-
3	2509.5	-
4	3346.0	-
5	4182.5	-
6	5019.0	-
7	5855.5	-
8	6692.0	-
9	7528.5	-
10	8365.0	-

16-QAM:


Spurious Emission Level (dBm)		
Harmonic	Middle channel Freq. (MHz)	Level [dBm]
2	1673.0	-
3	2509.5	-
4	3346.0	-
5	4182.5	-
6	5019.0	-
7	5855.5	-
8	6692.0	-
9	7528.5	-
10	8365.0	-

QPSK with 10 MHz channel bandwidth

Plot 1: Channel 20525 (Traffic mode up to 30 MHz)




Plot 2: Channel 20525 (30 MHz – 12.75 GHz)




16-QAM with 10 MHz channel bandwidth

Plot 3: Channel 20525 (Traffic mode up to 30 MHz)



Plot 4: Channel 20525 (30 MHz – 12.75 GHz)



11.1.4 Spurious emissions conducted

Description:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 8.5 GHz.
2. Determine mobile station transmits frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Measurement:

Measurement parameters	
Detector:	Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	Pre-measurement with 1 MHz On spurious detection re-measurement 100 kHz
Video bandwidth:	Pre-measurement with 1 MHz On spurious detection re-measurement 300 kHz
Span:	10 MHz – 8.5 GHz
Trace-Mode:	Max Hold
Used equipment:	see chapter 7.2 - A
Measurement uncertainty:	see chapter 8

Limits:

FCC	IC
CFR Part 22.917 CFR Part 2.1051	RSS 132
Spurious Emissions Conducted	
Attenuation $\geq 43 + 10\log(P)$ (P, Power in Watts)	
-13 dBm	

Results: for 1.4 MHz channel bandwidth

QPSK

Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1649.4	-	2	1673.0	-	2	1696.6	-
3	2474.1	-	3	2509.5	-	3	2544.9	-
4	3298.8	-	4	3346.0	-	4	3393.2	-
5	4123.5	-	5	4182.5	-	5	4241.5	-
6	4948.2	-	6	5019.0	-	6	5089.8	-
7	5772.9	-	7	5855.5	-	7	5938.1	-
8	6597.6	-	8	6692.0	-	8	6786.4	-
9	7422.3	-	9	7258.5	-	9	7634.7	-
10	8247.0	-	10	8365.0	-	10	8483	-

16-QAM

Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1649.4	-	2	1673.0	-	2	1696.6	-
3	2474.1	-	3	2509.5	-	3	2544.9	-
4	3298.8	-	4	3346.0	-	4	3393.2	-
5	4123.5	-	5	4182.5	-	5	4241.5	-
6	4948.2	-	6	5019.0	-	6	5089.8	-
7	5772.9	-	7	5855.5	-	7	5938.1	-
8	6597.6	-	8	6692.0	-	8	6786.4	-
9	7422.3	-	9	7258.5	-	9	7634.7	-
10	8247.0	-	10	8365.0	-	10	8483	-

Results: for 3 MHz channel bandwidth

QPSK

Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1651.0	-	2	1673.0	-	2	1695.0	-
3	2476.5	-	3	2509.5	-	3	2542.5	-
4	3302.0	-	4	3346.0	-	4	3390.0	-
5	4127.5	-	5	4182.5	-	5	4237.5	-
6	4953.0	-	6	5019.0	-	6	5085.0	-
7	5778.5	-	7	5855.5	-	7	5932.5	-
8	6604.0	-	8	6692.0	-	8	6780.0	-
9	7429.5	-	9	7258.5	-	9	7627.5	-
10	8255.0	-	10	8365.0	-	10	8475.0	-

16-QAM

Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1651.0	-	2	1673.0	-	2	1695.0	-
3	2476.5	-	3	2509.5	-	3	2542.5	-
4	3302.0	-	4	3346.0	-	4	3390.0	-
5	4127.5	-	5	4182.5	-	5	4237.5	-
6	4953.0	-	6	5019.0	-	6	5085.0	-
7	5778.5	-	7	5855.5	-	7	5932.5	-
8	6604.0	-	8	6692.0	-	8	6780.0	-
9	7429.5	-	9	7258.5	-	9	7627.5	-
10	8255.0	-	10	8365.0	-	10	8475.0	-

Results: for 5 MHz channel bandwidth

QPSK

Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1653.0	-	2	1673.0	-	2	1693.0	-
3	2479.5	-	3	2509.5	-	3	2539.5	-
4	3306.0	-	4	3346.0	-	4	3386.0	-
5	4132.5	-	5	4182.5	-	5	4232.5	-
6	4959.0	-	6	5019.0	-	6	5079.0	-
7	5785.5	-	7	5855.5	-	7	5925.5	-
8	6612.0	-	8	6692.0	-	8	6772.0	-
9	7438.5	-	9	7528.5	-	9	7618.5	-
10	8265.0	-	10	8365.0	-	10	8465.0	-

16-QAM

Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1653.0	-	2	1673.0	-	2	1693.0	-
3	2479.5	-	3	2509.5	-	3	2539.5	-
4	3306.0	-	4	3346.0	-	4	3386.0	-
5	4132.5	-	5	4182.5	-	5	4232.5	-
6	4959.0	-	6	5019.0	-	6	5079.0	-
7	5785.5	-	7	5855.5	-	7	5925.5	-
8	6612.0	-	8	6692.0	-	8	6772.0	-
9	7438.5	-	9	7528.5	-	9	7618.5	-
10	8265.0	-	10	8365.0	-	10	8465.0	-

Results: for 10 MHz channel bandwidth

QPSK


Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1658.0	-	2	1673.0	-	2	1688.0	-
3	2487.0	-	3	2509.5	-	3	2532.0	-
4	3316.0	-	4	3346.0	-	4	3376.0	-
5	4145.0	-	5	4182.5	-	5	4220.0	-
6	4974.0	-	6	5019.0	-	6	5064.0	-
7	5803.0	-	7	5855.5	-	7	5908.0	-
8	6632.0	-	8	6692.0	-	8	6752.0	-
9	7461.0	-	9	7528.5	-	9	7596.0	-
10	8290.0	-	10	8365.0	-	10	8440.0	-

16-QAM


Spurious Emission Level (dBm)								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1658.0	-	2	1673.0	-	2	1688.0	-
3	2487.0	-	3	2509.5	-	3	2532.0	-
4	3316.0	-	4	3346.0	-	4	3376.0	-
5	4145.0	-	5	4182.5	-	5	4220.0	-
6	4974.0	-	6	5019.0	-	6	5064.0	-
7	5803.0	-	7	5855.5	-	7	5908.0	-
8	6632.0	-	8	6692.0	-	8	6752.0	-
9	7461.0	-	9	7528.5	-	9	7596.0	-
10	8290.0	-	10	8365.0	-	10	8440.0	-

Plots: QPSK with 1.4 MHz channel bandwidth


Plot 1: Lowest Channel (10 MHz – 8.5 GHz)



Plot 2: Middle Channel (10 MHz – 8.5 GHz)




Plot 3: Highest Channel (10 MHz – 8.5 GHz)




Plots: 16-QAM with 1.4 MHz channel bandwidth


Plot 1: Lowest Channel (10 MHz - 8.5 GHz)



Plot 2: Middle Channel (10 MHz - 8.5 GHz)




Plot 3: Highest Channel (10 MHz - 8.5 GHz)




Plots: QPSK with 3 MHz channel bandwidth


Plot 4: Lowest Channel (10 MHz - 8.5 GHz)



Plot 5: Middle Channel (10 MHz - 8.5 GHz)




Plot 6: Highest Channel (10 MHz - 8.5 GHz)




Plots: 16-QAM with 3 MHz channel bandwidth


Plot 4: Lowest Channel (10 MHz - 8.5 GHz)



Plot 5: Middle Channel (10 MHz - 8.5 GHz)




Plot 6: Highest Channel (10 MHz - 8.5 GHz)




Plots: QPSK with 5 MHz channel bandwidth


Plot 1: Lowest Channel (10 MHz - 8.5 GHz)



Plot 2: Middle Channel (10 MHz - 8.5 GHz)




Plot 3: Highest Channel (10 MHz - 8.5 GHz)




Plots: 16-QAM with 5 MHz channel bandwidth


Plot 4: Lowest Channel (10 MHz - 8.5 GHz)



Plot 5: Middle Channel (10 MHz - 8.5 GHz)




Plot 6: Highest Channel (10 MHz - 8.5 GHz)




Plots: QPSK with 10 MHz channel bandwidth


Plot 1: Lowest Channel (10 MHz - 8.5 GHz)



Plot 2: Middle Channel (10 MHz - 8.5 GHz)




Plot 3: Highest Channel (10 MHz - 8.5 GHz)




Plots: 16-QAM with 10 MHz channel bandwidth


Plot 4: Lowest Channel (10 MHz - 8.5 GHz)



Plot 5: Middle Channel (10 MHz - 8.5 GHz)



Plot 6: Highest Channel (10 MHz - 8.5 GHz)



11.1.5 Block edge compliance

Description:

The spectrum at the band edges must comply with the spurious emissions limits.

Measurement:


Measurement parameters	
Detector:	RMS
Sweep time:	30 s
Resolution bandwidth:	1% - 5% of the OBW
Video bandwidth:	$\geq 3 \times \text{RBW}$
Span:	5 MHz
Trace-Mode:	Max Hold
Used equipment:	see chapter 7.2 - A
Measurement uncertainty:	see chapter 8

Limits:

FCC	IC
CFR Part 22.917 CFR Part 2.1051	RSS 132
Block Edge Compliance	
Attenuation $\geq 43 + 10\log(P)$ (P, Power in Watts)	
-13 dBm	


Results: 1.4 MHz channel bandwidth

Plot 1: Lowest channel – QPSK




Date: 2.OCT.2015 10:43:21

Plot 2: Highest channel – QPSK




Date: 2.OCT.2015 10:49:48

Plot 3: Lowest channel – 16-QAM



Date: 2.OCT.2015 10:44:57


Plot 4: Highest channel – 16-QAM



Date: 2.OCT.2015 10:51:23


Results: 3 MHz channel bandwidth

Plot 1: Lowest channel – QPSK




Date: 2.OCT.2015 10:53:13

Plot 2: Highest channel – QPSK




Date: 2.OCT.2015 10:59:40

Plot 3: Lowest channel – 16-QAM



Date: 2.OCT.2015 10:54:48


Plot 4: Highest channel – 16-QAM



Date: 2.OCT.2015 11:01:15


Results: 5 MHz channel bandwidth

Plot 1: Lowest channel – QPSK




Date: 2.OCT.2015 11:03:05

Plot 2: Highest channel – QPSK




Date: 2.OCT.2015 11:09:32

Plot 3: Lowest channel – 16-QAM



Date: 2.OCT.2015 11:04:41


Plot 4: Highest channel – 16-QAM



Date: 2.OCT.2015 11:11:07


Results: 10 MHz channel bandwidth

Plot 1: Lowest channel – QPSK




Date: 2.OCT.2015 11:12:58

Plot 2: Highest channel – QPSK




Date: 2.OCT.2015 11:19:25

Plot 3: Lowest channel – 16-QAM



Date: 2.OCT.2015 11:14:33

Plot 4: Highest channel – 16-QAM



Date: 2.OCT.2015 11:21:00

11.1.6 Occupied bandwidth

Description:

Measurement of the occupied bandwidth of the transmitted signal.

Measurement:

Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the LTE band V. The table below lists the measured 99% power and -26dBc occupied bandwidths. Spectrum analyzer plots are included on the following pages.

Measurement parameters	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1% - 5% of the OBW
Video bandwidth:	≥ 3xRBW
Span:	2 x nominal BW
Trace-Mode:	Max Hold
Used equipment:	see chapter 7.2
Measurement uncertainty:	see chapter 8

Limits:

FCC	IC
Occupied Bandwidth	
Spectrum must fall completely in the specified band	


Results:

Occupied Bandwidth – QPSK		
Bandwidth (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
1.4	1326.23	1254.6
3.0	3142.47	3060.9
5.0	5130.49	4981.5
10.0	10198.98	9949.0
Measurement uncertainty	± 10 kHz	


Occupied Bandwidth – 16-QAM		
Bandwidth (MHz)	99% OBW (kHz)	-26 dBc BW (kHz)
1.4	1323.99	1260.2
3.0	3144.89	3049.5
5.0	5137.49	4965.5
10.0	10228.98	9985.0
Measurement uncertainty	± 10 kHz	

Plots: QPSK


Plot 1: 1.4 MHz (99% - OBW)



Plot 2: 1.4 MHz (-26 dBc BW)




Plot 3: 3 MHz (99% - OBW)




Date: 26.OCT.2015 12:05:56

Plot 4: 3 MHz (-26 dBc BW)




Date: 27.OCT.2015 08:01:29


Plot 5: 5 MHz (99% - OBW)



Plot 6: 5 MHz (-26 dBc BW)




Plot 7: 10 MHz (99% - OBW)



Date: 26.OCT.2015 12:37:51


Plot 8: 10 MHz (-26 dBc BW)



Date: 27.OCT.2015 08:29:51


Plots: 16-QAM

Plot 1: 1.4 MHz (99% - OBW)




Date: 26.OCT.2015 11:52:11

Plot 2: 1.4 MHz (-26 dBc BW)




Date: 27.OCT.2015 07:56:25

Plot 3: 3 MHz (99% - OBW)




Date: 26.OCT.2015 12:08:07

Plot 4: 3 MHz (-26 dBc BW)




Date: 27.OCT.2015 08:02:45

Plot 5: 5 MHz (99% - OBW)




Date: 26.OCT.2015 12:24:03

Plot 6: 5 MHz (-26 dBc BW)




Date: 27.OCT.2015 08:07:41

Plot 7: 10 MHz (99% - OBW)



Plot 8: 10 MHz (-26 dBc BW)



12 Observations

No observations except those reported with the single test cases have been made.

Annex A Document history

Version	Applied changes	Date of release
	Initial release	2015-11-12
A	Retests after HW change	2016-02-05
-B	IC number removed; contact person changed	2016-05-12
-C	Correction of power supply conditions	2016-05-31

Annex B Further information

Glossary

AVG	-	Average
DUT	-	Device under test
EMC	-	Electromagnetic Compatibility
EN	-	European Standard
EUT	-	Equipment under test
ETSI	-	European Telecommunications Standard Institute
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	Not applicable
PP	-	Positive peak
QP	-	Quasi peak
S/N	-	Serial number
SW	-	Software
PMN		Product marketing name
HMN		Host marketing name
HVIN		Hardware version identification number
FVIN		Firmware version identification number

Annex C Accreditation Certificate

Front side of certificate

Back side of certificate



Deutsche Akkreditierungsstelle GmbH

Beliehene gemäß § 8 Absatz 1 AkkStelleG i.V.m. § 1 Absatz 1 AkkStelleGBV
 Unterzeichnerin der Multilateralen Abkommen
 von EA, ILAC und IAF zur gegenseitigen Anerkennung

Akkreditierung



Die Deutsche Akkreditierungsstelle GmbH bestätigt hiermit, dass das Prüflaboratorium

CETECOM ICT Services GmbH
 Untertürkheimer Straße 6-10, 66117 Saarbrücken

die Kompetenz nach DIN EN ISO/IEC 17025:2005 besitzt, Prüfungen in folgenden Bereichen durchzuführen:

- Funk
- Mobilfunk (GSM / DCS) + OTA
- Elektromagnetische Verträglichkeit (EMV)
- Produktsicherheit
- SAR / EMF
- Umwelt
- Smart Card Technology
- Bluetooth®
- Automotive
- Wi-Fi-Services
- Kanadische Anforderungen
- US-Anforderungen
- Akustik
- Near Field Communication (NFC)

Die Akkreditierungsurkunde gilt nur in Verbindung mit dem Bescheid vom 04.05.2016 mit der Akkreditierungsnummer D-PL-12076-01 und ist gültig bis 17.01.2018. Sie besteht aus diesem Deckblatt, der Rückseite des Deckblatts und der folgenden Anlage mit insgesamt 63 Seiten.

Registrierungsnummer der Urkunde: D-PL-12076-01-01

Frankfurt, 04.05.2016

Im Auftrag
 (Signature)
 Abteilungsleiter

Siehe Hinweise auf der Rückseite

Deutsche Akkreditierungsstelle GmbH

Standort Berlin
 Spittelmarkt 10
 10117 Berlin

Standort Frankfurt am Main
 Europa-Allee 52
 60327 Frankfurt am Main

Standort Braunschweig
 Bundesallee 100
 38116 Braunschweig

Die auszugsweise Veröffentlichung der Akkreditierungsurkunde bedarf der vorherigen schriftlichen Zustimmung der Deutsche Akkreditierungsstelle GmbH (DAkkS). Ausgenommen davon ist die separate Weiterverbreitung des Deckblattes durch die umeitig genannte Konformitätsbewertungsstelle in unveränderter Form.

Es darf nicht der Anschein erweckt werden, dass sich die Akkreditierung auch auf Bereiche erstreckt, die über den durch die DAkkS bestätigten Akkreditierungsbereich hinausgehen.

Die Akkreditierung erfolgte gemäß des Gesetzes über die Akkreditierungsstelle (AkkStelleG) vom 31. Juli 2009 (BGBl. I S. 2625) sowie der Verordnung (EG) Nr. 765/2008 des Europäischen Parlaments und des Rates vom 9. Juli 2008 über die Vorschriften für die Akkreditierung und Marktüberwachung im Zusammenhang mit der Vermarktung von Produkten (Abt. L 218 vom 9. Juli 2008, S. 30). Die DAkkS ist Unterzeichnerin der Multilateralen Abkommen zur gegenseitigen Anerkennung der European co-operation for Accreditation (EA), des International Accreditation Forum (IAF) und der International Laboratory Accreditation Cooperation (ILAC). Die Unterzeichner dieser Abkommen erkennen ihre Akkreditierungen gegenseitig an.

Der aktuelle Stand der Mitgliedschaft kann folgenden Webseiten entnommen werden:
 EA: www.european-accrreditation.org
 ILAC: www.ilac.org
 IAF: www.iaf.nu

Note:

The current certificate including annex can be received from CETECOM ICT Services GmbH on request.