

**TEST REPORT**  
 No.: 6-0491-14-14-2d

According to:  
**FCC Regulations**  
 Part 2.1091

**IC-Regulations**  
 RSS-102, Issue 4







for

peiker acustic GmbH & Co. KG

GSM/W-CDMA Module V1140-105  
 and  
 ATM-01 T1-US-3G

FCC-ID: QWY-V1140-105

IC-ID: 6588A-V1140105, PMN: LTE-NAD , HVIN: V1140-105

Laboratory Accreditation and Listings			
 Deutsche Akkreditierungsstelle D-PL-12047-01-01	 FEDERAL COMMUNICATIONS COMMISSION USA Reg. No.: 736496 MRA US-EU 0003	 Industry Canada Reg. No.: 3462D-1 Reg. No.: 3462D-2 Reg. No.: 3462D-3	 Voluntary Controls for Electromagnetic Emissions Reg. No.: R-2666 C-2914, T-1967, G-301
 <b>WiFi</b> ALLIANCE AUTHORIZED RF LABORATORY	 <b>CTIA Authorized Test Lab</b> LAB CODE 20011130-00		
accredited according to DIN EN ISO/IEC 17025			
<p align="center"> <b>CETECOM GmbH</b>            Laboratory Radio Communications &amp; Electromagnetic Compatibility            Im Teelbruch 116 • 45219 Essen • Germany            Registered in Essen, Germany, Reg. No.: HRB Essen 8984            Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964            E-mail: info@cetecom.com • Internet: www.cetecom.com         </p>			

## Table of contents

<b>1. SUMMARY OF TEST RESULTS.....</b>	<b>3</b>
1.1. TX mode, tests overview FCC Part 2.1091 and Canada IC Standards (RSS) .....	3
1.2. Attestation:.....	3
<b>2. ADMINISTRATIVE DATA .....</b>	<b>4</b>
2.1. Identification of the testing laboratory.....	4
2.2. Test location .....	4
2.3. Organizational items .....	4
2.4. Applicant’s details .....	4
2.5. Manufacturer’s details .....	4
<b>3. EQUIPMENT UNDER TEST (EUT).....</b>	<b>5</b>
3.1. TECHNICAL DESCRIPTION OF MAIN EUT .....	5
3.2. EUT: Type, S/N etc. and short descriptions used in this test report .....	7
3.3. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions.....	7
3.4. EUT set-ups .....	7
3.5. EUT operating modes .....	8
<b>4. MEASUREMENTS .....</b>	<b>9</b>
4.1. Radio Frequency Exposure Evaluation §2.1091 .....	9
4.2. Results for fixed and mobile operations .....	11
4.3. Conclusion for maximum admissible antenna gain including PCB loss .....	15
4.4. Measurement uncertainties .....	16
<b>5. ABBREVIATIONS USED IN THIS REPORT .....</b>	<b>16</b>
<b>6. ACCREDITATION DETAILS OF CETECOM’S LABORATORIES AND TEST SITES .....</b>	<b>17</b>
<b>7. VERSIONS OF TEST REPORTS (CHANGE HISTORY) .....</b>	<b>17</b>
<b>8. INSTRUMENTS AND ANCILLARY.....</b>	<b>18</b>
8.1. Used equipment “CTC” .....	18

## Table of annex

### Total pages

Annex 1: External EUT photographs – separate document TR6-0491-14-14-2d-A1

4

The listed attachments are an integral part of this report.

## 1. Summary of test results

The test results apply exclusively to the test samples as presented in this Report. The CETECOM GmbH does not assume responsibility for any conclusions and generalizations taken in conjunction with other specimens or samples of the type of the item presented to tests.

The Equipment Under Test (in this report, hereinafter referred as EUT) supports radiofrequency technologies. The presented RF Data-Module can be build inside host applications and extends their capability by wireless GSM and W-CDMA technology. Data transmissions application is possible field application.

An additional MPE report is issued based on the power values from test report no. 6-0315-13-3-2a and 6-0315-13-3-2b. from module's initial certification but based on new parameters regarding path loss due to new host equipment.

We refer to additional documents as supplied by the applicant and initial certification test reports.

### 1.1. TX mode, tests overview FCC Part 2.1091 and Canada IC Standards (RSS)

No. of Diag. group	Test Cases	Port	References & Limits			EUT set-up	EUT op-mode	Result
			FCC Standard	RSS Section	Test limits			
--	RF Power (conducted)	Antenna terminal (conducted)	§2.1046	--	N/A	--	1 to 4	passed Remark 1
--	Radio frequency Exposure Evaluation (MPE)	Cabinet	§1.1310 §2.1091	RSS-102, Issue 4	FCC: §1.1310 Table 1, Limits for General Population IC: Chapter 4.2 RF-Limits	--	1 to 4	passed

Remark: 1.) See separate test reports TR6-0315-13-3-2a/b and corresponding annexes.

**This MPE report does not take into consideration a possible collocation with other transmitter (ex. BT, Wi-Fi).**

### 1.2. Attestation:

I declare that all measurements were performed by me or under my supervision and that all measurements have been performed and are correct to my best knowledge and belief to Industry Canada standards. All requirements as shown in above table are met in accordance with enumerated standards.

.....  
Dipl.-Ing. Rachid Acharkaoui  
Responsible for test section

.....  
M. Nunier  
Responsible for test report

## 2. Administrative Data

### 2.1. Identification of the testing laboratory

Company name:	CETECOM GmbH
Address:	Im Teelbruch 116 45219 Essen - Kettwig Germany
Responsible for testing laboratory:	Dipl.-Ing. Rachid Acharkaoui
Deputy:	Dipl.-Ing. Niels Jeß

### 2.2. Test location

#### 2.2.1. Test laboratory "CTC"

Company name:	see chapter 2.1. Identification of the testing laboratory
---------------	---

### 2.3. Organizational items

Responsible for test report and project leader:	M. Nunier
Receipt of EUT:	2013-11-20
Date(s) of test:	2013-12-05 to 2013-12-13
Date of report:	2015-03-19
-----	
Version of template:	13.01

### 2.4. Applicant's details

Applicant's name:	peiker acoustic GmbH & Co. KG
Address:	Max-Planck-Straße 28-32 61381 Friedrichsdorf  Germany
Contact person:	Mr. Philippe Seguret

### 2.5. Manufacturer's details

Manufacturer's name:	please see Applicant's details
Address:	please see Applicant's details

### 3. Equipment under test (EUT)

#### 3.1. TECHNICAL DESCRIPTION OF MAIN EUT

##### GSM characteristics:

Main function	GSM/GPRS/E-GPRS/W-CDMA Wireless Module		
Type	V1140-105		
GSM Frequency range (US/Canada -bands)	GSM 850: 824 – 849 MHz (Uplink), 869-894 MHz (Downlink) GSM1900: 1850-1910 MHz (Uplink), 1930-1990 MHz (Downlink)		
Type of modulation	GSM, GPRS, GMSK EGPRS-Mode: 8-PSK		
Number of channels (USA/Canada -bands)	GSM 850: 128 – 251, 125 channels GSM1900: 512 – 810, 300 channels		
Test Channel frequencies	GSM/E-GPRS 850 MHz Band: Channel 128/192/251 GSM/E-GPRS 1900 MHz Band: Channel 512/661/810		
Emission designator(s)	247KGXW (GSM850) 245KG7W (EDGE850) 245KGXW (GSM1900) 245KG7W (EDGE 1900)		
Antenna Type	<input type="checkbox"/> Integrated <input type="checkbox"/> External, no RF- connector <input checked="" type="checkbox"/> External, separate RF-connector		
Antenna Gain (declared by applicant)	<input type="checkbox"/> conducted: not declared by applicant <input checked="" type="checkbox"/> radiated: not declared by the applicant		
Measured Output Power [dBm]: Conducted GSM 850 Conducted GSM 1900	Peak 32.1dBm / AV 31.9dBm (based on TR6-0315-13-3-2a) Peak 29.5dBm / AV 29.3dBm (based on TR6-0315-13-3-2a)		
FCC-ID	QWY-V1140-105		
IC	6588A-V1140105		
Installed options	<input checked="" type="checkbox"/> GSM 900 and GSM 1800 Bands (not usable in USA/Canada) <input checked="" type="checkbox"/> W-CDMA Band I and Band VIII (not usable in USA/Canada)		
Power supply	<input checked="" type="checkbox"/> possibility one: over AC/DC adapter: 12 V DC <input checked="" type="checkbox"/> possibility two: DC powered only by laboratory power supply with 3.8 Volt		
Special EMI components	--		
Voltage	<input checked="" type="checkbox"/> nominal 3.8 V DC		
EUT sample type	<input type="checkbox"/> Production	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Engineering
FCC label attached	<input type="checkbox"/> yes <input checked="" type="checkbox"/> no		

**W-CDMA characteristics:**

Main function	W-CDMA Wireless Module		
Type	V1140-105		
TX-frequency range	FDD Band 2: 1852.4–1907.6 MHz (Uplink), 1930-1990 MHz (Downlink) FDD Band 5: 826.4-846.6 MHz (Uplink), 869-894 MHz (Downlink)		
Type of modulation	FDD-Mode Release99: QPSK FDD Mode Release 5+6: 16QAM additional		
Number of channels	FDD Band 2: UARFCN range 9262 – 9400 – 9538 FDD Band 5: UARFCN range 4132 – 4183 – 4233		
UMTS-HSPA connectivity	no information available		
Emission designator(s)	Band II: 4M17F9W Band V: 4M17F9W		
Antenna Type	<input type="checkbox"/> Integrated <input type="checkbox"/> External, no RF- connector <input checked="" type="checkbox"/> External, separate RF-connector		
Antenna Gain	<input type="checkbox"/> conducted: not declared by applicant <input checked="" type="checkbox"/> radiated: not declared by the applicant		
MAX PEAK Output Power: Conducted	FDD-Mode 2	(PK) 26.9 dBm	
	FDD-Mode 5	(PK) 27.2 dBm	
FCC-ID	QWY-V1140-105		
IC	6588-V1140105		
Installed option	<input checked="" type="checkbox"/> GSM 900 and GSM 1800 Bands (not usable in USA/Canada) <input checked="" type="checkbox"/> W-CDMA Band I and Band VIII (not usable in USA/Canada)		
Power supply	<input checked="" type="checkbox"/> possibility one: over AC/DC adapter: 12 V DC <input checked="" type="checkbox"/> possibility two: DC powered only by laboratory power supply with 3.8 Volt		
Special EMI components	--		
EUT sample type	<input type="checkbox"/> Production	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Engineering
FCC label attached	<input type="checkbox"/> yes <input checked="" type="checkbox"/> no		

### 3.2. EUT: Type, S/N etc. and short descriptions used in this test report

Short description*)	EUT	Type	S/N serial number	HW hardware status	SW software status
EUT A	GSM/W-CDMA Module	V1140-105	NA_3G#605 V1140-105	V1140-105_Ver.3	M9615A-CETWTAZM-5.0.110014

\*) EUT short description is used to simplify the identification of the EUT in this test report.

### 3.3. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions

AE short description *)	Auxiliary Equipment	Type	S/N serial number	HW hardware status	SW software status
AE 1	Evaluation Board	LTE-NAD LP1307-1	218 UL94V-0	--	--
AE 2	Microphone	KL1/B	--	--	--
AE 3	Loudspeaker	--	9263744	--	--
AE 4	USB cable	High Speed 2.0	--	--	--
AE 5	AC/DC Adapter	Fairway	WN20U-12A	Output: 12 V DC 1.25A	--
AE 6	Notebook	Dell D2120	--	--	Windows 7
AE 7	Host device	ATM-01 R1-US-3G	--	--	--

\*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

### 3.4. EUT set-ups

EUT set-up no. *)	Combination of EUT and AE	Remarks
set. 1	EUT A + AE 1 +AE 2 +AE 3 +AE 4 +AE5 +AE 6	Setup for conducted tests, results not used within this report. Pls. see comment on chapter 4.1.4.
set. 2	EUT A + AE 7	Not tested: used for MPE re-evaluation

\*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

### 3.5. EUT operating modes

EUT operating mode no. *)	Description of operating modes	Additional information
op. 1	GPRS 850 TCH mode TCH=128/192/251	A communication link is established between the mobile station and the test simulator. The transmitter is operated at its maximum rated output power: 33 dBm (power class 4; power control level 5). USF_Duty CYCLE set to 100%, coding scheme CS-1 for GMSK modulation, slot 3 active, uplink gamma: 3 (33dBm). The input signal to the receiver is modulated with normal test modulation. The wanted RF input signal level to the receiver of the mobile station is set to a level to provide a stable communication link.
op. 2	GPRS 1900 TCH mode TCH=512/661/810	A communication link is established between the mobile station and the test simulator. The transmitter is operated at its maximum rated output power: 30 dBm (power class 1; power control level 0). USF_Duty CYCLE set to 100%, coding scheme CS-1 for GMSK modulation, slot 3 active, uplink gamma: 3 (30dBm). The input signal to the receiver is modulated with normal test modulation. The wanted RF input signal level to the receiver of the mobile station is set to a level to provide a stable communication link
op. 3	FDD Mode 2 RMC99-Mode	A communication link is established between the mobile station (UE) and the test simulator. The transmitter is operated on its maximum rated output power class: 24dBm.
op. 4	FDD Mode 5 RMC99-Mode	The input signal to the receiver is modulated with normal test modulation. The wanted RF input signal level to the receiver of the mobile station is set to a level to provide a stable communication link according Table E5.1/Table E5.1A as described in 3GPP TS34.121, Annex E.

\*) EUT operating mode no. is used to simplify the test report.



## 4. Measurements

### 4.1. Radio Frequency Exposure Evaluation §2.1091

#### 4.1.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> Please see Chapter. 2.2.2	<input type="checkbox"/> Please see Chapter. 2.2.3
For Evaluation instruments are not needed. Results are determined by calculation.			

#### 4.1.2. Requirements

FCC: §1.1310	<i>The criteria used for the evaluation of human exposure to radio frequency radiation is table 1 according FCC §1.1310 and table chapter 4.2 of RSS-102 standard and it is subject for evaluation of the RF exposure prior to equipment authorization. As the mobile equipment is authorized under Part 22 (Subpart H) and Part 24 of the FCC Rules, it is subject for evaluation of the RF exposure prior to equipment authorization.</i>
FCC § 2.1091	<i>Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, 'Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation.' For purposes of these requirements mobile devices are defined by the FCC as transmitters designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limits given in Table 1 of Appendix A.</i>
IC RSS-102 Issue 4	<i>"...sets out the requirements and measurement techniques used to evaluate radio frequency (RF) exposure compliance of radiocommunication apparatus designed to be used within the vicinity of the human body"</i>

Table 1: LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)				
Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Powe density [mW/cm²]	Averaging time [minutes]
30 - 300	61.4	0.163	1.0	6
300 - 1500	-	-	f/300	6
1500 - 100,000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*(100)	30
1.34 – 30	824/f	2.19/f	*(180/f²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 – 100,0	-	-	1.0	30

For given power density limit at a single frequency (accord. Table 1 Limits) the maximum antenna gain can be calculated.

The used equation to predict the power density in the far-field of one single radiating antenna can be made by following equation:

$$S = \frac{EIRP}{4\pi R^2} = \frac{P * G}{4\pi R^2}$$

$$G_{NUMERIC} = \frac{S * 4\pi R^2}{P}$$

#### 4.1.3. General Limits:

##### FCC:

FCC: §1.1307	<i>Cellular Radiotelephone Service (subpart H of part 22) Non-building-mounted antennas: height above ground level to lowest point of antenna &lt; 10 m and total power of all channels &gt; 1000 W ERP (1640 W EIRP)</i>
FCC §1.1307	<i>Personal Communications Services (part 24) Broadband PCS (subpart E): non-building-mounted antennas: height above ground level to lowest point of antenna &lt; 10 m and total power of all channels &gt; 2000 W ERP (3280 W EIRP)</i>
FCC §1.1310	<i>LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) Table 1(B) Limits for General Population/Uncontrolled Exposure 300–1500 MHz: <math>f/1500</math> mW/cm<sup>2</sup> 1500–100,000 MHz: 1.0 mW/cm<sup>2</sup></i>
FCC §2.1091	<i>Subject to routine evaluation is required when the device operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.</i>
FCC §24.232	<i>(a) Base stations are limited to 1640 watts peak equivalent isotropically radiated power (e.i.r.p.) with an antenna height up to 300 meters HAAT. b) Mobile/portable stations are limited to 2 watts e.i.r.p. peak power, ...</i>
FCC §22.913	<i>(a) Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.</i>
FCC §27.50 (C)(10)	<i>(10) Portable stations (hand-held devices) are limited to 3 watts ERP; and</i>
FCC §27.50(d)	<i>(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band are limited to 1 watt EIRP.</i>

#### 4.1.4. Measurement method

##### Valid for GSM/GPRS/EDGE mode:

- The power was tested on 3 frequencies (lowest/middle/highest) within each operable bands and the results compared to applicant's declared power values (tune-up info).
- Average burst power (slot power) and peak were measured (see separate report for GSM/GPRS/E-GPRS technology)
- Only one uplink slot (1 TX) was measured. 4 TX slots are maximum possible for this device and calculated as worst-case
- A duty-cycle correction factor of  $10 \cdot \log_{10}$  (max. number of possible active slots / 8 slots) were applied

Please find in the following tables the calculations based on applicants tune-up information for the power values. Also the maximum admissible allowed antenna gain is calculated which is not exceeding the MPE limit for fixed and mobile operations.

##### Valid for W-CDMA Mode:

- The power was checked on 3 frequencies (lowest/middle/highest) within each operable FDD-band (see separate report for W-CDMA technology) and the results compared to applicant's declared power values (tune-up info). A RMS detector was used.
- No duty-cycle correction factor is applicable

Please find in the following tables the calculations based on applicants tune-up information (document **Tune-Up Information for peiker 2G/3G LTE-NAD V1140-103 / V1140-105**, Rev. 1.0, dated 2013-11-20) for the power values. Also the maximum admissible allowed antenna gain is calculated which is not exceeding the MPE limit for fixed and mobile operations.

## 4.2. Results for fixed and mobile operations

### 4.2.1. Results for lower operational band: GSM850 and FDD Band 5

#### 4.2.1.1. MPE results

For MPE calculations the PCB path loss is considered according provided information by the applicant. Path loss value is 2.8 dB for the external antenna path.

Operating Mode	Frequency on channel  (MHz)	Declared maximum conducted output power  (dBm)	Max. positive tolerance according manufacturer	Maximum output power (declared+ Tune-up)  (dBm)	Duty cycle	Declared Maximum conducted output power  [W]	Equivalent conducted output power (maximum conducted output power)
GSM/GPRS (PK)	824.2	32.50	1.50	34.00	50%	2.5119	1255.94
	837	32.50		34.00		2.5119	1255.94
	848.8	32.50		34.00		2.5119	1255.94
GSM/GPRS (Avg. Burst Power)	824.2	32.50	1.50	34.00	50%	2.5119	1255.94
	837	32.50		34.00		2.5119	1255.94
	848.8	32.50		34.00		2.5119	1255.94
EDGE (PK)	824.2	26.50	2.50	29.00	50%	0.7943	397.16
	837	26.50		29.00		0.7943	397.16
	848.8	26.50		29.00		0.7943	397.16
EDGE (Avg. Burst Power)	824.2	26.50	2.50	29.00	50%	0.7943	397.16
	837	26.50		29.00		0.7943	397.16
	848.8	26.50		29.00		0.7943	397.16
WCDMA FDD Band 5 (RMS-Value)	826.4	23.00	2.00	25.00	100%	0.3162	316.23
	836.4	23.00		25.00		0.3162	316.23
	846.6	23.00		25.00		0.3162	316.23

Maximum calculated MPE value:		
MPE-Limit:	0.471	[mW/cm <sup>2</sup> ]
Highest MPE value:	0.131	[mW/cm <sup>2</sup> ]
Margin to limit	0.340	[mW/cm <sup>2</sup> ]

Remark: based on 0dBd antenna gain and additional path loss of 2.8dB

Canadian RSS-102 standard requires the RF-exposure value in W/m<sup>2</sup> unit:, therefore the value determined in mW/cm<sup>2</sup> unit, should be multiplied by 10 to have the required unit.

### 4.2.1.2. Max. antenna gain calculations

<b>Maximum antenna gain considerations for fixed/mobile operations for complying with limits:</b>		
---	--	--

POUT	Maximum power delivery at RF-Pad from Module incl. Duty cycle [mW]: (Avg. Burst Power or RMS)	1255.94
Atten-Pad	Attenuation - Path Loss NAD to ext. Ant. (MIMO 1) [dB] <b>(information from applicant)</b>	-2.8
PANT	Resulting delivered Power at antenna input [mW]	659.13
R	Safety distance [cm]:	20.00
S	MPE limit acc. §1.1310 and RSS-102 for uncontrolled exposure [mW/cm <sup>2</sup> ]: (FCC use mW/cm <sup>2</sup> & IC use W/m <sup>2</sup> )	0.55
G <sub>1</sub>	Maximum Antenna gain to comply with MPE limit [dBi]:	<b>6.22</b>

(For G<sub>1</sub> the lowest measured channel to reach minimum ant. Gain selected)

ERP power limit according to §2.1091 [W]: (Avg. Burst Power or RMS)		1.50
G <sub>2</sub>	Max. Antenna gain to comply with limit incl. Duty cycle [dBi]:	<b>5.72</b>

(For G<sub>2</sub> select the max. Avg. Burst Power or RMS value incl. Duty cycle)

ERP power limit according to §22.913 [W ERP]:		7.00
G <sub>3</sub>	Max. Antenna gain to comply with limit [dBi]:	<b>9.35</b>

(For G<sub>3</sub> select the max. Average burst power value **excluding** Duty cycle)

<b>G</b> 850MHz-Band	<b>Min (G<sub>1</sub>, G<sub>2</sub>, G<sub>3</sub>) [dBi]</b>	<b>5.72</b>
----------------------	--	-------------

<b>Summarized results:</b>	The max. ant. gain for mobile operation at 850 MHz band to comply with MPE and ERP limits incl. External path loss for shown application shall not exceed [dBd]:	<b>3.57</b>
----------------------------	--	-------------

**4.2.2. Results for upper operational band: GSM1900 and FDD 2**

**4.2.2.1. MPE results**

For MPE calculations the PCB path loss is considered according provided information by the applicant. Path loss value is 5.0 dB for the external antenna path.

Operation Mode	Frequency on channel	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Declared maximum output power (Measured+ Tune-up)	Duty cycle	Declared Maximum conducted output power	Equivalent conducted output power (maximum conducted output power x duty cycle) (mW)
	(MHz)	(dBm)	(dB)	(dBm)		(W)	
GSM/GPRS (PK-Burst value)	1850.2	29.5	1.50	31.00	50%	1.259	629
	1880.0	29.5		31.00		1.259	629
	1909.8	29.5		31.00		1.259	629
GSM/GPRS (AV Burst Power)	1850.2	29.5	1.50	31.00	50%	1.259	629
	1880.0	29.5		31.00		1.259	629
	1909.8	29.5		31.00		1.259	629
EDGE (PK-Burst value)	1850.2	25.5	2.50	28.00	50%	0.631	315
	1880.0	25.5		28.00		0.631	315
	1909.8	25.5		28.00		0.631	315
EDGE (AV Burst Power)	1850.2	25.5	2.50	28.00	50%	0.631	315
	1880.0	25.5		28.00		0.631	315
	1909.8	25.5		28.00		0.631	315
W-CDMA FDD Band 2 (RMS-Value)	1852.4	23.0	2.00	25.00	100%	0.316	316
	1880.0	23.0		25.00		0.316	316
	1907.6	23.0		25.00		0.316	316

<b>Maximum calculated MPE value:</b>		
<b>MPE-Limit:</b>	<b>1</b>	<b>[mW/cm ^2]</b>
<b>Highest MPE value:</b>	<b>0.040</b>	<b>[mW/cm ^2]</b>
<b>Margin to limit</b>	<b>0.960</b>	<b>[mW/cm ^2]</b>

Remark: based on 0dBi antenna gain and additional path loss of 5.0dB

**Canadian RSS-102** standard requires the RF-exposure value in W/m<sup>2</sup> unit:, therefore the value determined in mW/cm<sup>2</sup> unit, should be multiplied by 10 to have the required unit.

### 4.2.2.2. Max. antenna gain calculations

**Maximum antenna gain considerations for fixed/mobile operations for complying with limits:**

$P_{OUT}$	Maximum power delivery at RF-Pad from Module incl. Duty cycle (mW): (Avg. Burst Power or RMS)	629
Atten-Pad	Attenuation - Path Loss NAD to ext. Ant. (MIMO 1) [dB] (information from applicant)	-5.0
$P_{ANT}$	Resulting delivered Power at antenna input [mW]	199
R	Safety distance [cm]	20
S	MPE limit acc. §1.1310 and RSS-102 for uncontrolled exposure (mW/cm <sup>2</sup> ): (FCC use mW/cm <sup>2</sup> & IC use W/m <sup>2</sup> )	1.00
$G_1$	Maximum Antenna gain to comply with MPE limit (dBi):	<b>14.02</b>

(For G1 the lowest measured channel to reach minimum ant. Gain selected)

	ERP power limit according to §2.1091 [W]: (Avg. Burst Power or RMS)	3.00
$G_2$	Max. Antenna gain to comply with this limit incl. Duty cycle (dBi):	<b>13.93</b>

(For G2 select the max. Avg. Burst Power or RMS value incl. Duty cycle)

	EIRP power limit according to §24.232 [W]:	2.00
$G_3$	Max. Antenna gain to comply with this limit (dBi):	<b>7.01</b>

(For G3 select the max. Average burst power value **excluding** Duty cycle)

$G_{1900MHz-Band}$	<b>Min (G1, G2, G3) (dBi)</b>	<b>7.01</b>
--------------------	-------------------------------	-------------

<b>Summarized results:</b>	The max. ant. gain for mobile operation at 1900 MHz band to comply with MPE and EIRP limits incl. External path loss for shown application shall not exceed (dBi):	<b>7.01</b>
----------------------------	--	-------------

#### 4.3. Conclusion for maximum admissible antenna gain including PCB loss

Max. Gain in Lower operational band (850MHz)	3.57 dBd (5.72 dBi)
Max. Gain in Higher operational band (1900MHz)	7.01 dBi

Remark: calculations does not include other may be nearby situated second transmitters (Co-location)

#### 4.4. Measurement uncertainties

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved.

For uncertainty determination, each component used in the concrete measurement set-up was taken in account and it's contribution to the overall uncertainty according it's statistical distribution calculated.

Following table shows expectable uncertainties for each measurement type performed.

RF-Measurement	Frequency range	Calculated uncertainty based on a confidence level of 95%	Remarks:
Power Output conducted	9 kHz .. 20 GHz	1.0 dB	--
Power Output radiated	30 MHz .. 4 GHz	3.17 dB	Substitution method
Conducted emissions on antenna ports	9 kHz .. 20 GHz	1.0 dB	--
Radiated emissions enclosure	150 kHz .. 30 MHz	5.0 dB	Magnetic field
	30 MHz .. 1 GHz	4.2 dB	E-Field
	1 GHz .. 20 GHz	3.17 dB	Substitution method
Occupied bandwidth	9 kHz .. 4 GHz	0.1272 ppm (Delta Marker )	Frequency error
		1.0 dB	Power
Emission bandwidth	9 kHz .. 4 GHz	0.1272 ppm (Delta Marker)	Frequency error
		1.0 dB	Power
Frequency stability	9 kHz .. 20 GHz	0.0636 ppm	--
Conducted emissions on AC-mains port (U <sub>CISPR</sub> )	9 kHz .. 150 kHz	4.0 dB	--
	150 kHz .. 30 MHz	3.6 dB	--

**Table: measurement uncertainties, valid for conducted/radiated measurements**

#### 5. Abbreviations used in this report

The abbreviations	
ANSI	American National Standards Institute
AV , AVG, CAV	Average detector
EIRP	Equivalent isotropically radiated power, determined within a separate measurement
EGPRS	Enhanced General Packet Radio Service
EUT	Equipment Under Test
FCC	Federal Communications Commission, USA
IC	Industry Canada
n.a.	not applicable
Op-Mode	Operating mode of the equipment
PK	Peak
RBW	resolution bandwidth
RF	Radio frequency
RSS	Radio Standards Specification, Dokuments from Industry Canada
Rx	Receiver
TCH	Traffic channel
Tx	Transmitter
QP	Quasi peak detector
VBW	Video bandwidth
ERP	Effective radiated power



## 6. Accreditation details of CETECOM’s laboratories and test sites

Ref.-No.	Accreditation Certificate	Valid for laboratory area or test site	Accreditation Body
-	D-PL-12047-01-01	All laboratories and test sites of CETECOM GmbH, Essen	DAkkS, Deutsche Akkreditierungsstelle GmbH
337 487 558 348 348	736496	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measur.	FCC, Federal Communications Commission Laboratory Division, USA (MRA US-EU 0003)
337 487 550 558	3462D-1 3462D-2 3462D-2 3462D-3	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR)	IC, Industry Canada Certification and Engineering Bureau
487 550 348 348	R-2666 G-301 C-2914 T-1967	Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measur.	VCCI, Voluntary Control Council for Interference by Information Technology Equipment, Japan
OATS = Open Area Test Site, SAR = Semi Anechoic Room, FAR = Fully Anechoic Room			

## 7. Versions of test reports (change history)

Version	Applied changes	Date of release
--	Initial release	2015-03-19
--	--	--
--	--	--

## 8. Instruments and Ancillary

### 8.1. Used equipment “CTC”

The “Ref.-No” in the left column of the following tables allows the clear identification of the laboratory equipment.

#### 8.1.1. Test software and firmware of equipment

Ref.-No.	Equipment	Type	Serial-No.	Version of Firmware or Software during the test
001	EMI Test Receiver	ESS	825132/017	Firm.= 1.21 , OTP=2.0, GRA=2.0
012	Signal Generator (EMS-cond.)	SMY 01	839069/027	Firm.= V 2.02
013	Power Meter (EMS cond.)	NRVD	839111/003	Firm.= V 1.51
017	Digital Radiocommunication Tester	CMD 60 M	844365/014	Firmware = V 3.52 .22.01.99, DECT = D2.87 13.01.99
053	Audio Analyzer	UPA3	860612/022	Firm. V 4.3
119	RT Harmonics Analyzer dig. Flickermeter	B10	G60547	Firm.= V 3.1DHG
140	Signal Generator	SMHU	831314/006	Firm.= 3.21
261	Thermal Power Sensor	NRV-Z55	825083/0008	EPROM-Datum 02.12.04, SE EE 1 B
262	Power Meter	NRV-S	825770/0010	Firm.= 2.6
263	Signal Generator	SMP 04	826190/0007	Firm.=3.21
264	Spectrum Analyzer	FSEK 30	826939/005	Bios=2.1, Analyzer= 3.20
295	Racal Digital Radio Test Set	6103	1572	UNIT Firmware= 4.04, SW-Main=4.04, SW-BBP=1.04, SW-DSP=1.02, Hardboot=1.02, Softboot=2.02
298	Univ. Radio Communication Tester	CMU 200	832221/091	R&S Test Firmware =3.53 /3.54 (current Testsoftw. f. all band used
323	Digital Radiocommunication Tester	CMD 55	825878/0034	Firm.= 3.52 .22.01.99
331	Climatic Test Chamber -40/+80 Grad	HC 4055	43146	TSI 1.53
335	CTC-EMS-Conducted	System EMS Conducted	-	EMC 32 V 8.52
340	Digital Radiocommunication Tester	CMD 55	849709/037	Firm.= 3.52 .22.01.99
355	Power Meter	URV 5	891310/027	Firm.= 1.31
365	10V Insertion Unit 50 Ohm	URV5-Z2	100880	Eprom Data = 31.03.08
366	Ultra Compact Simulator	UCS 500 M4	V0531100594	Firm. UCS 500=001925/3.06a02, rc=ISMIEC 4.10
371	Bluetooth Tester	CBT32	100153	CBT V5.30+ SW-Option K55, K57
377	EMI Test Receiver	ESCS 30	100160	Firm.= 2.30, OTP= 02.01, GRA= 02.36
378	Broadband RF Field Monitor	RadiSense III	03D00013SNO-08	Firm.= V.03D13
383	Signal Generator	SME 03	842 828 /034	Firm.= 4.61
389	Digital Multimeter	Keithley 2000	0583926	Firm. = A13 (Mainboard) A02 (Display)
392	Radio Communication Tester	MT8820A	6K00000788	Firm.= 4.50 #005, IPL=4.01#001,OS=4.02#001, GSM=4.41#013, W-CDMA= 4.54#004, scenario= 4.52#002
436	Univ. Radio Communication Tester	CMU 200	103083	R&S Test Firmware Base=5.14, Mess-Software= GSM:5.14 WCDMA:5.14 (current Testsoftw. F. all band
441	CTC-SAR-EMI Cable Loss	System EMI field (SAR)	-	EMC 32 Version 8.52
442	CTC-SAR-EMS	System EMS field (SAR)	-	EMC 32 Version 8.40
443	CTC-FAR-EMI-RSE	System CTC-FAR-EMI-RSE	-	Spuri 7.2.5 or EMC 32 Ver. 8.53
444	CTC-FAR-EMS field	System-EMS-Field (FAR)	-	EMC 32 Version 8.40
460	Univ. Radio Communication Tester	CMU 200	108901	R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw.,f. all band to be used,
489	EMI Test Receiver	ESU40	1000-30	Firmware=4.43 SP3, Bios=V5.1-16-3, Spec. =01.00
491	ESD Simulator dito	ESD dito	dito307022	V 2.30
524	Voltage Drop Simulator	VDS 200	0196-16	Software Nr: 000037 Version V4.20a01
526	Burst Generator	EFT 200 A	0496-06	Software Nr. 000034 Version V2.32
527	Micro Pulse Generator	MPG 200 B	0496-05	Software-Nr. 000030 Version V2.43
528	Load Dump Simulator	LD 200B	0496-06	Software-Nr. 000031 Version V2.35a01
546	Univ. Radio Communication Tester	CMU 200	106436	R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw.,f. all band to be used
547	Univ. Radio Communication Tester	CMU 200	835390/014	R&S Test Firmware Base=V5.1403 (current Testsoftw., f. all band used, GSM = 5.14 WCDMA: = 5.14
584	Spectrum Analyzer	FSU 8	100248	2.82_SP3
597	Univ. Radio Communication Tester	CMU 200	100347	R&S Test Firmware Base=5.01, GSM=5.02 WCDMA= not installed, Mainboard= µP1=V.850
598	Spectrum Analyzer	FSEM 30 (Reserve)	831259/013	Firmware Bios 3.40 , Analyzer 3.40 Sp 2
620	EMI Test Receiver	ESU 26	100362	4.43_SP3
642	Wideband Radio Communication Tester	CMW 500	126089	Setup V03.26, Test programm component V03.02.20
692	Bluetooth Tester	CBT 32	100236	CBT V 5.40, FW: V.2.41 (FPGA Digital, V. 3.09 FPGA RF)

#### 8.1.2. Single instruments and test systems

Ref.-No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
001	EMI Test Receiver	ESS	825132/017	Rohde & Schwarz	12 M	-	31.03.2015
005	AC - LISN (50 Ohm/50µH, test site 1)	ESH2-Z5	861741/005	Rohde & Schwarz	12 M	-	31.03.2015
007	Single-Line V-Network (50 Ohm/5µH)	ESH3-Z6	892563/002	Rohde & Schwarz	12 M	-	31.03.2015
009	Power Meter (EMS-radiated)	NRV	863056/017	Rohde & Schwarz	24 M	-	31.03.2015
016	Line Impedance Simulating Network	Op. 24-D	B6366	Spitzenberger+Spies	36 M	-	31.03.2016
021	Loop Antenna (H-Field)	6502	9206-2770	EMCO	36 M	-	31.03.2015
030	Loop Antenna (H-field)	HFH-Z2	879604/026	Rohde & Schwarz	36 M	-	31.03.2015
033	RF-current probe (100kHz-30MHz)	ESH2-Z1	879581/18	Rohde & Schwarz	24 M	-	31.03.2015
057	relay-switch-unit (EMS system)	RSU	494440/002	Rohde & Schwarz	pre-m	1a	
060	power amplifier (DC-2kHz)	PAS 5000	B6363	Spitzenberger+Spies	-	3	
066	notch filter (WCDMA; FDD1)	WRCT 1900/2200-5/40-10EEK	5	Wainwright GmbH	12 M	1g	30.06.2014
086	DC - power supply, 0 -10 A	LNG 50-10	-	Heinzinger Electronic	pre-m	2	
087	DC - power supply, 0 -5 A	EA-3013 S	-	Elektro Automatik	pre-m	2	
090	Helmholtz coil: 2x10 coils in series	Helmholtz coil: 2x10 coils in	-	RWTÜV	12 M	4	31.03.2015
091	USB-LWL-Converter	OLS-1	007/2006	Ing. Büro Scheiba	-	4	
099	passive voltage probe	ESH2-Z3	299.7810.52	Rohde & Schwarz	36 M	-	31.03.2015
100	passive voltage probe	Probe TK 9416	without	Schwarzbeck	36 M	-	31.03.2015
110	USB-LWL-Converter	OLS-1	-	Ing. Büro Scheiba	-	4	
119	RT Harmonics Analyzer dig. Flickermeter	B10	G60547	BOCONSULT	36 M	-	31.03.2016
136	adjustable dipole antenna (Dipole 1)	3121C-DB4	9105-0697	EMCO	36 M	-	31.03.2015
140	Signal Generator	SMHU	831314/006	Rohde & Schwarz	24 M	-	31.03.2016
248	attenuator	SMA 6dB 2W	-	Radiall	pre-m	2	
249	attenuator	SMA 10dB 10W	-	Radiall	pre-m	2	
252	attenuator	N 6dB 12W	-	Radiall	pre-m	2	
256	attenuator	SMA 3dB 2W	-	Radiall	pre-m	2	
257	hybrid	4031C	04491	Narda	pre-m	2	
260	hybrid coupler	4032C	11342	Narda	pre-m	2	
261	Thermal Power Sensor	NRV-Z55	825083/0008	Rohde & Schwarz	24 M	-	31.03.2016
262	Power Meter	NRV-S	825770/0010	Rohde & Schwarz	24 M	-	31.03.2016
263	Signal Generator	SMP 04	826190/0007	Rohde & Schwarz	36 M	-	31.03.2016
264	Spectrum Analyzer	FSEK 30	826939/005	Rohde & Schwarz	12 M	-	31.03.2015
265	peak power sensor	NRV-Z33, Model 04	840414/009	Rohde & Schwarz	24 M	-	31.03.2016
266	Peak Power Sensor	NRV-Z31, Model 04	843383/016	Rohde & Schwarz	24 M	-	31.03.2016
267	notch filter GSM 850	WRCA 800/960-6EEK	9	Wainwright GmbH	pre-m	2	
270	termination	1418 N	BB6935	Weinschel	pre-m	2	
271	termination	1418 N	BE6384	Weinschel	pre-m	2	
272	attenuator (20 dB) 50 W	Model 47	BF6239	Weinschel	pre-m	2	
273	attenuator (10 dB) 100 W	Model 48	BF9229	Weinschel	pre-m	2	
274	attenuator (10 dB) 50 W	Model 47 (10 dB) 50 W	BG0321	Weinschel	pre-m	2	
275	DC-Block	Model 7003 (N)	C5129	Weinschel	pre-m	2	
276	DC-Block	Model 7006 (SMA)	C7061	Weinschel	pre-m	2	
279	power divider	1515 (SMA)	LH855	Weinschel	pre-m	2	
287	pre-amplifier 25MHz - 4GHz	AMF-2D-100M4G-35-10P	379418	Miteq	12 M	1c	30.06.2014
291	high pass filter GSM 850/900	WHJ 2200-4EE	14	Wainwright GmbH	12 M	1c	30.06.2014
298	Univ. Radio Communication Tester	CMU 200	832221/091	Rohde & Schwarz	pre-m	3	
300	AC LISN (50 Ohm/50µH, 1-phase)	ESH3-Z5	892 239/020	Rohde & Schwarz	12 M	-	31.03.2015
301	attenuator (20 dB) 50W, 18GHz	47-20-33	AW0272	Lucas Weinschel	pre-m	2	
302	horn antenna 40 GHz (Meas 1)	BBHA9170	155	Schwarzbeck	36 M	-	31.03.2017
303	horn antenna 40 GHz (Subst 1)	BBHA9170	156	Schwarzbeck	36 M	-	31.03.2017
331	Climatic Test Chamber -40/+80 Grad	HC 4055	43146	Heraeus Vötsch	24 M	-	30.11.2014
341	Digital Multimeter	Fluke 112	81650455	Fluke	24 M	-	31.03.2016
342	Digital Multimeter	Voltcraft M-4660A	IB 255466	Voltcraft	24 M	-	31.03.2015
347	laboratory site	radio lab.	-	-	-	5	
348	laboratory site	EMI conducted	-	-	-	5	
354	DC - Power Supply 40A	NGPE 40/40	448	Rohde & Schwarz	pre-m	2	
355	Power Meter	URV 5	891310/027	Rohde & Schwarz	24 M	-	31.03.2016
356	power sensor	NRV-Z1	882322/014	Rohde & Schwarz	24 M	-	31.03.2015
357	power sensor	NRV-Z1	861761/002	Rohde & Schwarz	24 M	-	31.03.2015
371	Bluetooth Tester	CBT32	100153	R&S	24 M	-	31.03.2016
373	Single-Line V-Network (50 Ohm/5µH)	ESH3-Z6	100535	Rohde & Schwarz	24 M	-	31.03.2016
376	Horn Antenna 6 GHz	BBHA9120 E	BBHA 9120 E 179	Schwarzbeck	12 M	-	31.03.2015
377	EMI Test Receiver	ESCS 30	100160	Rohde & Schwarz	12 M	-	31.03.2015
389	Digital Multimeter	Keithley 2000	0583926	Keithley	24 M	-	31.03.2015
392	Radio Communication Tester	MT8820A	6K0000788	Anritsu	12 M	-	31.03.2015
431	Model 7405	Near-Field Probe Set	9305-2457	EMCO	-	4	
436	Univ. Radio Communication Tester	CMU 200	103083	Rohde & Schwarz	12 M	-	31.03.2015
439	UltraLog-Antenna	HL 562	100248	Rohde & Schwarz	36 M	-	31.03.2017
441	CTC-SAR-EMI Cable Loss	System EMI field (SAR) Cable	-	CETECOM	12 M	5	31.10.2014
443	CTC-FAR-EMI-RSE	System CTC-FAR-EMI-RSE	-	ETS-Lindgren / CETECOM	12 M	5	15.07.2014
448	notch filter WCDMA_FDD II	WRCT 1850.0/2170.0-5/40-	5	Wainwright Instruments GmbH	12 M	1c	30.06.2014

Ref.-No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
449	notch filter WCDMA FDD V	WRCT 824.0/894.0-5/40-8SSK	1	Wainwright	12 M	1c	30.06.2014
454	Oscilloscope	HM 205-3	9210 P 29661	Hameg	-	4	
456	DC-Power supply 0-5 A	EA 3013 S	207810	Elektro Automatik	pre-m	2	
459	DC -Power supply 0-5 A , 0-32 V	EA-PS 2032-50	910722	Elektro Automatik	pre-m	2	
460	Univ. Radio Communication Tester	CMU 200	108901	Rohde & Schwarz	12 M	-	31.03.2015
463	Universal source	HP3245A	2831A03472	Agilent	-	4	
466	Digital Multimeter	Fluke 112	89210157	Fluke USA	24 M	-	31.03.2016
467	Digital Multimeter	Fluke 112	89680306	Fluke USA	36 M	-	31.03.2015
468	Digital Multimeter	Fluke 112	90090455	Fluke USA	36 M	-	31.03.2015
477	ReRadiating GPS-System	AS-47	-	Automotive Cons. Fink	-	3	
480	power meter (Fula)	NRVS	838392/031	Rohde & Schwarz	24 M	-	31.03.2015
482	filter matrix	Filter matrix SAR 1	-	CETECOM (Brl)	-	1d	
484	pre-amplifier 2,5 - 18 GHz	AMF-5D-02501800-25-10P	1244554	Miteq	12 M	-	30.06.2014
487	System CTC NSA-Verification SAR-EMI	System EMI field (SAR) NSA	-	ETS Lindgren / CETECOM	24 M	-	30.06.2015
489	EMI Test Receiver	ESU40	1000-30	Rohde & Schwarz	12 M	-	31.03.2015
502	band reject filter	WRCG 1709/1786-1699/1796-	SN 9	Wainwright	pre-m	2	
503	band reject filter	WRCG 824/849-814/859-	SN 5	Wainwright	pre-m	2	
512	notch filter GSM 850	WRCA 800/960-02/40-6EEK	SN 24	Wainwright	12 M	1c	30.06.2014
517	relais switch matrix	HF Relais Box Keithley	SE 04	Keithley	pre-m	2	
523	Digital Multimeter	L4411A	MY46000154	Agilent	24 M	-	31.03.2015
529	6 dB Broadband resistive power divider	Model 1515	LH 855	Weinschel	pre-m	2	
530	10 dB Broadband resistive power divider	R 416110000	LOT 9828	-	pre-m	2	
546	Univ. Radio Communication Tester	CMU 200	106436	R&S	12 M	-	12.02.2015
547	Univ. Radio Communication Tester	CMU 200	835390/014	Rohde & Schwarz	12 M	-	31.03.2015
548	Digital-Barometer	GBP 2300	without	Greisinger GmbH	36 M	-	30.06.2015
549	Log-Per-Antenna	HL025	1000060	Rohde & Schwarz	36/12 M	-	31.03.2015
552	high pass filter 2,8-18GHz	WHKX 2.8/18G-10SS	4	Wainwright	12 M	1c	30.06.2014
558	System CTC FAR S-VSWR	System CTC FAR S-VSWR	-	CTC	24 M	-	31.07.2015
574	Biconilog Hybrid Antenna	BTA-L	980026L	Frankonia	36/12 M	-	31.03.2016
584	Spectrum Analyzer	FSU 8	100248	Rohde & Schwarz	pre-m	-	
597	Univ. Radio Communication Tester	CMU 200	100347	Rohde & Schwarz	36 M	-	31.03.2016
598	Spectrum Analyzer	FSEM 30 (Reserve)	831259/013	Rohde & Schwarz	24 M	-	13.01.2015
600	power meter	NRVD (Reserve)	834501/018	Rohde & Schwarz	24 M	-	31.03.2015
601	medium-sensitivity diode sensor	NRV-Z5 (Reserve)	8435323/003	Rohde & Schwarz	24 M	-	31.03.2015
602	peak power sensor	NRV-Z32 (Reserve)	835080	Rohde & Schwarz	24 M	-	31.03.2015
611	DC power supply	E3632A	KR 75305854	Agilent	pre-m	2	
612	DC power supply	E3632A	MY 40001321	Agilent	pre-m	2	
613	Attenuator	R416120000 20dB 10W	Lot. 9828	Radiall	pre-m	2	
616	Digitalmultimeter	Fluke 177	88900339	Fluke	24 M	-	31.03.2016
617	Power Splitter/Combiner	ZFSC-2-2-S+	S F987001108	Mini Circuits	-	2	
618	Power Splitter/Combiner	50PD-634	600994	JFW Industries USA	-	2	
619	Power Splitter/Combiner	50PD-634	600995	JFW Industries, USA	-	3	
620	EMI Test Receiver	ESU 26	100362	Rohde-Schwarz	12 M	-	31.03.2015
621	Step Attenuator 0-139 dB	RSP	100017	Rohde & Schwarz	pre-m	2	
625	Generic Test Load USB	Generic Test Load USB	-	CETECOM	-	2	
627	data logger	OPUS 1	201.0999.9302.6.4.1.4 3	G. Lufft GmbH	24 M	-	30.05.2014
634	Spectrum Analyzer	FSM (HF-Unit)	826188/010	Rohde & Schwarz	pre-m	2	
636	Thermal Imaging camera	Ti32	Ti32-12060213	Fluke Corporation	24 M	-	31.07.2014
637	High Speed HDMI with Ethernet 1m	HDMI cable with Ethernet 1m	-	KogiLink	-	2	
638	HDMI Kabel with Ethernet 1,5 m flach	HDMI cable with Ethernet	-	Reichelt	-	2	
640	HDMI cable 2m rund	HDMI cable 2m rund	-	Reichelt	-	2	
641	HDMI cable with Ethernet	Certified HDMI cable with	-	PureLink	-	2	
642	Wideband Radio Communication Tester	CMW 500	126089	Rohde&Schwarz	12 M	-	31.03.2015
644	Amplifierer	ZX60-2534M+	SN865701299	Mini-Circuits	-	-	
670	Univ. Radio Communication Tester	CMU 200	106833	Rohde & Schwarz	12 M	-	31.03.2015
671	DC-power supply 0-5 A	EA-3013S	-	Elektro Automatik	pre-m	2	
678	Power Meter	NRP	101638	Rohde&Schwarz	pre-m	-	
683	Spectrum Analyzer	FSU 26	200571	Rohde & Schwarz	12 M	-	26.11.2014
686	Field Analyzer	EHP-200A	160WX30702	Narda Safety Test Solutions	24 M	-	18.07.2015
687	Signal Generator	SMF 100A	102073	Rohde&Schwarz	12 M	-	27.11.2014
688	Pre Amp	JS-18004000-40-8P	1750117	Miteq	pre-m	-	
692	Bluetooth Tester	CBT 32	100236	Rohde & Schwarz	12 M	-	31.03.2015
693	TS8997	CTC-Radio Lab 1_TS8997	-	Rohde&Schwarz	12 M	5	30.11.2014

Note / remarks		Calibrated during system calibration:
	1a	System CTC-SAR-EMS (Ref.-No. 442)
	1b	System-CTC-EMS-Conducted (Ref.-No. 335)
	1c	System CTC-FAR-EMI-RSE (Ref.-No . 443)
	1d	System CTC-SAR-EMI (Ref.-No . 441)
	1e	System CTC-OATS (EMI radiated) (Ref.-No. 337)
	1 f	System CTC-CTIA-OTA (Ref.-No . 420)
	1 g	System CTC-FAR-EMS (Ref.-No . 444)
	2	Calibration or equipment check immediately before measurement
	3	Regulatory maintained equipment for functional check or support purpose
	4	Ancillary equipment without calibration e.g. mechanical equipment or monitoring equipment
	5	Test System

Interval of calibration	12 M	12 month
	24 M	24 month
	36 M	36 month
	24/12 M	Calibration every 24 months, between this every 12 months internal validation
	36/12 M	Calibration every 36 months, between this every 12 months internal validation
	Pre-m	Check before starting the measurement
	-	Without calibration