

Appendix for the SAR Test Report

Dosimetric Assessment of the CEECOACH Bluetooth Device from peiker acustic GmbH & Co.KG. (FCC ID: QWYCEECOACH)

According to the FCC Requirements SAR Distribution Plots

March 26, 2015

IMST GmbH
Carl-Friedrich-Gauß-Str. 2 - 4
47475 Kamp-Lintfort
Germany

Customer
7layers AG
Borsigstrasse 11
40880 Ratingen
Germany

The test results only relate to the items tested.

This report shall not be reproduced except in full without the written approval of the testing laboratory.

1 SAR Distribution Plots

Test Lab: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhm front 0mm clip hs.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40;

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.97$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (8x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.397 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.3 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 0.671 W/kg

SAR(1 g) = 0.383 mW/g; SAR(10 g) = 0.213 mW/g

Maximum value of SAR (measured) = 0.419 mW/g




Fig. 1: SAR distribution for Bluetooth, channel 39, front side, headset and belt clip attached, gap = 0 mm

Test Lab: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhm back 0mm clip hs.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.97$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 23.07.2014

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (8x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.106 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.93 V/m; Power Drift = -0.079 dB

Peak SAR (extrapolated) = 0.165 W/kg

SAR(1 g) = 0.097 mW/g; SAR(10 g) = 0.057 mW/g

Maximum value of SAR (measured) = 0.105 mW/g




Fig. 2: SAR distribution for Bluetooth, channel 39, headset and belt clip attached, back side, gap = 0 mm

Test Lab: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhm bottom 0mm clip hs.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.97$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (6x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.122 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.51 V/m; Power Drift = -0.055 dB

Peak SAR (extrapolated) = 0.247 W/kg

SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.069 mW/g

Maximum value of SAR (measured) = 0.145 mW/g




Fig. 3: SAR distribution for Bluetooth, channel 39, headset and belt clip attached, bottom side, gap = 0 mm

Test Lab: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhm top 0mm clip hs.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.97$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (6x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.567 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.6 V/m; Power Drift = 0.164 dB

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.213 mW/g

Maximum value of SAR (measured) = 0.617 mW/g




Fig. 4: SAR distribution for Bluetooth, channel 39, headset and belt clip attached, top side, gap = 0 mm

Test Lab: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhm left 0mm clip hs.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.97$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (7x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.511 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.9 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.505 mW/g; SAR(10 g) = 0.231 mW/g

Maximum value of SAR (measured) = 0.573 mW/g




Fig. 5: SAR distribution for Bluetooth, channel 39, headset and belt clip attached, left side, gap = 0 mm

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhm right 0mm clip.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.97$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (7x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.383 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.5 V/m; Power Drift = -0.017 dB

Peak SAR (extrapolated) = 0.775 W/kg

SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.166 mW/g

Maximum value of SAR (measured) = 0.430 mW/g




Fig. 6: SAR distribution for Bluetooth, channel 39, belt clip attached, right side, gap = 0 mm

Test Lab: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhl top 0mm clip hs.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2402$ MHz; $\sigma = 1.91$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (6x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.429 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = 0.174 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.411 mW/g; SAR(10 g) = 0.171 mW/g

Maximum value of SAR (measured) = 0.486 mW/g




Fig. 7: SAR distribution for Bluetooth, channel 0, headset and belt clip attached, top side, gap = 0 mm

Test Lab: IMST GmbH, DASY Blue (I); File Name: [Ceecoach C40 bbhh top 0mm clip hs.da4](#)

DUT: Peiker; Type: Ceecoach; Serial: 00131E-271C40

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2480$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 53$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (6x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.470 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.420 mW/g; SAR(10 g) = 0.176 mW/g

Maximum value of SAR (measured) = 0.488 mW/g




Fig. 8: SAR distribution for Bluetooth, channel 78, headset and belt clip attached, top side, gap = 0 mm