

Hong Kong Standards and Testing Centre

No.: HM151178

Applicant: Toy Century Industrial Co., Ltd.

Unit 1010-1015, 10/F., Tower B,

New Mandarin Plaza,

No.14 Science Museum Road,

Tsim Sha Tsui, Kowloon, Hong Kong

Description of Samples: Model name: Radio Control Car, Simple Function

With Stop

Model no.: 6811 Brand name: N/A

FCC ID: QXATC27MHZPS

Date Samples Received: 2004-05-20

Date Tested: 2004-08-20

Investigation Requested: FCC Part 15 Subpart C

Conclusions: The submitted product <u>COMPLIED</u> with the

requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on

Section 2.2 in this Test Report.

Remarks: For additional models details, see page 5.

K C Lee, EMC for Chief Executive

DAR has accredited this laboratory in accordance with its terms of accreditation. This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre.



Hong Kong Standards and Testing Centre

No.: HM151178

CONTENT:

	Cover Content	Page 1 of 18 Page 2-3 of 18
<u>1.0</u>	General Details	
1.1	Test Laboratory	Page 4 of 18
1.2	Applicant Details Applicant HKSTC Code Number for Applicant Manufacturer	Page 4 of 18
1.3	Equipment Under Test [EUT] Description of EUT operation	Page 5 of 18
1.4	Date of Order	Page 5 of 18
1.5	Submitted Samples	Page 5 of 18
1.6	Test Duration	Page 5 of 18
1.7	Country of Origin	Page 5 of 18
1.8	Additional Information of EUT	Page 6 of 18
<u>2.0</u>	Technical Details	
2.1	Investigations Requested	Page 7 of 18
2.2	Test Standards and Results Summary	Page 7 of 18
<u>3.0</u>	Test Results	
3.1	Emission	Page 8-11 of 18
3.2	Bandwidth Measurement	Page 12-13 of 18



Hong Kong Standards and Testing Centre

Date: 2004-08-27 **TEST REPORT** Page 3 of 18

No.: HM151178

Appendix A

List of Measurement Equipment Page 14 of 18

Appendix B

Duty Cycle Correction During 100 msec Page 15-16 of 18

Appendix C

Photographs Page 17-18 of 18

香港新界大埔工業村大宏街 10 號



Hong Kong Standards and Testing Centre

No.: HM151178

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

Telephone: 852 2666 1888 Fax: 852 2664 4353

1.2 Applicant Details Applicant

Toy Century Ind. Co., Ltd. Unit 1010-1015, 10/F., Tower B, New Mandarin Plaza, No.14 Science Museum Road, Tsim Sha Tsui, Kowloon, Hong Kong

HKSTC Code Number for Applicant

TOC004

Manufacturer

Toy Century Ind. Co., Ltd. Unit 1010-1015, 10/F., Tower B, New Mandarin Plaza, No.14 Science Museum Road, Tsim Sha Tsui, Kowloon, Hong Kong



Hong Kong Standards and Testing Centre

No.: HM151178

1.3 Equipment Under Test [EUT] Description of Sample

Model Name: Radio Control Car, Simple Function With Stop

Manufacturer: Toy Century Industrial Co., Ltd.

Brand Name: N/A Model Number: 6811

Input Voltage: 9Vd.c ("6F22" size battery x 1)

Additional Model Number: 6812, 19529, 19536, 19547, 6682, 6683, 6684, 6688,

66881, 6689, 6690, 6695, 6697, 66984, 66986, 6705, 6800, 6801, 6804, 6805, 6811RC, 6883, 6989, 85928

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is a Toy Century Industrial Co., Ltd., Radio Control Car with Full Function. The transmitter is a 1 trigger transmitter. The EUT continues to transmit while button is being pressed, Modulation by IC. and type is pulse modulation.

1.4 Date of Order

2004-05-20

1.5 Submitted Sample(s):

8 Samples per model

1.6 Test Duration

2004-08-20

1.7 Country of Origin

China



Hong Kong Standards and Testing Centre

No.: HM151178

1.8 Additional Information of EUT

	Submitted	Not Available
User Manual		
Part List		5
Circuit Diagram		
Printed Circuit Board [PCB] Layout		
Block diagram	$\overline{\boxtimes}$	
FCC ID Label	\boxtimes	



香港標準及檢定中心 Hong Kong Standards and Testing Centre

No.: HM151178

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2003 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION									
Results Summary									
Test Condition	Test Requirement	Test Method	Class /	Te	est Resul				
			Severity	Pass	Failed	N/A			
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.227	ANSI C63.4:2003	N/A						
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2003	Class B						
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	Class B						

Note: N/A - Not Applicable



Hong Kong Standards and Testing Centre

Date: 2004-08-27 **TEST REPORT** Page 8 of 18

No.: HM151178

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions (30 – 1000MHz)


Test Requirement: FCC 47CFR 15.227
Test Method: ANSI C63.4:2003
Test Date: 2004-08-20
Mode of Operation: On mode

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

Test Setup:





Hong Kong Standards and Testing Centre

No.: HM151178

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.227]:

Frequency Range of	Field Strength of	Field Strength of
Fundamental	Fundamental Emission	Fundamental Emission
	[Peak]	[Average]
[MHz]	[μ V/m]	[μ V/m]
26.96-27.28	100,000	10,000

Results:

Field Strength of Fundamental Emissions Peak Value								
Frequency	Frequency Measured Correction Field Field Limit @3m E-Field							
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBµV/m	dBµV/m	dBµV/m	μV/m	μV/m			
27.15	53.30	21.9	75.2	5,754.4	100,000	Vertical		

	Field Strength of Fundamental Emissions									
	Average									
Frequency	Measured	Adjusted by	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Duty Cycle	Factor	Strength	Strength		Polarity			
MHz	dBµV/m	dB	dBµV/m	dBµV/m	μV/m	μV/m				
27.15	49.5	-3.8	21.9	71.4	3,715.4	10,000	Vertical			

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB



Hong Kong Standards and Testing Centre

No.: HM151178

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]		
30-88	100		
88-216	150		
216-960	200		
Above960	500		

The emission limits shown in the above table are based on measurement employing a CISPR quasipeak detector and above 1000MHz are based on measurements employing an average detector.

Results:

	Radiated Emissions								
	Quasi-Peak								
Frequency	Me	asured	Correction		Field		Field	Limit @3m	E-Field
	Lev	el @3m	Factor	Strength		Strength			Polarity
MHz	dE	3μV/m	dBµV/m	d	BµV/m		μV/m	μV/m	
54.29	/	14.1	10.1		24.2		16.2	150	Vertical
81.44	<	1.0	9.5	V	10.5	<	3.3	150	Horizontal
108.58	<	1.0	10.7	<	11.7	<	3.8	150	Horizontal
135.73	<	1.0	10.2	<	11.2	<	3.6	200	Horizontal
162.87	<	1.0	11.9	<	12.9	<	4.4	200	Horizontal
190.02	<	1.0	12.4	<	13.4	<	4.7	200	Horizontal
217.16	<	1.0	13.2	<	14.2	<	5.1	200	Horizontal
244.31	<	1.0	15.0	<	16.0	<	6.3	200	Horizontal
271.45	<	1.0	16.1	<	17.1	<	7.2	200	Horizontal

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB



Hong Kong Standards and Testing Centre

No.: HM151178

3.1.2 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC 47CFR 15.107 Class B

Test Method: ANSI C63.4:2003

Test Date: 2004-08-20

Mode of Operation: N/A

Test Method: N/A

The EUT is operated by a single source of internal battery power [located in the battery compartment], therefore power line conducted emission was deemed unnecessary.

香港新界大埔工業村大宏街 10 號



Hong Kong Standards and Testing Centre

No.: HM151178

3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.227

Test Method: ANSI C63.4:2003 (Section 13.1.7)

Test Date: 2004-08-20 Mode of Operation: On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.




Hong Kong Standards and Testing Centre

No.: HM151178

Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range	20dB Bandwidth	FCC Limits
[MHz]	[KHz]	[MHz]
27.145	62.7	within 26.96-27.28

20dB Bandwidth of Fundamental Emission





Hong Kong Standards and Testing Centre

No.: HM151178

Appendix A

List of Measurement Equipment

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	15/06/04
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	15/06/04
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	15/06/04
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	15/06/04
EM011	ATTENNUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	15/06/04
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	15/06/04
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	15/06/04
EM020	HORN ANTENNA	EMCO	3115	4032	15/06/04
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	04/08/00
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/11/02
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	13/01/04
EM145	EMI TEST RECEIVER	R&S	ESCS 30	830245/021	02/08/03
EM194	BICONILOG ANTENNA	EMCO	3142B	1795	21/10/03
EM195	ANTENNA POSITIONING MAST	EMCO	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	EMCO	2090	1662	N/A

Conducted Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	17/10/03
EM119	LISN	R&S	ESH3-Z5	0831.5518.52	01/10/02
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	СМ
EM142	PULES LIMITER	R&S	ESH3Z2	357.8810.52	07/07/03
EM181	EMI TEST RECEIVER	R&S	ESIB7	100072	06/01/04
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	17/10/03
EM197	LISN	EMCO	4825/2	1193	08/04/03

Remarks:

CM Corrective Maintenance
N/A Not Applicable or Not Available

TBD To Be Determined



Hong Kong Standards and Testing Centre

No.: HM151178

Appendix B


Duty Cycle Correction During 100msec


Each function key sends a different series of characters, but each packet period (30.937msec) never exceeds a series of 4 long (2.625msec) and 10 short (938µsec) pulses. Assuming any combination of short and long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered 4x2.625msec+ 10x938µsec per 30.937msec=64.2% duty cycle. Figure A through C show the characteristics of the pulse train for one of these functions.

Remarks:

Duty Cycle Correction = 20Log(0.642) =-3.8dB

The following figures [Figure A to Figure C] show the characteristics of the pulse train for one of these functions.







Hong Kong Standards and Testing Centre

No.: HM151178

Figure B [Long Pulse]





Figure C [Short Pulse]





Hong Kong Standards and Testing Centre

Date : 2004-08-27 **TEST REPORT** Page 17 of 18

No.: HM151178

Appendix C


Photographs of EUT

Front View of the product



Rear View of the product







Inner Circuit Bottom View





Hong Kong Standards and Testing Centre

Date : 2004-08-27 **TEST REPORT** Page 18 of 18

No.: HM151178

Photographs of EUT

Measurement of Radiated Emission Test Set Up



***** End of Test Report *****