

Report No. : AJ008847-001 Date : 2007 May 02

Application No. : LJ208624(0)

Applicant : Toy Century Industrial Co., Ltd

Room 15, 21/F, Tower North, 1 Science Museum Road, Tsim Sha Tsui East, Kowloon,

Hong Kong

Sample Description: One(1) submitted sample(s) stated to be 12" Radio Controlled Vehicle Full

<u>Functioned</u> of Model No. <u>89957</u>, <u>89967</u>, <u>89968</u>, <u>6830</u>, <u>6831</u>, <u>6832</u>, <u>6833</u>, <u>6834</u>, <u>6835</u>, <u>6836</u>, <u>6837</u>, <u>6838</u>, <u>6839</u>, <u>6840</u>, <u>6841</u>, <u>6842</u>, <u>6843</u>, <u>6844</u>, <u>6845</u>, <u>6846</u>, <u>6847</u>, <u>6848</u>, <u>6849</u>, <u>19563</u>, <u>19564</u>, <u>19565</u>, <u>19566</u>, <u>19567</u>, <u>19578</u>, <u>19579</u>, <u>19571</u>, <u>19572</u>, <u>19573</u>, <u>19574</u>, <u>19575</u>, <u>19576</u>, <u>19577</u>, <u>19578</u>, <u>19579</u>, <u>19580</u>, <u>19581</u>, <u>19583</u>, <u>89500</u>, <u>89501</u>, <u>89502</u>, <u>89503</u>, <u>89504</u>, <u>89505</u>, <u>89506</u>, <u>89507</u>, <u>89508</u>, <u>89509</u>, <u>89510</u>, <u>89511</u>, <u>89512</u>, <u>89513</u>, <u>89514</u>, <u>89515</u>, <u>89516</u>, <u>89517</u>,

89518, 89519, 89520

Radio Frequency : 49.860 MHz Transmitter
Rating : 1 x 7.2V rechargeable battery

No. of submitted sample: Three(3) piece(s) ***

Date Received : 2007 April 13

Test Period : 2007 April 16 – 2007 April 23

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)

ANSI C63.4 - 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart B.

For and on behalf of

CMA Industrial Development Foundation Limited

Authorized Signature : _

Danny Chui Deputy Manager - EL. Division

Page 1 of 11



Report No. : AJ008847-001 Date : 2007 May 02

Table of Contents

1	Gen	eral Information	3
_	1.1	General Description	
	1.2	Location of the test site	
	1.3	List of measuring equipment	
2	Desc	cription of the radiated emission test	
	2.1	Test Procedure	
	2.2	Test Result	
	2.3	Radiated Emission Measurement Data	7
3	Desc	cription of the Line-conducted Test	8
	3.1	Test Procedure	8
	3.2	Test Result	
	3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Phot	tograph	
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
	4.2	Photographs of the External and Internal Configurations of the EUT	
5	Supp	plementary document	10
	5.1	Bandwidth	
	5.2	Duty cycle	10
	5.3	Transmission time	
6	App	endices	11



Report No. : AJ008847-001 Date : 2007 May 02

1 General Information

1.1 General Description

The equipment under test (EUT) is a receiver for 12" Radio Controlled Vehicle Full Functioned. It operates at 49.860MHz and the oscillation of radio control is generated by a LRC circuit. The EUT is power by a 7.2V rechargeable battery. When received a forward, backward, turn left or turn right signal, it will go to corresponding direction.

The brief circuit description is listed as follows:

- Q1 and associated circuit act as a RF amplifier.
- IC1 and associated circuit act as a decoder.
- D1 and associated circuit act as a voltage regulator.
- Q4 ~ Q9 and associated circuit act as a motor driver for >M.
- Q2, Q3, Q10 ~ Q13 and associated circuit act as a motor driver for M<.



Report No. : AJ008847-001 Date : 2007 May 02

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AJ008847-001 Date : 2007 May 02

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCI	100152
Broadband Antenna	Schaffner	CBL6112B	2718



Report No. : AJ008847-001 Date : 2007 May 02

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to "cohere" the characteristic broadband emissions from the receiver.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

It was found that the EUT meet the FCC requirement.



Report No. : AJ008847-001 Date : 2007 May 02

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Frequency	Polarity	Reading at	Antenna and	Field	Limit at 3m	Margin
(MHz)	(H/V)	3m	Cable factor	Strength	(dBµV/m)	(dB)
		$(dB\mu V/m)$	(dB)	$(dB\mu V/m)$		
48.987	V	24.9	10.6	35.5	40.0	-4.5
49.280	V	25.8	10.6	36.4	40.0	-3.6
49.563	V	26.6	10.6	37.2	40.0	-2.8
50.157	V	27.5	8.4	35.9	40.0	-4.1
50.441	V	25.8	8.4	34.2	40.0	-5.8
52.490	V	23.6	8.4	32.0	40.0	-8.0
283.275	Н	17.6	13.9	31.5	46.0	-14.5
291.866	Н	16.4	13.9	30.3	46.0	-15.7
297.408	Н	15.0	13.9	28.9	46.0	-17.1
328.996	Н	14.5	14.9	29.4	46.0	-16.6



Report No. : AJ008847-001 Date : 2007 May 02

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



Report No. : AJ008847-001 Date : 2007 May 02

- 4 Photograph
- 4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



Report No. : AJ008847-001 Date : 2007 May 02

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

Not Applicable

5.2 Duty cycle

Not Applicable

5.3 Transmission time

Not Applicable



Report No. : AJ008847-001 Date : 2007 May 02

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label/Location	1	page
A5.	Block Diagram	1	page
A6.	Schematics Diagram	1	page
A7.	User Manual	1	page
A8.	Operation Description	1	page

***** End of Report *****