

RF Exposure Report

Report No.: SA170609C20

FCC ID: QXO-AP3915E

Test Model: AP3915e

Series Model: AP7632 (refer to item 3.1 for more details)

Received Date: Jun. 09, 2017

Test Date: Jun. 09 ~ Aug. 09, 2017

Issued Date: Aug. 09, 2017

Applicant: Extreme Networks, Inc.

Address: 6480 VIA DEL ORO SAN JOSE CA 95119 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA170609C20	Original release.	Aug. 09, 2017

1 Certificate of Conformity

Product: Wireless 802.11 a/ac+b/g/n Indoor Access Point

Brand: Extreme Networks

Test Model: AP3915e

Series Model: AP7632 (refer to item 3.1 for more details)

Sample Status: Engineering sample

Applicant: Extreme Networks, Inc.

Test Date: Jun. 09 ~ Aug. 09, 2017

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Aug. 09, 2017
Celine Chou / Specialist

Approved by : Ken Liu , **Date:** Aug. 09, 2017
Ken Liu / Senior Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 31 cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Function	Frequency Band (MHz)	Mode	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	ML-2452-APA2-01, ML-2452-APA2-02 and ML-2452-HPA5-036 Ant. (ML-2452-APA2-01 Ant. with the maximum gain was chosen for evaluate)						
	2412-2462	CDD	25.41	6.18	31	0.119	1
		Beamforming	22.25	6.18	31	0.058	1
	ML-2452-APA2-01, ML-2452-APA2-02 and ML-2452-HPA5-036 Ant. (ML-2452-APA2-02 Ant. with the maximum gain was chosen for evaluate)						
	5180-5240	CDD	25.50	8.01	31	0.186	1
		Beamforming	22.49	8.01	31	0.093	1
	5745-5825	CDD	25.83	8.01	31	0.200	1
		Beamforming	22.82	8.01	31	0.100	1
	ML-2452-HPAG4A6-01 Ant.						
	2412-2462	CDD	25.29	7.01	31	0.141	1
		Beamforming	22.24	7.01	31	0.070	1
	5180-5240	CDD	25.73	10.31	31	0.333	1
		Beamforming	22.72	10.31	31	0.166	1
	5745-5825	CDD	25.70	10.31	31	0.330	1
		Beamforming	22.69	10.31	31	0.165	1
	ML-2452-HPA6M4-S36 Ant.						
	2412-2462	CDD	25.29	9.01	31	0.223	1
		Beamforming	22.24	9.01	31	0.110	1
	5180-5240	CDD	25.73	9.01	31	0.247	1
		Beamforming	22.72	9.01	31	0.123	1
	5745-5825	CDD	25.70	9.01	31	0.245	1
		Beamforming	22.69	9.01	31	0.122	1
	ML-2452-PNL9M3-036 Ant.						
	2412-2462	CDD	24.86	11.00	31	0.319	1
		Beamforming	24.72	11.00	31	0.309	1
	5180-5240	CDD	25.06	10.70	31	0.312	1
		Beamforming	25.06	10.70	31	0.312	1
	5745-5825	CDD	25.25	10.70	31	0.326	1
Beamforming		25.25	10.70	31	0.326	1	

Function	Frequency Band (MHz)	Mode	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	ML-2452-PNL6M3-N36, ML-2452-PNA5-01R and ML-2452-PNA7-01R Ant. (ML-2452-PNA7-01R Ant. with the maximum gain was chosen for evaluate)						
	2412-2462	CDD	25.20	10.81	31	0.330	1
		Beamforming	22.08	10.81	31	0.161	1
	5180-5240	CDD	23.90	13.71	31	0.478	1
		Beamforming	20.89	13.71	31	0.239	1
	5745-5825	CDD	25.23	13.71	31	0.649	1
		Beamforming	22.12	13.71	31	0.317	1
	ML-2452-PTA2M2-036 and ML-2452-PTA4M4-036 Ant. (ML-2452-PTA4M4-036 Ant. with the maximum gain was chosen for evaluate)						
	2412-2462	CDD	25.57	8.01	31	0.189	1
		Beamforming	22.29	8.01	31	0.089	1
	5180-5240	CDD	25.74	9.61	31	0.284	1
		Beamforming	22.73	9.61	31	0.142	1
	5745-5825	CDD	25.82	9.61	31	0.289	1
		Beamforming	22.81	9.61	31	0.145	1
BT LE	ML-2499-HPA8-01 and ML-2452-PNA7-01R Ant. (ML-2499-HPA8-01 Ant. with the maximum gain was chosen for evaluate)						
	2402-2480	-	1.00	8.00	31	0.001	1
Zigbee	ML-2499-HPA8-01 and ML-2452-PNA7-01R Ant. (ML-2499-HPA8-01 Ant. with the maximum gain was chosen for evaluate)						
	2405-2480	-	2.10	8.00	31	0.001	1

Note:

2.4GHz:

ML-2452-APA2-01 Ant. directional gain = $3.17\text{dBi} + 10\log(2) = 6.18\text{dBi}$.

ML-2452-HPAG4A6-01 Ant. directional gain = $4\text{dBi} + 10\log(2) = 7.01\text{dBi}$.

ML-2452-HPA6M4-S36 Ant. directional gain = $6\text{dBi} + 10\log(2) = 9.01\text{dBi}$.

ML-2452-PNL9M3-036 Ant. gain = 11dBi

ML-2452-PNA7-01R Ant. directional gain = $7.8\text{dBi} + 10\log(2) = 10.81\text{dBi}$.

ML-2452-PTA4M4-036 Ant. directional gain = $5\text{dBi} + 10\log(2) = 8.01\text{dBi}$.

5GHz:

ML-2452-APA2-02 Ant. directional gain = $5\text{dBi} + 10\log(2) = 8.01\text{dBi}$.

ML-2452-HPAG4A6-01 Ant. directional gain = $7.3\text{dBi} + 10\log(2) = 10.31\text{dBi}$.

ML-2452-HPA6M4-S36 Ant. directional gain = $6\text{dBi} + 10\log(2) = 9.01\text{dBi}$.

ML-2452-PNL9M3-036 Ant. gain = 10.7dBi

ML-2452-PNA7-01R Ant. directional gain = $10.7\text{dBi} + 10\log(2) = 13.71\text{dBi}$.

ML-2452-PTA4M4-036 Ant. directional gain = $6.6\text{dBi} + 10\log(2) = 9.61\text{dBi}$

BT LE & Zigbee:

ML-2499-HPA8-01 Ant. gain = 8dBi.

Frequency Band	Max Power (dBm)			Total Power (dBm)	Power Limit (dBm)
	WLAN	BT LE	Zigbee		
2.4GHz	25.57	1.00	-	25.59	30
2.4GHz	25.57	-	2.10	25.59	30

Conclusion:

2.4GHz & 5GHz & BT LE or 2.4GHz & 5GHz & Zigbee technology can transmit at same time.
 BT LE and Zigbee cannot transmit simultaneously.

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

WLAN: ML-2452-APA2-01, ML-2452-APA2-02 & BT LE / Zigbee: ML-2499-HPA8-01 Ant.

1. WALN 2.4GHz + WALN 5GHz + BT LE = 0.119 + 0.200+ 0.001 = 0.320
2. WALN 2.4GHz + WALN 5GHz + Zigbee = 0.119 + 0.200+ 0.001 = 0.320

WLAN: ML-2452-HPAG4A6-01 & BT LE / Zigbee: ML-2499-HPA8-01 Ant.

1. WALN 2.4GHz + WALN 5GHz + BT LE = 0.141 + 0.333 + 0.001 = 0.475
2. WALN 2.4GHz + WALN 5GHz + Zigbee = 0.141 + 0.333 + 0.001 = 0.475

WLAN: ML-2452-HPA6M4-S36 & BT LE / Zigbee: ML-2499-HPA8-01 Ant.

1. WALN 2.4GHz + WALN 5GHz + BT LE = 0.223 + 0.247 + 0.001 = 0.471
2. WALN 2.4GHz + WALN 5GHz + Zigbee = 0.223 + 0.247 + 0.001 = 0.471

WLAN: ML-2452-PNL9M3-036 & BT LE / Zigbee: ML-2499-HPA8-01 Ant.

1. WALN 2.4GHz + WALN 5GHz + BT LE = 0.319 + 0.326 + 0.001 = 0.646
2. WALN 2.4GHz + WALN 5GHz + Zigbee = 0.319 + 0.326 + 0.001 = 0.646

WLAN: ML-2452-PNA7-01R & BT LE / Zigbee: ML-2499-HPA8-01 Ant.

1. WALN 2.4GHz + WALN 5GHz + BT LE = 0.330 + 0.649 + 0.001 = 0.980
2. WALN 2.4GHz + WALN 5GHz + Zigbee = 0.330 + 0.649 + 0.001 = 0.980

ML-2452-PTA4M4-036 Ant. & BT LE / Zigbee: ML-2499-HPA8-01 Ant.

1. WALN 2.4GHz + WALN 5GHz + BT LE = 0.189 + 0.289 + 0.001 = 0.479
2. WALN 2.4GHz + WALN 5GHz + Zigbee = 0.189 + 0.289 + 0.001 = 0.479

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---