

FCC Test Report

Equipment : Wireless 802.11 a/ac+b/g/n PCBA module
Brand Name : Extreme Networks
Model No. : AP3917k/AP7662k
FCC ID : QXO-AP3917K
Standard : 47 CFR FCC Part 15.247
Frequency : 2400 MHz – 2483.5 MHz
Function : Point-to-multipoint; Point-to-point
Applicant : Extreme Networks, Inc.
6480 Via Del Oro San Jose CA 95119 United States
Of America
Manufacturer : Senao Networks, Inc.
3F, No. 529, Chung Cheng Rd. Hsintien Taipei Taiwan

The product sample received on Sep. 21, 2017 and completely tested on Oct. 11, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Phoenix Chen / Assistant Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Testing Applied Standards	6
1.3	Testing Location Information	6
1.4	Measurement Uncertainty	6
2	TEST CONFIGURATION OF EUT.....	7
2.1	Test Condition	7
2.2	Test Channel Mode	7
2.3	The Worst Case Measurement Configuration.....	8
2.4	Support Equipment.....	9
2.5	Test Setup Diagram	10
3	TRANSMITTER TEST RESULT	11
3.1	AC Power-line Conducted Emissions	11
3.2	DTS Bandwidth.....	12
3.3	Maximum Conducted Output Power	13
3.4	Power Spectral Density	15
3.5	Emissions in Non-restricted Frequency Bands	16
3.6	Emissions in Restricted Frequency Bands.....	17
4	TEST EQUIPMENT AND CALIBRATION DATA	21
APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS		
APPENDIX B. TEST RESULTS OF DTS BANDWIDTH		
APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER		
APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY		
APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS		
APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS		
APPENDIX G. TEST PHOTOS		
PHOTOGRAPHS OF EUT V01		



Summary of Test Result

Conformance Test Specifications				
Report Clause	Ref. Std. Clause	Description	Limit	Result
1.1.2	15.203	Antenna Requirement	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	FCC 15.207	Complied
3.2	15.247(a)	DTS Bandwidth	≥500kHz	Complied
3.3	15.247(b)	Maximum Conducted Output Power	Power [dBm]:30	Complied
3.4	15.247(e)	Power Spectral Density	PSD [dBm/3kHz]:8	Complied
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	Non-Restricted Bands: >30 dBc	Complied
3.6	15.247(d)	Emissions in Restricted Frequency Bands	Restricted Bands: FCC 15.209	Complied



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Note:

- ◆ Bluetooth LE uses a GFSK (1Mbps) modulation for DSSS.
- ◆ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	1	-	-	Omini	I-PEX	7.5

1.1.3 EUT Information

Operational Condition	
EUT Power Type	From PoE
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device)
	Combined Equipment - Brand Name / Model No.: ...
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems)
	Host System - Brand Name / Model No.: ...
<input type="checkbox"/>	Other:

1.1.4 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
BT-LE(1Mbps)	0.641	1.931	401.563u	3k

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2013
- ◆ KDB 558074 D01 v04

1.3 Testing Location Information

Testing Location		
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456 FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.		
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) TEL : 886-3-656-9065 FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.		

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-HY	Ryan Hsiao	24.6°C / 65%	07/Oct/2017
Radiated	03CH02-HY	Lynus Tsai	23.3°C / 57%	29/Sep/2017
AC Conduction	CO04-HY	Eric lee	24.8°C / 61.2%	11/Oct/2017

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	2.1 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	2.6 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	2.9 dB	Confidence levels of 95%
Conducted Emission	1.3 dB	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Condition

RF Conducted	Abbreviation	Remark
TnomVnom	Tnom	20°C
-	Vnom	120V

2.2 Test Channel Mode




Test Software	Dos
---------------	-----

Mode	Power Setting
BT-LE(1Mbps)	-
2402MHz	default
2440MHz	default
2480MHz	default

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	PoE mode

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emissions in Restricted Frequency Bands		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Operating Mode < 1GHz	CTX		
1	PoE mode		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT		V	

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis
Operating Mode	CTX
1	Bluetooth+WLAN 2.4GHz+WLAN 5GHz
2	Zigbee+WLAN 2.4GHz+WLAN 5GHz
3	Bluetooth+WLAN 2.4GHz+4.9G
4	Zigbee+WLAN 2.4GHz+4.9G
Refer to Sporton Test Report No.: FA780809 for Co-location RF Exposure Evaluation.	



2.4 Support Equipment

Support Equipment – RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5410	DoC
2	Adapter for Notebook	DELL	HA65NM130	DoC
3	PoE	EnGenius	EPA5006GP	-
4	AC Source	G.W	APS-9102	-

Note: Support equipment No.3 was provided by customer.



Support Equipment – Radiated Emission				
No.	Equipment	Brand Name	Model Name	FCC ID
1	PoE	EnGenius	EPA5006GP	-

Note: Support equipment No.1 was provided by customer.

Support Equipment – AC Conduction				
No.	Equipment	Brand Name	Model Name	FCC ID
1	PoE	EnGenius	EPA5006GP	-

Note: Support equipment No.1 was provided by customer.

2.5 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as ANSI C63.10-2013, clause 6.2 foray power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
<ul style="list-style-type: none"> ▪ 6 dB bandwidth \geq 500 kHz. 	


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> ▪ For the emission bandwidth shall be measured using one of the options below: 	
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	<ul style="list-style-type: none"> ▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	<ul style="list-style-type: none"> ▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	<ul style="list-style-type: none"> ▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> ▪ Smart antenna system (SAS):
	<ul style="list-style-type: none"> - Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dBm
e.i.r.p. Power Limit:	
	<ul style="list-style-type: none"> ▪ 2400-2483.5 MHz Band
	<ul style="list-style-type: none"> ▪ Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
	<ul style="list-style-type: none"> ▪ Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
	<ul style="list-style-type: none"> ▪ Smart antenna system (SAS)
	<ul style="list-style-type: none"> - Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<ul style="list-style-type: none"> - Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
<p>P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.</p>	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> Maximum Peak Conducted Output Power 	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.1 Option 1 (RBW ≥ EBW method).
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.2 Option 2 (integrated band power method)
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.3 Option 3 (peak power meter for VBW ≥ DTS BW)
<ul style="list-style-type: none"> Maximum Average Conducted Output Power 	
Duty cycle ≥ 98%	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).
Duty cycle < 98%	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)
RF power meter and average over on/off periods with duty factor or gated trigger	
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 9.2.3.1 Method AVGPM (using an RF average power meter).
<ul style="list-style-type: none"> For conducted measurement. 	
<ul style="list-style-type: none"> If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. 	
<ul style="list-style-type: none"> If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$ 	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<ul style="list-style-type: none"> Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
	<ul style="list-style-type: none"> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz; Detector=peak).
	<ul style="list-style-type: none"> For conducted measurement.
	<ul style="list-style-type: none"> If The EUT supports multiple transmit chains using options given below:
	<ul style="list-style-type: none"> Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as KDB 558074, clause 11 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E



3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> ▪ The average emission levels shall be measured in [duty cycle \geq 98 or duty factor]. 	
<ul style="list-style-type: none"> ▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band. 	
<ul style="list-style-type: none"> ▪ For the transmitter unwanted emissions shall be measured using following options below: 	
<ul style="list-style-type: none"> ▪ Refer as KDB 558074, clause 12 for unwanted emissions into restricted bands. 	
	<ul style="list-style-type: none"> <input checked="" type="checkbox"/> Refer as KDB 558074, clause 12.2.5.3 (ANSI C63.10, clause 4.1.4.2.3), Reduced VBW\geq1/T.
	<ul style="list-style-type: none"> <input checked="" type="checkbox"/> Refer as KDB 558074, clause 12.2.4 measurement procedure peak limit.
<ul style="list-style-type: none"> ▪ For the transmitter band-edge emissions shall be measured using following options below: 	
<ul style="list-style-type: none"> ▪ Refer as KDB 558074 clause 13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below. 	
<ul style="list-style-type: none"> ▪ Refer as KDB 558074, clause 13.2 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements. 	
<ul style="list-style-type: none"> ▪ Refer as KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz). 	
<ul style="list-style-type: none"> ▪ For conducted and cabinet radiation measurement, refer as KDB 558074, clause 12.2.2. 	
<ul style="list-style-type: none"> ▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB 	
<ul style="list-style-type: none"> ▪ For KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred. 	

3.6.4 Test Setup





3.6.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.6.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument for AC Conduction

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
EMC Receiver	R&S	ESR3	102052	9KHz ~ 3.6GHz	29/Apr/2017	28/Apr/2018
LISN	R&S	ENV216	101295	9kHz ~ 30MHz	15/Nov/2016	14/Nov/2017
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	24/Oct/2016	23/Oct/2017
AC POWER	APC	AFC-11005G	F310050055	47Hz~63Hz 5~300V	NCR	NCR
Impuls Begrenzer Pulse Limiter	R&S	ESH3-Z2	100921	10 kHz~30 MHz	21/Oct/2016	20/Oct/2017

NCR : Non-Calibration Require

Instrument for Radiated Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSP40	100593	9KHz - 40GHz	26/Oct/2016	25/Oct/2017
3m Semi Anechoic	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz-1GHz	21/Oct/2016	20/Oct/2017
3m Semi Anechoic	SIDT FRANKONIA	SAC-3M	03CH02-HY	1GHz ~ 18GHz	12/Dec/2016	11/Dec/2017
Amplifier	Agilent	8447D	2944A11149	100KHz-1.3GHz	29/Jun/2017	28/Jun/2018
Amplifier	Ketsight	83017A	MY53270197	1GHz-26.5GHz	19/Sep/2017	18/Sep/2018
Horn Antenna	SCHWARZBECK	BBHA9120D	BBHA9120D 01531	1GHz-18GHz	11/May/2017	10/May/2018
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	18GHz-40GHz	06/Feb/2017	05/Feb/2018
Bilog Antenna	SCHAFFNER	CBL6112B	2723	30MHz-1GHz	09/Sep/2017	08/Sep/2018
RF Cable-high	SUHNER	SUCOFLEX104	MY34918/4	1GHz ~ 40GHz	26/Jan/2017	25/Jan/2018
RF Cable-R03m	Jye Bao	RG142	CB017	9kHz ~ 1GHz	26/Jan/2017	25/Jan/2018
Receiver	R&S	ESU3	102052	9kHz ~ 3.6GHz	29/Apr/2017	28/Apr/2018

Instrument for Conducted Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101013	9kHz-40GHz	30/Dec/2016	29/Dec/2017
Power Sensor	Anritsu	MA2411B	0917017	300MHz ~ 40GHz	10/Feb/2017	09/Feb/2018
Power Meter	Anritsu	ML2495A	0949003	300MHz ~ 40GHz	10/Feb/2017	09/Feb/2018
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	27/Jul/2017	26/Jul/2018
RF Cable-0.2m	HUBER+SUHNER	SUCOFLEX_104	MY10710/4	30MHz ~ 26.5GHz	25/Aug/2017	24/Aug/2018
RF Cable-0.2m	HUBER+SUHNER	SUCOFLEX_104	MY10709/4	30MHz ~ 26.5GHz	25/Aug/2017	24/Aug/2018
RF Cable-0.5m	HUBER+SUHNER	SUCOFLEX_104	MY10713/4	30MHz ~ 26.5GHz	25/Aug/2017	24/Aug/2018



AC Power-line Conducted Emissions Result			
Operating Mode	1	Power Phase	Neutral
Operating Function	PoE mode		
<div style="text-align: right;">Date: 2017-10-11</div> <p>The graph displays the AC power-line conducted emissions. The y-axis represents the level in dBUV, ranging from 0 to 80. The x-axis represents the frequency in MHz, ranging from 0.1502 to 30. Two red lines indicate the limits: NCC/IC/FCC-B (upper) and NCC/IC/FCC-B-AV (lower). A blue line shows the measured emission levels, which are generally below the limits, with a peak of 36.34 dBUV at 2.04409 MHz.</p>			
	Freq	Level	Over Limit
	MHz	dBuV	dB
	Limit	Line	Read Level
	dBuV	dBuV	LISN Factor
	dB	dB	Cable Loss
	dB	dB	Remark
1	0.16677	27.84	-27.28
2	0.16677	44.47	-20.65
3	0.44679	30.90	-16.03
4	0.44679	42.22	-14.71
5	0.60431	30.15	-15.85
6	0.60431	35.06	-20.94
7	1.10555	26.59	-19.41
8	1.10555	34.08	-21.92
9 MAX	2.04409	36.34	-9.66
10	2.04409	40.77	-15.23
11	17.10851	24.75	-25.25
12	17.10851	31.18	-28.82

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



AC Power-line Conducted Emissions Result								
Operating Mode	1	Power Phase	Line					
Operating Function	PoE mode							
<div style="text-align: right;">Date: 2017-10-11</div>								
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15403	37.55	-18.23	55.78	27.89	9.66	0.00	Average
2	0.15403	50.17	-15.61	65.78	40.51	9.66	0.00	QP
3 MAX	0.44916	35.77	-11.12	46.89	26.10	9.67	0.00	Average
4	0.44916	42.66	-14.23	56.89	32.99	9.67	0.00	QP
5	1.17813	28.46	-17.54	46.00	18.79	9.67	0.00	Average
6	1.17813	33.78	-22.22	56.00	24.11	9.67	0.00	QP
7	1.68913	29.98	-16.02	46.00	20.23	9.75	0.00	Average
8	1.68913	36.84	-19.16	56.00	27.09	9.75	0.00	QP
9	2.05495	30.45	-15.55	46.00	20.66	9.79	0.00	Average
10	2.05495	40.75	-15.25	56.00	30.96	9.79	0.00	QP
11	14.90683	29.78	-20.22	50.00	19.95	9.83	0.00	Average
12	14.90683	32.05	-27.95	60.00	22.22	9.83	0.00	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



Summary


Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	698.75k	1.032M	1M03F1D	688.75k	1.031M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	698.75k	1.031M
2440MHz	Pass	500k	692.5k	1.032M
2480MHz	Pass	500k	688.75k	1.032M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;





Summary

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	2.26	0.00168

Result

Mode	Result	Gain	Power	Power Limit
		(dBi)	(dBm)	(dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	7.50	2.26	28.50
2440MHz	Pass	7.50	2.17	28.50
2480MHz	Pass	7.50	2.22	28.50



Summary


Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-13.16

RBW=3kHz.

Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	7.50	-13.16	6.50
2440MHz	Pass	7.50	-13.45	6.50
2480MHz	Pass	7.50	-13.20	6.50

RBW=3kHz.






Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.402171G	0.34	-29.66	1.957552G	-60.11	2.39972G	-61.57	2.483552G	-43.28	2.4855G	-51.71	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.402171G	0.34	-29.66	2.394448G	-51.60	2.398004G	-46.13	2.484924G	-59.90	6.951814G	-55.07	1
2440MHz	Pass	2.402171G	0.34	-29.66	1.938608G	-60.07	2.39938G	-59.43	2.483908G	-59.69	6.996843G	-54.27	1
2480MHz	Pass	2.402171G	0.34	-29.66	1.957552G	-60.11	2.39972G	-61.57	2.483552G	-43.28	2.4855G	-51.71	1





Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	PK	37.76M	36.88	40.00	-3.12	-6.84	3	Vertical	360	1.00	-




Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2440MHz	Pass	PK	33.88M	26.68	40.00	-13.32	-4.75	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	101.78M	23.82	43.50	-19.68	-9.13	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	251.16M	22.69	46.00	-23.31	-6.40	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	515M	25.67	46.00	-20.33	-1.68	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	658.56M	26.86	46.00	-19.14	0.18	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	866.14M	28.85	46.00	-17.15	2.65	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	37.76M	36.88	40.00	-3.12	-6.84	3	Vertical	360	1.00	-
2440MHz	Pass	PK	76.56M	25.78	40.00	-14.22	-13.93	3	Vertical	360	1.00	-
2440MHz	Pass	PK	150.28M	27.72	43.50	-15.78	-9.67	3	Vertical	360	1.00	-
2440MHz	Pass	PK	546.04M	28.04	46.00	-17.96	-0.32	3	Vertical	360	1.00	-
2440MHz	Pass	PK	734.22M	29.25	46.00	-16.75	1.26	3	Vertical	360	1.00	-
2440MHz	Pass	PK	833.16M	29.69	46.00	-16.31	2.26	3	Vertical	360	1.00	-

BT-LE(1Mbps)

2440MHz_PoE




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	37.76M	36.88	40.00	-3.12	-6.84	3	Vertical	360	1.00	-	43.72	18.89	1.84	27.56
PK	76.56M	25.78	40.00	-14.22	-13.93	3	Vertical	360	1.00	-	39.71	11.58	1.93	27.44
PK	150.28M	27.72	43.50	-15.78	-9.67	3	Vertical	360	1.00	-	37.39	15.37	2.10	27.14
PK	546.04M	28.04	46.00	-17.96	-0.32	3	Vertical	360	1.00	-	28.36	23.93	3.65	27.90
PK	734.22M	29.25	46.00	-16.75	1.26	3	Vertical	360	1.00	-	27.99	24.86	4.29	27.88
PK	833.16M	29.69	46.00	-16.31	2.26	3	Vertical	360	1.00	-	27.43	25.28	4.63	27.66

BT-LE(1Mbps)

2440MHz_PoE



EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	33.88M	26.68	40.00	-13.32	-4.75	3	Horizontal	360	1.00	-	31.43	21.05	1.77	27.57
PK	101.78M	23.82	43.50	-19.68	-9.13	3	Horizontal	360	1.00	-	32.95	16.26	1.98	27.36
PK	251.16M	22.69	46.00	-23.31	-6.40	3	Horizontal	360	1.00	-	29.09	17.88	2.51	26.80
PK	515M	25.67	46.00	-20.33	-1.68	3	Horizontal	360	1.00	-	27.35	22.60	3.58	27.86
PK	658.56M	26.86	46.00	-19.14	0.18	3	Horizontal	360	1.00	-	26.68	23.98	4.17	27.97
PK	866.14M	28.85	46.00	-17.15	2.65	3	Horizontal	360	1.00	-	26.20	25.57	4.66	27.58



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	PK	2.4838G	72.60	74.00	-1.40	30.79	3	Vertical	258	1.66	-




Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	AV	2.352G	45.76	54.00	-8.24	30.32	3	Vertical	243	1.51	-
2402MHz	Pass	AV	2.402G	102.58	Inf	-Inf	30.50	3	Vertical	243	1.51	-
2402MHz	Pass	PK	2.3898G	62.02	74.00	-11.98	30.45	3	Vertical	243	1.51	-
2402MHz	Pass	PK	2.4022G	103.53	Inf	-Inf	30.50	3	Vertical	243	1.51	-
2402MHz	Pass	AV	4.803805G	33.53	54.00	-20.47	5.85	3	Horizontal	0	1.01	-
2402MHz	Pass	PK	4.803356G	47.39	74.00	-26.61	5.85	3	Horizontal	0	1.01	-
2402MHz	Pass	AV	4.803906G	33.73	54.00	-20.27	5.85	3	Vertical	33	1.50	-
2402MHz	Pass	PK	4.804803G	46.34	74.00	-27.66	5.85	3	Vertical	33	1.50	-
2440MHz	Pass	AV	2.3612G	45.72	54.00	-8.28	30.35	3	Vertical	312	1.50	-
2440MHz	Pass	AV	2.44G	103.18	Inf	-Inf	30.63	3	Vertical	312	1.50	-
2440MHz	Pass	AV	2.4956G	46.56	54.00	-7.44	30.83	3	Vertical	312	1.50	-
2440MHz	Pass	PK	2.3472G	58.33	74.00	-15.67	30.31	3	Vertical	312	1.50	-
2440MHz	Pass	PK	2.4396G	104.14	Inf	-Inf	30.63	3	Vertical	312	1.50	-
2440MHz	Pass	PK	2.4976G	58.86	74.00	-15.14	30.84	3	Vertical	312	1.50	-
2440MHz	Pass	AV	4.879667G	33.17	54.00	-20.83	6.02	3	Horizontal	360	1.16	-
2440MHz	Pass	PK	4.880507G	46.12	74.00	-27.88	6.03	3	Horizontal	360	1.16	-
2440MHz	Pass	AV	4.879797G	35.15	54.00	-18.85	6.02	3	Vertical	80	1.07	-
2440MHz	Pass	PK	4.879725G	46.64	74.00	-27.36	6.02	3	Vertical	80	1.07	-
2480MHz	Pass	AV	2.48G	103.03	Inf	-Inf	30.78	3	Vertical	258	1.66	-
2480MHz	Pass	AV	2.4844G	47.11	54.00	-6.89	30.79	3	Vertical	258	1.66	-
2480MHz	Pass	PK	2.4802G	103.97	Inf	-Inf	30.78	3	Vertical	258	1.66	-
2480MHz	Pass	PK	2.4838G	72.60	74.00	-1.40	30.79	3	Vertical	258	1.66	-
2480MHz	Pass	AV	4.959421G	33.42	54.00	-20.58	6.21	3	Horizontal	360	1.07	-
2480MHz	Pass	PK	4.959971G	47.18	74.00	-26.82	6.21	3	Horizontal	360	1.07	-
2480MHz	Pass	AV	4.959797G	35.04	54.00	-18.96	6.21	3	Vertical	82	1.16	-
2480MHz	Pass	PK	4.959508G	46.98	74.00	-27.02	6.21	3	Vertical	82	1.16	-

BT-LE(1Mbps)

2402MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.352G	45.76	54.00	-8.24	30.32	3	Vertical	243	1.51	-	15.44	27.12	3.21	-
AV	2.402G	102.58	Inf	-Inf	30.50	3	Vertical	243	1.51	-	72.09	27.25	3.25	-
PK	2.3898G	62.02	74.00	-11.98	30.45	3	Vertical	243	1.51	-	31.56	27.21	3.24	-
PK	2.4022G	103.53	Inf	-Inf	30.50	3	Vertical	243	1.51	-	73.03	27.25	3.25	-

BT-LE(1Mbps)

2402MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.803906G	33.73	54.00	-20.27	5.85	3	Vertical	33	1.50	-	27.88	31.19	4.51	29.85
PK	4.804803G	46.34	74.00	-27.66	5.85	3	Vertical	33	1.50	-	40.49	31.19	4.51	29.85

BT-LE(1Mbps)

2402MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.803805G	33.53	54.00	-20.47	5.85	3	Horizontal	0	1.01	-	27.68	31.19	4.51	29.85
PK	4.803356G	47.39	74.00	-26.61	5.85	3	Horizontal	0	1.01	-	41.54	31.19	4.51	29.85

BT-LE(1Mbps)

2440MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3612G	45.72	54.00	-8.28	30.35	3	Vertical	312	1.50	-	15.37	27.14	3.22	-
AV	2.4956G	46.56	54.00	-7.44	30.83	3	Vertical	312	1.50	-	15.73	27.49	3.35	-
AV	2.44G	103.18	Inf	-Inf	30.63	3	Vertical	312	1.50	-	72.54	27.34	3.29	-
PK	2.3472G	58.33	74.00	-15.67	30.31	3	Vertical	312	1.50	-	28.03	27.10	3.20	-
PK	2.4976G	58.86	74.00	-15.14	30.84	3	Vertical	312	1.50	-	28.01	27.49	3.35	-
PK	2.4396G	104.14	Inf	-Inf	30.63	3	Vertical	312	1.50	-	73.50	27.34	3.29	-

BT-LE(1Mbps)

2440MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.879797G	35.15	54.00	-18.85	6.02	3	Vertical	80	1.07	-	29.13	31.31	4.55	29.83
PK	4.879725G	46.64	74.00	-27.36	6.02	3	Vertical	80	1.07	-	40.62	31.31	4.55	29.83

BT-LE(1Mbps)

2440MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.879667G	33.17	54.00	-20.83	6.02	3	Horizontal	360	1.16	-	27.15	31.31	4.55	29.83
PK	4.880507G	46.12	74.00	-27.88	6.03	3	Horizontal	360	1.16	-	40.09	31.31	4.55	29.83

BT-LE(1Mbps)

2480MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.4844G	47.11	54.00	-6.89	30.79	3	Vertical	258	1.66	-	16.31	27.46	3.33	-
AV	2.48G	103.03	Inf	-Inf	30.78	3	Vertical	258	1.66	-	72.26	27.45	3.33	-
PK	2.4838G	72.60	74.00	-1.40	30.79	3	Vertical	258	1.66	-	41.80	27.46	3.33	-
PK	2.4802G	103.97	Inf	-Inf	30.78	3	Vertical	258	1.66	-	73.19	27.45	3.33	-

BT-LE(1Mbps)

2480MHz_TX




EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.959797G	35.04	54.00	-18.96	6.21	3	Vertical	82	1.16	-	28.84	31.44	4.59	29.82
PK	4.959508G	46.98	74.00	-27.02	6.21	3	Vertical	82	1.16	-	40.77	31.44	4.59	29.82

BT-LE(1Mbps)

2480MHz_TX



EUT=Y,ANT=Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.959421G	33.42	54.00	-20.58	6.21	3	Horizontal	360	1.07	-	27.22	31.44	4.59	29.82
PK	4.959971G	47.18	74.00	-26.82	6.21	3	Horizontal	360	1.07	-	40.98	31.44	4.59	29.82