


# Radio Exposure Evaluation Report

**FCC ID** : QXO-AP460

**Equipment** : Wireless Access Point

**Brand Name** :  or Extreme Networks

**Model Name** : AP460i, AP460e

**Applicant** : Extreme Networks, Inc.  
6480 Via Del Oro, San Jose, CA 95119, United States

**Manufacturer** : Extreme Networks, Inc.  
6480 Via Del Oro, San Jose, CA 95119, United States

**Standard** : 47 CFR Part 2.1091

The product was received on Aug. 13, 2019, and testing was started from Aug. 26, 2019 and completed on Nov. 09, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of United States government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 EUT General Information .....5

1.2 Table for Multiple Listing .....5

1.3 Testing Location .....5

**2 MAXIMUM PERMISSIBLE EXPOSURE .....6**

2.1 Limit of Maximum Permissible Exposure .....6

2.2 MPE Calculation Method .....6

2.3 Calculated Result and Limit .....7

**Photographs of EUT V01**



History of this test report

Report No.	Version	Description	Issued Date
FA970235-01	01	Initial issue of report	Mar. 03, 2020



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None.

Reviewed by: Sam Tsai

Report Producer: Jenny Yang

# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11 ax: OFDMA(BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11 ax: OFDMA(BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)
Thread	2400-2483.5	2405-2480	DSSS (O-QPSK)

## 1.2 Table for Multiple Listing

Sample Number	Model Name	Description
1	AP460i	The "i" in AP460i indicates that it comes with internal antennas and the "e" in AP460e indicates that the access point comes with external antenna connectors.
2	AP460e	

## 1.3 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA970235

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
U-NII-2A and UNII-2C were added.	N/A

## 1.4 Testing Location

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 31 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

2.4G(Radio1)+ 5G(Radio 2)+ 2.4G(Radio 3)+Thread(Radio 4)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;D1D	13.51	22.46	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
5.8G;D1D	11.60	24.37	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
2.4G;D1D	13.51	22.34	35.85	0.00	35.85	3.84592	31	0.31847	1.00000	0.31847
2.4G;D1D	8.00	1.09	9.09	0.00	9.09	0.00811	31	0.00067	1.00000	0.00067
									Sum Ratio	0.97392
									Ratio Limit	1

2.4G(Radio 1)+ 5G(Radio 2)+ 2.4G(Radio 3)+ Bluetooth (Radio 4)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;D1D	10.50	25.47	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
5.8G;D1D	11.60	24.37	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
2.4G;D1D	13.51	22.34	35.85	0.00	35.85	3.84592	31	0.31847	1.00000	0.31847
2.4G;BT-LE	8.00	-0.76	7.24	0.00	7.24	0.00530	31	0.00044	1.00000	0.00044
									Sum Ratio	0.97369
									Ratio Limit	1



**2.4G(Radio 1)+ 5G(Radio 2)+ 5G(Radio 3)+Thread(Radio 4)**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;D1D	10.50	25.47	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
5.8G;D1D	11.60	24.37	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
5.8G;D1D	8.00	27.47	35.47	0.00	35.47	3.52371	31	0.29179	1.00000	0.29179
2.4G;D1D	8.00	1.09	9.09	0.00	9.09	0.00811	31	0.00067	1.00000	0.00067
									Sum Ratio	0.94724
									Ratio Limit	1

**2.4G(Radio 1)+ 5G(Radio 2)+ 5G(Radio 3)+ Bluetooth (Radio 4)**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;D1D	10.50	25.47	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
5.8G;D1D	11.60	24.37	35.97	0.00	35.97	3.95367	31	0.32739	1.00000	0.32739
2.4G;D1D	8.00	27.47	35.47	0.00	35.47	3.52371	31	0.29179	1.00000	0.29179
2.4G;BT-LE	8.00	-0.76	7.24	0.00	7.24	0.00530	31	0.00044	1.00000	0.00044
									Sum Ratio	0.94701
									Ratio Limit	1

—————THE END—————