



FCC RADIO EXPOSURE TEST REPORT

FCC ID : QXO-AP510I
Equipment : 802.11ax Access Point
Brand Name : Extreme Networks
Model Name : AP510i
Applicant : Extreme Networks, Inc.
6480 Via Del Oro, San Jose, CA 95119
Manufacturer : Extreme Networks, Inc.
6480 Via Del Oro, San Jose, CA 95119
Standard : 47 CFR Part 2.1091

The product was received on Nov. 03, 2018, and testing was started from Nov. 14, 2018 and completed on Dec. 18, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.


Approved by: Cliff Chang

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....3

Summary of Test Result.....4

1 General Description5

1.1 EUT General Information5

1.2 Table for Class II Change.....6

1.3 Testing Location6

2 Maximum Permissible Exposure7

2.1 Limit of Maximum Permissible Exposure7

2.2 MPE Calculation Method.....7

2.3 Calculated Result and Limit.....8

Photographs of EUT v01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: **Cliff Chang**

Report Producer: **Wendy Pan**



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ax: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5250 5250-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)
Thread	2400-2483.5	2405-2480	Thread: O-QPSK (250kbps)

1.1.1 Table for Multiple Listing

The EUT has three radios, the information as following table:

Radio	Function		
	WLAN 2.4GHz	WLAN 5GHz	Bluetooth/Thread
1	V	V	-
2	-	V	-
3	-	-	V

1.1.2 Table for EUT support function

Function	Support Type	Support Band
AP	Master	WLAN 2.4GHz/Bluetooth/Thread/WLAN 5GHz Band 1~4
Client	Slave without Radar Detection (Sensor Mode)	WLAN 2.4GHz/Bluetooth/Thread/WLAN 5GHz Band 1+4
Bridge	Master	WLAN 2.4GHz/Bluetooth/Thread/WLAN 5GHz Band 1+4
Mesh	Master	WLAN 2.4GHz/Bluetooth/Thread/WLAN 5GHz Band 1+4

Note: The above information was declared by manufacturer.



1.2 Table for Class II Change

This product is an extension of original one reported under Sporton project number: FA8O1739-01

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Adding 5GHz band 2 and band 3 (5250~5350 MHz, 5470~5725 MHz) for this device. 2. Adding 802.11ac 160MHz and 802.11ax 160MHz Mode.	Maximum Permissible Exposure.

Note: Maximum Permissible Exposure of 2.4GHz, Bluetooth, Thread and 5GHz band 1, 4 are based on original test report.

1.3 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 26 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For WLAN Function:

Test Mode: 1T1S

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D (Radio 1)	3.90	22.93	26.83	0.50	27.33	0.54075	26	0.06366	1
5.2G;D1D (Radio 1)	5.89	21.09	26.98	0.50	27.48	0.55976	26	0.06589	1
5.3G;D1D (Radio 1)	5.89	20.39	26.28	0.50	26.78	0.47643	26	0.05608	1
5.6G;D1D (Radio 1)	5.89	18.02	23.91	0.50	24.41	0.27606	26	0.03250	1
5.8G;D1D (Radio 1)	5.89	21.47	27.36	0.50	27.86	0.61094	26	0.07192	1
5.2G;D1D (Radio 2)	4.57	19.62	24.19	0.50	24.69	0.29444	26	0.03466	1
5.3G;D1D (Radio 2)	4.57	20.67	25.24	0.50	25.74	0.37497	26	0.04414	1
5.6G;D1D (Radio 2)	4.57	21.08	25.65	0.50	26.15	0.41210	26	0.04851	1
5.8G;D1D (Radio 2)	4.57	22.84	27.41	0.50	27.91	0.61802	26	0.07275	1

Test Mode: 2T2S

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;D1D (Radio 1)	3.87	23.17	27.04	0.50	27.54	0.56754	26	0.06681	1
5.2G;D1D (Radio 1)	5.63	24.09	29.72	0.50	30.22	1.05196	26	0.12383	1
5.3G;D1D (Radio 1)	5.63	23.55	29.18	0.50	29.68	0.92897	26	0.10935	1
5.6G;D1D (Radio 1)	5.63	20.89	26.52	0.50	27.02	0.50350	26	0.05927	1
5.8G;D1D (Radio 1)	5.63	24.48	30.11	0.50	30.61	1.15080	26	0.13547	1
5.2G;D1D (Radio 2)	4.49	22.10	26.59	0.50	27.09	0.51168	26	0.06023	1
5.3G;D1D (Radio 2)	4.49	22.66	27.15	0.50	27.65	0.58210	26	0.06852	1
5.6G;D1D (Radio 2)	4.49	23.76	28.25	0.50	28.75	0.74989	26	0.08827	1
5.8G;D1D (Radio 2)	4.49	25.94	30.43	0.50	30.93	1.23880	26	0.14583	1



Test Mode: 4T1S

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D (Radio 1)	3.90	28.09	31.99	0.50	32.49	1.77419	26	0.20885	1
5.2G;D1D (Radio 1)	11.59	24.30	35.89	0.10	35.99	3.97192	26	0.46756	1
5.3G;D1D (Radio 1)	11.59	18.37	29.96	0.03	29.99	0.99770	26	0.11745	1
5.6G;D1D (Radio 1)	11.59	18.38	29.97	0.02	29.99	0.99770	26	0.11744	1
5.8G;D1D (Radio 1)	11.59	24.40	35.99	0.01	36.00	3.98107	26	0.46863	1
5.2G;D1D (Radio 2)	10.81	24.56	35.37	0.50	35.87	3.86367	26	0.45481	1
5.3G;D1D (Radio 2)	10.81	19.15	29.96	0.03	29.99	0.99770	26	0.11744	1
5.6G;D1D (Radio 2)	10.81	19.12	29.93	0.06	29.99	0.99770	26	0.11744	1
5.8G;D1D (Radio 2)	10.81	25.16	35.97	0.02	35.99	3.97192	26	0.46757	1

Test Mode: 4T4S

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;D1D (Radio 1)	3.76	25.11	28.87	0.50	29.37	0.86497	26	0.10182	1
5.2G;D1D (Radio 1)	5.58	26.52	32.10	0.50	32.60	1.81970	26	0.21421	1
5.3G;D1D (Radio 1)	5.58	23.90	29.48	0.50	29.98	0.99541	26	0.11717	1
5.6G;D1D (Radio 1)	5.58	23.34	28.92	0.50	29.42	0.87498	26	0.10300	1
5.8G;D1D (Radio 1)	5.58	27.49	33.07	0.50	33.57	2.27510	26	0.26781	1
5.2G;D1D (Radio 2)	4.79	25.03	29.82	0.50	30.32	1.07647	26	0.12672	1
5.3G;D1D (Radio 2)	4.79	23.96	28.75	0.50	29.25	0.84140	26	0.09905	1
5.6G;D1D (Radio 2)	4.79	23.96	28.75	0.50	29.25	0.84140	26	0.09905	1
5.8G;D1D (Radio 2)	4.79	28.38	33.17	0.50	33.67	2.32809	26	0.27405	1



For Bluetooth Function:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;BT-LE (Radio 3)	4.40	1.67	6.07	0.50	6.57	0.00454	26	0.00053	1

For Thread Function:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D (Radio 3)	4.40	1.92	6.32	0.50	6.82	0.00481	26	0.00057	1

Simultaneous Transmission Analysis Mode:

Mode 1: WLAN 2.4GHz (Radio 1) + WLAN 5GHz (Radio 2) + Bluetooth (Radio 3)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;G1D (Radio 1)	3.90	28.09	31.99	0.50	32.49	1.77419	26	0.20885	1	0.20885
5.8G;D1D (Radio 2)	10.81	25.16	35.97	0.02	35.99	3.97192	26	0.46756	1	0.46756
2.4G;BT (Radio 3)	4.40	1.67	6.07	0.50	6.57	0.00454	26	0.00053	1	0.00053
									Sum Ratio	0.67694
									Ratio Limit	1

Mode 2: WLAN 5GHz (Radio 1) + WLAN 5GHz (Radio 2) + Bluetooth (Radio 3)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
5.8G;D1D (Radio 1)	11.59	24.40	35.99	0.01	36.00	3.98107	26	0.46863	1	0.46863
5.8G;D1D (Radio 2)	10.81	25.16	35.97	0.02	35.99	3.97192	26	0.46756	1	0.46756
2.4G;BT (Radio 3)	4.40	1.67	6.07	0.50	6.57	0.00454	26	0.00053	1	0.00053
									Sum Ratio	0.93672
									Ratio Limit	1



Mode 3: WLAN 2.4GHz (Radio 1) + WLAN 5GHz (Radio 2) + Thread (Radio 3)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;G1D (Radio 1)	3.90	28.09	31.99	0.50	32.49	1.77419	26	0.20885	1	0.20885
5.8G;D1D (Radio 2)	10.81	25.16	35.97	0.02	35.99	3.97192	26	0.46756	1	0.46756
2.4G;D1D (Radio 3)	4.40	1.92	6.32	0.50	6.82	0.00481	26	0.00057	1	0.00057
									Sum Ratio	0.67698
									Ratio Limit	1

Mode 4: WLAN 5GHz (Radio 1) + WLAN 5GHz (Radio 2) + Thread (Radio 3)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
5.8G;D1D (Radio 1)	11.59	24.40	35.99	0.01	36.00	3.98107	26	0.46863	1	0.46863
5.8G;D1D (Radio 2)	10.81	25.16	35.97	0.02	35.99	3.97192	26	0.46756	1	0.46756
2.4G;G1D (Radio 3)	4.40	1.92	6.32	0.50	6.82	0.00481	26	0.00057	1	0.00057
									Sum Ratio	0.93676
									Ratio Limit	1

Note: The above antenna gain was declared by manufacturer.

————THE END————