

1. Maximum Permissible Exposure (MPE)

Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

| Frequency Range | Electric Field | Magnetic Field | Power Density | Averaging Time | | | |
|---|----------------|----------------|---------------|----------------|--|--|--|
| (MHz) | Strength (V/m) | Strength (A/m) | (mW/cm^2) | (minute) | | | |
| Limits for General Population/Uncontrolled Exposure | | | | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 | | | |
| 1.34-30 | 824/f | 2.19/f | $*(180/f^2)$ | 30 | | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | | | |
| 300-1500 | / | / | F/1500 | 30 | | | |
| 1500-15000 | / | / | 1.0 | 30 | | | |

F = frequency in MHz

^{* =} Plane-wave equipment power density





Maximum Permissible Exposure (MPE) Evaluation

2.4GHz mode:

The worst case: refer to FCC test report for detail measurement date.

Power measurement:

BDR Mode

| Frequency (MHz) | Peak Reading Power (dBm) | Cable Loss | Output Power (dBm) | Output Power (W) | Limit (W) |
|--------------------|--------------------------|------------|--------------------|------------------|--------------|
| 2402.00 | 1.10 | 0.00 | 1.10 | 0.00129 | 0.125 |
| 2441.00 | 1.59 | 0.00 | 1.59 | 0.00144 | 0.125 |
| 2480.00 | 2.49 | 0.00 | 2.49 | 0.00177 | 0.125 |

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4 \pi R^2$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

| Maximum output power at antenna input terminal: | 2.49 | (dBm) |
|---|-------------|-----------|
| Maximum output power at antenna input terminal: | 1.774189481 | (mW) |
| Tune-Up power Tolerance: | 2 | dB |
| Duty cycle: | 76 | (%) |
| Maximum Pav : | 2.137044631 | (mW) |
| Antenna gain (typical): | 2.1 | (dBi) |
| Maximum antenna gain: | 1.621810097 | (numeric) |
| Prediction distance: | 20 | (cm) |
| | | |
| MPE limit for uncontrolled exposure at prediction | 1 | (mW/cm^2) |
| Power density at predication frequency at 20 (cm) | 0.0006899 | (mW/cm^2) |

Measurement Result:

The predicted power density level at 20 cm is $0.0006899 \text{ mW/cm}^2$.. This is below the uncontrolled exposure limit of 1 mW/cm^2 .

~ End of Report ~