



- NOTE:
1. Material: PC KLX 1860 T 0.254mm, it must be approved by UL & CSA standard
 2. Adhesive: 3M467
 3. Follow RD approval sample as standard
 4. Color: TEXT Foreground: Pantone Cool Gray 3C
Background: Pantone Black
 5. Label should have pressure sensitive adhesive with protective release liner on the back side.
 6. Label manufacturer must use a process & materials those which have been approved by UL & CSA
 7. Sample must approve GP standard
 8. 黏性: 黏著力為 2.3 以上
 9. 表面: 粗糙面
 10. 貼附位置: D件
 11. 環測項目及條件. (判定標準 follow "QAP-4-75-A 系統表面處理的測試規範")

ITEM	CONTENTS OF CHANGE	RVS	CHK	APV	M/D/Y	TOL ±						DATE	MATERIAL	SEE NOTES	TREATMENT	REMARK									
							Pla	Met	Ins	Por	Cab	Pac	Gas	PCB	UNIT	MM	SCALE	--	DRAWING NAME	TF1-LABEL; RATING, W/O UL1604, GETAC, B300X					
						0~6	0.1	0.1	0.1	0.2	0.5	1	0.5	0.1	DRAWN	DESIGNED	CHECKED	APPROVED	MATERIAL NO.	MF	242	8317	00001	R	01
						6~30	0.1	0.1	.15	.25	1	1	0.5	0.1											
						30~80	0.1	.15	0.2	0.3	2	1.5	1	0.1											
						80~180	.15	.15	.25	0.3	2	2	1	.15											
						180~315	.15	0.2	0.3	0.4	2.5	2	1	.15											
						315~800	0.2	0.3	0.4	0.5	3	3	2	.15											

Getac Technology Corp.