



# RF Exposure Evaluation Report

**APPLICANT** : Getac Technology Corporation  
**EQUIPMENT** : Notebook PC  
**BRAND NAME** : Getac  
**MODEL NAME** : B300  
**FCC ID** : QYL3X01  
**FILING TYPE** : Certification  
**STANDARD** : OET Bulletin 65 Supplement C (Edition 01-01)

The product was integrated the WWAN Module (Brand Name: QUALCOMM / Model Name: Gobi2000, FCC ID: J9CGOBI2000) during the test.

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with FCC OET Bulletin 65 Supplement C (Edition 01-01).

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

---

Roy Wu / Manager

## **SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**



**Table of Contents**

**REVISION HISTORY ..... 3**

**1. INTRODUCTION..... 4**

**2. ADMINISTRATION DATA ..... 6**

    2.1 Testing Laboratory ..... 6

    2.2 Applicant ..... 6

    2.3 Manufacturer ..... 6

**3. GENERAL INFORMATION ..... 7**

    3.1 Description of Device Under Test (DUT) ..... 7

**4. RF EXPOSURE EVALUATION ..... 9**

    4.1 Radio Frequency Radiation Exposure Evaluation ..... 9



**Revision History**

<b>REPORT NO.</b>	<b>VERSION</b>	<b>DESCRIPTION</b>	<b>ISSUED DATE</b>
FA052506-01A	Rev. 01	Initial issue of report	Jun. 28, 2010



## **1. Introduction**

The report has been prepared on behalf of Getac Technology Corporation Notebook PC to show compliance with the RF Exposure.

### **➤ Requirements**

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile and portable and are defined as follows:

#### **▪ Fixed installation:**

Fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.

#### **▪ Mobile Devices:**

A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitters' radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR 2.1091.

#### **▪ Portable Devices:**

A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR 2.1093)

For this test report the **Getac B300** is being done as a mobile device and the MPE is evaluated at the 20cm test distance.

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:



▪ **Occupational/controlled Exposure:**

In general, occupational/controlled exposure limits are applicable to situation in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.

▪ **General Population/Uncontrolled Exposure:**

The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category and the general population/uncontrolled exposure limits apply to these devices.

Since there are no warnings or training associated with this unit and it can be used by anyone, Notebook PC is evaluated to the General Population / Uncontrolled Exposure limits.



**2. Administration Data**

**2.1 Testing Laboratory**

<b>Test Site</b>	SPORTON INTERNATIONAL INC.
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978

**2.2 Applicant**

<b>Company Name</b>	Getac Technology Corporation
<b>Address</b>	5F., Building A, No. 209, Sec.1, Nangang Rd., Nangang Dist., Taipei City 11568, Taiwan, R.O.C.

**2.3 Manufacturer**

<b>Company Name</b>	GeTAC Technology (Kunshan) LTD.
<b>Address</b>	No. 269, 2nd Road, Export Processing Zone, Changjiang South Road, Kunshan, Jiangsu, P.R.C.



### 3. General Information

#### 3.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	Notebook PC
Brand Name	Getac
Model Name	B300
FCC ID	QYL3X01
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz CDMA2000 BC0 : 824 MHz ~ 849 MHz CDMA2000 BC1 : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz CDMA2000 BC0 : 869 MHz ~ 894 MHz CDMA2000 BC1 : 1930 MHz ~ 1990 MHz
Antenna Type	Fixed Internal Antenna
HW Version	R0A
SW Version	R0.05.070520G
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM HSUPA : BPSK CDMA2000 : QPSK
DUT Stage	Identical Prototype

**List of Accessory:**

Specification of Accessory		
<b>AC Adapter 1</b>	<b>Brand Name</b>	DELTA
	<b>Model Name</b>	ADP-90CD
	<b>Power Rating</b>	I/P:100-240Vac, 50-60Hz, 1.5A; O/P: 19Vdc, 4.74A
	<b>DC Power Cord Type</b>	1.8 meter shielded cable with ferrite core
<b>AC Adapter 2</b>	<b>Brand Name</b>	Getac
	<b>Model Name</b>	ADM-9019M
	<b>Power Rating</b>	I/P:100-240Vac, 50-60Hz, 1.5A; O/P: 19Vdc, 4.74A
	<b>DC Power Cord Type</b>	1.5 meter shielded cable with ferrite core
<b>Battery</b>	<b>Brand Name</b>	Sanyo
	<b>Model Name</b>	BP3S3P2600(S)
	<b>Power Rating</b>	11.1Vdc, 7800mAh
	<b>Type</b>	Li-ion
<b>LCD Panel</b>	<b>Brand Name</b>	Toshiba
	<b>Model Name</b>	TMD13.3"
<b>WWAN Module</b>	<b>Brand Name</b>	QUALCOMM
	<b>Model Name</b>	Gobi2000
<b>WLAN Module</b>	<b>Brand Name</b>	Intel
	<b>Model Name</b>	633ANHMW
<b>Bluetooth Module</b>	<b>Brand Name</b>	CastleNet
	<b>Model Name</b>	BTC04R
<b>GPS Module</b>	<b>Brand Name</b>	GlobalSat
	<b>Model Name</b>	ET313

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.





## **4. RF Exposure Evaluation**

### **4.1 Radio Frequency Radiation Exposure Evaluation**

According to 1.1310 of the FCC rules, the power density limit for General Population/Uncontrolled Exposure is f/1500 mW/cm<sup>2</sup> for 300 MHz to 1500 MHz and 1.0 mW/cm<sup>2</sup> for 1500 MHz to 100000 MHz. As this is a mobile application the MPE shall be calculated at 20 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

For this device, the calculation is as follows:

Function	ERP (dBm)	EIRP (dBm)	Peak EIRP (mW)	Average EIRP (mW)	Calculated RF Exposure at d = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
GSM850	30.95	33.10	2041.74	255.22	0.05	0.55
GSM1900		25.04	319.15	39.89	0.01	1.00

Function	ERP (dBm)	EIRP (dBm)	EIRP (mW)	Calculated RF Exposure at d = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
CDMA2000 BC0	26.55	28.70	741.31	0.15	0.55
CDMA2000 BC1		22.34	171.40	0.03	1.00

Function	ERP (dBm)	EIRP (dBm)	EIRP (mW)	Calculated RF Exposure at d = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
WCDMA Band V	24.72	26.87	486.41	0.10	0.55
WCDMA Band II		20.27	106.41	0.02	1.00



**Maximum Power Density for IEEE 802.11b/g/n mode:**

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated RF Exposure (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2.75	1.88	16.56	45.29	0.02	1.00

**Maximum Power Density for IEEE 802.11a/n mode :**

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated RF Exposure (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
-0.30	0.93	16.52	44.87	0.01	1.00

**WWAN and WLAN (Ant-A) Transmit Simultaneously.**

WWAN Max. Power Density	WLAN Max. Power Density	Totally RF Exposure (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
0.15	0.02	0.17	0.55

Based on the above calculation at 20 cm the Notebook PC is below the Power Density limit.