



新圖發行  
舊圖 R01 作廢

NOV/03/2010

- NOTE:
1. Material: PC KLX 1860 T 0.254mm, it must be approved by UL & CSA standard
  2. Adhesive: 3M467
  3. Follow RD approval sample as standard
  4. Color: TEXT Foreground: Pantone Cool Gray 3C  
Background: Pantone Black
  5. Label should have pressure sensitive adhesive with protective release liner on the back side.
  6. Label manufacturer must use a process & materials those which have been approved by UL & CSA
  7. Sample must approve GP standard
  8. 黏性: 黏著力為 2.3 以上
  9. 表面: 粗糙面
  10. 貼附位置: D件
  11. 環測項目及條件. (判定標準 follow "QAP-4-75-A 系統表面處理的測試規範")

ITEM	CONTENTS OF CHANGE	RVS	CHK	APV	M/D/Y	TOL ±	REVISIONS									DATE	MATERIAL	SEE NOTES	TREATMENT	REMARK	
							Plt	Met	Ins	Por	Cab	Pac	Gas	PCB	UNIT	SCALE	--	DRAWING NAME	MATERIAL NO.	MF	
						RANGE	0~6	0.1	0.1	0.1	0.2	0.5	1	0.5	0.1	2010-06-21				TF1-LABEL;RATING,STANDARD,B300X	
							6~30	0.1	0.1	.15	.25	1	1	0.5	0.1						
2	ECR#G55110AOT4						30~80	0.1	.15	0.2	0.3	2	1.5	1	0.1						
							80~180	.15	.15	.25	0.3	2	2	1	.15						
1	ECR#G55110ANCD						180~315	.15	0.2	0.3	0.4	2.5	2	1	.15						
							315~800	0.2	0.3	0.4	0.5	3	3	2	.15						
																廖梅華	李惠民			Getac Technology Corp.	

A

B

C

D

E