

## FCC Test Report

**Report No.:** RF170428C33

**FCC ID:** QYL8260GAINV110

**Test Model:** V110

**Received Date:** Apr. 28, 2017

**Test Date:** May 12, 2017 ~ May 19, 2017

**Issued Date:** Jun. 08, 2017

**Applicant:** Getac Technology Corporation.

**Address:** 5F., Building A, No. 209, Sec.1, Nangang Rd., Nangang Dist., Taipei City  
11568, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
( R.O.C )

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan, R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

<b>Release Control Record</b> .....	<b>4</b>
<b>1 Certificate of Conformity</b> .....	<b>5</b>
<b>2 Summary of Test Results</b> .....	<b>6</b>
2.1 Measurement Uncertainty .....	6
2.2 Modification Record .....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Description of Test Modes .....	8
3.2.1 Test Mode Applicability and Tested Channel Detail .....	9
3.3 Duty Cycle of Test Signal .....	11
3.4 Description of Support Units .....	12
3.4.1 Configuration of System under Test .....	12
3.5 General Description of Applied Standards .....	12
<b>4 Test Types and Results</b> .....	<b>13</b>
4.1 Radiated Emission and Bandedge Measurement .....	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement .....	13
4.1.2 Test Instruments .....	14
4.1.3 Test Procedures .....	15
4.1.4 Deviation from Test Standard .....	15
4.1.5 Test Set Up .....	16
4.1.6 EUT Operating Conditions .....	16
4.1.7 Test Results .....	17
4.2 Conducted Emission Measurement .....	30
4.2.1 Limits of Conducted Emission Measurement .....	30
4.2.2 Test Instruments .....	30
4.2.3 Test Procedures .....	31
4.2.4 Deviation from Test Standard .....	31
4.2.5 Test Setup .....	31
4.2.6 EUT Operating Conditions .....	31
4.2.7 Test Results .....	32
4.3 6 dB Bandwidth Measurement .....	34
4.3.1 Limits of 6 dB Bandwidth Measurement .....	34
4.3.2 Test Setup .....	34
4.3.3 Test Instruments .....	34
4.3.4 Test Procedure .....	34
4.3.5 Deviation from Test Standard .....	34
4.3.6 EUT Operating Conditions .....	34
4.3.7 Test Result .....	35
4.4 Conducted Output Power Measurement .....	37
4.4.1 Limits of Conducted Output Power Measurement .....	37
4.4.2 Test Setup .....	37
4.4.3 Test Instruments .....	37
4.4.4 Test Procedures .....	37
4.4.5 Deviation from Test Standard .....	37
4.4.6 EUT Operating Conditions .....	37
4.4.7 Test Results .....	38
4.5 Power Spectral Density Measurement .....	39
4.5.1 Limits of Power Spectral Density Measurement .....	39
4.5.2 Test Setup .....	39
4.5.3 Test Instruments .....	39
4.5.4 Test Procedure .....	39
4.5.5 Deviation from Test Standard .....	39
4.5.6 EUT Operating Condition .....	39

4.5.7 Test Results .....	40
4.6 Conducted Out of Band Emission Measurement .....	42
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	42
4.6.2 Test Setup.....	42
4.6.3 Test Instruments .....	42
4.6.4 Test Procedure .....	42
4.6.5 Deviation from Test Standard .....	42
4.6.6 EUT Operating Condition .....	42
4.6.7 Test Results .....	43
<b>5 Pictures of Test Arrangements.....</b>	<b>55</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>56</b>

### Release Control Record

Issue No.	Description	Date Issued
RF170428C33	Original Release	Jun. 08, 2017

## 1 Certificate of Conformity

**Product:** Industrial Tablet

**Brand:** Getac

**Test Model:** V110

**Sample Status:** Production Unit

**Applicant:** Getac Technology Corporation.

**Test Date:** May 12, 2017 ~ May 19, 2017

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**

*Rona Chen*

, **Date:**

Jun. 08, 2017

Rona Chen / Specialist

**Approved by :**

*David Huang*

, **Date:**

Jun. 08, 2017

David Huang / Project Engineer

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -8.12 dB at 0.15000 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -8.01 dB at 2389.92 MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

<b>Product</b>	Industrial Tablet
<b>Brand</b>	Getac
<b>Test Model</b>	V110
<b>Status of EUT</b>	Production Unit
<b>Power Supply Rating</b>	19 Vdc (Adapter) 11.1 Vdc (Li-ion battery)
<b>Modulation Type</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>Modulation Technology</b>	DSSS, OFDM
<b>Transfer Rate</b>	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7
<b>Operating Frequency</b>	2412 ~ 2462 MHz
<b>Number of Channel</b>	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
<b>Output Power</b>	293.765 mW
<b>Antenna Type</b>	PIFA antenna with 2 dBi gain
<b>Antenna Connector</b>	N/A
<b>Accessory Device</b>	Refer to Note as below
<b>Data Cable Supplied</b>	Refer to Note as below

Note:

- The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (HT20)	2TX
802.11n (HT40)	2TX

- The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	Chicony	A12-065N2A	I/P: 100-240Vac, 50/60Hz, 1.7A O/P: 19Vdc, 3.42A
Battery	Getac Technology Corp.	BP3S1P2100-S	11.1Vdc, 2100mAh
WLAN/BT Module	Intel	8260NGW	--
Digitizer	KYE	T116 EMR Digitizer	--
LTE Module	Sierra	EM7355	Function: WWAN SW: SWI9X15C_01.05.11.08 HW: 1.1
OS	N/A	N/A	Win10 64bit

- The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

7 channels are provided for 802.11n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		



### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	
A	√	√	√	√	SISO
B	√	√	-	√	MIMO

Where **RE $\geq$ 1G**: Radiated Emission above 1 GHz      **RE<1G**: Radiated Emission below 1 GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis and NB Mode. The worst case was found when positioned on **NB Mode**.  
“-“ means no effects

#### **Radiated Emission Test (Above 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
B	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0

#### **Radiated Emission Test (Below 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	1	OFDM	BPSK	6.0

#### **Power Line Conducted Emission Test:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	1	OFDM	BPSK	6.0

**Bandedge Measurement:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
B	802.11n (HT20)	1 to 11	1, 11	OFDM	BPSK	MCS0
	802.11n (HT40)	3 to 9	3, 9	OFDM	BPSK	MCS0

**Antenna Port Conducted Measurement:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
B	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0

**Test Condition:**


Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Getaz Yang
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Getaz Yang
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Getaz Yang
APCM	25 deg. C, 65 % RH	11.1 Vdc	Carlos Chen

### 3.3 Duty Cycle of Test Signal

#### Mode A

**802.11b:** Duty cycle of test signal is 100 %, duty factor is not required.


**802.11g:** Duty cycle =  $2.050/2.170 = 0.945$ , Duty factor =  $10 * \log(1/0.945) = 0.25$



#### Mode B

**802.11n (HT20):** Duty cycle =  $0.978/1.162 = 0.841$ , Duty factor =  $10 * \log(1/0.841) = 0.75$


**802.11n (HT40):** Duty cycle =  $0.490/0.593 = 0.826$ , Duty factor =  $10 * \log(1/0.826) = 0.84$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v04**

**662911 D01 Multiple Transmitter Output v02r01**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).  
The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

#### 4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Feb. 17, 2017	Feb. 16, 2018
Spectrum Analyzer Agilent	N9010A	MY52220314	Dec. 16, 2016	Dec. 15, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 13, 2016	Dec. 12, 2017
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 26, 2016	Dec. 27, 2017
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Dec. 12, 2016	Dec. 13, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 14, 2016	Dec. 13, 2017
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 08, 2016	Jul. 07, 2017
Loop Antenna	EM-6879	269	Aug. 11, 2016	Aug. 10, 2017
Preamplifier EMCI	EMC 012645	980115	Oct. 21, 2016	Oct. 20, 2017
Preamplifier EMCI	EMC 184045	980116	Oct. 21, 2016	Oct. 20, 2017
Preamplifier EMCI	EMC 330H	980112	Oct. 21, 2016	Oct. 20, 2017
Power Meter Anritsu	ML2495A	1232002	Sep. 08, 2016	Sep. 07, 2017
Power Sensor Anritsu	MA2411B	1207325	Sep. 08, 2016	Sep. 07, 2017
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 21, 2016	Oct. 20, 2017
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 21, 2016	Oct. 20, 2017
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 21, 2016	Oct. 20, 2017
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC7450F-10.

#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360 KHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1/T for Average (Duty cycle < 98 %) for Average detection at frequency above 1 GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle  $\geq$  98 %) for Average detection (AV) at frequency above 1 GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up

##### <Frequency Range below 1 GHz>



##### <Frequency Range above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



4.1.7 Test Results

Above 1 GHz Data :

Mode A

802.11b

EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.14	52.63	59.14	74	-21.37	26.91	4.08	37.5	100	131	Peak
2389.92	45.16	51.69	54	-8.84	26.91	4.08	37.52	100	131	Average
2412	96.02	102.49			26.96	4.09	37.52	100	131	Average
2412	102.13	108.6			26.96	4.09	37.52	100	131	Peak
4824	34.38	49.68	54	-19.62	30.99	6.79	53.08	133	183	Average
4824	42.19	57.49	74	-31.81	30.99	6.79	53.08	133	183	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.14	44.77	51.28	54	-9.23	26.91	4.08	37.5	171	2	Average
2386.41	52.48	58.99	74	-21.52	26.91	4.08	37.5	171	2	Peak
2412	95.23	101.7			26.96	4.09	37.52	171	2	Average
2412	99.86	106.33			26.96	4.09	37.52	171	2	Peak
4824	35.18	50.48	54	-18.82	30.99	6.79	53.08	117	156	Average
4824	42.55	57.85	74	-31.45	30.99	6.79	53.08	117	156	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412 MHz: Fundamental frequency.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2358.69	36.19	42.82	54	-17.81	26.81	4.05	37.49	100	129	Average
2368.23	47.83	54.45	74	-26.17	26.81	4.07	37.5	100	129	Peak
2437	97.95	104.23			27.06	4.12	37.46	100	129	Average
2437	102.25	108.53			27.06	4.12	37.46	100	129	Peak
2483.52	37.83	43.85	54	-16.17	27.15	4.15	37.32	100	129	Average
2484.72	55.97	61.99	74	-18.03	27.15	4.15	37.32	100	129	Peak
4874	34.71	49.85	54	-19.29	31.06	6.85	53.05	130	179	Average
4874	45.24	60.38	74	-28.76	31.06	6.85	53.05	130	179	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2343.93	47.46	54.14	74	-26.54	26.77	4.04	37.49	172	0	Peak
2362.2	36.37	42.98	54	-17.63	26.81	4.07	37.49	172	0	Average
2437	94.93	101.21			27.06	4.12	37.46	172	0	Average
2437	99.01	105.29			27.06	4.12	37.46	172	0	Peak
2485.64	36.65	42.67	54	-17.35	27.15	4.15	37.32	172	0	Average
2492.64	48.12	54.01	74	-25.88	27.2	4.16	37.25	172	0	Peak
4874	35.24	50.38	54	-18.76	31.06	6.85	53.05	115	163	Average
4874	45.8	60.94	74	-28.2	31.06	6.85	53.05	115	163	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.

EUT Test Condition		Measurement Detail	
Channel	Channel 11	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	97.53	103.69			27.1	4.13	37.39	100	127	Average
2462	101.71	107.87			27.1	4.13	37.39	100	127	Peak
2483.52	41.71	47.73	54	-12.29	27.15	4.15	37.32	100	127	Average
2485.4	55.29	61.31	74	-18.71	27.15	4.15	37.32	100	127	Peak
4924	34.61	49.64	54	-19.39	31.12	6.88	53.03	128	170	Average
4924	42.66	57.69	74	-31.34	31.12	6.88	53.03	128	170	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	93.47	99.63			27.1	4.13	37.39	172	0	Average
2462	98.17	104.33			27.1	4.13	37.39	172	0	Peak
2484.08	51.39	57.41	74	-22.61	27.15	4.15	37.32	172	0	Peak
2487.92	39.41	45.37	54	-14.59	27.2	4.16	37.32	172	0	Average
4924	35.34	50.37	54	-18.66	31.12	6.88	53.03	116	167	Average
4924	43.05	58.08	74	-30.95	31.12	6.88	53.03	116	167	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462 MHz: Fundamental frequency.

802.11g

EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.83	63.05	69.58	74	-10.95	26.91	4.08	37.52	100	127	Peak
<b>2389.92</b>	<b>45.99</b>	<b>52.52</b>	<b>54</b>	<b>-8.01</b>	<b>26.91</b>	<b>4.08</b>	<b>37.52</b>	<b>100</b>	<b>127</b>	<b>Average</b>
2412	92.2	98.67			26.96	4.09	37.52	100	127	Average
2412	102	108.47			26.96	4.09	37.52	100	127	Peak
4824	34.11	49.41	54	-19.89	30.99	6.79	53.08	132	184	Average
4824	43.74	59.04	74	-30.26	30.99	6.79	53.08	132	184	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.47	60.81	67.32	74	-13.19	26.91	4.08	37.5	171	1	Peak
2389.74	44.12	50.63	54	-9.88	26.91	4.08	37.5	171	1	Average
2412	89.32	95.79			26.96	4.09	37.52	171	1	Average
2412	99.05	105.52			26.96	4.09	37.52	171	1	Peak
4824	35.11	50.41	54	-18.89	30.99	6.79	53.08	116	164	Average
4824	42.83	58.13	74	-31.17	30.99	6.79	53.08	116	164	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412 MHz: Fundamental frequency.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2357.16	35.28	41.91	54	-18.72	26.81	4.05	37.49	100	127	Average
2375.97	55.09	61.66	74	-18.91	26.86	4.07	37.5	100	127	Peak
2437	91.96	98.24			27.06	4.12	37.46	100	127	Average
2437	101.65	107.93			27.06	4.12	37.46	100	127	Peak
2483.8	36.82	42.84	54	-17.18	27.15	4.15	37.32	100	127	Average
2490.88	54.47	60.43	74	-19.53	27.2	4.16	37.32	100	127	Peak
4874	34.19	49.33	54	-19.81	31.06	6.85	53.05	129	180	Average
4874	42.57	57.71	74	-31.43	31.06	6.85	53.05	129	180	Peak

Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.5	34.85	41.36	54	-19.15	26.91	4.08	37.5	172	0	Average
2389.56	53.78	60.29	74	-20.22	26.91	4.08	37.5	172	0	Peak
2437	89.05	95.33			27.06	4.12	37.46	172	0	Average
2437	98.87	105.15			27.06	4.12	37.46	172	0	Peak
2483.88	53.2	59.22	74	-20.8	27.15	4.15	37.32	172	0	Peak
2484.48	36.41	42.43	54	-17.59	27.15	4.15	37.32	172	0	Average
4874	35.1	50.24	54	-18.9	31.06	6.85	53.05	116	164	Average
4874	42.75	57.89	74	-31.25	31.06	6.85	53.05	116	164	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.

EUT Test Condition		Measurement Detail	
Channel	Channel 11	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2458	90.31	96.47			27.1	4.13	37.39	100	128	Average
2458	101.14	107.3			27.1	4.13	37.39	100	128	Peak
2484.08	56.81	62.83	74	-17.19	27.15	4.15	37.32	100	128	Peak
2488.08	37.53	43.49	54	-16.47	27.2	4.16	37.32	100	128	Peak
4924	34.2	49.23	54	-19.8	31.12	6.88	53.03	133	185	Average
4924	42.97	58	74	-31.03	31.12	6.88	53.03	133	185	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	87.22	93.38			27.1	4.13	37.39	172	2	Average
2462	97.48	103.64			27.1	4.13	37.39	172	2	Peak
2483.64	39.28	45.3	54	-14.72	27.15	4.15	37.32	172	2	Average
2484.52	55.49	61.51	74	-18.51	27.15	4.15	37.32	172	2	Peak
4924	35.32	50.35	54	-18.68	31.12	6.88	53.03	114	165	Average
4924	43.52	58.55	74	-30.48	31.12	6.88	53.03	114	165	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462 MHz: Fundamental frequency.

**Mode B**

**802.11n (HT20)**

EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.56	55.3	61.81	74	-18.7	26.91	4.08	37.5	201	64	Peak
2389.92	38.67	45.2	54	-15.33	26.91	4.08	37.52	201	64	Average
2412	90.02	96.49			26.96	4.09	37.52	201	64	Average
2412	99.94	106.41			26.96	4.09	37.52	201	64	Peak
4824	33.25	48.55	54	-20.75	30.99	6.79	53.08	107	319	Average
4824	45.42	60.72	74	-28.58	30.99	6.79	53.08	107	319	Peak

Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2385.15	55.78	62.34	74	-18.22	26.86	4.08	37.5	200	360	Peak
2389.92	38.05	44.58	54	-15.95	26.91	4.08	37.52	200	360	Average
2412	88	94.47			26.96	4.09	37.52	200	360	Average
2412	98.55	105.02			26.96	4.09	37.52	200	360	Peak
4824	33.04	48.34	54	-20.96	30.99	6.79	53.08	110	252	Average
4824	45.14	60.44	74	-28.86	30.99	6.79	53.08	110	252	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2412 MHz: Fundamental frequency.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2315.31	54.26	61.03	74	-19.74	26.67	4.03	37.47	203	60	Peak
2363.73	34.78	41.39	54	-19.22	26.81	4.07	37.49	203	60	Average
2437	89.8	96.08			27.06	4.12	37.46	203	60	Average
2437	99.79	106.07			27.06	4.12	37.46	203	60	Peak
2491.08	36.2	42.16	54	-17.8	27.2	4.16	37.32	203	60	Average
2493.52	54.22	60.11	74	-19.78	27.2	4.16	37.25	203	60	Peak
4874	33.17	48.31	54	-20.83	31.06	6.85	53.05	105	329	Average
4874	42.91	58.05	74	-31.09	31.06	6.85	53.05	105	329	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2377.86	34.57	41.14	54	-19.43	26.86	4.07	37.5	200	360	Average
2378.85	52.08	58.65	74	-21.92	26.86	4.07	37.5	200	360	Peak
2437	87.59	93.87			27.06	4.12	37.46	200	360	Average
2437	97.72	104			27.06	4.12	37.46	200	360	Peak
2485.6	35.53	41.55	54	-18.47	27.15	4.15	37.32	200	360	Average
2492.2	51.12	57.01	74	-22.88	27.2	4.16	37.25	200	360	Peak
4874	33.59	48.73	54	-20.41	31.06	6.85	53.05	111	258	Average
4874	43.53	58.67	74	-30.47	31.06	6.85	53.05	111	258	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.



EUT Test Condition		Measurement Detail	
Channel	Channel 11	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	88.61	94.77			27.1	4.13	37.39	203	60	Average
2462	98.81	104.97			27.1	4.13	37.39	203	60	Peak
2483.52	36.9	42.92	54	-17.1	27.15	4.15	37.32	203	60	Average
2484	54.91	60.93	74	-19.09	27.15	4.15	37.32	203	60	Peak
4924	33.41	48.44	54	-20.59	31.12	6.88	53.03	105	316	Average
4924	43.07	58.1	74	-30.93	31.12	6.88	53.03	105	316	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	86.29	92.45			27.1	4.13	37.39	200	359	Average
2462	96.29	102.45			27.1	4.13	37.39	200	359	Peak
2485.6	36.06	42.08	54	-17.94	27.15	4.15	37.32	200	359	Average
2488.4	53.66	59.62	74	-20.34	27.2	4.16	37.32	200	359	Peak
4924	33.31	48.34	54	-20.69	31.12	6.88	53.03	113	253	Average
4924	43.11	58.14	74	-30.89	31.12	6.88	53.03	113	253	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2462 MHz: Fundamental frequency.

802.11n (HT40)

EUT Test Condition		Measurement Detail	
Channel	Channel 3	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

**Antennal Polarity & Test Distance: Horizontal at 3 m**

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.86	40.44	46.95	54	-13.56	26.91	4.08	37.5	201	60	Average
2386.86	52.89	59.4	74	-21.11	26.91	4.08	37.5	201	60	Peak
2422	86.04	92.38			27.01	4.11	37.46	201	60	Average
2422	95.62	101.96			27.01	4.11	37.46	201	60	Peak
2492.8	49.69	55.58	74	-24.31	27.2	4.16	37.25	201	60	Peak
2494.04	37.88	43.77	54	-16.12	27.2	4.16	37.25	201	60	Average
4844	32.89	48.12	54	-21.11	31.01	6.82	53.06	106	320	Average
4844	43.21	58.44	74	-30.79	31.01	6.82	53.06	106	320	Peak

**Antennal Polarity & Test Distance: Vertical at 3 m**

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.38	52.43	58.94	74	-21.57	26.91	4.08	37.5	200	360	Peak
2389.47	40.15	46.66	54	-13.85	26.91	4.08	37.5	200	360	Average
2422	85.09	91.43			27.01	4.11	37.46	200	360	Average
2422	94.84	101.18			27.01	4.11	37.46	200	360	Peak
2493.64	53.38	59.27	74	-20.62	27.2	4.16	37.25	200	360	Peak
2495.48	36.91	42.8	54	-17.09	27.2	4.16	37.25	200	360	Average
4844	33.12	48.35	54	-20.88	31.01	6.82	53.06	113	241	Average
4844	42.76	57.99	74	-31.24	31.01	6.82	53.06	113	241	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2422 MHz: Fundamental frequency.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2388.84	35.59	42.1	54	-18.41	26.91	4.08	37.5	203	59	Average
2389.74	49.2	55.71	74	-24.8	26.91	4.08	37.5	203	59	Peak
2437	86.22	92.5			27.06	4.12	37.46	203	59	Average
2437	95.17	101.45			27.06	4.12	37.46	203	59	Peak
2484.16	50.45	56.47	74	-23.55	27.15	4.15	37.32	203	59	Peak
2484.64	37.6	43.62	54	-16.4	27.15	4.15	37.32	203	59	Average
4874	33.5	48.64	54	-20.5	31.06	6.85	53.05	108	324	Average
4874	43.14	58.28	74	-30.86	31.06	6.85	53.05	108	324	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2381.46	47.3	53.86	74	-26.7	26.86	4.08	37.5	200	360	Peak
2389.92	35.55	42.08	54	-18.45	26.91	4.08	37.52	200	360	Average
2437	84.71	90.99			27.06	4.12	37.46	200	360	Average
2437	94.82	101.1			27.06	4.12	37.46	200	360	Peak
2484.6	48.9	54.92	74	-25.1	27.15	4.15	37.32	200	360	Peak
2484.96	37.28	43.3	54	-16.72	27.15	4.15	37.32	200	360	Average
4874	33.37	48.51	54	-20.63	31.06	6.85	53.05	111	251	Average
4874	42.72	57.86	74	-31.28	31.06	6.85	53.05	111	251	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.

EUT Test Condition		Measurement Detail	
Channel	Channel 9	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2387.22	35.55	42.06	54	-18.45	26.91	4.08	37.5	204	62	Average
2387.85	47.15	53.66	74	-26.85	26.91	4.08	37.5	204	62	Peak
2452	84.98	91.18			27.06	4.13	37.39	204	62	Average
2452	94.63	100.83			27.06	4.13	37.39	204	62	Peak
2483.52	40.75	46.77	54	-13.25	27.15	4.15	37.32	204	62	Average
2490.44	55.87	61.83	74	-18.13	27.2	4.16	37.32	204	62	Peak
4904	33.55	48.6	54	-20.45	31.1	6.88	53.03	108	320	Average
4904	44.71	59.76	74	-29.29	31.1	6.88	53.03	108	320	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2366.07	50.04	56.66	74	-23.96	26.81	4.07	37.5	200	360	Peak
2378.31	35.29	41.86	54	-18.71	26.86	4.07	37.5	200	360	Average
2452	83.56	89.76			27.06	4.13	37.39	200	360	Average
2452	93.87	100.07			27.06	4.13	37.39	200	360	Peak
2484.36	51.45	57.47	74	-22.55	27.15	4.15	37.32	200	360	Peak
2485.04	38.72	44.74	54	-15.28	27.15	4.15	37.32	200	360	Average
4904	33.59	48.64	54	-20.41	31.1	6.88	53.03	110	255	Average
4904	42.93	57.98	74	-31.07	31.1	6.88	53.03	110	255	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2452 MHz: Fundamental frequency.

**9 kHz ~ 30 MHz DATA:**

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

**30 MHz ~ 1 GHz WORST-CASE DATA:**

**Mode A**

**802.11g**

EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	30 MHz ~ 1 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Getaz Yang

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
159.98	21.3	39.3	43.5	-22.2	12.73	1.15	31.88	136	219	Peak
263.77	24.86	43.37	46	-21.14	11.88	1.53	31.92	109	227	Peak
324.88	23.74	40.35	46	-22.26	13.54	1.7	31.85	108	311	Peak
412.18	22.43	36.92	46	-23.57	15.58	1.93	32	135	159	Peak
504.33	25.52	37.61	46	-20.48	17.42	2.1	31.61	103	244	Peak
647.89	25.63	35.12	46	-20.37	20.19	2.35	32.03	131	70	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
32.91	25.19	43.21	40	-14.81	12.47	0.6	31.09	116	341	Peak
120.21	24.67	44.39	43.5	-18.83	11.02	1.16	31.9	118	140	Peak
263.77	24.99	43.5	46	-21.01	11.88	1.53	31.92	111	156	Peak
318.09	24.69	41.53	46	-21.31	13.38	1.68	31.9	129	45	Peak
504.33	27.23	39.32	46	-18.77	17.42	2.1	31.61	139	171	Peak
647.89	27.72	37.21	46	-18.28	20.19	2.35	32.03	112	39	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCS 30	100288	Aug. 18, 2016	Aug. 17, 2017
RF signal cable Woken	5D-FB	Cable-cond2-01	Dec. 22, 2016	Dec. 21, 2017
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Jan. 17, 2017	Jan. 16, 2018
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 26, 2016	Jul. 25, 2017
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.

#### 4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note: 1. Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.


#### 4.2.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/5/19

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
<b>1</b>	<b>0.15000</b>	<b>10.06</b>	<b>47.82</b>	<b>24.25</b>	<b>57.88</b>	<b>34.31</b>	<b>66.00</b>	<b>56.00</b>	<b>-8.12</b>	<b>-21.69</b>
2	0.17734	9.98	42.89	26.56	52.87	36.54	64.61	54.61	-11.74	-18.07
3	0.21641	9.92	36.73	22.04	46.65	31.96	62.96	52.96	-16.31	-21.00
4	0.47813	9.92	22.78	12.37	32.70	22.29	56.37	46.37	-23.67	-24.08
5	3.33594	10.01	12.68	6.90	22.69	16.91	56.00	46.00	-33.31	-29.09
6	13.50781	10.18	14.91	4.45	25.09	14.63	60.00	50.00	-34.91	-35.37

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/5/19

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.88	43.38	28.45	53.26	38.33	65.79	55.79	-12.53	-17.46
2	0.19297	9.80	40.11	23.35	49.91	33.15	63.91	53.91	-14.00	-20.76
3	0.28672	9.86	28.05	10.03	37.91	19.89	60.62	50.62	-22.71	-30.73
4	0.46641	9.95	21.44	14.54	31.39	24.49	56.58	46.58	-25.19	-22.09
5	2.91406	10.07	13.20	8.10	23.27	18.17	56.00	46.00	-32.73	-27.83
6	12.83594	10.19	13.13	6.43	23.32	16.62	60.00	50.00	-36.68	-33.38

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6 dB Bandwidth Measurement

#### 4.3.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

##### Mode A

##### 802.11b

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	10.09	0.5	Pass
6	2437	10.14	0.5	Pass
11	2462	10.09	0.5	Pass

##### 802.11g

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	15.17	0.5	Pass
6	2437	15.18	0.5	Pass
11	2462	15.16	0.5	Pass

##### Mode B

##### 802.11n (HT20)


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	15.16	15.70	0.5	Pass
6	2437	15.16	15.73	0.5	Pass
11	2462	15.13	15.14	0.5	Pass

##### 802.11n (HT40)


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	33.89	35.15	0.5	Pass
6	2437	33.89	35.14	0.5	Pass
9	2452	33.96	35.14	0.5	Pass

### Spectrum Plot of Worst Value


#### 802.11b




#### 802.11g



#### 802.11n (HT20)



#### 802.11n (HT40)



## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20 MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.4.7 Test Results

##### Mode A

##### 802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	129.42	21.12	30	Pass
6	2437	135.207	21.31	30	Pass
11	2462	133.968	21.27	30	Pass

##### 802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	285.102	24.55	30	Pass
6	2437	293.765	24.68	30	Pass
11	2462	286.418	24.57	30	Pass

##### Mode B

##### 802.11n (HT20)

Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	21.14	11.11	142.929	21.55	30	Pass
6	2437	21.33	10.73	147.661	21.69	30	Pass
11	2462	20.87	9.60	131.3	21.18	30	Pass

##### 802.11n (HT40)


Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	20.38	9.26	117.577	20.70	30	Pass
6	2437	20.44	9.42	119.412	20.77	30	Pass
9	2452	20.39	8.37	116.267	20.65	30	Pass

## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.5.7 Test Results

##### Mode A

##### 802.11b

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Pass / Fail
1	2412	-7.06	8	Pass
6	2437	-7.53	8	Pass
11	2462	-7.01	8	Pass

##### 802.11g

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Pass / Fail
1	2412	-10.85	8	Pass
6	2437	-10.07	8	Pass
11	2462	-10.00	8	Pass

##### Mode B

##### 802.11n (HT20)

TX Chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Total PSD (dBm)	Limit (dBm)	Pass / Fail
0	1	2412	-13.10	3.01	-10.09	8	Pass
	6	2437	-12.86	3.01	-9.85	8	Pass
	11	2462	-13.16	3.01	-10.15	8	Pass
1	1	2412	-19.43	3.01	-16.42	8	Pass
	6	2437	-19.79	3.01	-16.78	8	Pass
	11	2462	-19.43	3.01	-16.42	8	Pass

**NOTE:** Directional gain = 2 dBi + 10log(2) = 5.01 dBi < 6 dBi, so the limit no need to reduced.

##### 802.11n (HT40)


TX Chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Total PSD (dBm)	Limit (dBm)	Pass / Fail
0	3	2422	-15.56	3.01	-12.55	8	Pass
	6	2437	-15.77	3.01	-12.76	8	Pass
	9	2452	-16.13	3.01	-13.12	8	Pass
1	3	2422	-22.89	3.01	-19.88	8	Pass
	6	2437	-22.47	3.01	-19.46	8	Pass
	9	2452	-23.19	3.01	-20.18	8	Pass

**NOTE:** Directional gain = 2 dBi + 10log(2) = 5.01 dBi < 6 dBi, so the limit no need to reduced.




### Spectrum Plot of Worst Value


#### 802.11b




#### 802.11g



#### 802.11n (HT20)



#### 802.11n (HT40)




## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 4.6.7 Test Results


The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement.


#### Mode A 802.11b



### Ch 1 Band Edge





### Ch 11 Band Edge





# 802.11g



## Ch 1




## Ch 6




## Ch 11




### Ch 1 Band Edge




### Ch 11 Band Edge




**Mode B**  
**802.11n (HT20)**  
**CHAIN 0**



### Ch 1 Band Edge





### Ch 11 Band Edge







# CHAIN 1



## Ch 1




## Ch 6




## Ch 11



### Ch 1 Band Edge





### Ch 11 Band Edge





802.11n (HT40)  
CHAIN 0



Ch 3




Ch 6




Ch 9



### Ch 3 Band Edge





### Ch 9 Band Edge





# CHAIN 1



## Ch 3





## Ch 6



## Ch 9





## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---