



FCC RADIO TEST REPORT

FCC ID : QYLEM9190B
Equipment : Wireless Module
Brand Name : Getac
Model Name : EM9190
Applicant : Getac Technology Corporation.
5F., Building A, No. 209, Sec.1, Nangang Rd.,
Nangang Dist., Taipei City 11568, Taiwan, R.O.C.
Standard : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)

The product was received on Dec. 21, 2020 and testing was started from Jan. 27, 2021 and completed on Mar. 05, 2021. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	6
1.3 Testing Location	6
1.4 Applicable Standards	7
2 Test Configuration of Equipment Under Test	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration	9
2.4 Frequency List of Low/Middle/High Channels.....	9
3 Conducted Test Result	10
3.1 Measuring Instruments.....	10
3.2 Conducted Output Power and ERP/EIRP	11
4 Radiated Test Items	12
4.1 Measuring Instruments.....	12
4.2 Test Setup	12
4.3 Test Result of Radiated Test.....	13
4.4 Field Strength of Spurious Radiation Measurement	14
5 List of Measuring Equipment.....	15
6 Uncertainty of Evaluation	17
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of Radiated Test	
Appendix C. Test Setup Photographs	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Pass	-
	§22.913 (a)(2)	Effective Radiated Power (WCDMA Band V)		
	§24.232 (c)	Equivalent Isotropic Radiated Power (WCDMA Band II)		
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power (WCDMA Band IV)		
-	§24.232 (d)	Peak-to-Average Ratio	-	See Note
-	§2.1049 §22.917 (b) §24.238 (b) §27.53 (g)	Occupied Bandwidth (WCDMA Band V) (WCDMA Band II) (WCDMA Band IV)	-	See Note
-	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Band Edge Measurement (WCDMA Band V) (WCDMA Band II) (WCDMA Band IV)	-	See Note
-	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Conducted Emission (WCDMA Band V) (WCDMA Band II) (WCDMA Band IV)	-	See Note
-	§2.1055 §22.355 §24.235 §27.54	Frequency Stability Temperature & Voltage	-	See Note
4.4	§2.1053 §22.917 (a) §24.238 (a) §27.53 (h)	Field Strength of Spurious Radiation (WCDMA Band V) (WCDMA Band II) (WCDMA Band IV)	Pass	Under limit 33.60 dB at 7518.000 MHz

Note: The module (Model: EM9190) makes no difference after verifying output power, this report reuses test data from the module report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Celery Wei



1 General Description

1.1 Product Feature of Equipment Under Test

WCDMA/LTE/5G NR, and GNSS.

Product Specification subjective to this standard	
Sample 1	EUT with Host 1
Sample 2	EUT with Host 2
Antenna Type	WWAN: PIFA Antenna GPS/Glonass/BDS/Galileo/SBAS: PATCH Antenna
Antenna Gain	Cellular Band: 0.95 dBi PCS Band: 2.28 dBi AWS Band: 2.64 dBi

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

The product was installed into Notebook (Brand Name: Getac, Model Name: B360, B360 Pro) during test, and the host information was recorded in the following table.

Host Information	
Host 1	Host with SKU A
Host 2	Host with SKU B

Host Sample Information		
B360	SKUA	SKUB
CPU	i7-10610U	i7-10710U
Memory(DDR4)	8G	8G
Storage(OPAL SSD)	Main:256GB	Main:256GB
	Second:256GB	Second:256GB
WLAN	AX200NGW	AX200NGW
WWAN	EM9190	EM9190
Camera FN20FF-679H (RGB)	N/A	v
Camera FN23FF-678H (RGB+IR)	v	N/A
FINGERPRINT	v	v
VGA	v	N/A
HDMI	v	v
RS232	v	v
LAN	v	v
USB	v	v
USB3.1 Type C	N/A	v
Smart Card	v	v
SD Card Reader	N/A	N/A
ODD(Expansion)	N/A	v
RS232(Expansion)	N/A	v
Touch Screen	v	v
PCMCIA	v	v
GPS	v	v



1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH05-HY
Test Engineer	Hao Syu and Howard Lin
Temperature	20.3~23.6°C
Relative Humidity	43.3~54.3%

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH12-HY (TAF Code: 3786)
Test Engineer	Jack Cheng, Lance Chiang and Chuan Chu
Temperature	24.3~26.4°C
Relative Humidity	58~66%
Remark	The Radiated test item subcontracted to Sporton International Inc. Wensan Laboratory

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for WCDMA Band V
2. 30 MHz to 18000 MHz for WCDMA Band IV
3. 30 MHz to 19100 MHz for WCDMA Band II

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System





2.3 Support Unit used in test configuration

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

2.4 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6


3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for WCDMA Band V

The EIRP of mobile transmitters must not exceed 2 Watts for WCDMA Band II

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select the lowest, middle, and the highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
11. $ERP (dBm) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jul. 14, 2020	Jan. 27, 2021~ Feb. 02, 2021	Jul. 13, 2021	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	40103 & 07	30MHz~1GHz	Apr. 29, 2020	Jan. 27, 2021~ Feb. 02, 2021	Apr. 28, 2021	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1328	1GHz~18GHz	Nov. 23, 2020	Jan. 27, 2021~ Feb. 02, 2021	Nov. 22, 2021	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-1241	1GHz ~ 18GHz	Jul. 15, 2020	Jan. 27, 2021~ Feb. 02, 2021	Jul. 14, 2021	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917058 4	18GHz~40GHz	Dec. 11, 2020	Jan. 27, 2021~ Feb. 02, 2021	Dec. 10, 2021	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917057 6	18GHz ~ 40GHz	May 22, 2020	Jan. 27, 2021~ Feb. 02, 2021	May 21, 2021	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2020	Jan. 27, 2021~ Feb. 02, 2021	Mar. 24, 2021	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY57280120	1GHz~26.5GHz	Jul. 20, 2020	Jan. 27, 2021~ Feb. 02, 2021	Jul. 19, 2021	Radiation (03CH12-HY)
Preamplifier	E-INSTRUME NT TECH LTD.	ERA-100M-18 G-56-01-A70	EC1900249	1GHz~18GHz	Dec. 05, 2020	Jan. 27, 2021~ Feb. 02, 2021	Dec. 04, 2021	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 11, 2020	Jan. 27, 2021~ Feb. 02, 2021	Dec. 10, 2021	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY54200485	10Hz~44GHz	Feb. 10, 2020	Jan. 27, 2021~ Feb. 02, 2021	Feb. 09, 2021	Radiation (03CH12-HY)
Signal Generator	Anritsu	MG3694C	163401	0.1Hz~40GHz	Feb. 15, 2020	Jan. 27, 2021~ Feb. 02, 2021	Feb. 14, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz~30MHz	Mar. 12, 2020	Jan. 27, 2021~ Feb. 02, 2021	Mar. 11, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 11, 2020	Jan. 27, 2021~ Feb. 02, 2021	Dec. 10, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 25, 2020	Jan. 27, 2021~ Feb. 02, 2021	Feb. 24, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 25, 2020	Jan. 27, 2021~ Feb. 02, 2021	Feb. 24, 2021	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP140349	N/A	Oct. 02, 2020	Jan. 27, 2021~ Feb. 02, 2021	Oct. 01, 2021	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jan. 27, 2021~ Feb. 02, 2021	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jan. 27, 2021~ Feb. 02, 2021	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jan. 27, 2021~ Feb. 02, 2021	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Jan. 27, 2021~ Feb. 02, 2021	N/A	Radiation (03CH12-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Radio Communication Analyzer	Anritsu	MT8821C	6261849015	LTE	Sep. 18, 2020	Mar. 05, 2021	Sep. 17, 2021	Conducted (TH05-HY)
5G Wireless Test Platform	Anritsu	MT8000A	6261940327	FR1 (+MT8821C SN:6261849015)	Sep. 23, 2020	Mar. 05, 2021	Sep. 22, 2021	Conducted (TH05-HY)
Base Station (Measure)	Anritsu	MT8821C	6262002534 1	N/A	Oct. 06, 2020	Mar. 05, 2021	Oct. 05, 2021	Conducted (TH05-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.07
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.21
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.80
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power & ERP/EIRP)

WCDMA Band V Maximum Average Power [dBm] (GT - LC = 0.95 dB)					
Channel	4132	4182	4233	ERP (dBm)	ERP (W)
Frequency	826.4	836.4	846.6		
RMC 12.2K	23.83	23.92	23.84	23.92	0.2466
HSDPA Subtest-1	22.65	22.86	22.76		
HSDPA Subtest-2	22.81	22.81	22.85		
HSDPA Subtest-3	22.41	22.36	22.48		
HSDPA Subtest-4	22.27	22.33	22.44		
HSUPA Subtest-1	22.84	22.83	22.71		
HSUPA Subtest-2	20.87	20.91	20.74		
HSUPA Subtest-3	21.81	21.79	21.94		
HSUPA Subtest-4	20.79	20.92	20.93		
HSUPA Subtest-5	22.95	22.94	22.72		
Limit	ERP < 7W				

WCDMA Band II Maximum Average Power [dBm] (GT - LC = 2.28 dB)					
Channel	9262	9400	9538	EIRP (dBm)	EIRP (W)
Frequency	1852.4	1880	1907.6		
RMC 12.2K	23.81	23.91	23.89	23.91	0.2460
HSDPA Subtest-1	22.68	22.84	22.71		
HSDPA Subtest-2	22.62	22.95	22.79		
HSDPA Subtest-3	22.33	22.47	22.50		
HSDPA Subtest-4	22.43	22.30	22.44		
HSUPA Subtest-1	22.78	22.83	22.87		
HSUPA Subtest-2	20.90	20.96	20.85		
HSUPA Subtest-3	21.92	21.94	21.84		
HSUPA Subtest-4	20.69	20.92	20.94		
HSUPA Subtest-5	22.89	22.80	22.81		
Limit	EIRP < 2W				

WCDMA Band IV Maximum Average Power [dBm] (GT - LC = 2.64 dB)					
Channel	1312	1413	1513	EIRP (dBm)	EIRP (W)
Frequency	1712.4	1732.6	1752.6		
RMC 12.2K	23.63	23.66	23.74	23.74	0.2366
HSDPA Subtest-1	22.67	22.50	22.79		
HSDPA Subtest-2	22.63	22.63	22.84		
HSDPA Subtest-3	22.07	22.11	22.26		
HSDPA Subtest-4	21.95	22.19	22.04		
HSUPA Subtest-1	22.47	22.86	22.90		
HSUPA Subtest-2	20.80	20.49	20.61		
HSUPA Subtest-3	21.83	21.54	21.73		
HSUPA Subtest-4	20.45	20.63	20.80		
HSUPA Subtest-5	22.70	22.52	22.88		
Limit	EIRP < 1W				



Appendix B. Test Results of Radiated Test

<Sample 1>

WCDMA 1900

WCDMA 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-54.96	-13	-41.96	-72.89	-66.17	1.41	12.62	H
	5556	-50.95	-13	-37.95	-73.77	-62.51	1.74	13.30	H
	7410	-46.82	-13	-33.82	-73.8	-56.12	1.94	11.24	H
									H
									H
									H
	3702	-54.31	-13	-41.31	-72.39	-65.52	1.41	12.62	V
	5556	-51.50	-13	-38.50	-73.86	-63.06	1.74	13.30	V
	7410	-47.03	-13	-34.03	-73.86	-56.33	1.94	11.24	V
									V
									V
									V
Middle	3762	-54.70	-13	-41.70	-72.88	-65.93	1.43	12.66	H
	5640	-51.33	-13	-38.33	-74.21	-62.90	1.73	13.30	H
	7518	-46.97	-13	-33.97	-73.44	-56.08	1.99	11.10	H
									H
									H
									H
	3762	-54.44	-13	-41.44	-72.84	-65.67	1.43	12.66	V
	5640	-51.57	-13	-38.57	-74.04	-63.14	1.73	13.30	V
	7518	-46.60	-13	-33.60	-73.03	-55.71	1.99	11.10	V
									V
									V
									V



Highest	3816	-54.55	-13	-41.55	-72.92	-65.80	1.44	12.69	H
	5724	-50.88	-13	-37.88	-74.18	-62.45	1.73	13.30	H
	7632	-47.86	-13	-34.86	-73.9	-56.98	2.01	11.13	H
									H
									H
									H
	3816	-54.33	-13	-41.33	-72.94	-65.58	1.44	12.69	V
	5724	-51.68	-13	-38.68	-74.35	-63.25	1.73	13.30	V
	7632	-47.94	-13	-34.94	-73.89	-57.06	2.01	11.13	V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



<Sample 2>

WCDMA 850

WCDMA 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1656	-62.58	-13	-49.58	-71.06	-68.20	0.92	8.69	H
	2480	-59.08	-13	-46.08	-72.61	-66.46	1.15	10.67	H
	3304	-57.90	-13	-44.90	-73.21	-66.45	1.32	12.03	H
									H
									H
									H
	1656	-63.06	-13	-50.06	-70.97	-68.68	0.92	8.69	V
	2480	-58.84	-13	-45.84	-72.54	-66.22	1.15	10.67	V
	3304	-57.61	-13	-44.61	-73.39	-66.16	1.32	12.03	V
									V
									V
									V
Middle	1664	-58.16	-13	-45.16	-66.66	-63.81	0.93	8.72	H
	2512	-59.10	-13	-46.10	-72.66	-66.51	1.15	10.71	H
	3344	-57.73	-13	-44.73	-72.93	-66.37	1.33	12.13	H
									H
									H
									H
	1664	-61.76	-13	-48.76	-69.67	-67.41	0.93	8.72	V
	2512	-58.20	-13	-45.20	-71.95	-65.61	1.15	10.71	V
	3344	-57.34	-13	-44.34	-72.99	-65.98	1.33	12.13	V
									V
									V
									V



Highest	1696	-62.55	-13	-49.55	-71.14	-68.31	0.94	8.84	H
	2536	-59.39	-13	-46.39	-72.96	-66.82	1.16	10.74	H
	3384	-58.17	-13	-45.17	-73.26	-66.90	1.34	12.22	H
									H
									H
									H
	1696	-63.61	-13	-50.61	-71.49	-69.37	0.94	8.84	V
	2536	-59.13	-13	-46.13	-72.83	-66.56	1.16	10.74	V
	3384	-57.53	-13	-44.53	-73.06	-66.26	1.34	12.22	V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA 1700

WCDMA 1700									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3427	-57.23	-13	-44.23	-73.22	-68.21	1.35	12.32	H
	5135	-52.34	-13	-39.34	-74.29	-63.48	1.65	12.79	H
	6850	-49.12	-13	-36.12	-74.53	-59.49	1.74	12.11	H
									H
									H
									H
	3427	-56.42	-13	-43.42	-72.82	-67.40	1.35	12.32	V
	5135	-52.81	-13	-39.81	-74.51	-63.95	1.65	12.79	V
	6850	-49.57	-13	-36.57	-74.57	-59.94	1.74	12.11	V
									V
									V
									V
Middle	3462	-56.91	-13	-43.91	-73.24	-67.97	1.35	12.41	H
	5198	-52.50	-13	-39.50	-74.43	-63.72	1.66	12.88	H
	6927	-48.19	-13	-35.19	-73.98	-58.46	1.73	12.00	H
									H
									H
									H
	3462	-56.23	-13	-43.23	-72.95	-67.29	1.35	12.41	V
	5198	-52.75	-13	-39.75	-74.52	-63.97	1.66	12.88	V
	6927	-48.72	-13	-35.72	-74.06	-58.99	1.73	12.00	V
									V
									V
									V



Highest	3504	-56.39	-13	-43.39	-73.11	-67.53	1.36	12.50	H
	5254	-52.62	-13	-39.62	-74.75	-63.90	1.68	12.96	H
	7011	-47.69	-13	-34.69	-73.9	-57.85	1.73	11.88	H
									H
									H
									H
									H
	3504	-56.02	-13	-43.02	-73.09	-67.16	1.36	12.50	V
	5254	-52.88	-13	-39.88	-74.78	-64.16	1.68	12.96	V
	7011	-48.09	-13	-35.09	-73.81	-58.25	1.73	11.88	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA 1900

WCDMA 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-55.15	-13	-42.15	-73.08	-66.36	1.41	12.62	H
	5556	-50.70	-13	-37.70	-73.85	-62.26	1.74	13.30	H
	7410	-47.51	-13	-34.51	-74.3	-56.81	1.94	11.24	H
									H
									H
									H
	3702	-54.98	-13	-41.98	-73.06	-66.19	1.41	12.62	V
	5556	-51.20	-13	-38.20	-73.89	-62.76	1.74	13.30	V
	7410	-47.32	-13	-34.32	-73.96	-56.62	1.94	11.24	V
									V
									V
									V
Middle	3762	-54.67	-13	-41.67	-72.87	-65.90	1.43	12.66	H
	5640	-51.47	-13	-38.47	-74.69	-63.04	1.73	13.30	H
	7518	-47.71	-13	-34.71	-73.99	-56.82	1.99	11.10	H
									H
									H
									H
	3762	-54.44	-13	-41.44	-72.86	-65.67	1.43	12.66	V
	5640	-51.75	-13	-38.75	-74.56	-63.32	1.73	13.30	V
	7518	-47.54	-13	-34.54	-73.78	-56.65	1.99	11.10	V
									V
									V
									V



Highest	3816	-54.61	-13	-41.61	-73.02	-65.86	1.44	12.69	H
	5724	-50.80	-13	-37.80	-74.45	-62.37	1.73	13.30	H
	7632	-48.33	-13	-35.33	-74.18	-57.45	2.01	11.13	H
									H
									H
									H
	3816	-54.56	-13	-41.56	-73.21	-65.81	1.44	12.69	V
	5724	-51.45	-13	-38.45	-74.47	-63.02	1.73	13.30	V
	7632	-48.40	-13	-35.40	-74.16	-57.52	2.01	11.13	V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.