



FCC RADIO TEST REPORT

FCC ID : QYLPN7462S
Equipment : NFC Module
Brand Name : Getac
Model Name : S410G4 PN7462
Applicant : Getac Technology Corporation.
5F., Building A, No. 209, Sec.1, Nangang
Rd., Nangang Dist., Taipei City 11568, Taiwan, R.O.C.
Standard : FCC Part 15 Subpart C §15.225

The product was received on Sep. 23, 2020 and testing was started from Oct. 12, 2020 and completed on Oct. 22, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Reviewed by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1. General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	6
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2. Test Configuration of Equipment Under Test.....	7
2.1 Descriptions of Test Mode.....	7
2.2 Connection Diagram of Test System.....	8
2.3 Table for Supporting Units.....	8
2.4 EUT Operation Test Setup	9
3. Test Results	10
3.1 AC Power Line Conducted Emissions Measurement	10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement.....	12
3.3 Frequency Stability Measurement	13
3.4 Field Strength of Fundamental Emissions and Mask Measurement.....	14
3.5 Radiated Emissions Measurement	16
3.6 Antenna Requirements.....	19
4. List of Measuring Equipment	20
5. Uncertainty of Evaluation	21
Appendix A. Test Results of Conducted Emission Test	
Appendix B. Test Results of Conducted Test Items	
B1. Test Result of 20dB Spectrum Bandwidth	
B2. Test Result of Frequency Stability	
Appendix C. Test Results of Radiated Test Items	
C1. Test Result of Field Strength of Fundamental Emissions	
C2. Results of Radiated Emissions (9 kHz~30MHz)	
C3. Results of Radiated Emissions (30MHz~1GHz)	
Appendix D. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR5N3002-88	01	Initial issue of report	Dec. 01, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.207	AC Power Line Conducted Emissions	Pass
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass
	2.1049	99% OBW Spectrum Bandwidth	Reporting only
3.3	15.225(e)	Frequency Stability	Pass
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass
3.6	15.203	Antenna Requirements	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Cindy Liu



1. General Description

1.1 Product Feature of Equipment Under Test

NFC

Product Specification subjective to this standard	
Antenna Type	Loop Antenna

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

The product was installed into Notebook (Brand Name: Getac, Model Name: S410, S410G4, S410XXXXX (X = 0~9, A~Z, a~z, "-" or blank, for marketing use only, with no impact on RF compliance of the product)) during test, and the host information was recorded in the following table.

<Sample Information>

Report Sample	Sample 1	Sample 2	Sample 3
DVT SKUs	S410G4 SKU A	S410G4 SKU B	S410G4 SKU C
CPU	Tiger Lake QS-i5-vPro	Tiger Lake QS-i7-vPro	Tiger Lake QS-3-i7-None-vPro
Display Resolution	HD	HD	FHD
Discrete Graphics	Not Support	Not Support	MXM
Wifi/BT	Support(AX201)	Support(AX201)	Support(AX201)
Touch	Not Support	Support	Support
Sunlight Readable	Support	Support	Support
Main Storage	SSD 256GB	SSD 512GB	SSD 1TB
Battery	Main	Main	Main
2nd Storage	Not Support	SATA SDATN8Y-1TB	Not Support
Webcam	Support	Support	Support
Smart Card	Support	Support	Support
Option I/O Ports	RS232 + VGA + PowerShare USB2.0	RS232 + DP + PowerShare USB2.0	RS232 + DP + 2nd LAN
Discrete GPS	Support(MC1010G)	Support(EM7511)	Not Support
Finger Print	Not Support	Not Support	Support
Contactless Smart Card(NFC)	Not Support	Not Support	Support
LTE	Not Support	Support(EM7511)	Not Support



1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH03-HY	CO05-HY	03CH07-HY
Test Engineer	Oscar Chi	Howard Huang and Bor-Shiang Huang	Stan Hsieh and Ken Wu
Temperature	24.7°C	24~26°C	23~25°C
Relative Humidity	54.3%	42~50%	56~62%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.


The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report.

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) Idle + Bluetooth Idle + NFC Link + TF + TC + Battery + Adapter 2 for Sample 3 Mode 2 : WLAN (5GHz) Idle + Bluetooth Idle + NFC On + TF + TC + Battery + Adapter 2 for Sample 3
Remark: 1. The worst case of conducted emission is mode 2; only the test data of it was reported. 2. For Radiated Test Cases, the tests were performed with Adapter 2 and Sample 3. 3. TF stands for test function, and consists of Color Bar, Camera, Fingerprint, and Touch Pen. 4. TC stands for test configuration, and consists of Earphone with Mic, Smart Card, SD Card, USB HD (USB 2.0 out*1, USB 3.0 out*2, Type C out*1), Monitor (HDMI out), Monitor (DP out), RJ-45 (LAN1) Link, RJ-45 (LAN2) Link, and RS-232 Cable (Load).	

2.2 Connection Diagram of Test System



2.3 Table for Supporting Units

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
4.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	LCD Monitor	DELL	U2312HMt	FCC DoC	N/A	Unshielded,1.8m
6.	LCD Monitor	DELL	P2715Qt	FCC DoC	N/A	Unshielded,1.8m
7.	USB HD	ADATA	HV620S-1T	FCC DoC	Shielded, 1.0m	N/A
8.	USB HD	lenovo	F310S	FCC DoC	Shielded, 1.0m	N/A
9.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
10.	Smart Card	N/A	N/A	N/A	N/A	N/A
11.	NFC Card	Metro Taipei	Easy Card	N/A	N/A	N/A



2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0 cm gap to the EUT.



3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than ± 100 ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.



3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

Remark:

- 1. The field strength test result is in 3m test distance, follow test rules the test data use distance extrapolation factor and reported in this report at 30m test result.
- 2. Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB)

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
 3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
 4. For Fundamental emissions, use the receiver to measure QP reading.
 5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
 6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
- Note: Emission level (dB μ V/m) = 20 log Emission level (μ V/m).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.



3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (µV/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4. List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	35419 & 03	30MHz~1GHz	Apr. 29, 2020	Oct. 12, 2020~ Oct. 13, 2020	Apr. 28, 2021	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Oct. 12, 2020~ Oct. 13, 2020	Dec. 25, 2020	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	May 19, 2020	Oct. 12, 2020~ Oct. 13, 2020	May 18, 2021	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4, MY28655/4	9kHz~30MHz	Feb. 25, 2020	Oct. 12, 2020~ Oct. 13, 2020	Feb. 24, 2021	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4, MY24971/4, MY15682/4	30MHz~1GHz	Feb. 25, 2020	Oct. 12, 2020~ Oct. 13, 2020	Feb. 24, 2021	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Oct. 12, 2020~ Oct. 13, 2020	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208368	Control Ant Mast	N/A	Oct. 12, 2020~ Oct. 13, 2020	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Oct. 12, 2020~ Oct. 13, 2020	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Oct. 12, 2020~ Oct. 13, 2020	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	N/A	Oct. 12, 2020~ Oct. 13, 2020	N/A	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz~26.5GHz	May 21, 2020	Oct. 12, 2020~ Oct. 13, 2020	May 20, 2021	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8-24	80504004656H	N/A	N/A	Oct. 12, 2020~ Oct. 13, 2020	N/A	Radiation (03CH07-HY)
AC Power Source	AC POWER	AFC-500W	F104070011	50Hz~60Hz	Apr. 09, 2020	Oct. 12, 2020	Apr. 08, 2021	Conducted (TH03-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Oct. 12, 2020	Mar. 01, 2021	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 03, 2020	Oct. 12, 2020	Sep. 02, 2021	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30°C ~70°C	Nov. 26, 2019	Oct. 12, 2020	Nov. 25, 2020	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 15, 2020~ Oct. 22, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Oct. 15, 2020~ Oct. 22, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Oct. 15, 2020~ Oct. 22, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Oct. 15, 2020~ Oct. 22, 2020	Nov. 19, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Oct. 15, 2020~ Oct. 22, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Oct. 15, 2020~ Oct. 22, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Oct. 15, 2020~ Oct. 22, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Oct. 15, 2020~ Oct. 22, 2020	Jan. 01, 2021	Conduction (CO05-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3
---	-----

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7
---	-----




Appendix A. Test Results of Conducted Emission Test

Test Engineer : Howard Huang and Bor-Shiang Huang	Temperature :	24~26°C
	Relative Humidity :	42~50%

EUT Information

Report NO : 5N3002-88
 Test Mode : Mode 2
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.87	55.88	26.01	L1	OFF	19.5
0.152250	50.28	---	65.88	15.60	L1	OFF	19.5
0.379050	---	28.98	48.30	19.32	L1	OFF	19.5
0.379050	43.93	---	58.30	14.37	L1	OFF	19.5
0.420630	---	20.08	47.44	27.36	L1	OFF	19.5
0.420630	37.87	---	57.44	19.57	L1	OFF	19.5
0.602250	---	28.49	46.00	17.51	L1	OFF	19.5
0.602250	43.01	---	56.00	12.99	L1	OFF	19.5
0.643560	---	26.54	46.00	19.46	L1	OFF	19.5
0.643560	42.83	---	56.00	13.17	L1	OFF	19.5
0.692250	---	21.64	46.00	24.36	L1	OFF	19.5
0.692250	39.74	---	56.00	16.26	L1	OFF	19.5
0.863250	---	24.54	46.00	21.46	L1	OFF	19.5
0.863250	41.80	---	56.00	14.20	L1	OFF	19.5
0.948750	---	29.19	46.00	16.81	L1	OFF	19.5
0.948750	43.48	---	56.00	12.52	L1	OFF	19.5
1.068000	---	27.29	46.00	18.71	L1	OFF	19.5
1.068000	42.12	---	56.00	13.88	L1	OFF	19.5
1.151250	---	23.60	46.00	22.40	L1	OFF	19.6
1.151250	41.18	---	56.00	14.82	L1	OFF	19.6
1.254750	---	18.45	46.00	27.55	L1	OFF	19.6

1.254750	35.38	---	56.00	20.62	L1	OFF	19.6
1.360410	---	23.55	46.00	22.45	L1	OFF	19.6
1.360410	39.95	---	56.00	16.05	L1	OFF	19.6
1.482000	---	26.71	46.00	19.29	L1	OFF	19.6
1.482000	41.26	---	56.00	14.74	L1	OFF	19.6
1.640130	---	23.27	46.00	22.73	L1	OFF	19.6
1.640130	38.55	---	56.00	17.45	L1	OFF	19.6
3.669000	---	29.88	46.00	16.12	L1	OFF	19.6
3.669000	38.49	---	56.00	17.51	L1	OFF	19.6
3.995250	---	29.69	46.00	16.31	L1	OFF	19.6
3.995250	38.37	---	56.00	17.63	L1	OFF	19.6
4.337250	---	31.76	46.00	14.24	L1	OFF	19.6
4.337250	40.73	---	56.00	15.27	L1	OFF	19.6
4.697160	---	34.55	46.00	11.45	L1	OFF	19.6
4.697160	44.57	---	56.00	11.43	L1	OFF	19.6
4.992540	---	36.53	46.00	9.47	L1	OFF	19.6
4.992540	46.06	---	56.00	9.94	L1	OFF	19.6
5.332560	---	35.63	50.00	14.37	L1	OFF	19.6
5.332560	44.09	---	60.00	15.91	L1	OFF	19.6
13.560000	---	42.86	50.00	7.14	L1	OFF	19.8
13.560000	48.22	---	60.00	11.78	L1	OFF	19.8

EUT Information

Report NO : 5N3002-88
 Test Mode : Mode 2
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	29.90	55.63	25.73	N	OFF	19.5
0.156750	50.43	---	65.63	15.20	N	OFF	19.5
0.381300	---	29.39	48.25	18.86	N	OFF	19.5
0.381300	44.42	---	58.25	13.83	N	OFF	19.5
0.411000	---	29.90	47.63	17.73	N	OFF	19.5
0.411000	44.37	---	57.63	13.26	N	OFF	19.5
0.616380	---	26.85	46.00	19.15	N	OFF	19.5
0.616380	42.82	---	56.00	13.18	N	OFF	19.5
0.681000	---	29.32	46.00	16.68	N	OFF	19.5
0.681000	44.21	---	56.00	11.79	N	OFF	19.5
0.867750	---	24.49	46.00	21.51	N	OFF	19.6
0.867750	42.17	---	56.00	13.83	N	OFF	19.6
0.936330	---	27.64	46.00	18.36	N	OFF	19.6
0.936330	43.17	---	56.00	12.83	N	OFF	19.6
1.087710	---	25.76	46.00	20.24	N	OFF	19.6
1.087710	41.65	---	56.00	14.35	N	OFF	19.6
1.176990	---	24.44	46.00	21.56	N	OFF	19.6
1.176990	41.61	---	56.00	14.39	N	OFF	19.6
1.263750	---	22.71	46.00	23.29	N	OFF	19.6
1.263750	38.37	---	56.00	17.63	N	OFF	19.6
1.378500	---	23.16	46.00	22.84	N	OFF	19.6

1.378500	40.51	---	56.00	15.49	N	OFF	19.6
1.527000	---	25.90	46.00	20.10	N	OFF	19.6
1.527000	41.23	---	56.00	14.77	N	OFF	19.6
1.720050	---	23.57	46.00	22.43	N	OFF	19.6
1.720050	39.26	---	56.00	16.74	N	OFF	19.6
3.669000	---	30.13	46.00	15.87	N	OFF	19.6
3.669000	38.76	---	56.00	17.24	N	OFF	19.6
3.966000	---	29.92	46.00	16.08	N	OFF	19.6
3.966000	39.32	---	56.00	16.68	N	OFF	19.6
4.237620	---	31.67	46.00	14.33	N	OFF	19.6
4.237620	40.71	---	56.00	15.29	N	OFF	19.6
4.521750	---	32.68	46.00	13.32	N	OFF	19.6
4.521750	42.90	---	56.00	13.10	N	OFF	19.6
5.046000	---	37.25	50.00	12.75	N	OFF	19.7
5.046000	46.67	---	60.00	13.33	N	OFF	19.7
5.374680	---	34.69	50.00	15.31	N	OFF	19.7
5.374680	43.57	---	60.00	16.43	N	OFF	19.7
13.560000	---	42.94	50.00	7.06	N	OFF	19.9
13.560000	48.28	---	60.00	11.72	N	OFF	19.9



Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
Date: 12.OCT.2020 09:50:04		Date: 12.OCT.2020 09:48:15	
20dB Bandwidth (kHz)	2.640	99% OccupiedBW(kHz)	2.240
Frequency range (MHz)	$f_L > 13.553$	13.55924	Test Result
	$f_H < 13.567$	13.56188	Complies

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.



B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
120	13.560560	-20	0	13.560560
			2	13.560560
			5	13.560560
			10	13.560560
		-10	0	13.560550
			2	13.560540
			5	13.560540
			10	13.560550
		0	0	13.560540
			2	13.560540
			5	13.560550
			10	13.560550
		10	0	13.560560
			2	13.560560
			5	13.560560
			10	13.560550
		20	0	13.560550
			2	13.560540
			5	13.560540
			10	13.560540
		30	0	13.560550
			2	13.560540
			5	13.560540
			10	13.560560
		40	0	13.560650
			2	13.560640
			5	13.560650
			10	13.560660




Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
		50	0	13.560680
			2	13.560700
			5	13.560700
			10	13.560700
Max.Deviation (MHz)	0.000560	Max.Deviation (MHz)		0.000700
Max.Deviation (ppm)	41.2979	Max.Deviation (ppm)		51.6224
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS




Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions




Frequency (MHz)	Level (dBμV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	19.93	40	-64.07	84	38.46	21.06	0.41	100	0	QP






C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)



Frequency (MHz)	Level (dBμV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.05021	-23.93	80	-57.52	33.59	36.43	19.5	0.14	-	-	Average
0.06825	-36.4	80	-67.32	30.92	24.45	19	0.15	-	-	Average
0.10904	-30.99	80	-57.84	26.85	30.33	18.5	0.18	-	-	QP
0.11008	-30.77	80	-57.54	26.77	30.55	18.5	0.18	-	-	Average
0.15272	-25.71	80	-49.64	23.93	35.42	18.67	0.2	-	-	Average
0.77538	7.86	40	-21.95	29.81	28.46	19.08	0.32	100	0	QP
13.56	19.93	40	-9.57	29.5	38.46	21.06	0.41	-	-	QP
13.992	-2.14	40	-31.64	29.5	16.34	21.1	0.42	-	-	QP
24.433	-2.69	40	-32.19	29.5	14.84	22.05	0.42	-	-	QP
29.37	-1.95	40	-31.45	29.5	14.73	22.45	0.87	-	-	QP



Test Mode :	NFC Tx	Polarization :	Vertical
-------------	--------	----------------	----------




Frequency (MHz)	Level (dBμV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01298	-15.58	80	-60.92	45.34	45.6	18.7	0.12	-	-	Average
0.06819	-37.6	80	-68.53	30.93	23.25	19	0.15	-	-	Average
0.10706	-36.41	80	-63.42	27.01	24.92	18.5	0.17	-	-	QP
0.11328	-35.81	80	-62.33	26.52	25.51	18.5	0.18	-	-	Average
0.15	-30.67	80	-54.75	24.08	30.46	18.67	0.2	-	-	Average
0.72281	4.73	40	-25.69	30.42	25.3	19.11	0.32	100	0	QP
13.56	10.69	40	-18.81	29.5	29.22	21.06	0.41	-	-	QP
14.848	-3.23	40	-32.73	29.5	15.16	21.19	0.42	-	-	QP
18.178	-3.31	40	-32.81	29.5	14.78	21.52	0.39	-	-	QP
29.56	-2.4	40	-31.9	29.5	14.25	22.46	0.89	-	-	QP

Note:


1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
3. Limit line = specific limits (dBμV) + distance extrapolation factor
4. 13.56 MHz is fundamental signal which can be ignored



C3. Results of Radiated Spurious Emissions (30MHz~1GHz)



Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.68	29.74	-10.26	40	39.66	19	1.08	30	-	-	Peak
240.9	38.69	-7.31	46	48.82	17.18	2.61	29.92	100	120	QP
281.37	38.58	-7.42	46	46.92	18.74	2.83	29.91	-	-	Peak
321.7	35.53	-10.47	46	42.99	19.41	3.03	29.9	-	-	Peak
722.8	35.48	-10.52	46	33.7	26.84	4.56	29.62	-	-	Peak
773.2	37.78	-8.22	46	34.84	27.71	4.74	29.51	-	-	Peak



Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.