



FCC SAR TEST REPORT

FCC ID : N7NWP7610
Equipment : WWAN Module
Brand Name : Getac
Model Name : WP7610
Applicant : Getac Technology Corporation.
5F., Building A, No. 209, Sec.1, Nangang Rd., Nangang Dist.,
Taipei City 11568, Taiwan, R.O.C.
Manufacturer : Ability Enterprise Co., Ltd.
4F., No.8, Lane7, Wuchiuan Rd, Wugu Dist., New Taipei City
24886, Taiwan, R.O.C.
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was installed into Body Worn Camera (Brand Name Getac, Model Name: BC-03) during test.

The product was received on Jan. 30, 2020 and testing was started from Jan. 27, 2020 and completed on Feb. 01, 2020. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 General LTE SAR Test and Reporting Considerations	6
4. RF Exposure Limits.....	8
4.1 Uncontrolled Environment.....	8
4.2 Controlled Environment.....	8
5. Specific Absorption Rate (SAR).....	9
5.1 Introduction	9
5.2 SAR Definition.....	9
6. System Description and Setup	10
6.1 E-Field Probe	11
6.2 Data Acquisition Electronics (DAE)	11
6.3 Phantom.....	12
6.4 Device Holder.....	13
7. Measurement Procedures	14
7.1 Spatial Peak SAR Evaluation.....	14
7.2 Power Reference Measurement.....	15
7.3 Area Scan	15
7.4 Zoom Scan.....	16
7.5 Volume Scan Procedures.....	16
7.6 Power Drift Monitoring.....	16
8. Test Equipment List	17
9. System Verification	18
9.1 Tissue Simulating Liquids.....	18
9.2 Tissue Verification	19
9.3 System Performance Check Results.....	20
10. UMTS/LTE Output Power (Unit: dBm)	21
11. WiFi/Bluetooth Output Power (Unit: dBm)	42
12. Bluetooth Exclusions Applied	45
13. Antenna Location	46
14. SAR Test Results	47
14.1 Body SAR	49
15. Simultaneous Transmission Analysis	52
15.1 Body Exposure Conditions	52
16. Uncertainty Assessment	53
17. References.....	53
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	



History of this test report



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Getac Technology Corporation., WWAN Module, WP7610, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary	
		Body (Separation 0mm)	1g SAR (W/kg)
Licensed	WCDMA II	0.48	0.74
	WCDMA IV	0.46	
	WCDMA V	0.39	
	LTE Band 2	0.39	
	LTE Band 5	0.33	
	LTE Band 12 / 17	0.31	
	LTE Band 13	0.49	
	LTE Band 14	0.48	
	LTE Band 4 / 66	0.46	
DTS	2.4GHz WLAN	0.09	0.74
NII	5GHz WLAN	0.01	0.67
Date of Testing:		2020/1/27 ~ 2020/2/1	

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Jason Wang

Report Producer: Wan Liu

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05



3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	WWAN Module
Brand Name	Getac
Model Name	WP7610
FCC ID	N7NWP7610
S/N	WKBXXB0032
Wireless Technology and Frequency Range	WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz LTE Band 14: 790.5 MHz ~ 795.5 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz
Mode	RMC 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM, 64QAM
Remark:	1. This device has five kinds of accessory to collocate, RF Exposure chose Chest Clip as the main test, and the others were spot checked the worst of Chest Clip.

Host Information	
Equipment Name	Body Worn Camera
Brand Name	Getac
Model Name	BC-03
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2472 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Mode	WLAN: 802.11a/b/g/n/ac HT20 / HT40 / VHT20 / VHT40 / VHT80 Bluetooth BR/EDR/LE NFC:ASK
EUT Stage	Production Unit
Remark:	1. In this report adding WiFi/BT SAR to perform Sim-Tx analysis.

Accessories	Brand Name	Getac	Model Name	Chest Mount
	Brand Name	Getac	Model Name	Pocket Mount
	Brand Name	Getac	Model Name	Chest Clip
	Brand Name	Getac	Model Name	Epaulette Clip
	Brand Name	Getac	Model Name	Magnetic Mount

**3.2 General LTE SAR Test and Reporting Considerations**

Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	N7NWP7610							
Equipment Name	WWAN Module							
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz LTE Band 14: 790.5 MHz ~ 795.5 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz							
Channel Bandwidth	LTE Band 02: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 04: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 05: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 12: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 13: 5MHz, 10MHz LTE Band 14: 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz LTE Band 66: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz							
uplink modulations used	QPSK / 16QAM / 64QAM							
LTE Voice / Data requirements	Data only							
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3								
LTE MPR permanently built-in by design	Modulation	Channel bandwidth / Transmission bandwidth (NRB)						MPR (dB)
1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz			
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	
256 QAM				≥ 1			≤ 5	
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)							
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							



Transmission (H, M, L) channel numbers and frequencies in each LTE band																	
LTE Band 2																	
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz						
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)					
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860					
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880					
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900					
LTE Band 4																	
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz						
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)					
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720					
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5					
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745					
LTE Band 5																	
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz						
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)					
L	20407	824.7	20415		825.5		20425		826.5		20450	829					
M	20525	836.5	20525		836.5		20525		836.5		20525	836.5					
H	20643	848.3	20635		847.5		20625		846.5		20600	844					
LTE Band 12																	
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz						
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)					
L	23017	699.7	23025		700.5		23035		701.5		23060	704					
M	23095	707.5	23095		707.5		23095		707.5		23095	707.5					
H	23173	715.3	23165		714.5		23155		713.5		23130	711					
LTE Band 13																	
	Bandwidth 5 MHz					Bandwidth 10 MHz											
	Channel #		Freq.(MHz)			Channel #		Freq.(MHz)									
L	23205		779.5			23230		782									
M	23230		782														
H	23255		784.5														
LTE Band 14																	
	Bandwidth 5 MHz					Bandwidth 10 MHz											
	Channel #		Channel #			Channel #		Freq.(MHz)									
L	23305		790.5			23330		793									
M	23330		793														
H	23355		795.5														
LTE Band 17																	
	Bandwidth 5 MHz					Bandwidth 10 MHz											
	Channel #		Freq.(MHz)			Channel #		Freq. (MHz)									
L	23755		706.5			23780		709									
M	23790		710			23790		710									
H	23825		713.5			23800		711									
LTE Band 66																	
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz						
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)					
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720					
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745					
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770					



4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.



5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held
Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops



7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g



7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	



7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}		≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$ graded grid	≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm
Minimum zoom scan volume	x, y, z	≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remains in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan are completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT installed full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1107	Mar. 08, 2019	Mar. 07, 2020
SPEAG	835MHz System Validation Kit	D835V2	4d167	Nov. 25, 2019	Nov. 24, 2020
SPEAG	1750MHz System Validation Kit	D1750V2	1112	Mar. 07, 2019	Mar. 06, 2020
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Sep. 11, 2018	Sep. 09, 2020
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 31, 2018	Aug. 29, 2020
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 27, 2018	Sep. 25, 2020
SPEAG	Data Acquisition Electronics	DAE3	577	Sep. 17, 2019	Sep. 16, 2020
SPEAG	Data Acquisition Electronics	DAE4	778	May. 21, 2019	May. 20, 2020
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	Sep. 20, 2019	Sep. 19, 2020
SPEAG	Dosimetric E-Field Probe	EX3DV4	7306	Jul. 22, 2019	Jul. 21, 2020
RCPTWN	Thermometer	HTC-1	TM685-1	Nov. 12, 2019	Nov. 11, 2020
RCPTWN	Thermometer	HTC-1	TM560-2	Nov. 12, 2019	Nov. 11, 2020
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Oct. 31, 2019	Oct. 30, 2020
Agilent	Wireless Communication Test Set	E5515C	MY50267236	Apr. 01, 2019	Mar. 31, 2020
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Nov. 20, 2019	Nov. 19, 2020
Agilent	ENA Network Analyzer	E5071C	MY46104758	Sep. 06, 2019	Sep. 05, 2020
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 18, 2019	Sep. 17, 2020
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 10, 2019	Sep. 09, 2020
Anritsu	Power Meter	ML2495A	1036004	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Sensor	MA2411B	1027253	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Meter	ML2495A	1419002	May. 29, 2019	May. 28, 2020
Anritsu	Power Sensor	MA2411B	1339124	May. 29, 2019	May. 28, 2020
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 27, 2019	Aug. 26, 2020
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 27, 2019	Jun. 26, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 16, 2019	Oct. 15, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 12, 2019	Aug. 11, 2020
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

- Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
- Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
- The justification data of dipole D5GHzV2, SN: 1006, D1900V2, SN: 5d041, D2450V2, SN: 736 can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.



Fig 10.1 Photo of Liquid Height for Head SAR



Fig 10.2 Photo of Liquid Height for Body SAR



9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

< Tissue Dielectric Parameter Check Results >

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	22.7	0.901	42.050	0.89	41.90	1.24	0.36	± 5	2020/1/28
750	22.6	0.899	42.706	0.89	41.90	1.01	1.92	± 5	2020/1/31
835	22.7	0.893	41.478	0.90	41.50	-0.78	-0.05	± 5	2020/1/28
835	22.6	0.934	42.410	0.90	41.50	3.78	2.19	± 5	2020/1/31
1750	22.1	1.373	40.185	1.37	40.10	0.22	0.21	± 5	2020/1/27
1750	22.6	1.384	40.789	1.37	40.10	1.02	1.72	± 5	2020/1/31
1900	22.1	1.406	40.174	1.40	40.00	0.43	0.43	± 5	2020/1/27
1900	22.6	1.459	40.944	1.40	40.00	4.21	2.36	± 5	2020/1/31
2450	22.4	1.793	38.961	1.80	39.20	-0.39	-0.61	± 5	2020/2/1
5250	22.4	4.572	36.816	4.71	35.95	-2.93	2.41	± 5	2020/2/1
5600	22.4	4.975	36.482	5.07	35.50	-1.87	2.77	± 5	2020/2/1
5750	22.4	5.126	35.932	5.22	35.35	-1.80	1.65	± 5	2020/2/1

9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2020/1/28	750	250	D750V3-1107	EX3DV4 - SN7306	DAE3 Sn577	2.22	8.32	8.88	6.73
2020/1/31	750	250	D750V3-1107	EX3DV4 - SN3925	DAE4 Sn778	2.13	8.32	8.52	2.40
2020/1/28	835	250	D835V2-4d167	EX3DV4 - SN7306	DAE3 Sn577	2.49	9.55	9.96	4.29
2020/1/31	835	250	D835V2-4d167	EX3DV4 - SN3925	DAE4 Sn778	2.51	9.55	10.04	5.13
2020/1/27	1750	250	D1750V2-1112	EX3DV4 - SN7306	DAE3 Sn577	9.06	36.70	36.24	-1.25
2020/1/31	1750	250	D1750V2-1112	EX3DV4 - SN3925	DAE4 Sn778	9.38	36.70	37.52	2.23
2020/1/27	1900	250	D1900V2-5d041	EX3DV4 - SN7306	DAE3 Sn577	10.30	40.20	41.2	2.49
2020/1/31	1900	250	D1900V2-5d041	EX3DV4 - SN3925	DAE4 Sn778	9.77	40.20	39.08	-2.79
2020/2/1	2450	250	D2450V2-736	EX3DV4 - SN3925	DAE4 Sn778	13.90	52.70	55.6	5.50
2020/2/1	5250	100	D5GHzV2-1006-5250	EX3DV4 - SN3925	DAE4 Sn778	7.86	80.70	78.6	-2.60
2020/2/1	5600	100	D5GHzV2-1006-5600	EX3DV4 - SN3925	DAE4 Sn778	7.95	83.30	79.5	-4.56
2020/2/1	5750	100	D5GHzV2-1006-5750	EX3DV4 - SN3925	DAE4 Sn778	7.56	80.40	75.6	-5.97




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo



10. UMTS/LTE Output Power (Unit: dBm)

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlined in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

**HSUPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/2 25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

**DC-HSDPA 3GPP release 8 Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a. Subtest 1: $\beta_c/\beta_d=2/15$
 - b. Subtest 2: $\beta_c/\beta_d=12/15$
 - c. Subtest 3: $\beta_c/\beta_d=15/8$
 - d. Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlined in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

PARAMETER	UNIT	VALUE
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Proces ses	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK

Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.

Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration

**<WCDMA Conducted Power>****General Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.



Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	RMC 12.2Kbps	21.97	22.06	22.18	23.00	21.95	21.93	21.71	23.00	21.66	21.75	21.50	23.00
3GPP Rel 6	HSDPA Subtest-1	21.66	21.82	21.87	23.00	21.64	21.03	21.24	23.00	21.54	21.17	21.43	23.00
3GPP Rel 6	HSDPA Subtest-2	21.19	21.28	21.32	23.00	21.24	21.28	21.47	23.00	21.04	20.70	21.02	23.00
3GPP Rel 6	HSDPA Subtest-3	21.81	21.87	21.66	22.50	21.70	21.18	21.29	22.50	21.58	21.18	21.40	22.50
3GPP Rel 6	HSDPA Subtest-4	21.71	21.76	21.75	22.50	21.45	21.70	21.41	22.50	21.52	21.74	21.47	22.50
3GPP Rel 8	DC-HSDPA Subtest-1	21.61	21.76	21.86	23.00	21.55	21.03	21.21	23.00	21.54	21.12	21.38	23.00
3GPP Rel 8	DC-HSDPA Subtest-2	21.12	21.26	21.31	23.00	21.19	21.18	21.39	23.00	20.96	20.65	20.99	23.00
3GPP Rel 8	DC-HSDPA Subtest-3	21.80	21.80	21.63	22.50	21.62	21.09	21.23	22.50	21.58	21.10	21.34	22.50
3GPP Rel 8	DC-HSDPA Subtest-4	21.68	21.67	21.69	22.50	21.35	21.70	21.36	22.50	21.49	21.69	21.38	22.50
3GPP Rel 6	HSUPA Subtest-1	21.84	21.45	21.61	23.00	21.41	21.79	21.03	23.00	21.53	21.09	21.01	23.00
3GPP Rel 6	HSUPA Subtest-2	20.82	20.95	20.58	21.00	20.75	20.58	20.36	21.00	20.60	20.44	20.26	21.00
3GPP Rel 6	HSUPA Subtest-3	20.70	20.84	20.55	22.00	20.33	20.41	20.20	22.00	20.72	19.68	20.52	22.00
3GPP Rel 6	HSUPA Subtest-4	20.84	20.89	20.99	21.00	20.74	20.85	20.24	21.00	20.96	20.71	20.86	21.00
3GPP Rel 6	HSUPA Subtest-5	22.13	22.10	21.90	23.00	21.70	21.60	21.50	23.00	21.70	21.64	21.60	23.00



<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B5 / B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 4 / 17 SAR test was covered by Band 66 / 12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



**<LTE Band 2>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	21.16	21.35	21.11	23	0
20	QPSK	1	49	21.46	21.55	21.47		
20	QPSK	1	99	21.10	21.09	21.00		
20	QPSK	50	0	20.53	20.45	20.52	22	1
20	QPSK	50	24	20.56	20.58	20.53		
20	QPSK	50	50	20.34	20.35	20.48		
20	QPSK	100	0	20.50	20.44	20.45		
20	16QAM	1	0	20.33	20.24	20.13	22	1
20	16QAM	1	49	20.09	20.34	20.26		
20	16QAM	1	99	20.14	20.08	20.09		
20	16QAM	50	0	19.48	19.45	19.34	21	2
20	16QAM	50	24	19.41	19.33	19.34		
20	16QAM	50	50	19.46	19.20	19.47		
20	16QAM	100	0	19.52	19.15	19.45		
20	64QAM	1	0	20.17	20.31	20.00	21	2
20	64QAM	1	49	20.27	20.37	20.11		
20	64QAM	1	99	19.95	19.69	19.83		
20	64QAM	50	0	19.65	19.37	19.43		
20	64QAM	50	24	19.37	19.34	19.52	20	3
20	64QAM	50	50	19.43	19.30	19.45		
20	64QAM	100	0	19.43	19.27	19.54		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	21.08	21.28	21.12	23	0
15	QPSK	1	37	21.15	21.40	21.34		
15	QPSK	1	74	21.14	21.15	21.05		
15	QPSK	36	0	20.32	20.19	20.41	22	1
15	QPSK	36	20	20.34	20.20	20.30		
15	QPSK	36	39	20.22	20.29	20.32		
15	QPSK	75	0	20.40	20.31	20.43		
15	16QAM	1	0	20.17	20.21	20.03	22	1
15	16QAM	1	37	20.05	20.15	20.09		
15	16QAM	1	74	20.03	20.05	20.02		
15	16QAM	36	0	19.27	19.11	19.29		
15	16QAM	36	20	19.24	19.27	19.23	21	2
15	16QAM	36	39	19.20	19.15	19.27		
15	16QAM	75	0	19.33	19.23	19.43		
15	64QAM	1	0	19.67	20.18	19.44		
15	64QAM	1	37	20.45	20.23	20.21	21	2
15	64QAM	1	74	19.86	19.84	19.80		
15	64QAM	36	0	19.15	19.29	19.32		
15	64QAM	36	20	19.18	19.33	19.28		
15	64QAM	36	39	19.11	19.15	19.35	20	3
15	64QAM	75	0	19.13	19.28	19.39		
Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	21.10	21.34	21.06	23	0
10	QPSK	1	25	21.63	21.28	21.43		
10	QPSK	1	49	21.09	21.02	21.02		
10	QPSK	25	0	20.46	20.43	20.42	22	1
10	QPSK	25	12	20.41	20.32	20.52		

**FCC SAR TEST REPORT****Report No. : FA9D1046**

10	QPSK	25	25	20.26	20.29	20.39	22	1
10	QPSK	50	0	20.46	20.42	20.43		
10	16QAM	1	0	20.32	20.18	20.04		
10	16QAM	1	25	20.01	20.30	20.19		
10	16QAM	1	49	20.10	20.08	20.02		
10	16QAM	25	0	19.42	19.40	19.33	21	2
10	16QAM	25	12	19.31	19.28	19.25		
10	16QAM	25	25	19.43	19.11	19.38		
10	16QAM	50	0	19.47	19.10	19.39		
10	64QAM	1	0	20.15	20.30	19.94	21	2
10	64QAM	1	25	20.21	20.30	20.04		
10	64QAM	1	49	19.93	19.67	19.75		
10	64QAM	25	0	19.60	19.29	19.37		
10	64QAM	25	12	19.36	19.24	19.43		
10	64QAM	25	25	19.42	19.22	19.45	20	3
10	64QAM	50	0	19.33	19.21	19.47		
Channel				188625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				18852.5	18880	1907.5		
5	QPSK	1	0	21.16	21.31	21.09	23	0
5	QPSK	1	12	21.58	21.24	21.46		
5	QPSK	1	24	21.07	21.02	21.08		
5	QPSK	12	0	20.46	20.42	20.50		
5	QPSK	12	7	20.38	20.26	20.50		
5	QPSK	12	13	20.28	20.31	20.45	22	1
5	QPSK	25	0	20.44	20.36	20.38		
5	16QAM	1	0	20.28	20.17	20.12		
5	16QAM	1	12	20.07	20.29	20.19		
5	16QAM	1	24	20.06	20.04	20.03		
5	16QAM	12	0	19.46	19.40	19.34	21	2
5	16QAM	12	7	19.39	19.28	19.29		
5	16QAM	12	13	19.36	19.16	19.42		
5	16QAM	25	0	19.49	19.05	19.40		
5	64QAM	1	0	20.09	20.21	19.91	21	2
5	64QAM	1	12	20.25	20.31	20.08		
5	64QAM	1	24	19.89	19.68	19.73		
5	64QAM	12	0	19.61	19.33	19.41		
5	64QAM	12	7	19.28	19.27	19.42		
5	64QAM	12	13	19.37	19.24	19.42	20	3
5	64QAM	25	0	19.41	19.25	19.46		
Channel				188615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				18851.5	18880	1908.5		
3	QPSK	1	0	21.12	21.28	21.07	23	0
3	QPSK	1	8	21.56	21.26	21.46		
3	QPSK	1	14	21.05	21.09	21.03		
3	QPSK	8	0	20.45	20.40	20.45		
3	QPSK	8	4	20.38	20.34	20.51		
3	QPSK	8	7	20.27	20.35	20.44	22	1
3	QPSK	15	0	20.49	20.35	20.39		
3	16QAM	1	0	20.30	20.14	20.04		
3	16QAM	1	8	20.19	20.32	20.25		
3	16QAM	1	14	20.13	20.05	20.02		
3	16QAM	8	0	19.40	19.41	19.26	21	2
3	16QAM	8	4	19.35	19.30	19.32		
3	16QAM	8	7	19.37	19.14	19.43		
3	16QAM	15	0	19.48	19.14	19.37		
3	64QAM	1	0	20.15	20.30	20.00	21	2

**FCC SAR TEST REPORT****Report No. : FA9D1046**

3	64QAM	1	8	20.25	20.32	20.07	20	3
3	64QAM	1	14	19.94	19.63	19.78		
3	64QAM	8	0	19.64	19.27	19.33		
3	64QAM	8	4	19.34	19.25	19.48		
3	64QAM	8	7	19.42	19.27	19.36		
3	64QAM	15	0	19.34	19.27	19.50		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	21.14	21.34	21.05	23	0
1.4	QPSK	1	3	21.45	21.55	21.38		
1.4	QPSK	1	5	21.09	21.09	21.04		
1.4	QPSK	3	0	21.21	21.18	21.14		
1.4	QPSK	3	1	21.26	21.22	21.17		
1.4	QPSK	3	3	21.18	21.16	21.15		
1.4	QPSK	6	0	20.45	20.38	20.36	22	1
1.4	16QAM	1	0	20.31	20.14	20.11	22	1
1.4	16QAM	1	3	20.06	20.24	20.17		
1.4	16QAM	1	5	20.06	20.07	20.00		
1.4	16QAM	3	0	20.15	20.08	20.03		
1.4	16QAM	3	1	20.10	20.04	20.03		
1.4	16QAM	3	3	20.16	20.01	20.10		
1.4	16QAM	6	0	19.48	19.09	19.43	21	2
1.4	64QAM	1	0	20.07	20.31	19.92	21	2
1.4	64QAM	1	3	20.18	20.33	20.04		
1.4	64QAM	1	5	19.86	19.64	19.74		
1.4	64QAM	3	0	19.55	19.27	19.41		
1.4	64QAM	3	1	19.34	19.27	19.52		
1.4	64QAM	3	3	19.36	19.20	19.40		
1.4	64QAM	6	0	19.43	19.27	19.48	20	3

**<LTE Band 4>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	21.10	21.12	21.12	23	0
20	QPSK	1	49	21.54	21.59	21.48		
20	QPSK	1	99	21.10	21.02	21.06		
20	QPSK	50	0	20.32	20.43	20.48	22	1
20	QPSK	50	24	20.41	20.51	20.50		
20	QPSK	50	50	20.37	20.37	20.22		
20	QPSK	100	0	20.30	20.30	20.34		
20	16QAM	1	0	20.12	20.16	20.22	22	1
20	16QAM	1	49	20.15	20.07	20.05		
20	16QAM	1	99	20.11	20.13	20.15		
20	16QAM	50	0	19.27	19.32	19.33	21	2
20	16QAM	50	24	19.33	19.42	19.14		
20	16QAM	50	50	19.26	19.26	19.18		
20	16QAM	100	0	19.27	19.32	19.25		
20	64QAM	1	0	19.87	20.02	19.69	21	2
20	64QAM	1	49	19.69	19.72	19.84		
20	64QAM	1	99	19.60	19.41	19.65		
20	64QAM	50	0	19.37	19.33	19.32	20	3
20	64QAM	50	24	19.41	19.45	19.35		
20	64QAM	50	50	19.25	19.41	19.24		
20	64QAM	100	0	19.18	19.21	19.20		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	21.00	21.11	21.04	23	0
15	QPSK	1	37	21.51	21.57	21.43		
15	QPSK	1	74	21.20	21.06	21.13		
15	QPSK	36	0	20.25	20.33	20.46	22	1
15	QPSK	36	20	20.31	20.45	20.45		
15	QPSK	36	39	20.46	20.28	20.31		
15	QPSK	75	0	20.39	20.37	20.30		
15	16QAM	1	0	20.10	20.25	20.26	22	1
15	16QAM	1	37	20.07	20.10	20.10		
15	16QAM	1	74	20.20	20.15	20.11		
15	16QAM	36	0	19.17	19.35	19.24	21	2
15	16QAM	36	20	19.30	19.45	19.10		
15	16QAM	36	39	19.21	19.27	19.12		
15	16QAM	75	0	19.30	19.28	19.29		
15	64QAM	1	0	19.86	20.12	19.70	21	2
15	64QAM	1	37	19.73	19.72	19.76		
15	64QAM	1	74	19.65	19.49	19.55		
15	64QAM	36	0	19.44	19.38	19.25	20	3
15	64QAM	36	20	19.39	19.49	19.35		
15	64QAM	36	39	19.29	19.36	19.17		
15	64QAM	75	0	19.08	19.19	19.15		
Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	21.14	21.15	21.19	23	0
10	QPSK	1	25	21.47	21.55	21.57		
10	QPSK	1	49	21.13	21.02	21.15		
10	QPSK	25	0	20.23	20.48	20.43	22	1
10	QPSK	25	12	20.33	20.56	20.55		

**FCC SAR TEST REPORT****Report No. : FA9D1046**

10	QPSK	25	25	20.28	20.36	20.15	22	1
10	QPSK	50	0	20.28	20.27	20.34		
10	16QAM	1	0	20.11	20.13	20.18		
10	16QAM	1	25	20.07	20.09	20.00		
10	16QAM	1	49	20.16	20.12	20.20		
10	16QAM	25	0	19.35	19.39	19.23	21	2
10	16QAM	25	12	19.28	19.41	19.18		
10	16QAM	25	25	19.25	19.26	19.10		
10	16QAM	50	0	19.29	19.40	19.16		
10	64QAM	1	0	19.78	20.08	19.69	21	2
10	64QAM	1	25	19.62	19.62	19.90		
10	64QAM	1	49	19.60	19.33	19.75		
10	64QAM	25	0	19.35	19.43	19.24		
10	64QAM	25	12	19.35	19.42	19.35		
10	64QAM	25	25	19.26	19.49	19.20	20	3
10	64QAM	50	0	19.17	19.23	19.27		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	21.15	21.03	21.19	23	0
5	QPSK	1	12	21.54	21.57	21.43		
5	QPSK	1	24	21.05	21.02	21.13		
5	QPSK	12	0	20.33	20.38	20.38		
5	QPSK	12	7	20.43	20.46	20.49		
5	QPSK	12	13	20.47	20.47	20.24	22	1
5	QPSK	25	0	20.26	20.32	20.25		
5	16QAM	1	0	20.22	20.20	20.22		
5	16QAM	1	12	20.22	20.03	20.14		
5	16QAM	1	24	20.21	20.11	20.05		
5	16QAM	12	0	19.30	19.31	19.28	21	2
5	16QAM	12	7	19.30	19.45	19.23		
5	16QAM	12	13	19.18	19.29	19.12		
5	16QAM	25	0	19.23	19.36	19.31		
5	64QAM	1	0	19.85	20.11	19.76	21	2
5	64QAM	1	12	19.73	19.73	19.89		
5	64QAM	1	24	19.60	19.35	19.74		
5	64QAM	12	0	19.42	19.34	19.36		
5	64QAM	12	7	19.46	19.51	19.41		
5	64QAM	12	13	19.22	19.41	19.31	20	3
5	64QAM	25	0	19.25	19.30	19.19		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	21.10	21.05	21.15	23	0
3	QPSK	1	8	21.45	21.54	21.58		
3	QPSK	1	14	21.06	21.06	21.04		
3	QPSK	8	0	20.42	20.35	20.53		
3	QPSK	8	4	20.41	20.50	20.51		
3	QPSK	8	7	20.29	20.47	20.14	22	1
3	QPSK	15	0	20.22	20.29	20.33		
3	16QAM	1	0	20.19	20.21	20.26		
3	16QAM	1	8	20.24	20.02	20.03		
3	16QAM	1	14	20.14	20.10	20.10		
3	16QAM	8	0	19.31	19.23	19.42	21	2
3	16QAM	8	4	19.32	19.36	19.18		
3	16QAM	8	7	19.35	19.19	19.23		
3	16QAM	15	0	19.37	19.37	19.16		
3	64QAM	1	0	19.85	20.06	19.66	21	2

**FCC SAR TEST REPORT****Report No. : FA9D1046**

3	64QAM	1	8	19.77	19.62	19.90	20	3
3	64QAM	1	14	19.53	19.41	19.60		
3	64QAM	8	0	19.35	19.37	19.26		
3	64QAM	8	4	19.41	19.45	19.39		
3	64QAM	8	7	19.30	19.48	19.15		
3	64QAM	15	0	19.19	19.15	19.24		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	21.17	21.08	21.20	23	0
1.4	QPSK	1	3	21.51	21.58	21.47		
1.4	QPSK	1	5	21.10	21.12	21.15		
1.4	QPSK	3	0	21.25	21.10	21.21		
1.4	QPSK	3	1	21.57	21.55	21.56		
1.4	QPSK	3	3	21.16	21.18	21.05		
1.4	QPSK	6	0	20.37	20.38	20.40	22	1
1.4	16QAM	1	0	20.02	20.22	20.17	22	1
1.4	16QAM	1	3	20.12	20.17	20.04		
1.4	16QAM	1	5	20.02	20.21	20.05		
1.4	16QAM	3	0	20.09	20.30	20.07		
1.4	16QAM	3	1	20.15	20.22	20.02		
1.4	16QAM	3	3	20.05	20.16	20.12		
1.4	16QAM	6	0	19.20	19.29	19.34	21	2
1.4	64QAM	1	0	19.80	19.99	19.67	21	2
1.4	64QAM	1	3	19.63	19.65	19.88		
1.4	64QAM	1	5	19.54	19.35	19.71		
1.4	64QAM	3	0	19.35	19.38	19.42		
1.4	64QAM	3	1	19.50	19.40	19.41		
1.4	64QAM	3	3	19.27	19.36	19.20		
1.4	64QAM	6	0	19.11	19.27	19.12	20	3

**<LTE Band 5>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	21.22	21.34	21.24	23	0
10	QPSK	1	25	21.08	21.60	21.49		
10	QPSK	1	49	21.08	21.00	21.06		
10	QPSK	25	0	20.34	20.33	20.33	22	1
10	QPSK	25	12	20.30	20.41	20.40		
10	QPSK	25	25	20.20	20.23	20.36		
10	QPSK	50	0	20.25	20.35	20.39		
10	16QAM	1	0	20.05	20.14	20.03	22	1
10	16QAM	1	25	20.14	20.26	20.37		
10	16QAM	1	49	20.16	20.22	20.12		
10	16QAM	25	0	19.18	19.45	19.25	21	2
10	16QAM	25	12	19.13	19.34	19.33		
10	16QAM	25	25	19.21	19.24	19.21		
10	16QAM	50	0	19.10	19.37	19.40		
10	64QAM	1	0	19.50	20.05	20.13	21	2
10	64QAM	1	25	20.03	20.25	20.26		
10	64QAM	1	49	19.75	20.28	20.02		
10	64QAM	25	0	19.28	19.45	19.34	20	3
10	64QAM	25	12	19.33	19.12	19.32		
10	64QAM	25	25	19.27	19.34	19.48		
10	64QAM	50	0	19.32	19.55	19.41		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	21.13	21.25	21.20	23	0
5	QPSK	1	12	21.10	21.59	21.40		
5	QPSK	1	24	21.00	21.06	21.00		
5	QPSK	12	0	20.38	20.37	20.24	22	1
5	QPSK	12	7	20.39	20.31	20.44		
5	QPSK	12	13	20.19	20.30	20.41		
5	QPSK	25	0	20.24	20.25	20.43		
5	16QAM	1	0	20.06	20.04	20.07	22	1
5	16QAM	1	12	20.07	20.18	20.31		
5	16QAM	1	24	20.15	20.23	20.22		
5	16QAM	12	0	19.09	19.41	19.29		
5	16QAM	12	7	19.20	19.26	19.32	21	2
5	16QAM	12	13	19.17	19.28	19.16		
5	16QAM	25	0	19.11	19.37	19.41		
5	64QAM	1	0	19.43	19.99	20.12		
5	64QAM	1	12	20.00	20.29	20.24	21	2
5	64QAM	1	24	19.83	20.22	20.01		
5	64QAM	12	0	19.29	19.38	19.37		
5	64QAM	12	7	19.26	19.13	19.30		
5	64QAM	12	13	19.21	19.34	19.56	20	3
5	64QAM	25	0	19.36	19.47	19.50		
Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	21.12	21.35	21.22	23	0
3	QPSK	1	8	21.03	21.52	21.52		
3	QPSK	1	14	21.10	21.09	21.13		
3	QPSK	8	0	20.24	20.38	20.30	22	1
3	QPSK	8	4	20.30	20.37	20.40		

**FCC SAR TEST REPORT****Report No. : FA9D1046**

3	QPSK	8	7	20.22	20.24	20.28		
3	QPSK	15	0	20.26	20.37	20.44		
3	16QAM	1	0	20.08	20.09	20.02	22	1
3	16QAM	1	8	20.04	20.30	20.34		
3	16QAM	1	14	20.06	20.26	20.20	21	2
3	16QAM	8	0	19.23	19.48	19.27		
3	16QAM	8	4	19.07	19.41	19.35	21	2
3	16QAM	8	7	19.13	19.14	19.20		
3	16QAM	15	0	19.09	19.44	19.42	21	2
3	64QAM	1	0	19.41	20.15	20.18		
3	64QAM	1	8	20.13	20.35	20.22	21	2
3	64QAM	1	14	19.85	20.25	19.93		
3	64QAM	8	0	19.30	19.52	19.25	20	3
3	64QAM	8	4	19.41	19.10	19.42		
3	64QAM	8	7	19.25	19.37	19.42	20	3
3	64QAM	15	0	19.29	19.60	19.43		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	21.31	21.38	21.26	23	0
1.4	QPSK	1	3	21.05	21.51	21.41		
1.4	QPSK	1	5	21.03	21.04	21.00		
1.4	QPSK	3	0	21.22	21.39	21.19		
1.4	QPSK	3	1	21.13	21.49	21.47		
1.4	QPSK	3	3	21.09	21.12	21.05		
1.4	QPSK	6	0	20.29	20.29	20.38		
1.4	16QAM	1	0	20.10	20.11	20.00	22	1
1.4	16QAM	1	3	20.15	20.25	20.43		
1.4	16QAM	1	5	20.18	20.25	20.13		
1.4	16QAM	3	0	20.33	20.26	20.33		
1.4	16QAM	3	1	20.05	20.03	20.10		
1.4	16QAM	3	3	20.19	20.34	20.38		
1.4	16QAM	6	0	19.15	19.30	19.36		
1.4	64QAM	1	0	19.45	20.02	20.03	21	2
1.4	64QAM	1	3	19.97	20.16	20.36		
1.4	64QAM	1	5	19.77	20.25	19.95		
1.4	64QAM	3	0	19.24	19.43	19.43		
1.4	64QAM	3	1	19.30	19.10	19.23		
1.4	64QAM	3	3	19.23	19.41	19.48		
1.4	64QAM	6	0	19.39	19.58	19.48		

**<LTE Band 12>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	22.32	22.15	21.64	23	0
10	QPSK	1	25	22.33	22.35	22.23		
10	QPSK	1	49	21.65	22.09	22.06		
10	QPSK	25	0	20.96	20.95	20.88	22	1
10	QPSK	25	12	20.99	20.95	21.15		
10	QPSK	25	25	20.91	20.89	21.12		
10	QPSK	50	0	21.01	20.91	21.04		
10	16QAM	1	0	20.41	20.67	20.57	22	1
10	16QAM	1	25	21.02	21.05	21.03		
10	16QAM	1	49	20.75	20.67	20.91		
10	16QAM	25	0	20.20	20.04	19.98	21	2
10	16QAM	25	12	20.15	19.98	20.26		
10	16QAM	25	25	20.08	20.01	20.14		
10	16QAM	50	0	20.17	20.01	20.19		
10	64QAM	1	0	20.34	20.65	20.63	21	2
10	64QAM	1	25	20.98	20.97	20.93		
10	64QAM	1	49	20.68	20.57	20.84		
10	64QAM	25	0	19.88	19.76	19.87	20	3
10	64QAM	25	12	19.25	19.97	19.98		
10	64QAM	25	25	19.33	19.98	19.82		
10	64QAM	50	0	19.21	19.93	19.77		
Channel				23035	23095	23155	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	22.24	22.08	21.60	23	0
5	QPSK	1	12	22.33	22.29	22.19		
5	QPSK	1	24	21.62	22.12	22.12		
5	QPSK	12	0	20.95	21.05	20.95	22	1
5	QPSK	12	7	21.03	20.94	21.08		
5	QPSK	12	13	20.84	20.94	21.17		
5	QPSK	25	0	20.96	20.88	21.14		
5	16QAM	1	0	20.50	20.74	20.61	22	1
5	16QAM	1	12	20.92	21.00	21.11		
5	16QAM	1	24	20.66	20.71	20.98		
5	16QAM	12	0	20.28	19.95	20.06	21	2
5	16QAM	12	7	20.20	20.01	20.23		
5	16QAM	12	13	20.01	20.01	20.06		
5	16QAM	25	0	20.12	20.08	20.16		
5	64QAM	1	0	20.38	20.56	20.55	21	2
5	64QAM	1	12	21.00	20.98	20.87		
5	64QAM	1	24	20.71	20.66	20.75		
5	64QAM	12	0	19.79	19.68	19.91	20	3
5	64QAM	12	7	19.34	19.90	19.93		
5	64QAM	12	13	19.24	19.92	19.92		
5	64QAM	25	0	19.24	19.85	19.69		
Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	22.32	22.24	21.69	23	0
3	QPSK	1	8	22.28	22.30	22.16		
3	QPSK	1	14	21.65	22.14	22.15		
3	QPSK	8	0	20.99	21.05	20.92	22	1
3	QPSK	8	4	21.07	20.89	21.09		

**FCC SAR TEST REPORT****Report No. : FA9D1046**

3	QPSK	8	7	20.89	20.95	21.06		
3	QPSK	15	0	20.93	20.83	21.01		
3	16QAM	1	0	20.45	20.58	20.49	22	1
3	16QAM	1	8	20.93	21.08	20.94		
3	16QAM	1	14	20.82	20.62	21.00	21	2
3	16QAM	8	0	20.30	20.02	19.99		
3	16QAM	8	4	20.08	20.05	20.22	21	2
3	16QAM	8	7	20.02	19.98	20.16		
3	16QAM	15	0	20.20	19.98	20.26	21	2
3	64QAM	1	0	20.40	20.71	20.62		
3	64QAM	1	8	20.96	20.93	20.83	21	2
3	64QAM	1	14	20.60	20.62	20.81		
3	64QAM	8	0	19.97	19.75	19.78	20	3
3	64QAM	8	4	19.26	19.90	19.95		
3	64QAM	8	7	19.29	19.88	19.87	20	3
3	64QAM	15	0	19.21	19.89	19.81		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.28	22.19	21.70	23	0
1.4	QPSK	1	3	22.23	22.28	22.15		
1.4	QPSK	1	5	21.58	22.14	22.09		
1.4	QPSK	3	0	22.28	22.27	21.60		
1.4	QPSK	3	1	22.33	22.18	22.24		
1.4	QPSK	3	3	21.64	22.11	22.00		
1.4	QPSK	6	0	21.06	20.81	21.03		
1.4	16QAM	1	0	20.47	20.66	20.62	22	1
1.4	16QAM	1	3	21.09	21.05	21.05		
1.4	16QAM	1	5	20.77	20.57	21.00		
1.4	16QAM	3	0	20.54	20.76	20.63		
1.4	16QAM	3	1	21.13	20.99	21.08		
1.4	16QAM	3	3	20.82	20.62	20.94		
1.4	16QAM	6	0	20.20	19.96	20.24		
1.4	64QAM	1	0	20.39	20.66	20.58	21	2
1.4	64QAM	1	3	20.99	20.94	20.99		
1.4	64QAM	1	5	20.60	20.62	20.76		
1.4	64QAM	3	0	19.89	19.81	19.82		
1.4	64QAM	3	1	19.35	19.91	20.05		
1.4	64QAM	3	3	19.38	19.96	19.86		
1.4	64QAM	6	0	19.15	19.87	19.69		

**<LTE Band 13>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)		
Channel				23230						
Frequency (MHz)				782						
10	QPSK	1	0		21.71		23	0		
10	QPSK	1	25		22.00					
10	QPSK	1	49		21.59					
10	QPSK	25	0		20.78		22	1		
10	QPSK	25	12		20.92					
10	QPSK	25	25		20.90					
10	QPSK	50	0		20.91					
10	16QAM	1	0		20.56		22	1		
10	16QAM	1	25		20.96					
10	16QAM	1	49		20.60					
10	16QAM	25	0		19.87					
10	16QAM	25	12		19.90		21	2		
10	16QAM	25	25		19.85					
10	16QAM	50	0		19.91					
10	64QAM	1	0		20.49		21	2		
10	64QAM	1	25		20.90					
10	64QAM	1	49		20.25					
10	64QAM	25	0		20.00		20	3		
10	64QAM	25	12		19.97					
10	64QAM	25	25		19.89					
10	64QAM	50	0		19.95					
Channel				23205	23230	23255	Tune-up limit (dBm)	MPR (dB)		
Frequency (MHz)				779.5	782	784.5				
5	QPSK	1	0	21.54	21.54	21.77	23	0		
5	QPSK	1	12	21.97	21.87	21.96				
5	QPSK	1	24	21.56	21.59	21.47				
5	QPSK	12	0	20.73	20.70	20.83	22	1		
5	QPSK	12	7	20.83	20.90	20.76				
5	QPSK	12	13	20.69	20.83	20.72				
5	QPSK	25	0	20.82	20.78	20.74				
5	16QAM	1	0	20.47	20.55	20.57	22	1		
5	16QAM	1	12	20.38	21.06	20.49				
5	16QAM	1	24	20.54	20.49	20.52				
5	16QAM	12	0	19.67	19.70	19.73				
5	16QAM	12	7	19.85	20.00	19.74	21	2		
5	16QAM	12	13	19.64	19.79	19.70				
5	16QAM	25	0	19.79	19.85	19.72				
5	64QAM	1	0	20.19	20.22	20.42	21	2		
5	64QAM	1	12	20.43	20.86	20.52				
5	64QAM	1	24	20.60	20.36	20.39				
5	64QAM	12	0	19.71	19.48	19.75				
5	64QAM	12	7	19.74	19.78	19.57	20	3		
5	64QAM	12	13	19.67	19.78	19.63				
5	64QAM	25	0	19.82	19.87	19.76				

**<LTE Band 14>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)		
Channel				23330						
Frequency (MHz)				793						
10	QPSK	1	0		21.83		23	0		
10	QPSK	1	25		22.10					
10	QPSK	1	49		21.73					
10	QPSK	25	0		20.88		22	1		
10	QPSK	25	12		21.06					
10	QPSK	25	25		21.03					
10	QPSK	50	0		21.09		22	1		
10	16QAM	1	0		20.68					
10	16QAM	1	25		21.08					
10	16QAM	1	49		20.80		21	2		
10	16QAM	25	0		20.00					
10	16QAM	25	12		20.01					
10	16QAM	25	25		19.97		21	2		
10	16QAM	50	0		20.05					
10	64QAM	1	0		20.69					
10	64QAM	1	25		20.92		21	2		
10	64QAM	1	49		20.38					
10	64QAM	25	0		19.95					
10	64QAM	25	12		19.96		20	3		
10	64QAM	25	25		19.91					
10	64QAM	50	0		19.94					
Channel				23305	23330	23355	Tune-up limit (dBm)	MPR (dB)		
Frequency (MHz)				790.5	793	795.5				
5	QPSK	1	0	21.69	21.64	21.96	23	0		
5	QPSK	1	12	22.07	22.07	22.05				
5	QPSK	1	24	21.70	21.71	21.67				
5	QPSK	12	0	20.85	20.83	20.93	22	1		
5	QPSK	12	7	20.93	21.05	20.89				
5	QPSK	12	13	20.85	21.03	20.92				
5	QPSK	25	0	20.99	20.95	20.85	22	1		
5	16QAM	1	0	20.66	20.66	20.74				
5	16QAM	1	12	20.48	21.24	20.64				
5	16QAM	1	24	20.71	20.65	20.64	21	2		
5	16QAM	12	0	19.81	19.90	19.85				
5	16QAM	12	7	20.05	20.20	19.84				
5	16QAM	12	13	19.77	19.94	19.88	21	2		
5	16QAM	25	0	19.94	19.96	19.89				
5	64QAM	1	0	20.29	20.35	20.55				
5	64QAM	1	12	20.57	20.84	20.72	21	2		
5	64QAM	1	24	20.74	20.53	20.52				
5	64QAM	12	0	19.87	19.65	19.90				
5	64QAM	12	7	19.90	19.88	19.71	20	3		
5	64QAM	12	13	19.83	19.98	19.82				
5	64QAM	25	0	19.98	19.99	19.93				

**<LTE Band 17>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
		Channel		23780	23790	23800		
		Frequency (MHz)		709	710	711		
10	QPSK	1	0	21.92	22.08	21.94	23	0
10	QPSK	1	25	21.70	22.31	22.08		
10	QPSK	1	49	22.13	22.14	22.09		
10	QPSK	25	0	20.95	20.83	20.89	22	1
10	QPSK	25	12	20.91	20.91	20.95		
10	QPSK	25	25	20.97	21.04	21.20		
10	QPSK	50	0	20.88	20.89	20.82		
10	16QAM	1	0	21.07	20.81	20.77	22	1
10	16QAM	1	25	20.93	20.88	20.94		
10	16QAM	1	49	21.13	21.01	20.93		
10	16QAM	25	0	19.88	19.97	19.97	21	2
10	16QAM	25	12	20.07	20.05	19.95		
10	16QAM	25	25	20.10	20.16	20.21		
10	16QAM	50	0	20.04	20.03	19.94		
10	64QAM	1	0	20.97	20.77	20.72	21	2
10	64QAM	1	25	20.77	20.80	20.88		
10	64QAM	1	49	20.95	20.91	20.87		
10	64QAM	25	0	19.97	19.92	19.91	20	3
10	64QAM	25	12	20.00	19.88	20.00		
10	64QAM	25	25	19.89	19.79	19.85		
10	64QAM	50	0	19.99	19.86	19.72		
		Channel		23755	23790	23825	Tune-up limit (dBm)	MPR (dB)
		Frequency (MHz)		706.5	710	713.5		
5	QPSK	1	0	21.87	22.04	21.89	23	0
5	QPSK	1	12	21.65	21.90	22.02		
5	QPSK	1	24	22.05	22.12	22.05		
5	QPSK	12	0	20.91	20.81	20.86	22	1
5	QPSK	12	7	20.88	20.83	20.90		
5	QPSK	12	13	20.88	21.04	21.12		
5	QPSK	25	0	20.82	20.87	20.82		
5	16QAM	1	0	21.00	20.79	20.77	22	1
5	16QAM	1	12	20.86	20.78	20.88		
5	16QAM	1	24	21.03	20.99	20.83		
5	16QAM	12	0	19.87	19.97	19.97	21	2
5	16QAM	12	7	19.99	20.02	19.92		
5	16QAM	12	13	20.08	20.14	20.15		
5	16QAM	25	0	20.03	20.00	19.88		
5	64QAM	1	0	20.92	20.77	20.64	21	2
5	64QAM	1	12	20.16	20.71	20.83		
5	64QAM	1	24	20.85	20.89	20.86		
5	64QAM	12	0	19.88	19.83	19.99	20	3
5	64QAM	12	7	19.91	19.93	20.00		
5	64QAM	12	13	19.93	19.98	20.00		
5	64QAM	25	0	19.94	19.94	19.93		

**<LTE Band 66>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572		
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	21.02	21.31	21.15	23	0
20	QPSK	1	49	21.34	21.54	21.32		
20	QPSK	1	99	21.21	21.20	21.14		
20	QPSK	50	0	20.40	20.57	20.32	22	1
20	QPSK	50	24	20.41	20.61	20.33		
20	QPSK	50	50	20.50	20.21	20.29		
20	QPSK	100	0	20.37	20.33	20.28		
20	16QAM	1	0	20.12	20.28	20.35	22	1
20	16QAM	1	49	20.21	20.07	20.13		
20	16QAM	1	99	20.04	20.08	20.02		
20	16QAM	50	0	19.45	19.43	19.09		
20	16QAM	50	24	19.37	19.18	19.29	21	2
20	16QAM	50	50	19.56	19.06	19.21		
20	16QAM	100	0	19.37	19.17	19.24		
20	64QAM	1	0	20.04	20.11	19.59	21	2
20	64QAM	1	49	19.83	20.12	20.18		
20	64QAM	1	99	19.93	19.48	19.66		
20	64QAM	50	0	19.33	19.50	19.25		
20	64QAM	50	24	19.52	19.22	19.27	20	3
20	64QAM	50	50	19.55	19.24	19.24		
20	64QAM	100	0	19.33	19.18	19.16		
Channel				132047	132322	132597	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	21.02	21.33	21.12	23	0
15	QPSK	1	37	21.41	21.41	21.37		
15	QPSK	1	74	21.31	21.26	21.04		
15	QPSK	36	0	20.47	20.59	20.25	22	1
15	QPSK	36	20	20.36	20.70	20.37		
15	QPSK	36	39	20.59	20.18	20.30		
15	QPSK	75	0	20.29	20.42	20.19		
15	16QAM	1	0	20.22	20.25	20.43	22	1
15	16QAM	1	37	20.27	20.06	20.12		
15	16QAM	1	74	20.05	20.12	20.07		
15	16QAM	36	0	19.38	19.48	19.11	21	2
15	16QAM	36	20	19.29	19.14	19.35		
15	16QAM	36	39	19.65	19.09	19.13		
15	16QAM	75	0	19.38	19.09	19.14		
15	64QAM	1	0	20.08	20.02	19.65	21	2
15	64QAM	1	37	19.82	20.02	20.09		
15	64QAM	1	74	20.01	19.46	19.72		
15	64QAM	36	0	19.32	19.43	19.25		
15	64QAM	36	20	19.59	19.30	19.30	20	3
15	64QAM	36	39	19.63	19.34	19.26		
15	64QAM	75	0	19.25	19.13	19.18		
Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	21.08	21.25	21.07	23	0
10	QPSK	1	25	21.32	21.42	21.40		
10	QPSK	1	49	21.23	21.25	21.04		
10	QPSK	25	0	20.36	20.51	20.31	22	1
10	QPSK	25	12	20.32	20.68	20.29		

**FCC SAR TEST REPORT****Report No. : FA9D1046**

10	QPSK	25	25	20.57	20.31	20.32	22	1
10	QPSK	50	0	20.33	20.23	20.18		
10	16QAM	1	0	20.12	20.20	20.26		
10	16QAM	1	25	20.30	20.01	20.04		
10	16QAM	1	49	20.05	20.11	20.02		
10	16QAM	25	0	19.47	19.37	19.00	21	2
10	16QAM	25	12	19.36	19.26	19.30		
10	16QAM	25	25	19.66	19.01	19.18		
10	16QAM	50	0	19.35	19.25	19.24		
10	64QAM	1	0	20.01	20.10	19.69	21	2
10	64QAM	1	25	19.93	20.21	20.27		
10	64QAM	1	49	19.98	19.38	19.74		
10	64QAM	25	0	19.33	19.45	19.18		
10	64QAM	25	12	19.43	19.27	19.36	20	3
10	64QAM	25	25	19.56	19.33	19.26		
10	64QAM	50	0	19.39	19.08	19.18		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	21.01	21.37	21.16	23	0
5	QPSK	1	12	21.25	21.43	21.36		
5	QPSK	1	24	21.28	21.21	21.13		
5	QPSK	12	0	20.47	20.48	20.24		
5	QPSK	12	7	20.38	20.65	20.28	22	1
5	QPSK	12	13	20.59	20.24	20.37		
5	QPSK	25	0	20.38	20.40	20.36		
5	16QAM	1	0	20.19	20.29	20.32		
5	16QAM	1	12	20.19	20.06	20.11	22	1
5	16QAM	1	24	20.11	20.13	20.04		
5	16QAM	12	0	19.48	19.39	19.03		
5	16QAM	12	7	19.41	19.26	19.39		
5	16QAM	12	13	19.66	19.00	19.29	21	2
5	16QAM	25	0	19.30	19.24	19.14		
5	64QAM	1	0	20.07	20.10	19.69	21	2
5	64QAM	1	12	19.81	20.20	20.26		
5	64QAM	1	24	19.92	19.55	19.73		
5	64QAM	12	0	19.41	19.41	19.35		
5	64QAM	12	7	19.58	19.21	19.29	20	3
5	64QAM	12	13	19.46	19.19	19.17		
5	64QAM	25	0	19.37	19.16	19.14		
Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	21.02	21.27	21.07	23	0
3	QPSK	1	8	21.41	21.52	21.35		
3	QPSK	1	14	21.11	21.11	21.16		
3	QPSK	8	0	20.43	20.64	20.39	22	1
3	QPSK	8	4	20.31	20.66	20.43		
3	QPSK	8	7	20.56	20.21	20.22		
3	QPSK	15	0	20.36	20.33	20.27		
3	16QAM	1	0	20.10	20.29	20.45	22	1
3	16QAM	1	8	20.25	20.00	20.16		
3	16QAM	1	14	20.06	20.12	20.00		
3	16QAM	8	0	19.39	19.40	19.14	21	2
3	16QAM	8	4	19.29	19.28	19.23		
3	16QAM	8	7	19.60	19.16	19.19		
3	16QAM	15	0	19.44	19.13	19.30		
3	64QAM	1	0	20.12	20.06	19.58	21	2

**FCC SAR TEST REPORT****Report No. : FA9D1046**

3	64QAM	1	8	19.79	20.19	20.14	20	3
3	64QAM	1	14	19.86	19.39	19.64		
3	64QAM	8	0	19.29	19.56	19.27		
3	64QAM	8	4	19.45	19.19	19.31		
3	64QAM	8	7	19.55	19.17	19.26		
3	64QAM	15	0	19.37	19.13	19.24		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	21.00	21.24	21.25	23	0
1.4	QPSK	1	3	21.34	21.46	21.31		
1.4	QPSK	1	5	21.29	21.19	21.16		
1.4	QPSK	3	0	21.03	21.27	21.34		
1.4	QPSK	3	1	21.27	21.54	21.35		
1.4	QPSK	3	3	21.25	21.28	21.08		
1.4	QPSK	6	0	20.42	20.27	20.18	22	1
1.4	16QAM	1	0	20.06	20.22	20.25	22	1
1.4	16QAM	1	3	20.22	20.11	20.04		
1.4	16QAM	1	5	20.09	20.11	20.10		
1.4	16QAM	3	0	20.06	20.28	20.28		
1.4	16QAM	3	1	20.19	20.12	20.12		
1.4	16QAM	3	3	20.10	20.01	20.10		
1.4	16QAM	6	0	19.37	19.11	19.25	21	2
1.4	64QAM	1	0	20.08	20.02	19.59	21	2
1.4	64QAM	1	3	19.89	20.22	20.17		
1.4	64QAM	1	5	19.83	19.54	19.76		
1.4	64QAM	3	0	19.25	19.50	19.30		
1.4	64QAM	3	1	19.45	19.29	19.22		
1.4	64QAM	3	3	19.61	19.27	19.30		
1.4	64QAM	6	0	19.41	19.15	19.25	20	3



11. WiFi/Bluetooth Output Power (Unit: dBm)

General Note:

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closest/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN ANT 1>

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11b 1Mbps	1	2412	14.30	14.50	98.94
		6	2437	14.70	15.00	
		11	2462	15.10	15.50	
		12	2467	15.50	15.50	
		13	2472	15.90	16.00	
	802.11g 6Mbps	1	2412	12.80	13.00	92.38
		6	2437	13.30	13.50	
		11	2462	13.80	14.00	
		12	2467	14.30	14.50	
		13	2472	14.80	15.00	
	802.11n-HT20 MCS0	1	2412	12.50	13.00	92.58
		6	2437	13.00	13.50	
		11	2462	13.50	14.00	
		12	2467	14.00	14.50	
		13	2472	14.50	15.00	
	802.11ac-VHT20 MCS0	1	2412	12.40	13.00	92.58
		6	2437	12.90	13.50	
		11	2462	13.40	14.00	
		12	2467	13.90	14.50	
		13	2472	14.40	15.00	

<5GHz WLAN ANT 1>

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	36	5180	4.10	4.50	92.69
		40	5200	4.30	4.50	
		44	5220	4.50	4.50	
		48	5240	4.30	4.50	
	802.11n-HT20 MCS0	36	5180	3.60	4.00	94.84
		40	5200	4.00	4.50	
		44	5220	4.40	4.50	
		48	5240	4.20	4.50	
	802.11n-HT40 MCS0	38	5190	2.90	3.00	89.71
		46	5230	3.90	4.00	
	802.11ac-VHT20 MCS0	36	5180	3.50	4.00	94.84
		40	5200	3.90	4.50	
		44	5220	4.30	4.50	
		48	5240	4.10	4.50	
	802.11ac-VHT40 MCS0	38	5190	2.80	3.00	89.71
		46	5230	3.80	4.00	
	802.11ac-VHT80 MCS0	42	5210	3.40	3.50	81.56



5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	52	5260	5.00	5.00	92.69
		56	5280	5.10	5.50	
		60	5300	5.10	5.50	
		64	5320	5.20	5.50	
	802.11n-HT20 MCS0	52	5260	4.00	4.00	94.84
		56	5280	4.40	4.50	
		60	5300	4.70	5.00	
		64	5320	4.80	5.00	
	802.11n-HT40 MCS0	54	5270	4.30	5.00	89.71
		62	5310	4.60	5.00	
	802.11ac-VHT20 MCS0	52	5260	3.90	4.00	94.84
		56	5280	4.30	4.50	
		60	5300	4.60	5.00	
		64	5320	4.70	5.00	
	802.11ac-VHT40 MCS0	54	5270	4.20	5.00	89.71
		62	5310	4.50	5.00	
	802.11ac-VHT80 MCS0	58	5290	4.10	4.50	81.56

5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	6.50	6.50	92.69
		116	5580	6.70	7.00	
		124	5620	7.40	7.50	
		132	5660	7.70	8.00	
		144	5720	8.10	8.50	
	802.11n-HT20 MCS0	100	5500	6.00	6.50	94.84
		116	5580	6.70	7.00	
		124	5620	7.10	7.50	
		132	5660	7.30	7.50	
		144	5720	7.50	7.50	
	802.11n-HT40 MCS0	102	5510	5.70	6.00	89.71
		110	5550	5.70	6.00	
		126	5630	6.30	6.50	
		134	5670	6.90	7.00	
		142	5710	7.10	7.50	
	802.11ac-VHT20 MCS0	100	5500	5.90	6.50	94.84
		116	5580	6.60	7.00	
		124	5620	7.00	7.50	
		132	5660	7.20	7.50	
		144	5720	7.40	7.50	
	802.11ac-VHT40 MCS0	102	5510	5.60	6.00	89.71
		110	5550	5.60	6.00	
		126	5630	6.20	6.50	
		134	5670	6.80	7.00	
		142	5710	7.00	7.50	
	802.11ac-VHT80 MCS0	106	5530	5.40	5.50	81.56
		122	5610	5.60	6.00	
		138	5690	6.50	6.50	



5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	149	5745	7.30	7.50	92.69
		157	5785	7.00	7.50	
		165	5825	6.80	7.00	
	802.11n-HT20 MCS0	149	5745	7.10	7.50	94.84
		157	5785	6.90	7.00	
		165	5825	6.50	6.50	
	802.11n-HT40 MCS0	151	5755	7.10	7.50	89.71
		159	5795	6.20	6.50	
	802.11ac-VHT20 MCS0	149	5745	7.00	7.50	94.84
		157	5785	6.80	7.00	
		165	5825	6.40	6.50	
	802.11ac-VHT40 MCS0	151	5755	7.00	7.50	89.71
		159	5795	6.10	6.50	
	802.11ac-VHT80 MCS0	155	5775	6.30	6.50	81.56

12. Bluetooth Exclusions Applied

Mode Band	Max Average power(dBm)	
	BR/EDR	LE
2.4GHz Bluetooth	6.0	6.0

Note:

1. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
6.0	< 5	2.48	1.25

Note:

Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 2.52 which is ≤ 3 , SAR testing is not required.



13. Antenna Location





14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - $\leq 0.8 \text{ W/kg}$ or 2.0 W/kg , for 1-g or 10-g respectively, when the transmission band is $\leq 100 \text{ MHz}$
 - $\leq 0.6 \text{ W/kg}$ or 1.5 W/kg , for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - $\leq 0.4 \text{ W/kg}$ or 1.0 W/kg , for 1-g or 10-g respectively, when the transmission band is $\geq 200 \text{ MHz}$
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8 \text{ W/kg}$.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is $\leq 1.2 \text{ W/kg}$, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

**LTE Note:**

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are \leq 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is $>$ 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is \leq 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is \leq 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B12 / B5 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 4 / 17 SAR test was covered by Band 66 / 12; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is \leq 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is \leq 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is $>$ 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closest/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is \leq 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is $>$ 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is \leq 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

**14.1 Body SAR****<WCDMA SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Accessory	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Back	0mm	Chest Clip	9538	1907.6	22.18	23.00	1.208	0.14	0.180	0.217
	WCDMA II	RMC 12.2Kbps	Back	0mm	Chest Clip	9400	1880	22.06	23.00	1.242	0.15	0.212	0.263
	WCDMA II	RMC 12.2Kbps	Back	0mm	Chest Clip	9262	1852.4	21.97	23.00	1.268	0.09	0.245	0.311
	WCDMA II	RMC 12.2Kbps	Back	0mm	Chest Mount	9262	1852.4	21.97	23.00	1.268	0.17	0.238	0.302
01	WCDMA II	RMC 12.2Kbps	Back	0mm	Magnetic Mount	9262	1852.4	21.97	23.00	1.268	-0.17	0.380	0.482
	WCDMA II	RMC 12.2Kbps	Back	0mm	Epaulette Clip	9262	1852.4	21.97	23.00	1.268	0.07	0.119	0.151
	WCDMA II	RMC 12.2Kbps	Back	0mm	Pocket Mount	9262	1852.4	21.97	23.00	1.268	0.09	0.260	0.330
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Chest Clip	1312	1712.4	21.95	23.00	1.274	0.14	0.227	0.289
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Chest Clip	1413	1732.6	21.93	23.00	1.279	0.08	0.238	0.304
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Chest Clip	1513	1752.6	21.71	23.00	1.346	0.07	0.264	0.355
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Chest Mount	1513	1752.6	21.71	23.00	1.346	0.12	0.214	0.287
02	WCDMA IV	RMC 12.2Kbps	Back	0mm	Magnetic Mount	1513	1752.6	21.71	23.00	1.346	-0.15	0.340	0.458
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Epaulette Clip	1513	1752.6	21.71	23.00	1.346	0.13	0.110	0.149
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Pocket Mount	1513	1752.6	21.71	23.00	1.346	0.16	0.235	0.317
	WCDMA V	RMC 12.2Kbps	Back	0mm	Chest Clip	4182	836.4	21.75	23.00	1.334	0.18	0.265	0.353
03	WCDMA V	RMC 12.2Kbps	Back	0mm	Chest Clip	4132	826.4	21.66	23.00	1.361	-0.14	0.283	0.385
	WCDMA V	RMC 12.2Kbps	Back	0mm	Chest Clip	4233	846.6	21.50	23.00	1.413	0.15	0.247	0.349
	WCDMA V	RMC 12.2Kbps	Back	0mm	Chest Mount	4132	826.4	21.66	23.00	1.361	0.15	0.273	0.372
	WCDMA V	RMC 12.2Kbps	Back	0mm	Magnetic Mount	4132	826.4	21.66	23.00	1.361	0.17	0.274	0.373
	WCDMA V	RMC 12.2Kbps	Back	0mm	Epaulette Clip	4132	826.4	21.66	23.00	1.361	0.16	0.135	0.184
	WCDMA V	RMC 12.2Kbps	Back	0mm	Pocket Mount	4132	826.4	21.66	23.00	1.361	0	0.278	0.378

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Accessory	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Chest Clip	18900	1880	21.55	23.00	1.396	-0.1	0.189	0.264
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Chest Clip	18700	1860	21.46	23.00	1.426	-0.12	0.212	0.302
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Chest Clip	19100	1900	21.47	23.00	1.422	-0.12	0.171	0.243
	LTE Band 2	20M	QPSK	50	24	Back	0mm	Chest Clip	18900	1880	20.58	22.00	1.387	0.02	0.152	0.211
04	LTE Band 2	20M	QPSK	1	49	Back	0mm	Chest Mount	18700	1860	21.46	23.00	1.426	0.03	0.207	0.295
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Magnetic Mount	18700	1860	21.46	23.00	1.426	-0.16	0.270	0.385
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Epaulette Clip	18700	1860	21.46	23.00	1.426	-0.09	0.083	0.118
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Pocket Mount	18700	1860	21.46	23.00	1.426	0.05	0.185	0.264
	LTE Band 5	10M	QPSK	1	25	Back	0mm	Chest Clip	20525	836.5	21.60	23.00	1.380	0.01	0.222	0.306
	LTE Band 5	10M	QPSK	25	12	Back	0mm	Chest Clip	20525	836.5	20.41	22.00	1.442	-0.01	0.174	0.251
	LTE Band 5	10M	QPSK	1	25	Back	0mm	Chest Mount	20525	836.5	21.60	23.00	1.380	0.12	0.235	0.324
05	LTE Band 5	10M	QPSK	1	25	Back	0mm	Magnetic Mount	20525	836.5	21.60	23.00	1.380	-0.04	0.240	0.331
	LTE Band 5	10M	QPSK	1	25	Back	0mm	Epaulette Clip	20525	836.5	21.60	23.00	1.380	-0.14	0.083	0.115
	LTE Band 5	10M	QPSK	1	25	Back	0mm	Pocket Mount	20525	836.5	21.60	23.00	1.380	-0.01	0.203	0.280
	LTE Band 12	10M	QPSK	1	25	Back	0mm	Chest Clip	23095	707.5	22.35	23.00	1.161	-0.16	0.243	0.282
	LTE Band 12	10M	QPSK	25	12	Back	0mm	Chest Clip	23095	707.5	20.95	22.00	1.274	-0.05	0.187	0.238
	LTE Band 12	10M	QPSK	1	25	Back	0mm	Chest Mount	23095	707.5	22.35	23.00	1.161	-0.05	0.237	0.275
06	LTE Band 12	10M	QPSK	1	25	Back	0mm	Magnetic Mount	23095	707.5	22.35	23.00	1.161	-0.1	0.263	0.305
	LTE Band 12	10M	QPSK	1	25	Back	0mm	Epaulette Clip	23095	707.5	22.35	23.00	1.161	-0.01	0.135	0.157
	LTE Band 12	10M	QPSK	1	25	Back	0mm	Pocket Mount	23095	707.5	22.35	23.00	1.161	-0.18	0.235	0.273

**FCC SAR TEST REPORT**

Report No. : FA9D1046

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Accessory	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
07	LTE Band 13	10M	QPSK	1	25	Back	0mm	Chest Clip	23230	782	22.00	23.00	1.259	-0.14	0.388	0.488
	LTE Band 13	10M	QPSK	25	12	Back	0mm	Chest Clip	23230	782	20.92	22.00	1.282	-0.14	0.321	0.412
	LTE Band 13	10M	QPSK	1	25	Back	0mm	Chest Mount	23230	782	22.00	23.00	1.259	-0.08	0.370	0.466
	LTE Band 13	10M	QPSK	1	25	Back	0mm	Magnetic Mount	23230	782	22.00	23.00	1.259	-0.16	0.317	0.399
	LTE Band 13	10M	QPSK	1	25	Back	0mm	Epaulette Clip	23230	782	22.00	23.00	1.259	-0.15	0.218	0.274
	LTE Band 13	10M	QPSK	1	25	Back	0mm	Pocket Mount	23230	782	22.00	23.00	1.259	0.15	0.344	0.433
08	LTE Band 14	10M	QPSK	1	25	Back	0mm	Chest Clip	23330	793	22.10	23.00	1.230	-0.01	0.387	0.476
	LTE Band 14	10M	QPSK	25	12	Back	0mm	Chest Clip	23330	793	21.06	22.00	1.242	0.18	0.294	0.365
	LTE Band 14	10M	QPSK	1	25	Back	0mm	Chest Mount	23330	793	22.10	23.00	1.230	0.1	0.342	0.421
	LTE Band 14	10M	QPSK	1	25	Back	0mm	Magnetic Mount	23330	793	22.10	23.00	1.230	-0.02	0.310	0.381
	LTE Band 14	10M	QPSK	1	25	Back	0mm	Epaulette Clip	23330	793	22.10	23.00	1.230	0.02	0.237	0.292
	LTE Band 14	10M	QPSK	1	25	Back	0mm	Pocket Mount	23330	793	22.10	23.00	1.230	0.1	0.338	0.416
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Chest Clip	132322	1745	21.54	23.00	1.400	-0.04	0.222	0.311
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Chest Clip	132072	1720	21.34	23.00	1.466	0	0.201	0.295
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Chest Clip	132572	1770	21.32	23.00	1.472	0	0.251	0.370
	LTE Band 66	20M	QPSK	50	24	Back	0mm	Chest Clip	132322	1745	20.61	22.00	1.377	-0.16	0.185	0.255
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Chest Mount	132572	1770	21.32	23.00	1.472	0.13	0.199	0.293
09	LTE Band 66	20M	QPSK	1	49	Back	0mm	Magnetic Mount	132572	1770	21.32	23.00	1.472	-0.15	0.310	0.456
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Epaulette Clip	132572	1770	21.32	23.00	1.472	-0.15	0.076	0.112
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Pocket Mount	132572	1770	21.32	23.00	1.472	0.09	0.178	0.262

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Accessory	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
10	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Chest Clip	13	2472	15.90	16.00	1.023	98.94	1.011	-0.15	0.086	0.089
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Chest Clip	12	2467	15.50	15.50	1.000	98.94	1.011	0	0.083	0.083
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Chest Clip	11	2462	15.10	15.50	1.096	98.94	1.011	0.17	0.075	0.083
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Chest Clip	6	2437	14.70	15.00	1.072	98.94	1.011	0.18	0.062	0.067
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Chest Clip	1	2412	14.30	14.50	1.047	98.94	1.011	0	0.041	0.043
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Chest Mount	13	2472	15.90	16.00	1.023	98.94	1.011	0.18	0.058	0.060
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Magnetic Mount	13	2472	15.90	16.00	1.023	98.94	1.011	0.19	0.045	0.047
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Epaulette Clip	13	2472	15.90	16.00	1.023	98.94	1.011	0.02	0.001	0.001
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Pocket Mount	13	2472	15.90	16.00	1.023	98.94	1.011	0.11	0.069	0.071

**FCC SAR TEST REPORT****Report No. : FA9D1046**

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Accessory	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
11	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	64	5320	5.20	5.50	1.072	92.69	1.079	0.17	0.010	0.012
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	52	5260	5.00	5.00	1.000	92.69	1.079	0.08	0.009	0.010
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	56	5280	5.10	5.50	1.096	92.69	1.079	0.09	0.008	0.010
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	60	5300	5.10	5.50	1.096	92.69	1.079	0.13	0.007	0.008
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Mount	64	5320	5.20	5.50	1.072	92.69	1.079	0.12	0.005	0.005
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Magnetic Mount	64	5320	5.20	5.50	1.072	92.69	1.079	0.01	0.006	0.007
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Epaulette Clip	64	5320	5.20	5.50	1.072	92.69	1.079	0.06	0.005	0.006
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Pocket Mount	64	5320	5.20	5.50	1.072	92.69	1.079	0.06	0.001	0.001
12	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	144	5720	8.10	8.50	1.096	92.69	1.079	-0.18	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	100	5500	6.50	6.50	1.000	92.69	1.079	0.19	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	116	5580	6.70	7.00	1.072	92.69	1.079	0.14	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	124	5620	7.40	7.50	1.023	92.69	1.079	0.14	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Clip	132	5660	7.70	8.00	1.072	92.69	1.079	0.01	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Chest Mount	144	5720	8.10	8.50	1.096	92.69	1.079	0.08	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Magnetic Mount	144	5720	8.10	8.50	1.096	92.69	1.079	0.19	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Epaulette Clip	144	5720	8.10	8.50	1.096	92.69	1.079	0.1	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 1	Pocket Mount	144	5720	8.10	8.50	1.096	92.69	1.079	0.04	0.001	0.001
13	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	Ant 1	Chest Clip	151	5755	7.10	7.50	1.096	89.71	1.115	0	0.001	0.001
	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	Ant 1	Chest Clip	159	5795	6.20	6.50	1.072	89.71	1.115	0.08	0.001	0.001
	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	Ant 1	Chest Mount	151	5755	7.10	7.50	1.096	89.71	1.115	0.13	0.001	0.001
	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	Ant 1	Magnetic Mount	151	5755	7.10	7.50	1.096	89.71	1.115	0.09	0.001	0.001
	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	Ant 1	Epaulette Clip	151	5755	7.10	7.50	1.096	89.71	1.115	0.08	0.001	0.001
	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	Ant 1	Pocket Mount	151	5755	7.10	7.50	1.096	89.71	1.115	0.11	0.001	0.001



15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	WWAN + WLAN + Bluetooth	Yes

General Note:

1. All licensed modes share the same antenna part and cannot transmit simultaneously
2. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
3. The Scaled SAR summation is calculated based on the same configuration and test position.
4. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) SPLSR = $(\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If SPLSR ≤ 0.04 , simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
5. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v06 based on the formula below. .
 - i) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$ for test separation distances ≤ 50 mm; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - ii) When the minimum separation distance is < 5 mm, the distance is used 5mm to determine SAR test exclusion.
 - iii) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Bluetooth Max Power	Exposure Position	All Positions
6dBm	Estimated SAR (W/kg)	0.167 W/kg

15.1 Body Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 1	5GHz WLAN Ant 1	Bluetooth Ant 2		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)		
WCDMA	WCDMA II	Back	0.482	0.089	0.012	0.167	0.738	0.661
	WCDMA IV	Back	0.458	0.089	0.012	0.167	0.714	0.637
	WCDMA V	Back	0.385	0.089	0.012	0.167	0.641	0.564
LTE	LTE Band 2	Back	0.385	0.089	0.012	0.167	0.641	0.564
	LTE Band 5	Back	0.331	0.089	0.012	0.167	0.587	0.510
	LTE Band 12	Back	0.305	0.089	0.012	0.167	0.561	0.484
	LTE Band 13	Back	0.488	0.089	0.012	0.167	0.744	0.667
	LTE Band 14	Back	0.476	0.089	0.012	0.167	0.732	0.655
	LTE Band 66	Back	0.456	0.089	0.012	0.167	0.712	0.635

Test Engineer : Randy Lin and Andy Chiang



16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [8] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [9] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [10] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.