

TEST REPORT

Test Report Reference: F091910E2

Equipment under Test: CC 9055

FCC ID: QZ9-CC9055

IC: 5927A-CC9055

Serial Number: None

Applicant: Bury GmbH & Co. KG

Manufacturer: Bury GmbH & Co. KG

**Test Laboratory
(CAB)
accredited by
DATech in der TGA GmbH
in compliance with DIN EN ISO/IEC 17025
under the
Reg. No. DAT-P-105/99-21,
FCC Test site registration number 90877
and
Industry Canada Test site registration IC3469A-1 and
FCC Test site registration number 90877**

TEST REPORT REFERENCE: F091910E2

Contents:	Page
1 IDENTIFICATION	3
1.1 APPLICANT	3
1.2 MANUFACTURER	3
1.3 DATES	3
1.4 TEST LABORATORY	4
1.5 RESERVATION	4
1.6 NORMATIVE REFERENCES	4
1.7 TEST RESULTS	4
2 TECHNICAL DATA OF EQUIPMENT	5
2.1 PERIPHERY DEVICES	5
3 OPERATIONAL STATES AND PHYSICAL BOUNDARIES	6
4 LIST OF MEASUREMENTS	7
5 TEST RESULTS	8
5.1 20 dB BANDWIDTH	8
5.1.1 METHOD OF MEASUREMENT (20 dB BANDWIDTH)	8
5.1.2 TEST RESULTS (20 dB BANDWIDTH)	9
5.2 CARRIER FREQUENCY SEPARATION	11
5.2.1 METHOD OF MEASUREMENT (CARRIER FREQUENCY SEPARATION)	11
5.2.2 TEST RESULTS (CARRIER FREQUENCY SEPARATION)	12
5.3 NUMBER OF HOPPING FREQUENCIES	14
5.3.1 METHOD OF MEASUREMENT (NUMBER OF HOPPING FREQUENCIES)	14
5.3.2 TEST RESULTS (NUMBER OF HOPPING FREQUENCIES)	15
5.4 DWELL TIME	16
5.4.1 METHOD OF MEASUREMENT (DWELL TIME)	16
5.4.2 TEST RESULTS (DWELL TIME)	17
5.5 MAXIMUM PEAK OUTPUT POWER	20
5.5.1 METHOD OF MEASUREMENT (MAXIMUM PEAK OUTPUT POWER)	20
5.5.2 TEST RESULTS (MAXIMUM PEAK OUTPUT POWER)	21
5.6 BAND-EDGE COMPLIANCE	23
5.6.1 METHOD OF MEASUREMENT (BAND-EDGE COMPLIANCE (RADIATED))	23
5.6.2 TEST RESULT (BAND-EDGE COMPLIANCE (RADIATED))	24
5.7 RADIATED EMISSIONS	28
5.7.1 METHOD OF MEASUREMENT (RADIATED EMISSIONS)	28
5.7.2 TEST RESULTS (RADIATED EMISSIONS)	33
5.7.2.1 PRELIMINARY MEASUREMENT (9 kHz to 25 GHz)	33
5.7.2.2 FINAL RADIATED EMISSION TEST (30 MHz to 1 GHz)	42
5.7.2.3 FINAL MEASUREMENT (1 GHz to 25 GHz)	44
6 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS	47
7 LIST OF ANNEXES	49

TEST REPORT REFERENCE: F091910E2

1 IDENTIFICATION

1.1 APPLICANT

Name:	Bury GmbH & Co. KG
Address:	Robert-Koch-Straße 1-7
	32584 Löhne
Country:	Germany
Name for contact purposes:	Mr. Frank UNTERKÖTTER
Tel:	(0 57 32) 97 06-246
Fax:	(0 57 32) 97 06-99
e-mail address:	unterkoetter@thb.de

1.2 MANUFACTURER

Name:	Bury GmbH & Co. KG
Address:	Robert-Koch-Straße 1-7
	32584 Löhne
Country:	Germany
Name for contact purposes:	Mr. Frank UNTERKÖTTER
Tel:	(0 57 32) 97 06-246
Fax:	(0 57 32) 97 06-99
e-mail address:	unterkoetter@thb.de

1.3 DATES



Date of receipt of test sample:	29 July 2009
Start of test:	11 August 2009
End of test:	21 August 2009

TEST REPORT REFERENCE: F091910E2

1.4 TEST LABORATORY

The tests were carried out at: **PHOENIX TESTLAB GmbH**
Königswinkel 10
D-32825 Blomberg Phone: **+49 (0) 52 35 / 95 00-0**
Germany Fax: **+49 (0) 52 35 / 95 00-10**

accredited by DATech in der TGA GmbH in compliance with DIN EN ISO/IEC 17025 under Reg. No. DAT-P-105/99, Industry Canada Test site registration IC3469A-1 and FCC Test site registration number 90877.

Test engineer:	Thomas KÜHN		24 August 2009
	Name	Signature	Date
Test report checked:	Bernd STEINER		24 August 2009
	Name	Signature	Date

PHOENIX TESTLAB GmbH
Königswinkel 10
32825 Blomberg
Tel. 0 52 35 / 95 00-0
Fax 0 52 35 / 95 00-10

Stamp

1.5 RESERVATION

This test report is only valid in its original form.

Any reproduction of its contents without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT REFERENCE.

1.6 NORMATIVE REFERENCES

- [1] **ANSI C63.4-2003** American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
- [2] **FCC CFR 47 Part 15 (October 2008)** Radio Frequency Devices
- [3] **FCC Public Notice DA 00-705 (March 2000)**
- [4] **RSS-210 Issue 7 (June 2007)** Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment
- [5] **RSS-Gen Issue 2 (June 2007)** General Requirements and Information for the Certification of Radiocommunication Equipment
- [6] **Publication Number 913591 (March 2007)** Measurement of radiated emissions at the edge of the band for a Part 15 RF Device

1.7 TEST RESULTS

The requirements of this test document are fulfilled by the equipment under test. The complete test results are presented in the following.

TEST REPORT REFERENCE: F091910E2

2 TECHNICAL DATA OF EQUIPMENT

Type / model designation: *	CC 9055					
Type of equipment: *	Bluetooth hands free unit for vehicular environment					
Hard- / Software Version: *	0101 / H7ts					
Used power setting:	44					
FCC ID: *	QZ9-CC9055					
IC: *	5927A-CC9055					
Fulfills Bluetooth specification: *	2.0 but no EDR					
Antenna type: *	Integral (Copperplate BT-Antenna Art. -No.: 54-0286-1_LF)					
Antenna gain: *	2.0 dBi					
Antenna connector: *	None (Integrated Bluetooth-antenna)					
Power supply (Bluetooth-unit): *	U _{nom} =	3.0 V DC	U _{min} =	2.7 V DC	U _{max} =	3.3 V DC
Type of modulation: *	FHSS (GFSK)					
Operating frequency range:*	2402 MHz to 2480 MHz					
Number of channels: *	79					
Temperature range: *	-25 °C to +70 °C					

*: declared by the applicant

Bluetooth operates in the unlicensed ISM band at 2.4 GHz. In North America (USA and Canada) a band with a width of 83.5 MHz is available. In this band 79 RF channels spaced 1 MHz apart are defined. The channel is represented by a pseudo random hopping sequence through the 79 channels. The normally occupancy time of one frequency will be 625 µs. The ordinary hopping rate will be 1600 hops/s. All frequencies will be used equally.

The following external I/O cables were used:

Identification	Connector		Lenght
	EUT	Ancillary	
SPI interface (only installed at test samples)	Customised connector	-	10 cm
UART interface (H4) (only installed at test samples)	Soldered to the PCB	9 pole D-Sub connector	10 cm
Power supply	4 pole Molex connector	-	2 m

*: Length during the test if no other specified.

2.1 PERIPHERY DEVICES

The following equipment was used as control unit and ancillary equipment:

- A personal computer with a terminal-software was used, connected temporary to the EUT, for setting the equipment into the necessary operation mode. During the measurements the personal computer was disconnected.

TEST REPORT REFERENCE: F091910E2

3 OPERATIONAL STATES AND PHYSICAL BOUNDARIES

The EUT is intended to be used in a vehicular environment as Bluetooth hands free unit. All radiated tests were carried out with a sample with integral antenna; conductive tests were carried out with a sample, which was equipped with a temporary antenna connector and a power supply connector for the Bluetooth unit.

During the all tests the CC 9055 was powered by an external 13.4 V DC power supply. The tested sample was equipped with an additionally UART- and SPI- interface for choosing the relevant operation mode as given in the table below. The test mode was adjusted with the help of a test-software and a laptop computer, which was connected to the UART/SPI interface of the EUT. After adjusting the test mode, the connection between the EUT and the laptop computer was terminated.


If not otherwise stated, for modulating the transmitter, a pseudo random bit sequence with a length of 44 byte and a pattern type DH1 was used. As declared by the applicant, the EUT is intended to operate with the DH1, DH3 and DH5 hopping mode, so the dwell time measurements were only carried out in these hopping modes.

During the tests, the EUT was not labelled with a FCC-label.

The following operation modes were used during the tests:

Operation mode	Description of the operation mode
1	Continuous transmitting on 2402 MHz
2	Continuous transmitting on 2441 MHz
3	Continuous transmitting on 2480 MHz
4	Transmitter hopping on all channels
5	Continuous receiving on 2441 MHz

Physical boundary of the EUT



TEST REPORT REFERENCE: F091910E2

4 LIST OF MEASUREMENTS

Application	Frequency range [MHz]	FCC 47 CFR Part 15 section [2]	RSS 210, Issue 7 [4] or RSS-Gen, Issue 2 [5]	Status	Refer page
20 dB bandwidth	General	15.247 (a) (1)	A8.1 (b) [4]	Passed	8 et seq.
Carrier frequency separation	General	15.247 (a) (1)	A8.1 (b) [4]	Passed	11 et seq.
Number of hopping channels	2400.0 - 2483.5	15.247 (a) (1) (iii)	A8.1 (d) [4]	Passed	14 et seq.
Dwell time	2400.0 - 2483.5	15.247 (a) (1) (iii)	A8.1 (d) [4]	Passed	16 et seq.
Maximum peak output power	2400.0 - 2483.5	15.247 (b) (1)	A8.4 (2) [4]	Passed	20 et seq.
Band edge compliance	2400.0 - 2483.5	15.247 (d)	A8.5 [4]	Passed	23 et seq.
Radiated emissions (transmitter)	0.009 - 25,000	15.205 (a) 15.209 (a)	A8.5 [4] 2.6 [4]	Passed	28 et seq.
Conducted emissions on supply line	0.15 - 30	15.207 (a)	7.2.2 [5]	Not applicable *	-
Radiated emissions (receiver)	0.009 - 25,000	15.109 (a)	6 [5] 2.6 [4]	Passed	Annex D

*: Not applicable, because the EUT is intended to be used in a vehicular environment.

TEST REPORT REFERENCE: F091910E2

5 TEST RESULTS

5.1 20 dB BANDWIDTH

5.1.1 METHOD OF MEASUREMENT (20 dB BANDWIDTH)

The calibration of the spectrum analyser has to be checked with the help of a known signal from a signal generator. The EUT has to be connected to the spectrum analyser via a low loss cable. If the EUT is not equipped with an antenna connector, a temporary antenna connector has to be installed. The EUT has to be switched on and the hopping function has to be disabled, the transmitter shall work with its maximum data rate.

The following spectrum analyser settings shall be used:

- Span: App. 2 to 3 times the 20 dB bandwidth, centred on the actual hopping channel.
- Resolution bandwidth: $\geq 1\%$ of the 20 dB bandwidth.
- Video bandwidth: \geq the resolution bandwidth.
- Sweep: Auto.
- Detector function: peak.
- Trace mode: Max hold.

After trace stabilisation the marker shall be set on the signal peak. The first display line has to be set on this value. The second display line has to be set 20 dB below the first line (or the peak marker). The frequency lines shall be set on the intersection points between the second display line and the measured curve.

The measurement will be performed at the upper, the lower end and the middle of the assigned frequency band.

Test set-up:




TEST REPORT REFERENCE: F091910E2


5.1.2 TEST RESULTS (20 dB BANDWIDTH)

Ambient temperature	21 °C	Relative humidity	50 %
---------------------	-------	-------------------	------

91910_45.wmf: (20 dB bandwidth at the lower end of the assigned frequency band):




91910_46.wmf: (20 dB bandwidth at the middle of the assigned frequency band):



TEST REPORT REFERENCE: F091910E2

91910_47.wmf: (20 dB bandwidth at the upper end of the assigned frequency band):



Channel number	Channel frequency [MHz]	20 dB bandwidth [kHz]
0	2402	719.949
39	2441	759.615
78	2480	766.026
Measurement uncertainty		+0.66 dB / -0.72 dB

TEST EQUIPMENT USED FOR THE TEST:

30

TEST REPORT REFERENCE: F091910E2

5.2 CARRIER FREQUENCY SEPARATION

5.2.1 METHOD OF MEASUREMENT (CARRIER FREQUENCY SEPARATION)

The calibration of the spectrum analyser has to be checked with the help of a known signal from a signal generator. The EUT has to be connected to the spectrum analyser via a low loss cable. If the EUT is not equipped with an antenna connector, a temporary antenna connector has to be installed. The EUT has to be switched on and the hopping function has to be enabled.


The following spectrum analyser settings shall be used:

- Span: Wide enough to capture the peaks of two adjacent channels.
- Resolution bandwidth: ≥ 1 % of the span.
- Video bandwidth: \geq the resolution bandwidth.
- Sweep: Auto.
- Detector function: peak.
- Trace mode: Max hold.

After trace stabilisation the marker and the delta marker function will be used to determine the separation between the peaks of two adjacent channel signals.

The measurement will be performed at the upper, the lower end and the middle of the assigned frequency band.

Test set-up:




TEST REPORT REFERENCE: F091910E2


5.2.2 TEST RESULTS (CARRIER FREQUENCY SEPARATION)

Ambient temperature	21 °C	Relative humidity	50 %
---------------------	-------	-------------------	------

91910_48.wmf: (channel separation at the lower end of the assigned frequency band):




91910_49.wmf: (channel separation at the middle of the assigned frequency band):



TEST REPORT REFERENCE: F091910E2

91910_50.wmf: (channel separation at the upper end of the assigned frequency band):



Channel number	Channel frequency [MHz]	Channel separation [kHz]	Minimum limit [kHz]
0	2402	1000	719.949 (20 dB bandwidth)
39	2441	1000	759.615 (20 dB bandwidth)
78	2480	1000	766.026 (20 dB bandwidth)
Measurement uncertainty			$<10^{-7}$

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:

30

TEST REPORT REFERENCE: F091910E2

5.3 NUMBER OF HOPPING FREQUENCIES

5.3.1 METHOD OF MEASUREMENT (NUMBER OF HOPPING FREQUENCIES)


The calibration of the spectrum analyser has to be checked with the help of a known signal from a signal generator. The EUT has to be connected to the spectrum analyser via a low loss cable. If the EUT is not equipped with an antenna connector, a temporary antenna connector has to be installed. The EUT has to be switched on and the hopping function has to be enabled.

The following spectrum analyser settings shall be used:

- Span: Equal to the assigned frequency band.
- Resolution bandwidth: ≥ 1 % of the span.
- Video bandwidth: \geq the resolution bandwidth.
- Sweep: Auto.
- Detector function: Peak.
- Trace mode: Max hold.

After trace stabilisation the number of hopping channels could be counted. It might be possible to divide the span into some sub ranges in order to clearly show all hopping frequencies.

Test set-up:




TEST REPORT REFERENCE: F091910E2

5.3.2 TEST RESULTS (NUMBER OF HOPPING FREQUENCIES)

Ambient temperature	21 °C
---------------------	-------

Relative humidity	50 %
-------------------	------

91910_51.wmf (number of hopping channels):



Number of hopping channels	Limit
79	At least 15

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:
30

TEST REPORT REFERENCE: F091910E2

5.4 DWELL TIME

5.4.1 METHOD OF MEASUREMENT (DWELL TIME)

The calibration of the spectrum analyser has to be checked with the help of a known signal from a signal generator. The EUT has to be connected to the spectrum analyser via a low loss cable. If the EUT is not equipped with an antenna connector, a temporary antenna connector has to be installed. The EUT has to be switched on and the hopping function has to be enabled.

The following spectrum analyser settings shall be used:


- Span: Zero, centred on a hopping channel.
- Resolution bandwidth: 1 MHz.
- Video bandwidth: \geq the resolution bandwidth.
- Sweep: As necessary to capture the entire dwell time per hopping channel.
- Detector function: peak.
- Trace mode: Max hold.

The marker and delta marker function of the spectrum analyser will be used to determine the dwell time.

The measurement will be performed at the upper and lower end and the middle of the assigned frequency band.

If the EUT is possible to operate with different mode of operation (data rates, modulation formats etc.) the test will be repeated with every different operation mode of the EUT.

Test set-up:




TEST REPORT REFERENCE: F091910E2


5.4.2 TEST RESULTS (DWELL TIME)

Ambient temperature	21 °C	Relative humidity	50 %
---------------------	-------	-------------------	------

91910_52.wmf: Dwell time at the middle of the assigned frequency band), hopping mode DH1:




91910_53.wmf: Dwell time at the middle of the assigned frequency band), hopping mode DH3:



TEST REPORT REFERENCE: F091910E2

91910_54.wmf: Dwell time at the middle of the assigned frequency band), hopping mode DH5:



TEST REPORT REFERENCE: F091910E2

The dwell time is calculated with the following formula:

Dwell time = $t_{\text{pulse}} \times n_{\text{hops}} / \text{number of hopping channels} \times 31.6$ (equal to 0.4 s x number of hopping channels)

Where:

t_{pulse} is the measured pulse time (pls. refer the plots of the spectrum analyser above) [s],
 n_{hops} is the number of hops per second in the actual operating mode of the transmitter [1/s].

The hopping rate of the system is 1600 hops per second and the system uses 79 channels. For this reason one time slot has a length of 625 μs .

With the used hopping mode (DH1) a packet need 1 timeslot for transmitting and the next timeslot for receiving. So the system makes in worst case 800 hops per second in transmit mode ($n_{\text{hops}} = 800$ 1/s).

With the used hopping mode (DH3) a packet need 3 timeslots for transmitting and the next timeslot for receiving. So the system makes in worst case 400 hops per second in transmit mode ($n_{\text{hops}} = 400$ 1/s).

With the used hopping mode (DH5) a packet need 5 timeslots for transmitting and the next timeslot for receiving. So the system makes in worst case 267 hops per second in transmit mode ($n_{\text{hops}} = 267$ 1/s).

Hopping mode DH1				
Channel number	Channel frequency [MHz]	t_{pulse} [μs]	Dwell time [ms]	Limit [ms]
39	2441	535.256	171.285	400
Hopping mode DH3				
Channel number	Channel frequency [MHz]	t_{pulse} [μs]	Dwell time [ms]	Limit [ms]
39	2441	1807.692	289.231	400
Hopping mode DH5				
Channel number	Channel frequency [MHz]	t_{pulse} [μs]	Dwell time [ms]	Limit [ms]
39	2441	3057.692	326.158	400
Measurement uncertainty			<10 ⁻⁷	

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:
30

TEST REPORT REFERENCE: F091910E2

5.5 MAXIMUM PEAK OUTPUT POWER

5.5.1 METHOD OF MEASUREMENT (MAXIMUM PEAK OUTPUT POWER)

The calibration of the spectrum analyser has to be checked with the help of a known signal from a signal generator. The EUT has to be connected to the spectrum analyser via a low loss cable. If the EUT is not equipped with an antenna connector, a temporary antenna connector has to be installed. The EUT has to be switched on and the hopping function has to be disabled.


The following spectrum analyser settings shall be used:

- Span: Approx. 5 times the 20 dB bandwidth, centred on a hopping channel.
- Resolution bandwidth: > the 20 dB bandwidth of the emission being measured.
- Video bandwidth: \geq the resolution bandwidth.
- Sweep: Auto.
- Detector function: peak.
- Trace mode: Max hold.

After trace stabilisation the marker shall be set on the signal peak. The indicated level is the peak output power, which has to be corrected with the value of the cable loss and an external attenuation (if necessary).

The measurement will be performed at the upper and lower end and the middle of the assigned frequency band.

Test set-up:




TEST REPORT REFERENCE: F091910E2


5.5.2 TEST RESULTS (MAXIMUM PEAK OUTPUT POWER)

Ambient temperature	21 °C	Relative humidity	50 %
---------------------	-------	-------------------	------

91910_55.wmf (maximum peak output power at the lower end of the assigned frequency band):




91910_56.wmf (maximum peak output power at the middle of the assigned frequency band):



TEST REPORT REFERENCE: F091910E2

91910_57.wmf (maximum peak output power at the upper end of the assigned frequency band):



Channel number	Channel frequency [MHz]	Maximum peak output power [dBm]	Antenna gain [dBi]	Peak power limit [dBm]
0	2402	-10.3	2.0	30.0
39	2441	-9.7	2.0	30.0
78	2480	-9.3	2.0	30.0
Measurement uncertainty				+0.66 dB / -0.72 dB

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:
30

TEST REPORT REFERENCE: F091910E2

5.6 BAND-EDGE COMPLIANCE

5.6.1 METHOD OF MEASUREMENT (BAND-EDGE COMPLIANCE (RADIATED))

The same test set-up as used for the final radiated emission measurement shall be used (refer also subclause 5.8.1 of this test report). The measurements shall be carried out with using a resolution bandwidth of 100 kHz.

The following spectrum analyser settings shall be used:

- Span: Wide enough to capture the peak level of the emission on the channel closest to the band-edge, as well as any modulation products, which fall outside the assigned frequency band.
- Resolution bandwidth: 100 kHz.
- Video bandwidth: \geq the resolution bandwidth.
- Sweep: Auto.
- Detector function: Peak.
- Trace mode: Max hold.

After trace stabilisation the marker shall be set on the signal peak. The first display line has to be set on this value. The second display line has to be set 20 dB below the first line (or the peak marker). The frequency line shall be set on the edge of the assigned frequency band. Set the second marker on the emission at the band-edge, or on the highest modulation product outside of the band, if this level is higher than that at the band-edge. This frequency shall be measured with the EMI receiver as described in subclause 5.8.1 of this test report, but 100 kHz resolution bandwidth shall be used.


The measurement will be performed at the upper end of the assigned frequency band and with hopping on and off.

TEST REPORT REFERENCE: F091910E2


5.6.2 TEST RESULT (BAND-EDGE COMPLIANCE (RADIATED))

Ambient temperature	21 °C	Relative humidity	60 %
---------------------	-------	-------------------	------

91910_13.wmf (radiated band-edge compliance, lower band edge, hopping off):




91910_14.wmf (radiated band-edge compliance, lower band edge, hopping on):




TEST REPORT REFERENCE: F091910E2

91910_16.wmf (radiated band-edge compliance, upper band edge, hopping off):



91910_15.wmf (radiated band-edge compliance, upper band edge, hopping on):



TEST REPORT REFERENCE: F091910E2

The plots on the page before are showing the radiated band-edge compliance for the upper band-edge, with and without hopping. The display line 1 (D1) in these plots represents the highest level within the assigned frequency band. The display line 2 (D2) represents the 20 dB offset to this highest level and shows the compliance with FCC 47 CFR Part 15.247 (d). The frequency line 1 (F1) shows the edge of the assigned frequency.

Band-edge compliance (lower band edge, hopping disabled)										
Result measured with the peak detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.402	86.4	-	-	53.9	28.8	0.0	3.7	150	Vert.	-
2.3997	44.0	74.0	30.0	11.5	28.8	0.0	3.7	150	Vert.	No
Result measured with the average detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.402	76.3	-	-	43.8	28.8	0.0	3.7	150	Vert.	-
2.3997	33.9	56.3	22.4	1.4	28.8	0.0	3.7	150	Vert.	No
Measurement uncertainty							+2.2 dB / -3.6 dB			

Band-edge compliance (lower band edge, hopping enabled)										
Result measured with the peak detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.402	86.4	-	-	53.9	28.8	0.0	3.7	150	Vert.	-
2.3804	42.1	74.0	31.9	9.7	28.7	0.0	3.7	150	Vert.	Yes
Result measured with the average detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.402	76.3	-	-	43.8	28.8	0.0	3.7	150	Vert.	-
2.3804	32.0	54.0	22.0	-0.4	28.7	0.0	3.7	150	Vert.	Yes
Measurement uncertainty							+2.2 dB / -3.6 dB			

TEST REPORT REFERENCE: F091910E2

Band-edge compliance (upper band edge, hopping disabled)										
Result measured with the peak detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.480	85.9	-	-	53.1	29.0	0.0	3.8	150	Vert.	-
2.484	45.1	74.0	28.9	12.3	29.0	0.0	3.8	150	Vert.	Yes
Result measured with the average detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2480	75.8	-	-	43.0	29.0	0.0	3.8	150	Vert.	-
2.484	35.0	54.0	19.0	2.2	29.0	0.0	3.8	150	Vert.	Yes
Measurement uncertainty							+2.2 dB / -3.6 dB			

Band-edge compliance (upper band edge, hopping enabled)										
Result measured with the peak detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.480	85.9	-	-	53.1	29.0	0.0	3.8	150	Vert.	-
2.484	47.9	74.0	26.1	15.1	29.0	0.0	3.8	150	Vert.	Yes
Result measured with the average detector:										
Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.480	75.8	-	-	43.0	29.0	0.0	3.8	150	Vert.	-
2.484	37.8	54.0	16.2	5.0	29.0	0.0	3.8	150	Vert.	Yes
Measurement uncertainty							+2.2 dB / -3.6 dB			

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:

29, 31 – 34, 36, 44

TEST REPORT REFERENCE: F091910E2

5.7 RADIATED EMISSIONS

5.7.1 METHOD OF MEASUREMENT (RADIATED EMISSIONS)

The radiated emission measurement is subdivided into four stages.

- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 30 MHz to 1 GHz.
- A final measurement carried out on an open area test site with reflecting ground plane and various antenna height in the frequency range 30 MHz to 1 GHz.
- A preliminary measurement carried out in a fully anechoic chamber with a variable antenna distance and height in the frequency range 1 GHz to 110 GHz.
- A final measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 1 GHz to 110 GHz.

All measurements will be carried out with the EUT working on the middle of the assigned frequency band.


Preliminary measurement (30 MHz to 1 GHz)

In the first stage a preliminary measurement will be performed in a fully anechoic chamber with a measuring distance of 3 meter. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to ANSI C63.4-2003 [1].

The frequency range 30 MHz to 1 GHz will be measured with an EMI Receiver set to MAX Hold mode and a resolution bandwidth of 100 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 230 MHz	100 kHz
230 MHz to 1 GHz	100 kHz



TEST REPORT REFERENCE: F091910E2

Procedure preliminary measurement:

Prescans were performed in the frequency range 30 MHz to 230 MHz and 230 MHz to 1 GHz.
The following procedure will be used:


1. Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
2. Manipulate the system cables within the range to produce the maximum level of emission.
3. Rotate the EUT by 360 ° to maximize the detected signals.
4. Make a hardcopy of the spectrum.
5. Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
6. Repeat 1) to 4) with the other orthogonal axes of the EUT (because of EUT is a module and might be used in a handheld equipment application).
7. Repeat 1) to 5) with the vertical polarisation of the measuring antenna.

Final measurement (30 MHz to 1 GHz)

A final measurement on an open area test site will be performed on selected frequencies found in the preliminary measurement. During this test the EUT will be rotated in the range of 0 ° to 360 °, the measuring antenna will be set to horizontal and vertical polarisation and raised and lowered in the range from 1 m to 4 m to find the maximum level of emissions.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 1 GHz	120 kHz



TEST REPORT REFERENCE: F091910E2

Procedure final measurement:

The following procedure will be used:

- 1) Measure on the selected frequencies at an antenna height of 1 m and a EUT azimuth of 23 °.
- 2) Move the antenna from 1 m to 4 m and note the maximum value at each frequency.
- 3) Rotate the EUT by 45 ° and repeat 2) until an azimuth of 337 ° is reached.
- 4) Repeat 1) to 3) for the other orthogonal antenna polarization.
- 5) Move the antenna and the turntable to the position where the maximum value is detected.
- 6) Measure while moving the antenna slowly +/- 1 m.
- 7) Set the antenna to the position where the maximum value is found.
- 8) Measure while moving the turntable +/- 45 °.
- 9) Set the turntable to the azimuth where the maximum value is found.
- 10) Measure with Final detector (QP and AV) and note the value.
- 11) Repeat 5) to 10) for each frequency.
- 12) Repeat 1) to 11) for each orthogonal axes of the EUT (because of EUT is a module and might be used in a handheld equipment application).

Preliminary and final measurement (1 GHz to 110 GHz)

This measurement will be performed in a fully anechoic chamber. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to ANSI C63.4-2003 [1].


Preliminary measurement (1 GHz to 110 GHz)

The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The spectrum analyser set to MAX Hold mode and a resolution bandwidth of 100 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna, the antenna close to the EUT and while moving the antenna over all sides of the EUT. With the spectrum analyser in CLEAR / WRITE mode the cone of the emission should be found and than the measuring distance will be set to 3 m with the receiving antenna moving in this cone of emission. At this position the final measurement will be carried out.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	100 kHz
4 GHz to 12 GHz	100 kHz
12 GHz to 18 GHz	100 kHz
18 GHz to 26.5 GHz	100 kHz
26.5 GHz to 40 GHz	100 kHz
40 GHz to 60 GHz	100 kHz
50 GHz to 75 GHz	100 kHz
75 GHz to 110 GHz	100 kHz

TEST REPORT REFERENCE: F091910E2




Final measurement (1 GHz to 110 GHz)

The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1 MHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 ° in order to have the antenna inside the cone of radiation.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	1 MHz
4 GHz to 12 GHz	1 MHz
12 GHz to 18 GHz	1 MHz
18 GHz to 26.5 GHz	1 MHz
26.5 GHz to 40 GHz	1 MHz
40 GHz to 60 GHz	1 MHz
50 GHz to 75 GHz	1 MHz
75 GHz to 110 GHz	1 MHz

TEST REPORT REFERENCE: F091910E2



Procedure of measurement:

The measurements were performed in the frequency range 1 GHz to 4 GHz, 4 GHz to 12 GHz, 12 GHz to 18 GHz, 18 GHz to 26.5 GHz, 26.5 GHz to 40 GHz, 40 GHz to 60 GHz, 60 GHz to 75 GHz and 75 GHz to 110 GHz.

The following procedure will be used:

- 1) Monitor the frequency range at horizontal polarisation and move the antenna over all sides of the EUT (if necessary move the EUT to another orthogonal axis).
- 2) Change the antenna polarisation and repeat 1) with vertical polarisation.
- 3) Make a hardcopy of the spectrum.
- 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
- 5) Change the analyser mode to Clear / Write and found the cone of emission.
- 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3 m and the antenna will be still inside the cone of emission.
- 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarisation and azimuth and the peak and average detector, which causes the maximum emission.
- 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Step 1) to 6) are defined as preliminary measurement.

TEST REPORT REFERENCE: F091910E2


5.7.2 TEST RESULTS (RADIATED EMISSIONS)

5.7.2.1 PRELIMINARY MEASUREMENT (9 kHz to 25 GHz)

Ambient temperature	21 °C	Relative humidity	60 %
---------------------	-------	-------------------	------

- Position of EUT:** The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
- Cable guide:** The cable of the EUT is running vertically to the false floor. For detail information of test set-up and the cable guide refer to the pictures in annex A of this test report.
- Test record:** All results are shown in the following.
- Supply voltage:** During all measurements the EUT was supplied with 13.4 V DC.
- Remark:** As pre-tests have shown, the emissions in the frequency range 9 kHz to 1 GHz are not depending on the transmitter operation mode or frequency. Therefore the emissions in this frequency range were measured only with the transmitter operates in operation mode 2.

91910_23.wmf: (9 kHz to 150 kHz):




TEST EQUIPMENT USED FOR THE TEST:


29, 31 – 37, 39, 43, 44, 46, 49 – 51, 55, 72

TEST REPORT REFERENCE: F091910E2

91910_24.wmf: (150 kHz to 1 MHz):




91910_25.wmf: (1 MHz to 30 MHz)




No significant frequencies above the noise floor of the system were found during the preliminary radiated emission test, so no measurements were carried out on the outdoor test site.

TEST REPORT REFERENCE: F091910E2

91910_19.wmf (30 MHz to 230 MHz):



91910_20.wmf (230 MHz to 1 GHz):




The following frequency was found during the preliminary radiated emission test:

816.340 MHz.


This frequency has to be measured on the open area test site. The result is presented in the following

TEST REPORT REFERENCE: F091910E2

91910_7.wmf (12 GHz to 18 GHz):



91910_12.wmf (18 GHz to 25 GHz):



The following frequencies were found inside the restricted bands during the preliminary radiated emission test:

- 1.603 GHz, 4.005 GHz, 4.804 GHz and 12.010 GHz.

The following frequency was found outside the restricted bands during the preliminary radiated emission test:


- 2.402 GHz.

These frequencies have to be measured in a final measurement. The results were presented in the following.


TEST REPORT REFERENCE: F091910E2

Transmitter operates at the middle of the assigned frequency band (operation mode 2)

91910_1.wmf (1 GHz to 4 GHz):




91910_5.wmf (4 GHz to 12 GHz):




TEST REPORT REFERENCE: F091910E2

91910_8.wmf (12 GHz to 18 GHz):



91910_11.wmf (18 GHz to 25 GHz):



The following frequencies were found inside the restricted bands during the preliminary radiated emission test:

- 4.070 GHz, 4.882 GHz and 12.205 GHz.


The following frequencies were found outside the restricted bands during the preliminary radiated emission test:

- 1.629 GHz and 2.441 GHz.


These frequencies have to be measured in a final measurement. The results were presented in the following.

TEST REPORT REFERENCE: F091910E2

91910_9.wmf (12 GHz to 18 GHz):



91910_10.wmf (18 GHz to 25 GHz):



The following frequencies were found inside the restricted bands during the preliminary radiated emission test:

- 4.134 GHz, 4.960 GHz and 12.400 GHz.

The following frequencies were found outside the restricted bands during the preliminary radiated emission test:

- 1.655 GHz and 2.480 GHz.

These frequencies have to be measured in a final measurement. The results were presented in the following.

TEST REPORT REFERENCE: F091910E2


5.7.2.2 FINAL RADIATED EMISSION TEST (30 MHz to 1 GHz)

Ambient temperature	21 °C	Relative humidity	60 %
---------------------	-------	-------------------	------

- Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
- Cable guide: The cable of the EUT is running vertically to the false floor. For detail information of test set-up and the cable guide refer to the pictures in annex A of this test report.
- Test record: All results are shown in the following.
- Supply voltage: During all measurements the EUT was supplied with 13.4 V DC.
- Test results: The test results were calculated with the following formula:

$$\text{Result [dB}\mu\text{V/m]} = \text{reading [dB}\mu\text{V]} + \text{cable loss [dB]} + \text{antenna factor [dB/m]}$$

The measured points and the limit line in the following diagram refer to the standard measurement of the emitted interference in compliance with the above-mentioned standard. The measured points marked with an x are the measured results of the standard final measurement on the open area test site.



Data record name: 91910ffTX

TEST REPORT REFERENCE: F091910E2

The results of the standard subsequent measurement on the open area test site are indicated in the table below. The limits as well as the measured results (levels) refer to the above mentioned standard while taking account of the specified requirements for a 3 m measuring distance.

The measurement time with the quasi-peak measuring detector is 1 second.

Result measured with the quasipeak detector:
(This value is marked in the diagram by an x)

Spurious emissions outside restricted bands									
Frequency	Result	Limit	Margin	Readings	Antenna factor	Cable loss	Height	Azimuth	Pol.
MHz	dB μ V/m	dB μ V/m	dB	dB μ V	dB/m	dB	cm	deg	
816.340	27.5	46.0	18.5	2.5	21.8	3.2	100.0	68.0	Vert.
Spurious emissions in restricted bands									
Frequency	Result	Limit	Margin	Readings	Antenna factor	Cable loss	Height	Azimuth	Pol.
MHz	dB μ V/m	dB μ V/m	dB	dB μ V	dB/m	dB	cm	deg	
-	-	-	-	-	-	-	-	-	-
Measurement uncertainty				+2.2 dB / -3.6 dB					

The test results were calculated with the following formula:

$$\text{Result [dB}\mu\text{V/m]} = \text{reading [dB}\mu\text{V]} + \text{cable loss [dB]} + \text{antenna factor [dB/m]}$$

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:
14 – 20

TEST REPORT REFERENCE: F091910E2

5.7.2.3 FINAL MEASUREMENT (1 GHz to 25 GHz)

Ambient temperature	21 °C	Relative humidity	60 %
---------------------	-------	-------------------	------

- Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
- Cable guide: The cable of the EUT is running vertically to the false floor. For detail information of test set-up and the cable guide refer to the pictures in annex A of this test report.
- Test record: All results are shown in the following.
- Supply voltage: During all measurements the EUT was supplied with 13.4 V DC.
- Resolution bandwidth: For all measurements a resolution bandwidth of 1 MHz was used.

Transmitter operates at the lower end of the assigned frequency band (operation mode 1)

Result measured with the peak detector:

Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.402	86.4	-	-	53.9	28.8	0.0	3.7	150	Vert.	-
1.603	48.0	74.0	26.0	19.0	26.0	0.0	3.0	150	Hor.	Yes
4.005	46.4	74.0	27.6	34.4	33.3	26.1	4.8	150	Vert.	Yes
4.804	66.3	74.0	7.7	53.0	33.7	25.7	5.3	150	Vert.	Yes
12.010	50.7	74.0	23.3	40.5	33.6	25.9	2.5	100	Vert.	Yes
Measurement uncertainty							+2.2 dB / -3.6 dB			

Result measured with the average detector:

Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.402	76.3	-	-	43.8	28.8	0.0	3.7	150	Vert.	-
1.603	39.6	54.0	14.4	10.6	26.0	0.0	3.0	150	Hor.	Yes
4.005	34.0	54.0	20.0	22.0	33.3	26.1	4.8	150	Vert.	Yes
4.804	53.9	54.0	0.1	40.6	33.7	25.7	5.3	150	Vert.	Yes
12.010	34.6	54.0	19.4	24.4	33.6	25.9	2.5	100	Vert.	Yes
Measurement uncertainty							+2.2 dB / -3.6 dB			

TEST REPORT REFERENCE: F091910E2

Transmitter operates at the middle of the assigned frequency band (operation mode 2)

Result measured with the peak detector:

Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height Cm	Pol.	Restr. Band
2.441	86.2	-	-	53.6	28.9	0.0	3.7	150	Vert.	-
1.629	48.8	74.0	25.2	19.6	26.1	0.0	3.1	150	Hor.	No
4.070	47.0	74.0	27.0	35.0	33.3	26.1	4.8	150	Vert.	Yes
4.882	65.8	74.0	8.2	52.4	33.8	25.7	5.3	150	Vert.	Yes
12.205	48.4	74.0	25.6	38.2	33.6	25.9	2.5	100	Vert.	Yes
Measurement uncertainty							+2.2 dB / -3.6 dB			

Result measured with the average detector:

Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band
2.441	76.1	-	-	43.5	28.9	0.0	3.7	150	Vert.	-
1.629	40.5	56.1	15.6	11.3	26.1	0.0	3.1	150	Hor.	No
4.070	34.1	54.0	19.9	22.1	33.3	26.1	4.8	150	Vert.	Yes
4.882	53.6	54.0	0.4	40.2	33.8	25.7	5.3	150	Vert.	Yes
12.205	33.7	54.0	20.3	23.5	33.6	25.9	2.5	100	Vert.	Yes
Measurement uncertainty							+2.2 dB / -3.6 dB			

TEST REPORT REFERENCE: F091910E2

Transmitter operates at the upper end of the assigned frequency band (operation mode 3)

Result measured with the peak detector:

Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band	
2.480	85.9	-	-	53.1	29.0	0.0	3.8	150	Vert.	-	
1.655	49.4	74.0	24.6	20.1	26.2	0.0	3.1	150	Vert.	No	
4.134	45.0	74.0	29.0	32.9	33.2	26.0	4.9	150	Vert.	Yes	
4.960	65.1	74.0	8.9	51.4	34.0	25.6	5.3	150	Vert.	Yes	
12.400	47.3	74.0	26.7	37.0	33.7	25.9	2.5	100	Vert.	Yes	
Measurement uncertainty							+2.2 dB / -3.6 dB				

Result measured with the average detector:

Frequency GHz	Corr. value dB μ V/m	Limit dB μ V/m	Margin dB	Readings dB μ V	Antenna factor 1/m	Preamp dB	Cable loss dB	Height cm	Pol.	Restr. Band	
2.480	75.8	-	-	43.0	29.0	0.0	3.8	150	Vert.	-	
1.655	42.4	55.8	13.4	13.1	26.2	0.0	3.1	150	Vert.	No	
4.134	31.1	54.0	22.9	19.0	33.2	26.0	4.9	150	Vert.	Yes	
4.960	53.6	54.0	0.4	39.9	34.0	25.6	5.3	150	Vert.	Yes	
12.400	32.2	54.0	21.8	21.9	33.7	25.9	2.5	100	Vert.	Yes	
Measurement uncertainty							+2.2 dB / -3.6 dB				

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:

29, 31 –34, 36, 37, 44, 46, 49, 50, 72

TEST REPORT REFERENCE: F091910E2

6 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

TEST REPORT REFERENCE: F091910E2

No.	Test equipment	Type	Manufacturer	Serial No.	PM. No.	Cal. Date	Cal. due
14	Open area test site	-	Phoenix Test-Lab	-	480085	Weekly verification (system cal.)	
15	Measuring receiver	ESIB7	Rohde & Schwarz	100304	480521	02/26/2008	02/2010
16	Controller	HD100	Deisel	100/670	480139	-	-
17	Turntable	DS420HE	Deisel	420/620/80	480087	-	-
18	Antenna support	AS615P	Deisel	615/310	480086	-	-
19	Antenna	CBL6111 A	Chase	1643	480147	08/01/2007	08/2012
20	EMI Software	ES-K1	Rohde & Schwarz	-	480111	-	-
29	Fully anechoic chamber M20	-	Albatross Projects	B83107-E2439-T232	480303	Weekly verification (system cal.)	
30	Spectrum analyser	FSU	Rohde & Schwarz	200125	480956	02/04/2009	02/2011
31	Measuring receiver	ESI 40	Rohde & Schwarz	100064	480355	02/25/2008	02/2010
32	Controller	MCU	Maturo	MCU/043/971107	480832	-	-
33	Turntable	DS420HE	Deisel	420/620/80	480315	-	-
34	Antenna support	AS615P	Deisel	615/310	480187	-	-
35	Antenna	CBL6112 B	Chase	2688	480328	10/11/2005	10/2010
36	Antenna	3115 A	EMCO	9609-4918	480183	04/11/2008	11/2013
37	Standard Gain Horn 11.9 GHz – 18 GHz	18240-20	Flann Microwave	483	480294	Six month verification (system cal.)	
39	Standard Gain Horn 17.9 GHz – 26.7 GHz	20240-20	Flann Microwave	411	480297	Six month verification (system cal.)	
43	RF-cable No. 30	RTK 081	Rosenberger	-	410141	Weekly verification (system cal.)	
44	RF-cable No. 31	RTK 081	Rosenberger	-	410142	Weekly verification (system cal.)	
46	RF-cable 1m	KPS-1533-400-KPS	Insulated Wire	-	480301	Six month verification (system cal.)	
49	Preamplifier	JS3-00101200-23-5A	Miteq	681851	480337	Six month verification (system cal.)	
50	Preamplifier	JS3-12001800-16-5A	Miteq	571667	480343	Six month verification (system cal.)	
51	Preamplifier	JS3-18002600-20-5A	Miteq	658697	480342	Six month verification (system cal.)	
55	Loop antenna	HFH2-Z2	Rohde & Schwarz	832609/014	480059	02/19/2008	02/2013
72	4 GHz High Pass Filter	WHKX4.0/18 G-8SS	Wainwright Instruments	1	480587	Weekly verification (system cal.)	

TEST REPORT REFERENCE: F091910E2

7 LIST OF ANNEXES

ANNEX A	PHOTOGRAPHS OF THE TEST SET-UPS:	6 pages
	CC 9055, test set-up fully anechoic chamber	91910_3.jpg
	CC 9055, test set-up fully anechoic chamber	91910_6.jpg
	CC 9055, test set-up fully anechoic chamber	91910_5.jpg
	CC 9055, test set-up fully anechoic chamber	91910_1.jpg
	CC 9055, test set-up fully anechoic chamber	91910_4.jpg
	CC 9055, open area test site	91910_13.jpg
ANNEX B	INTERNAL PHOTOGRAPHS OF THE TEST SAMPLE:	4 pages
	CC 9055, internal view	91910_d.jpg
	CC 9055, PCB, top view	91910_f.jpg
	CC 9055, PCB, bottom view	91910_g.jpg
	CC 9055, detail view to sample with temporary antenna connector	91910_h.jpg
ANNEX C	EXTERNAL PHOTOGRAPHS OF THE TEST SAMPLE:	3 pages
	CC 9055, 3-D view 1	91910_a.jpg
	CC 9055, 3-D view 2	91910_b.jpg
	CC 9055, type plate view	91910_c.jpg
ANNEX D	ADDITIONAL RESULTS FOR INDUSTRY CANADA:	5 pages