



Certification Exhibit

FCC ID: QZC-GNICI

FCC Rule Part: 47 CFR Part 2.1091

TÜV SÜD Project Number: 72154502

Manufacturer: Elster Solutions LLC
Model: Global Network Interface Card International (GNICI)

RF Exposure

General Information:

Applicant: Elster Solutions LLC
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: On-board stamped metal dipole
 Antenna Gain: 2.1 dBi
 Maximum Transmitter Conducted Power: 22.899 dBm, 194.94 mW
 Maximum System EIRP: 24.999 dBm, 316.15 mW
 Exposure Conditions: 20 centimeters or greater

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm²)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: MPE Calculation

Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
922	22.899	0.61	194.94	2.1	1.622	20	0.063