



## **Certification Exhibit**

**FCC ID: QZC-MNICI**

**FCC Rule Part: 47 CFR Part 2.1091**

**Project Number: 72124703**

Manufacturer: Elster Solutions  
Model: MNIC

## **RF Exposure**

**General Information:**

Applicant: Elster Solutions  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information:**

Antenna Type: Half-Wave Dipole  
 Antenna Gain: 5.15dBi dBi  
 Maximum Transmitter Conducted Power: 23.87 dBm, 234.78 mW  
 Maximum System EIRP: 29.02 dBm, 797.99 mW  
 Exposure Conditions: 20 centimeters or greater

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**Table 1: MPE Calculation**

Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm <sup>2</sup> )	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )
902.4	23.87	0.60	243.78	5.15	3.273	20	0.159