

Maximum Permissible Exposure

Test Requirement: 47 CFR Part 1

Test Specification: 47 CFR Part 1, Section 1.1307

Test Procedure:

Maximum Permissible Exposure limits are as follows:

FCC Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² . or S (minutes)
0.3 – 3.0	614	1.63	(100)*	6
3.0 - 30	1824/f	4.89/f	(900/f ²)*	6
30 - 300	61.4	0.163	1.0	6
300 – 1500	-	-	f/300	6
1500 – 100,000	-	-	5.0	6

* Plane-wave equivalent power density

FCC Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² . or S (minutes)
0.3 - 1.34	614	1.63	(100)*	30
1.34 - 30	824/f	2.19/f	(180/f ²)*	30
30 - 300	27.5	0.073	0.2	30
300 – 1500	-	-	f/1500	30
1500 – 100,000	-	-	1.0	30

*Plane-wave equivalent power density

Test Details: This device is considered to possibly be located in either environment. See calculation for assumptions.

Background: Per the following guidance from OET Bulletin 65 Supplement C required minimum spacings are provided to the professional installer.

Transmitter or Device Type ¹⁸	Output ¹⁹	Applicable Methods to Ensure Compliance ²⁰
Transmitters using indoor antennas that operate at 20 cm or more from nearby persons	>2.5 W at 915 MHz	If the MPE distance is greater than that required for normal operation of the device, operating instructions, warning instructions and/or warning labels may be used to ensure compliance by indicating the minimal separation distance to comply with MPE limits. If the antennas are professionally installed to ensure compliance, warning instructions and warning labels are not necessary.
	=< 2.5 W at 915 MHz or =< 4 W at 2450 MHz	Transmitters operating at 2.5 W EIRP (1.5 W ERP) or less at 915 MHz, or at 4 W EIRP (2.4 W ERP) or less at 2450 MHz, generally are not

		expected to exceed MPE limits when nearby persons are 20 cm or more from most antennas. Therefore, special instructions and warnings are normally not necessary to ensure compliance.
--	--	---

MPE Calculation with highest EIRP:

The highest radiated power was observed at the center channel (908.6 MHz) and these measurements are used for the calculation. Duty cycle is programmable and we assume worst case for this calculation (100%).

$$S = \text{EIRP} / (4 * \text{Pi} * R^2),$$

Power Density = $\text{EIRP} / (4 * \text{Pi} * R^2),$
--

where $\text{EIRP} = \text{Output Power} * \text{Antenna Gain}$

Uncontrolled/General Exposure

0.0401 Watt, 4.04 dBi antenna (2.535 linear), 20 cm spacing

Operating Frequency	908.628 MHz		
Output Power (Peak)	0.040 Watts		
Antenna Gain	4.03 dB	or (linear)	2.5 (unitless)
Separation Distance	0.2 m	-or-	7.874 inches

Peak Power Density	0.202 W/m ²	- or -	0.0202 mW/cm ²
--------------------	------------------------	--------	---------------------------

Exposure % (over 6 min timespan for uncontrolled)	100%
Transmit Duty Cycle (Peak-to-Average Ratio)	100%

Average Power Density	0.202 W/m ²	- or -	0.0202 mW/cm ²
-----------------------	-------------------------------	--------	----------------------------------

Limit for **Uncontrolled**

Exposure at Operating Frequency	6.057 W/m ²	- or -	0.6057 mW/cm ²
---------------------------------	-------------------------------	--------	----------------------------------