



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6554  
http://www.pctestlab.com



## RF EXPOSURE EVALUATION Maximum Permissible Exposure (MPE)

**Applicant Name:**  
Elster Solutions, LLC  
208 S. Rogers Lane  
Raleigh, NC 27610  
United States

**Date of Testing:**  
11/11/2013  
**Test Site/Location:**  
PCTEST Lab, Columbia, MD, USA  
**Test Report Serial No.:**  
0Y1311062123.QZC

<b>FCC ID:</b>	<b>QZCWWIC3EV</b>
<b>IC CERTIFICATION NO.:</b>	<b>4557A-WWIC3EV</b>
<b>APPLICANT:</b>	<b>Elster Solutions, LLC</b>



**EUT Type:** EA\_Gatekeeper with Wireless WIC3G  
**Model:** EA\_GKWWIC3\_EVXV  
**FCC Classifications:** PCS Licensed Transmitter (PCB),  
 FCC Part 15 Spread Spectrum Transmitter (DSS)  
**FCC Rule Part(s):** FCC Part 1 (§1.1310) and Part 2 (§2.1091)  
**IC Specification(s):** RSS-102 Issue 4  
**Test Procedure:** OET Bulletin 65, KDB 447498 v05r01

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC OET Bulletin 65 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
 Randy Ortanez  
 President





<b>FCC ID:</b> QZCWWIC3EV		<b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1311062123.QZC	<b>Test Dates:</b> 11/11/2013	<b>EUT Type:</b> EA_Gatekeeper with Wireless WIC3G	Page 1 of 7	

## TABLE OF CONTENTS

---

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	3
1.1	INTRODUCTION .....	3
1.2	EUT DESCRIPTION .....	3
1.3	MPE REQUIREMENTS OVERVIEW .....	4
1.4	PROCEDURE .....	5
1.5	SUMMARY OF RESULTS .....	6
2.0	CONCLUSION.....	7

<b>FCC ID:</b> QZCWWIC3EV		<b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1311062123.QZC	<b>Test Dates:</b> 11/11/2013	<b>EUT Type:</b> EA_Gatekeeper with Wireless WIC3G		Page 2 of 7

# 1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## 1.1 Introduction

This document is prepared on behalf of Elster Solutions, LLC to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30



**Table 1-1. Limits for Maximum Permissible Exposure (MPE)**

## 1.2 EUT Description

The Elster Model: EA\_GKWWIC3\_EVXV is a device containing a CDMA/EvDO module and a 900MHz ISM band module. For this MPE evaluation, the RF exposure of each transmitter is evaluated individually based on the highest theoretical output power and the highest antenna gain available for use with the device.

### EUT:

**Model:** EA\_GKWWIC3\_EVXV  
**Grantee:** Elster Solutions, LLC  
**FCC ID:** QZCWWIC3EV  
**Antenna Gains:** -2.5dBi (900MHz Tx)  
 5.9dBi (Cellular band Tx)  
 4.49dBi (PCS band Tx)

<b>FCC ID:</b> QZCWWIC3EV		<b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1311062123.QZC	<b>Test Dates:</b> 11/11/2013	<b>EUT Type:</b> EA_Gatekeeper with Wireless WIC3G		Page 3 of 7

### 1.3 MPE Requirements Overview



Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The Elster EA\_Gatekeeper with Wireless WIC3G FCC ID: QZCWWIC3EV is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure.

FCC ID: QZCWWIC3EV		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1311062123.QZC	Test Dates: 11/11/2013	EUT Type: EA_Gatekeeper with Wireless WIC3G	Page 4 of 7	

## 1.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a power meter or a spectrum analyzer and the powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at a distance of 20cm.

### Friis Transmission Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

$P_d$  = Power Density (mW/cm<sup>2</sup>)

$\pi$  = 3.1416

$P_{out}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

$G$  = gain of antenna in linear scale

### Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.



Co-location is addressed in the last of the following tables by calculating the ratio of the power density for each transmitter to its respective limit. The percentages are then added to ensure that the total is less than 100%, as specified in KDB 447498 v05r01, thus showing that the operation of simultaneous transmitters is compliant. Only the worst case simultaneous transmission case (e.g. 900MHz Tx + Cellular band Tx) is shown in the table below. The following power densities are calculated for each individual transmitter by frequency at 20cm spacing:

<b>Frequency</b>	824.7 MHz		
<b>Limit</b>	0.550 mW/cm <sup>2</sup>		
<b>Distance (cm), R =</b>	20 cm		
<b>Power (dBm), P =</b>	24.9 dBm	309.03 mW	
<b>TX Ant Gain (dBi), G =</b>	5.9 dBi		
<b>Power Density (S) =</b>	<b>0.239</b> mW/cm <sup>2</sup>	(at 20cm)	
<b>Minimum Distance =</b>	<b>13.2</b> cm		

**Table 1-2. Calculated MPE Data for Cellular Band**

<b>Frequency:</b>	1880 MHz		
<b>Limit:</b>	1.000 mW/cm <sup>2</sup>		
<b>Distance (cm), R =</b>	20 cm		
<b>Power (dBm), P =</b>	24.9 dBm	309.03 mW	
<b>TX Ant Gain (dBi), G =</b>	4.49 dBi		
<b>Power Density (S) =</b>	<b>0.173</b> mW/cm <sup>2</sup>	(at 20cm)	
<b>Minimum Distance =</b>	<b>8.3</b> cm		

**Table 1-3. Calculated MPE Data for PCS Band**

<b>FCC ID:</b> QZCWWIC3EV		<b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1311062123.QZC	<b>Test Dates:</b> 11/11/2013	<b>EUT Type:</b> EA_Gatekeeper with Wireless WIC3G	Page 5 of 7	

Frequency	927.6 MHz		
Limit	0.618 mW/cm <sup>2</sup>		
Distance (cm), R =	20 cm		
Power (dBm), P =	21.45 dBm	139.64 mW	
TX Ant Gain (dB), G =	-2.5 dBi		
Power Density (S) =	0.016 mW/cm <sup>2</sup>	(at 20cm)	
Minimum Distance =	3.2 cm		

Table 1-4. Calculated MPE Data for 900MHz Band



	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Percent MPE Used (%)
Transmitter #1	0.239	0.550	43.50
Transmitter #2	0.016	0.618	2.53
Total			46.03

Table 1-5. Co-location MPE Data For Simultaneous Transmission

## 1.5 Summary of Results



Frequency Band [MHz]	Maximum Antenna Gain [dBi]	MPE @ 20cm (mW/cm <sup>2</sup> )	Test Result
824.7 – 848.31	5.9	0.268	PASS
1851.25 – 1908.75	4.49	0.173	PASS
902.8 – 927.6	-2.5	0.016	PASS

Table 1-6. Maximum Permissible Exposure Summary Table

FCC ID: QZCWWIC3EV		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1311062123.QZC	Test Dates: 11/11/2013	EUT Type: EA_Gatekeeper with Wireless WIC3G		Page 6 of 7

## 2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations and Health Canada Safety Code 6. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: QZCWWIC3EV		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1311062123.QZC	Test Dates: 11/11/2013	EUT Type: EA_Gatekeeper with Wireless WIC3G		Page 7 of 7